

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Engine Test Cell Emissions per Year

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

- TestCell: Aircraft Engine Test Cell Emissions (TONs)
- TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)
- TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)
- TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)
- TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)
- TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

38. Aircraft

38.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar
Regulatory Area(s): San Antonio, TX

- Activity Title: 2024 T-7A Increase Trim Test and Engine Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1
Start Year: 2024

- Activity End Date

Indefinite: No
End Month: 12
End Year: 2024

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.190255
SO _x	0.061958
NO _x	1.057247
CO	3.263979
PM 10	0.074222

Pollutant	Total Emissions (TONs)
PM 2.5	0.066560
Pb	0.000000
NH ₃	0.000000
CO _{2e}	187.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	0.103831
SO _x	0.034068
NO _x	0.565988
CO	1.646748
PM 10	0.037849

Pollutant	Total Emissions (TONs)
PM 2.5	0.033916
Pb	0.000000
NH ₃	0.000000
CO _{2e}	103.0

- Activity Emissions [Test Cell part]:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Pollutant	Total Emissions (TONs)
VOC	0.086424
SO _x	0.027890
NO _x	0.491259
CO	1.617231
PM 10	0.036372

Pollutant	Total Emissions (TONs)
PM 2.5	0.032645
Pb	0.000000
NH ₃	0.000000
CO _{2e}	84.3

38.2 Aircraft & Engines

38.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

38.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

38.3 Flight Operations

38.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 18
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 1

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 6.8
 Takeoff [Military] (mins): 0.25
 Takeoff [After Burn] (mins): 0.25
 Climb Out [Intermediate] (mins): 1.4
 Approach [Approach] (mins): 4
 Taxi/Idle In [Idle] (mins): 4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

38.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

38.4 Auxiliary Power Unit (APU)

38.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

38.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

38.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

38.5 Aircraft Engine Test Cell

38.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Total Number of Aircraft Engines Tested Annually: 18

- Default Settings Used: No

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine):	1
Idle Duration (mins):	0
Approach Duration (mins):	12
Intermediate Duration (mins):	0
Military Duration (mins):	8
After Burner Duration (mins):	2

38.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

38.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$TestCell = TestCellPS_{IDLE} + TestCellPS_{APPROACH} + TestCellPS_{INTERMEDIATE} + TestCellPS_{MILITARY} + TestCellPS_{AFTERBURN}$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

39. Aircraft

39.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2025 T-38 Removal Trim Test and Test Cell

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Description:

- Activity Start Date

Start Month: 1
Start Year: 2025

- Activity End Date

Indefinite: No
End Month: 12
End Year: 2025

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	-0.169981
SO _x	-0.042395
NO _x	-0.122617
CO	-2.186180
PM 10	-0.046070

Pollutant	Total Emissions (TONs)
PM 2.5	-0.016658
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-128.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	-0.109701
SO _x	-0.028464
NO _x	-0.081041
CO	-1.447601
PM 10	-0.030287

Pollutant	Total Emissions (TONs)
PM 2.5	-0.010342
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-86.0

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	-0.060280
SO _x	-0.013931
NO _x	-0.041576
CO	-0.738579
PM 10	-0.015783

Pollutant	Total Emissions (TONs)
PM 2.5	-0.006316
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-42.1

39.2 Aircraft & Engines

39.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

39.2.2 Aircraft & Engines Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

39.3 Flight Operations

39.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	12
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	0
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	3

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	12.8
Takeoff [Military] (mins):	0.2
Takeoff [After Burn] (mins):	0.2
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	3.8
Taxi/Idle In [Idle] (mins):	6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

39.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

39.4 Auxiliary Power Unit (APU)

39.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

39.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

39.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

39.5 Aircraft Engine Test Cell

39.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

 Total Number of Aircraft Engines Tested Annually: 12

- Default Settings Used: Yes

- Annual Run-ups / Test Durations

 Annual Run-ups (Per Aircraft Engine): 3 (default)

 Idle Duration (mins): 0 (default)

 Approach Duration (mins): 12 (default)

 Intermediate Duration (mins): 0 (default)

 Military Duration (mins): 8 (default)

 After Burner Duration (mins): 2 (default)

39.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

39.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Total Number of Engines (For All Aircraft)
 ARU: Annual Run-ups (Per Aircraft Engine)
 2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

TestCell: Aircraft Engine Test Cell Emissions (TONs)
 TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)
 TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)
 TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)
 TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)
 TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

40. Aircraft

40.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

- Activity Title: 2025 T-7A Increase Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1
 Start Year: 2025

- Activity End Date

Indefinite: No
 End Month: 12
 End Year: 2025

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.264243
SO _x	0.086053
NO _x	1.468398
CO	4.533304
PM 10	0.103086

Pollutant	Total Emissions (TONs)
PM 2.5	0.092445
Pb	0.000000
NH ₃	0.000000
CO _{2e}	260.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Pollutant	Total Emissions (TONs)
VOC	0.144210
SO _x	0.047317
NO _x	0.786095
CO	2.287149
PM 10	0.052569

Pollutant	Total Emissions (TONs)
PM 2.5	0.047105
Pb	0.000000
NH ₃	0.000000
CO _{2e}	143.0

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	0.120033
SO _x	0.038737
NO _x	0.682304
CO	2.246155
PM 10	0.050517

Pollutant	Total Emissions (TONs)
PM 2.5	0.045340
Pb	0.000000
NH ₃	0.000000
CO _{2e}	117.1

40.2 Aircraft & Engines

40.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

40.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

40.3 Flight Operations

40.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 25
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 1

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 6.8
 Takeoff [Military] (mins): 0.25
 Takeoff [After Burn] (mins): 0.25
 Climb Out [Intermediate] (mins): 1.4

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Approach [Approach] (mins):	4
Taxi/Idle In [Idle] (mins):	4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

40.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AE_{TCO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

40.4 Auxiliary Power Unit (APU)

40.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

40.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

40.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

40.5 Aircraft Engine Test Cell

40.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 25

- Default Settings Used: No

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine):	1
Idle Duration (mins):	0
Approach Duration (mins):	12
Intermediate Duration (mins):	0
Military Duration (mins):	8
After Burner Duration (mins):	2

40.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

40.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$TestCell = TestCellPS_{IDLE} + TestCellPS_{APPROACH} + TestCellPS_{INTERMEDIATE} + TestCellPS_{MILITARY} + TestCellPS_{AFTERBURN}$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

41. Aircraft

41.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Location

County: Bexar
Regulatory Area(s): San Antonio, TX

- Activity Title: 2026 T-38 Removal Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1
Start Year: 2026

- Activity End Date

Indefinite: No
End Month: 12
End Year: 2026

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	-0.269136
SO _x	-0.067125
NO _x	-0.194144
CO	-3.461451
PM 10	-0.072944

Pollutant	Total Emissions (TONs)
PM 2.5	-0.026376
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-202.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	-0.173693
SO _x	-0.045068
NO _x	-0.128315
CO	-2.292035
PM 10	-0.047954

Pollutant	Total Emissions (TONs)
PM 2.5	-0.016375
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-136.2

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	-0.095443
SO _x	-0.022057
NO _x	-0.065829
CO	-1.169417
PM 10	-0.024990

Pollutant	Total Emissions (TONs)
PM 2.5	-0.010001
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-66.7

41.2 Aircraft & Engines

41.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

41.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

41.3 Flight Operations

41.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 19
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 3

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 12.8
 Takeoff [Military] (mins): 0.2
 Takeoff [After Burn] (mins): 0.2
 Climb Out [Intermediate] (mins): 0.9
 Approach [Approach] (mins): 3.8
 Taxi/Idle In [Idle] (mins): 6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 0
 Approach (mins): 4.97
 Intermediate (mins): 10.45
 Military (mins): 6.14
 AfterBurn (mins): 2.04

41.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
 AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
 AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
 AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

41.4 Auxiliary Power Unit (APU)

41.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

41.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

41.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

41.5 Aircraft Engine Test Cell

41.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 19

- Default Settings Used: Yes

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 3 (default)

Idle Duration (mins): 0 (default)

Approach Duration (mins): 12 (default)

Intermediate Duration (mins): 0 (default)

Military Duration (mins): 8 (default)

After Burner Duration (mins): 2 (default)

41.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

41.5.3 Aircraft Engine Test Cell Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$\text{TestCellPS}_{\text{POL}} = (\text{TD} / 60) * (\text{FC} / 1000) * \text{EF} * \text{NE} * \text{ARU} / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONS

- Aircraft Engine Test Cell Emissions per Year

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

42. Aircraft

42.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2026 T-7A Increase Trim Test and Engine Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: No

End Month: 12

End Year: 2026

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.412218
SO _x	0.134243
NO _x	2.290701

Pollutant	Total Emissions (TONs)
PM 2.5	0.144214
Pb	0.000000
NH ₃	0.000000

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

CO	7.071954
PM 10	0.160814

CO _{2e}	405.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	0.224967
SO _x	0.073814
NO _x	1.226308
CO	3.567953
PM 10	0.082007

Pollutant	Total Emissions (TONs)
PM 2.5	0.073484
Pb	0.000000
NH ₃	0.000000
CO _{2e}	223.1

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	0.187251
SO _x	0.060429
NO _x	1.064393
CO	3.504001
PM 10	0.078807

Pollutant	Total Emissions (TONs)
PM 2.5	0.070730
Pb	0.000000
NH ₃	0.000000
CO _{2e}	182.6

42.2 Aircraft & Engines

42.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

42.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

42.3 Flight Operations

42.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 39
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 1

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Taxi/Idle Out [Idle] (mins):	6.8
Takeoff [Military] (mins):	0.25
Takeoff [After Burn] (mins):	0.25
Climb Out [Intermediate] (mins):	1.4
Approach [Approach] (mins):	4
Taxi/Idle In [Idle] (mins):	4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

42.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

42.4 Auxiliary Power Unit (APU)

42.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

42.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

42.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

OH: Operation Hours for Each LTO (hour)
LTO: Number of LTOs
EF_{POL}: Emission Factor for Pollutant (lb/hr)
2000: Conversion Factor pounds to tons

42.5 Aircraft Engine Test Cell

42.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 39

- **Default Settings Used:** Yes

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 1 (default)
Idle Duration (mins): 0 (default)
Approach Duration (mins): 12 (default)
Intermediate Duration (mins): 0 (default)
Military Duration (mins): 8 (default)
After Burner Duration (mins): 2 (default)

42.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

42.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$TestCell = TestCellPS_{IDLE} + TestCellPS_{APPROACH} + TestCellPS_{INTERMEDIATE} + TestCellPS_{MILITARY} + TestCellPS_{AFTERBURN}$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

43. Aircraft

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

43.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location
 - County: Bexar
 - Regulatory Area(s): San Antonio, TX

- Activity Title: 2027 T-38 Removal Trim Test and Test Cell

- Activity Description:

- Activity Start Date
 - Start Month: 1
 - Start Year: 2027

- Activity End Date
 - Indefinite: No
 - End Month: 12
 - End Year: 2027

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	-0.495778
SO _x	-0.123651
NO _x	-0.357633
CO	-6.376358
PM 10	-0.134371

Pollutant	Total Emissions (TONs)
PM 2.5	-0.048587
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-373.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	-0.319962
SO _x	-0.083020
NO _x	-0.236369
CO	-4.222169
PM 10	-0.088337

Pollutant	Total Emissions (TONs)
PM 2.5	-0.030165
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-250.9

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	-0.175816
SO _x	-0.040631
NO _x	-0.121264
CO	-2.154189
PM 10	-0.046034

Pollutant	Total Emissions (TONs)
PM 2.5	-0.018423
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-122.8

43.2 Aircraft & Engines

43.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-38C
 - Engine Model: J85-GE-5R

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No
 - Original Aircraft Name:
 - Original Engine Name:

43.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

43.3 Flight Operations

43.3.1 Flight Operations Assumptions

- Flight Operations
 - Number of Aircraft: 35
 - Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 - Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 - Number of Annual Trim Test(s) per Aircraft: 3

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)
 - Taxi/Idle Out [Idle] (mins): 6.8
 - Takeoff [Military] (mins): 0.25
 - Takeoff [After Burn] (mins): 0.25
 - Climb Out [Intermediate] (mins): 1.4
 - Approach [Approach] (mins): 4
 - Taxi/Idle In [Idle] (mins): 4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test
 - Idle (mins): 0
 - Approach (mins): 4.97
 - Intermediate (mins): 10.45
 - Military (mins): 6.14
 - AfterBurn (mins): 2.04

43.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year
 $AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

43.4 Auxiliary Power Unit (APU)

43.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

43.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

43.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

43.5 Aircraft Engine Test Cell

43.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 35

- Default Settings Used: Yes

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 3 (default)

Idle Duration (mins): 0 (default)

Approach Duration (mins): 12 (default)

Intermediate Duration (mins): 0 (default)

Military Duration (mins): 8 (default)

After Burner Duration (mins): 2 (default)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

43.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

43.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$\text{TestCellPS}_{\text{POL}} = (\text{TD} / 60) * (\text{FC} / 1000) * \text{EF} * \text{NE} * \text{ARU} / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

44. Aircraft

44.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2027 T-7A Increase Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: No

End Month: 12

End Year: 2027

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.613043
SO _x	0.199644
NO _x	3.406684
CO	10.517266
PM 10	0.239159

Pollutant	Total Emissions (TONs)
PM 2.5	0.214473
Pb	0.000000
NH ₃	0.000000
CO _{2e}	603.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	0.334567
SO _x	0.109775
NO _x	1.823740
CO	5.306186
PM 10	0.121959

Pollutant	Total Emissions (TONs)
PM 2.5	0.109284
Pb	0.000000
NH ₃	0.000000
CO _{2e}	331.8

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	0.278476
SO _x	0.089869
NO _x	1.582944
CO	5.211079
PM 10	0.117200

Pollutant	Total Emissions (TONs)
PM 2.5	0.105189
Pb	0.000000
NH ₃	0.000000
CO _{2e}	271.6

44.2 Aircraft & Engines

44.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

44.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

44.3 Flight Operations

44.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 58
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 1

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	6.8
Takeoff [Military] (mins):	0.25
Takeoff [After Burn] (mins):	0.25
Climb Out [Intermediate] (mins):	1.4
Approach [Approach] (mins):	4
Taxi/Idle In [Idle] (mins):	4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

44.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
 AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
 AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
 AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
 AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
 AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
 AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
 AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
 AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

44.4 Auxiliary Power Unit (APU)

44.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

44.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

44.4.3 Auxiliary Power Unit (APU) Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

44.5 Aircraft Engine Test Cell

44.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 58

- Default Settings Used: No

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine):	1
Idle Duration (mins):	0
Approach Duration (mins):	12
Intermediate Duration (mins):	0
Military Duration (mins):	8
After Burner Duration (mins):	2

44.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

44.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$$TestCell = TestCellPS_{IDLE} + TestCellPS_{APPROACH} + TestCellPS_{INTERMEDIATE} + TestCellPS_{MILITARY} + TestCellPS_{AFTERBURN}$$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

45. Aircraft

45.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar; Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2028 T-38 Removal Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: No

End Month: 12

End Year: 2028

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	-0.779079
SO _x	-0.194309
NO _x	-0.561995
CO	-10.019991
PM 10	-0.211155

Pollutant	Total Emissions (TONs)
PM 2.5	-0.076351
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-587.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	-0.502797
SO _x	-0.130460
NO _x	-0.371437
CO	-6.634837
PM 10	-0.138815

Pollutant	Total Emissions (TONs)
PM 2.5	-0.047402
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-394.3

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	-0.276282
SO _x	-0.063849
NO _x	-0.190557
CO	-3.385154
PM 10	-0.072340

Pollutant	Total Emissions (TONs)
PM 2.5	-0.028950
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-193.0

45.2 Aircraft & Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

45.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

45.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

45.3 Flight Operations

45.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 55
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 3

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 6.8
 Takeoff [Military] (mins): 0.25
 Takeoff [After Burn] (mins): 0.25
 Climb Out [Intermediate] (mins): 1.4
 Approach [Approach] (mins): 4
 Taxi/Idle In [Idle] (mins): 4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 0
 Approach (mins): 4.97
 Intermediate (mins): 10.45
 Military (mins): 6.14
 AfterBurn (mins): 2.04

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

45.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

45.4 Auxiliary Power Unit (APU)

45.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

45.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

45.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

45.5 Aircraft Engine Test Cell

45.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 55

- Default Settings Used: Yes

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 3 (default)
 Idle Duration (mins): 0 (default)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Approach Duration (mins):	12 (default)
Intermediate Duration (mins):	0 (default)
Military Duration (mins):	8 (default)
After Burner Duration (mins):	2 (default)

45.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

45.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$\text{TestCellPS}_{\text{POL}} = (\text{TD} / 60) * (\text{FC} / 1000) * \text{EF} * \text{NE} * \text{ARU} / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

46. Aircraft

46.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2028 T-7A Increase Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1

Start Year: 2028

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.761018
SO _x	0.247833
NO _x	4.228987
CO	13.055916
PM 10	0.296887

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.266242
Pb	0.000000
NH ₃	0.000000
CO _{2e}	749.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.415324
SO _x	0.136272
NO _x	2.263953
CO	6.586990
PM 10	0.151397

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.135663
Pb	0.000000
NH ₃	0.000000
CO _{2e}	411.9

- Activity Emissions [Test Cell part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.345694
SO _x	0.111562
NO _x	1.965034
CO	6.468926
PM 10	0.145489

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.130579
Pb	0.000000
NH ₃	0.000000
CO _{2e}	337.2

46.2 Aircraft & Engines

46.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

46.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

46.3 Flight Operations

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

46.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	72
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	0
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	1

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	6.8
Takeoff [Military] (mins):	0.25
Takeoff [After Burn] (mins):	0.25
Climb Out [Intermediate] (mins):	1.4
Approach [Approach] (mins):	4
Taxi/Idle In [Idle] (mins):	4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

46.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

46.4 Auxiliary Power Unit (APU)

46.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

46.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

46.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

46.5 Aircraft Engine Test Cell

46.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 72

- Default Settings Used: No

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 1
 Idle Duration (mins): 0
 Approach Duration (mins): 12
 Intermediate Duration (mins): 0
 Military Duration (mins): 8
 After Burner Duration (mins): 2

46.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

46.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

- TestCell: Aircraft Engine Test Cell Emissions (TONs)
- TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)
- TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)
- TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)
- TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)
- TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

47. Aircraft

47.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove
- Activity Location
 - County: Bexar
 - Regulatory Area(s): San Antonio, TX
- Activity Title: 2029 T-38 Removal Trim Test and Test Cell
- Activity Description:
- Activity Start Date
 - Start Month: 1
 - Start Year: 2029
- Activity End Date
 - Indefinite: No
 - End Month: 12
 - End Year: 2029

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	-0.878235
SO _x	-0.219040
NO _x	-0.633521
CO	-11.295262
PM 10	-0.238029

Pollutant	Total Emissions (TONs)
PM 2.5	-0.086069
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-662.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	-0.566789
SO _x	-0.147064
NO _x	-0.418711
CO	-7.479271
PM 10	-0.156482

Pollutant	Total Emissions (TONs)
PM 2.5	-0.053435
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-444.5

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	-0.311446

Pollutant	Total Emissions (TONs)
PM 2.5	-0.032634

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

SO _x	-0.071976
NO _x	-0.214810
CO	-3.815992
PM 10	-0.081547

Pb	0.000000
NH ₃	0.000000
CO _{2e}	-217.5

47.2 Aircraft & Engines

47.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

47.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

47.3 Flight Operations

47.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 62
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 3

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 12.8
 Takeoff [Military] (mins): 0.2
 Takeoff [After Burn] (mins): 0.2
 Climb Out [Intermediate] (mins): 0.9
 Approach [Approach] (mins): 3.8
 Taxi/Idle In [Idle] (mins): 6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

47.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

47.4 Auxiliary Power Unit (APU)

47.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

47.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

47.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

47.5 Aircraft Engine Test Cell

47.5.1 Aircraft Engine Test Cell Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 62

- Default Settings Used: Yes

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 3 (default)
Idle Duration (mins): 0 (default)
Approach Duration (mins): 12 (default)
Intermediate Duration (mins): 0 (default)
Military Duration (mins): 8 (default)
After Burner Duration (mins): 2 (default)

47.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

47.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$TestCell = TestCellPS_{IDLE} + TestCellPS_{APPROACH} + TestCellPS_{INTERMEDIATE} + TestCellPS_{MILITARY} + TestCellPS_{AFTERBURN}$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

48. Aircraft

48.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Title: 2030 T-38 Removal Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1
Start Year: 2030

- Activity End Date

Indefinite: No
End Month: 12
End Year: 2030

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	-0.949060
SO _x	-0.236704
NO _x	-0.684612
CO	-12.206171
PM 10	-0.257225

Pollutant	Total Emissions (TONs)
PM 2.5	-0.093010
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-715.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	-0.612498
SO _x	-0.158924
NO _x	-0.452478
CO	-8.082438
PM 10	-0.169102

Pollutant	Total Emissions (TONs)
PM 2.5	-0.057744
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-480.3

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	-0.336562
SO _x	-0.077780
NO _x	-0.232134
CO	-4.123733
PM 10	-0.088123

Pollutant	Total Emissions (TONs)
PM 2.5	-0.035266
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-235.1

48.2 Aircraft & Engines

48.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

48.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

48.3 Flight Operations

48.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	67
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	0
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	3

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	12.8
Takeoff [Military] (mins):	0.2
Takeoff [After Burn] (mins):	0.2
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	3.8
Taxi/Idle In [Idle] (mins):	6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

48.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

48.4 Auxiliary Power Unit (APU)

48.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

48.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

48.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

48.5 Aircraft Engine Test Cell

48.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 67

- Default Settings Used: Yes

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 3 (default)

Idle Duration (mins): 0 (default)

Approach Duration (mins): 12 (default)

Intermediate Duration (mins): 0 (default)

Military Duration (mins): 8 (default)

After Burner Duration (mins): 2 (default)

48.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

48.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

TestCell = TestCellPS_{IDLE} + TestCellPS_{APPROACH} + TestCellPS_{INTERMEDIATE} + TestCellPS_{MILITARY} + TestCellPS_{AFTERBURN}

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

49. Aircraft

49.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2031 T-38 Removal Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1

Start Year: 2031

- Activity End Date

Indefinite: No

End Month: 12

End Year: 2031

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	-1.147371
SO _x	-0.286165
NO _x	-0.827665
CO	-14.756714
PM 10	-0.310973

Pollutant	Total Emissions (TONs)
PM 2.5	-0.112445
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-864.9

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	-0.740483
SO _x	-0.192132
NO _x	-0.547026
CO	-9.771306
PM 10	-0.204437

Pollutant	Total Emissions (TONs)
PM 2.5	-0.069810
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-580.7

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	-0.406889
SO _x	-0.094033
NO _x	-0.280639
CO	-4.985408
PM 10	-0.106537

Pollutant	Total Emissions (TONs)
PM 2.5	-0.042635
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-284.2

49.2 Aircraft & Engines

49.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

49.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

49.3 Flight Operations

49.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 81
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 3

- Default Settings Used: No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	12.8
Takeoff [Military] (mins):	0.2
Takeoff [After Burn] (mins):	0.2
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	3.8
Taxi/Idle In [Idle] (mins):	6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

49.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

49.4 Auxiliary Power Unit (APU)

49.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

49.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

49.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU: Number of Auxiliary Power Units
OH: Operation Hours for Each LTO (hour)
LTO: Number of LTOs
EF_{POL}: Emission Factor for Pollutant (lb/hr)
2000: Conversion Factor pounds to tons

49.5 Aircraft Engine Test Cell

49.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 81

- **Default Settings Used:** Yes

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 3 (default)
Idle Duration (mins): 0 (default)
Approach Duration (mins): 12 (default)
Intermediate Duration (mins): 0 (default)
Military Duration (mins): 8 (default)
After Burner Duration (mins): 2 (default)

49.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

49.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$\text{TestCellPS}_{\text{POL}} = (\text{TD} / 60) * (\text{FC} / 1000) * \text{EF} * \text{NE} * \text{ARU} / 2000$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} +$

$\text{TestCellPS}_{\text{AFTERBURN}}$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

50. Personnel

50.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add
- Activity Location
 - County: Bexar
 - Regulatory Area(s): San Antonio, TX
- Activity Title: 2023 Increase 303 Personnel INDEFINITE
- Activity Description:
- Activity Start Date
 - Start Month: 1
 - Start Year: 2023
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.620085
SO _x	0.004562
NO _x	0.528932
CO	7.305354
PM 10	0.013181

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.011378
Pb	0.000000
NH ₃	0.041964
CO _{2e}	668.7

50.2 Personnel Assumptions

- Number of Personnel
 - Active Duty Personnel: 303
 - Civilian Personnel: 0
 - Support Contractor Personnel: 0
 - Air National Guard (ANG) Personnel: 0
 - Reserve Personnel: 0
- Default Settings Used: Yes
- Average Personnel Round Trip Commute (mile): 20 (default)
- Personnel Work Schedule
 - Active Duty Personnel: 5 Days Per Week (default)
 - Civilian Personnel: 5 Days Per Week (default)
 - Support Contractor Personnel: 5 Days Per Week (default)
 - Air National Guard (ANG) Personnel: 4 Days Per Week (default)
 - Reserve Personnel: 4 Days Per Month (default)

50.3 Personnel On Road Vehicle Mixture

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- On Road Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	37.55	60.32	0	0.03	0.2	0	1.9
GOVs	54.49	37.73	4.67	0	0	3.11	0

50.4 Personnel Emission Factor(s)

- On Road Vehicle Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
LDGV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859
LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HDCV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007
LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

50.5 Personnel Formula(s)

- Personnel Vehicle Miles Travel for Work Days per Year

$$VMT_p = NP * WD * AC$$

- VMT_p: Personnel Vehicle Miles Travel (miles/year)
- NP: Number of Personnel
- WD: Work Days per Year
- AC: Average Commute (miles)

- Total Vehicle Miles Travel per Year

$$VMT_{Total} = VMT_{AD} + VMT_C + VMT_{SC} + VMT_{ANG} + VMT_{AFRC}$$

- VMT_{Total}: Total Vehicle Miles Travel (miles)
- VMT_{AD}: Active Duty Personnel Vehicle Miles Travel (miles)
- VMT_C: Civilian Personnel Vehicle Miles Travel (miles)
- VMT_{SC}: Support Contractor Personnel Vehicle Miles Travel (miles)
- VMT_{ANG}: Air National Guard Personnel Vehicle Miles Travel (miles)
- VMT_{AFRC}: Reserve Personnel Vehicle Miles Travel (miles)

- Vehicle Emissions per Year

$$V_{POL} = (VMT_{Total} * 0.002205 * EF_{POL} * VM) / 2000$$

- V_{POL}: Vehicle Emissions (TONs)
- VMT_{Total}: Total Vehicle Miles Travel (miles)
- 0.002205: Conversion Factor grams to pounds
- EF_{POL}: Emission Factor for Pollutant (grams/mile)
- VM: Personnel On Road Vehicle Mixture (%)
- 2000: Conversion Factor pounds to tons

51. Heating

51.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Location

County: Bexar
Regulatory Area(s): San Antonio, TX

- Activity Title: 2023 Heating for Buildings INDEFINITE

- Activity Description:

- Activity Start Date

Start Month: 1
Start Year: 2023

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.028510
SO _x	0.003110
NO _x	0.518357
CO	0.435420
PM 10	0.039395

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.039395
Pb	0.000000
NH ₃	0.000000
CO _{2e}	624.0

51.2 Heating Assumptions

- Heating

Heating Calculation Type: Heat Energy Requirement Method

- Heat Energy Requirement Method

Area of floorspace to be heated (ft²): 100885
Type of fuel: Natural Gas
Type of boiler/furnace: Industrial (10 - 250 MMBtu/hr)
Heat Value (MMBtu/ft³): 0.00105
Energy Intensity (MMBtu/ft²): 0.1079

- Default Settings Used: Yes

- Boiler/Furnace Usage

Operating Time Per Year (hours): 900 (default)

51.3 Heating Emission Factor(s)

- Heating Emission Factors (lb/1000000 scf)

VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
5.5	0.6	100	84	7.6	7.6			120390

51.4 Heating Formula(s)

- Heating Fuel Consumption ft³ per Year

$$FC_{HER} = HA * EI / HV / 1000000$$

FC_{HER}: Fuel Consumption for Heat Energy Requirement Method

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

HA: Area of floorspace to be heated (ft²)
EI: Energy Intensity Requirement (MMBtu/ft²)
HV: Heat Value (MMBTU/ft³)
1000000: Conversion Factor

- Heating Emissions per Year

$$HE_{POL} = FC * EF_{POL} / 2000$$

HE_{POL}: Heating Emission Emissions (TONs)
FC: Fuel Consumption
EF_{POL}: Emission Factor for Pollutant
2000: Conversion Factor pounds to tons

52. Construction / Demolition

52.1 General Information & Timeline Assumptions

- Activity Location

County: Bexar
Regulatory Area(s): San Antonio, TX

- Activity Title: Construction and Demolition

- Activity Description:

- Activity Start Date

Start Month: 1
Start Month: 2022

- Activity End Date

Indefinite: False
End Month: 12
End Month: 2022

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.526940
SO _x	0.005198
NO _x	2.123360
CO	2.303931
PM 10	3.635660

Pollutant	Total Emissions (TONs)
PM 2.5	0.094714
Pb	0.000000
NH ₃	0.001988
CO ₂ e	506.5

52.1 Site Grading Phase

52.1.1 Site Grading Phase Timeline Assumptions

- Phase Start Date

Start Month: 1
Start Quarter: 1
Start Year: 2022

- Phase Duration

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Month: 1
 Number of Days: 0

52.1.2 Site Grading Phase Assumptions

- General Site Grading Information

Area of Site to be Graded (ft²): 322910
 Amount of Material to be Hauled On-Site (yd³): 0
 Amount of Material to be Hauled Off-Site (yd³): 0

- Site Grading Default Settings

Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Graders Composite	1	8
Other Construction Equipment Composite	1	8
Rubber Tired Dozers Composite	1	8
Tractors/Loaders/Backhoes Composite	2	7

- Vehicle Exhaust

Average Hauling Truck Capacity (yd³): 20 (default)
 Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

52.1.3 Site Grading Phase Emission Factor(s)

- Construction Exhaust Emission Factors (lb/hour) (default)

Graders Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0806	0.0014	0.4657	0.5731	0.0217	0.0217	0.0072	132.92
Other Construction Equipment Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0507	0.0012	0.2785	0.3488	0.0105	0.0105	0.0045	122.61
Rubber Tired Dozers Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.1919	0.0024	1.3611	0.7352	0.0536	0.0536	0.0173	239.51
Tractors/Loaders/Backhoes Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0383	0.0007	0.2301	0.3598	0.0095	0.0095	0.0034	66.884

- Vehicle Exhaust & Worker Trips Emission Factors (grams/mile)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
LDGV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859
LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HDGV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007
LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

52.1.4 Site Grading Phase Formula(s)

- Fugitive Dust Emissions per Phase

$$PM10_{FD} = (20 * ACRE * WD) / 2000$$

PM10_{FD}: Fugitive Dust PM 10 Emissions (TONs)

20: Conversion Factor Acre Day to pounds (20 lb / 1 Acre Day)

ACRE: Total acres (acres)

WD: Number of Total Work Days (days)

2000: Conversion Factor pounds to tons

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * EF_{POL}) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)

NE: Number of Equipment

WD: Number of Total Work Days (days)

H: Hours Worked per Day (hours)

EF_{POL}: Emission Factor for Pollutant (lb/hour)

2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = (HA_{OnSite} + HA_{OffSite}) * (1 / HC) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

HA_{OnSite}: Amount of Material to be Hauled On-Site (yd³)

HA_{OffSite}: Amount of Material to be Hauled Off-Site (yd³)

HC: Average Hauling Truck Capacity (yd³)

(1 / HC): Conversion Factor cubic yards to trips (1 trip / HC yd³)

HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Vehicle Exhaust On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)

WD: Number of Total Work Days (days)

WT: Average Worker Round Trip Commute (mile)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1.25: Conversion Factor Number of Construction Equipment to Number of Works

NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)

VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL} : Emission Factor for Pollutant (grams/mile)

VM: Worker Trips On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

52.2 Trenching/Excavating Phase

52.2.1 Trenching / Excavating Phase Timeline Assumptions

- Phase Start Date

Start Month: 2

Start Quarter: 1

Start Year: 2022

- Phase Duration

Number of Month: 1

Number of Days: 0

52.2.2 Trenching / Excavating Phase Assumptions

- General Trenching/Excavating Information

Area of Site to be Trenched/Excavated (ft²): 33000

Amount of Material to be Hauled On-Site (yd³): 0

Amount of Material to be Hauled Off-Site (yd³): 0

- Trenching Default Settings

Default Settings Used: Yes

Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Excavators Composite	2	8
Other General Industrial Equipmen Composite	1	8
Tractors/Loaders/Backhoes Composite	1	8

- Vehicle Exhaust

Average Hauling Truck Capacity (yd³): 20 (default)

Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HdGV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

	LDGV	LDGT	HdGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

52.2.3 Trenching / Excavating Phase Emission Factor(s)

- Construction Exhaust Emission Factors (lb/hour) (default)

Graders Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0806	0.0014	0.4657	0.5731	0.0217	0.0217	0.0072	132.92
Other Construction Equipment Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0507	0.0012	0.2785	0.3488	0.0105	0.0105	0.0045	122.61
Rubber Tired Dozers Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.1919	0.0024	1.3611	0.7352	0.0536	0.0536	0.0173	239.51
Tractors/Loaders/Backhoes Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0383	0.0007	0.2301	0.3598	0.0095	0.0095	0.0034	66.884

- Vehicle Exhaust & Worker Trips Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
LDGV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859
LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HdGV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007
LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

52.2.4 Trenching / Excavating Phase Formula(s)

- Fugitive Dust Emissions per Phase

$$PM10_{FD} = (20 * ACRE * WD) / 2000$$

PM10_{FD}: Fugitive Dust PM 10 Emissions (TONs)

20: Conversion Factor Acre Day to pounds (20 lb / 1 Acre Day)

ACRE: Total acres (acres)

WD: Number of Total Work Days (days)

2000: Conversion Factor pounds to tons

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * EF_{POL}) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)

NE: Number of Equipment

WD: Number of Total Work Days (days)

H: Hours Worked per Day (hours)

EF_{POL}: Emission Factor for Pollutant (lb/hour)

2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = (HA_{OnSite} + HA_{OffSite}) * (1 / HC) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

HA_{OnSite}: Amount of Material to be Hauled On-Site (yd³)
HA_{OffSite}: Amount of Material to be Hauled Off-Site (yd³)
HC: Average Hauling Truck Capacity (yd³)
(1 / HC): Conversion Factor cubic yards to trips (1 trip / HC yd³)
HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)
0.002205: Conversion Factor grams to pounds
EF_{POL}: Emission Factor for Pollutant (grams/mile)
VM: Vehicle Exhaust On Road Vehicle Mixture (%)
2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)
WD: Number of Total Work Days (days)
WT: Average Worker Round Trip Commute (mile)
1.25: Conversion Factor Number of Construction Equipment to Number of Works
NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
VMT_{VE}: Worker Trips Vehicle Miles Travel (miles)
0.002205: Conversion Factor grams to pounds
EF_{POL}: Emission Factor for Pollutant (grams/mile)
VM: Worker Trips On Road Vehicle Mixture (%)
2000: Conversion Factor pounds to tons

52.3 Building Construction Phase

52.3.1 Building Construction Phase Timeline Assumptions

- Phase Start Date

Start Month: 3
Start Quarter: 1
Start Year: 2022

- Phase Duration

Number of Month: 10
Number of Days: 0

52.3.2 Building Construction Phase Assumptions

- General Building Construction Information

Building Category: Office or Industrial
Area of Building (ft²): 101000
Height of Building (ft): 12
Number of Units: N/A

- Building Construction Default Settings

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Cranes Composite	1	6
Forklifts Composite	2	6
Generator Sets Composite	1	8
Tractors/Loaders/Backhoes Composite	1	8
Welders Composite	3	8

- Vehicle Exhaust

Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

- Vendor Trips

Average Vendor Round Trip Commute (mile): 40 (default)

- Vendor Trips Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

52.3.3 Building Construction Phase Emission Factor(s)

- Construction Exhaust Emission Factors (lb/hour) (default)

Cranes Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0797	0.0013	0.5505	0.3821	0.0203	0.0203	0.0071	128.81
Forklifts Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0274	0.0006	0.1265	0.2146	0.0043	0.0043	0.0024	54.457
Generator Sets Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0340	0.0006	0.2783	0.2694	0.0116	0.0116	0.0030	61.069
Tractors/Loaders/Backhoes Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0383	0.0007	0.2301	0.3598	0.0095	0.0095	0.0034	66.884
Welders Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0260	0.0003	0.1557	0.1772	0.0077	0.0077	0.0023	25.661

- Vehicle Exhaust & Worker Trips Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
--	-----	-----------------	-----------------	----	-------	--------	----	-----------------	------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

LDGV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859
LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HDGV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007
LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

52.3.4 Building Construction Phase Formula(s)

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * EF_{POL}) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)

NE: Number of Equipment

WD: Number of Total Work Days (days)

H: Hours Worked per Day (hours)

EF_{POL}: Emission Factor for Pollutant (lb/hour)

2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = BA * BH * (0.42 / 1000) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

BA: Area of Building (ft²)

BH: Height of Building (ft)

(0.42 / 1000): Conversion Factor ft³ to trips (0.42 trip / 1000 ft³)

HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Worker Trips On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)

WD: Number of Total Work Days (days)

WT: Average Worker Round Trip Commute (mile)

1.25: Conversion Factor Number of Construction Equipment to Number of Works

NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Worker Trips On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Vender Trips Emissions per Phase

$$VMT_{VT} = BA * BH * (0.38 / 1000) * HT$$

- VMT_{VT}: Vender Trips Vehicle Miles Travel (miles)
- BA: Area of Building (ft²)
- BH: Height of Building (ft)
- (0.38 / 1000): Conversion Factor ft³ to trips (0.38 trip / 1000 ft³)
- HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VT} * 0.002205 * EF_{POL} * VM) / 2000$$

- V_{POL}: Vehicle Emissions (TONs)
- VMT_{VT}: Vender Trips Vehicle Miles Travel (miles)
- 0.002205: Conversion Factor grams to pounds
- EF_{POL}: Emission Factor for Pollutant (grams/mile)
- VM: Worker Trips On Road Vehicle Mixture (%)
- 2000: Conversion Factor pounds to tons

52.4 Architectural Coatings Phase

52.4.1 Architectural Coatings Phase Timeline Assumptions

- Phase Start Date

Start Month: 12
 Start Quarter: 1
 Start Year: 2022

- Phase Duration

Number of Month: 1
 Number of Days: 0

52.4.2 Architectural Coatings Phase Assumptions

- General Architectural Coatings Information

Building Category: Non-Residential
 Total Square Footage (ft²): 15200
 Number of Units: N/A

- Architectural Coatings Default Settings

Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

52.4.3 Architectural Coatings Phase Emission Factor(s)

- Worker Trips Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
LDGV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HDGV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007
LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

52.4.4 Architectural Coatings Phase Formula(s)

- Worker Trips Emissions per Phase

$$VMT_{WT} = (1 * WT * PA) / 800$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)

1: Conversion Factor man days to trips (1 trip / 1 man * day)

WT: Average Worker Round Trip Commute (mile)

PA: Paint Area (ft²)

800: Conversion Factor square feet to man days (1 ft² / 1 man * day)

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Worker Trips On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

- Off-Gassing Emissions per Phase

$$VOC_{AC} = (AB * 2.0 * 0.0116) / 2000.0$$

VOC_{AC}: Architectural Coating VOC Emissions (TONs)

BA: Area of Building (ft²)

2.0: Conversion Factor total area to coated area (2.0 ft² coated area / total area)

0.0116: Emission Factor (lb/ft²)

2000: Conversion Factor pounds to tons

52.5 Paving Phase

52.5.1 Paving Phase Timeline Assumptions

- Phase Start Date

Start Month: 12

Start Quarter: 1

Start Year: 2022

- Phase Duration

Number of Month: 1

Number of Days: 0

52.5.2 Paving Phase Assumptions

- General Paving Information

Paving Area (ft²): 244000

- Paving Default Settings

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Pavers Composite	1	8
Paving Equipment Composite	2	6
Rollers Composite	2	6

- Vehicle Exhaust

Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

52.5.3 Paving Phase Emission Factor(s)

- Construction Exhaust Emission Factors (lb/hour) (default)

Graders Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0806	0.0014	0.4657	0.5731	0.0217	0.0217	0.0072	132.92
Other Construction Equipment Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0507	0.0012	0.2785	0.3488	0.0105	0.0105	0.0045	122.61
Rubber Tired Dozers Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.1919	0.0024	1.3611	0.7352	0.0536	0.0536	0.0173	239.51
Tractors/Loaders/Backhoes Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0383	0.0007	0.2301	0.3598	0.0095	0.0095	0.0034	66.884

- Vehicle Exhaust & Worker Trips Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
LDGV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859
LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HDCV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007
LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

52.5.4 Paving Phase Formula(s)

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * EF_{POL}) / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

CEE_{POL}: Construction Exhaust Emissions (TONs)

NE: Number of Equipment

WD: Number of Total Work Days (days)

H: Hours Worked per Day (hours)

EF_{POL}: Emission Factor for Pollutant (lb/hour)

2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = PA * 0.25 * (1 / 27) * (1 / HC) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

PA: Paving Area (ft²)

0.25: Thickness of Paving Area (ft)

(1 / 27): Conversion Factor cubic feet to cubic yards (1 yd³ / 27 ft³)

HC: Average Hauling Truck Capacity (yd³)

(1 / HC): Conversion Factor cubic yards to trips (1 trip / HC yd³)

HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Vehicle Exhaust On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)

WD: Number of Total Work Days (days)

WT: Average Worker Round Trip Commute (mile)

1.25: Conversion Factor Number of Construction Equipment to Number of Works

NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{VE}: Worker Trips Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Worker Trips On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

- Off-Gassing Emissions per Phase

$$VOC_P = (2.62 * PA) / 43560$$

VOC_P: Paving VOC Emissions (TONs)

2.62: Emission Factor (lb/acre)

PA: Paving Area (ft²)

43560: Conversion Factor square feet to acre (43560 ft² / acre)² / acre)

E-2 SEGUIN AAF (GUADALUPE COUNTY)

The content of Section E-2 presents the data and methodology used for preparing aircraft operations data for the ACAM modeling followed by the ACAM results. The data in Section E-2 represents all operations that occur in Guadalupe County associated with the Proposed Action and Action Alternatives.

This section includes the following:

- Seguin AAF operation numbers
- Seguin AAF T-7 TIMs Summary
- Seguin AAF T-7 TIMs Ground Idle Times
- Seguin AAF T-7 TIMS Arrivals
- Seguin AAF T-7 Closed Patterns
- Seguin AAF T-7 TIMS Departures
- Seguin AAF T-7 TIMS Errors and Omissions
- Outside Bexar County T-7 & T-38 TIMS Summary
- Proposed Action ACAM Report
- Proposed Action ACAM Detailed Report
- Alternative 1 ACAM Report
- Alternative 1 ACAM Detailed Report
- Alternative 2 ACAM Report
- Alternative 2 ACAM Detailed Report
- Alternative 3 ACAM Report
- Alternative 3 ACAM Detailed Report

PROPOSED ACTION

T-7A Beddown Seguin AAF
 (All values in total number for specified year)

Not a final analysis

		Baseline Year											
		2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033
T-7A	Total number of <i>sorties all permanent AETC T-7A's</i> will complete at Seguin AAF?	0	0	0	0	0	0	0	0	0	0	0	0
	Total number of <i>closed patterns all permanent AETC T-7A's</i> will complete at the Seguin AAF?	0	645	2,880	13,200	21,200	30,320	35,280	38,560	39,440	39,920	41,200	41,200
net change:			645	2,235	10,320	8,000	9,120	4,960	3,280	880	480	1,280	0
		2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033
T-38C	Total number of <i>sorties all permanent AETC T-38C's</i> will complete at Seguin AAF?	0	0	0	0	0	0	0	0	0	0	0	0
	Total number of <i>closed patterns all permanent AETC T-38C's</i> will complete at Seguin AAF? ^b	42,000	57,400	56,700	46,100	39,800	28,700	21,100	16,700	10,800	2,680	0	0
net change:			15,400	-700	-10,600	-6,300	-11,100	-7,600	-4,400	-5,900	-8,120	-2,680	0

ONLY CHANGE VALUES IN RED TEXT IN BLUE SHADED BOXES

ONLY CHANGE VALUES IN RED TEXT IN BLUE SHADED BOXES

Alternative 1

T-7A Beddown Seguin AAF
 (All values in total number for specified year)

Not a final analysis

		Baseline Year											
		2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033
T-7A	Total number of sorties all permanent AETC T-7A's will complete at Seguin AAF?	0	0	0	0	0	0	0	0	0	0	0	0
	Total number of closed patterns all permanent AETC T-7A's will complete at the Seguin AAF?	0	645	2,880	13,200	21,200	30,320	32,562	32,562	32,562	32,562	32,562	32,562
net change			645	2,235	10,320	8,000	9,120	2,242	0	0	0	0	0
		2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033
T-38C	Total number of sorties all permanent AETC T-38C's will complete at Seguin AAF?	0	0	0	0	0	0	0	0	0	0	0	0
	Total number of closed patterns all permanent AETC T-38C's will complete at Seguin AAF? ^b	42,000	57,400	56,700	46,100	39,800	28,700	0	0	0	0	0	0
NET CHANGE			15,400	-700	-10,600	-6,300	-11,100	-28,700	0	0	0	0	0

ONLY CHANGE VALUES IN RED TEXT IN BLUE SHADED BOXES

ONLY CHANGE VALUES IN RED TEXT IN BLUE SHADED BOXES

Alternative 2

T-7A Beddown Seguin AAF
 (All values in total number for specified year)

Not a final analysis

		Baseline Year											
		2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033
T-7A	Total number of sorties all permanent AETC T-7A's will complete at Seguin AAF?	0	0	0	0	0	0	0	0	0	0	0	0
	Total number of closed patterns all permanent AETC T-7A's will complete at the Seguin AAF?	0	645	3,312	15,180	24,380	34,868	40,572	44,344	45,356	45,908	47,380	47,380
NET CHANGE			645	2,667	11,868	9,200	10,488	5,704	3,772	1,012	552	1,472	0
		2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033
T-38C	Total number of sorties all permanent AETC T-38C's will complete at Seguin AAF?	0	0	0	0	0	0	0	0	0	0	0	0
	Total number of closed patterns all permanent AETC T-38C's will complete at Seguin AAF? ^b	42,000	57,400	56,700	46,100	39,800	28,700	21,100	16,700	10,800	2,680	0	0
NET CHANGE			15,400	-700	-10,600	-6,300	-11,100	-7,600	-4,400	-5,900	-8,120	-2,680	0

ONLY CHANGE VALUES
 IN RED TEXT IN BLUE
 SHADED BOXES

ONLY CHANGE VALUES
 IN RED TEXT IN BLUE
 SHADED BOXES

Alternative 3

T-7A Beddown Seguin AAF
 (All values in total number for specified year)

Not a final analysis

		Baseline Year											
		2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033
T-7A	Total number of <i>sorties all permanent AETC T-7A's</i> will complete at Seguin AAF?	0	0	0	0	0	0	0	0	0	0	0	0
	Total number of <i>closed patterns all permanent AETC T-7A's</i> will complete at the Seguin AAF?	0	645	3,600	16,500	26,500	37,900	44,100	48,200	49,300	49,900	51,500	51,500
NET CHANGE			645	2,955	12,900	10,000	11,400	6,200	4,100	1,100	600	1,600	0
		2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033
T-38C	Total number of <i>sorties all permanent AETC T-38C's</i> will complete at Seguin AAF?	0	0	0	0	0	0	0	0	0	0	0	0
	Total number of <i>closed patterns all permanent AETC T-38C's</i> will complete at Seguin AAF? ^b	42,000	57,400	56,700	46,100	39,800	28,700	21,100	16,700	10,800	2,680	0	0
NET CHANGE			15,400	-700	-10,600	-6,300	-11,100	-7,600	-4,400	-5,900	-8,120	-2,680	0

ONLY CHANGE VALUES IN RED TEXT IN BLUE SHADED BOXES

ONLY CHANGE VALUES IN RED TEXT IN BLUE SHADED BOXES

Seguin AAF T-7 TIMs Summary						
	Idle In	Idle Out	Takeoff AB	Takeoff Mil	Climbout	Approach
LTO Flight	0.00	0.00	0.00	0.52	2.33	6.48
LTO Taxi	3.17	8.17	0.00	0.00	0.00	0.00
Total LTO	3.17	8.17	0.00	0.52	2.33	6.48
Closed Patterns	0.00	0.00	0.00	0.93	1.91	2.50

Methodology and Scientific Integrity

Methodology:

Air impact analyses are based on “reasonably foreseeable” estimated net annual emissions of criteria pollutants. Reasonably foreseeable actions include “activities not yet taken, but sufficiently likely to occur” and “do not include those actions that are highly speculative” (43 CFR 46.30). Estimated annual emissions from aircraft flight operations are determined from Annual Representative Flight Operations Cycles: Landing and Takeoff Cycle (LTO Cycle, includes arrivals and departures), Closed Pattern Cycle (CP Cycle), and Low Flight Pattern Cycle (LFP Cycle).

Within the U.S. Air Force, these Annual Representative Flight Operations Cycles are derived through weighted-averaging and utilizing the site-specific flight operational data (i.e., noise profile data) collected specifically for a location-specific noise analysis (for specific methodology see Standardized Procedures for Deriving Flight Operations Cycles from Noise Flight Profiles, AFCEC/CZTQ, 13 May 2020).

The current U.S. Air Force methodology for establishing site-specific flight operational data (i.e., noise profile data) is a single pilot interview where the pilot is asked to recollect and record flight parameter data by drawing points on a map and then estimating the distance flown, elevation, power setting, and airspeed at each point. Noise profile data collected from a single pilot recollection of specific flight parameter data is extremely imprecise and relatively speculative in nature at best. However, given the alternative is to use EPA default Annual Representative Flight Operations Cycles that are outdated and unverifiable; the U.S. Air Force believes the noise profile data is currently the best available data.

Professional and Scientific Integrity

As with all modelling, air quality must apply a statistical approach to modelling for ensuring the scientific integrity of the results. In accordance with 40 CFR 1502.23 “agencies shall ensure the professional integrity, including scientific integrity, of the discussions and analyses” and “shall make use of reliable existing data and resources”.

Noise profile data, used for deriving Annual Representative Flight Operations Cycles (LTO, CP, and LFP Cycles), is far from perfect data for air impact analyses. Because noise profile data was not collected or intended for air impact analyses, it has errors and omissions (incomplete information needed for air quality); therefore, you cannot simply pull noise profile data into an air analysis. Noise profile data collected from a single pilot recollection of specific flight parameter data is extremely imprecise and relatively speculative; therefore, this data has no quantifiable statistical validity. Additionally, most of the critical data points (e.g. at 500 and 3,000 ft AGL) are not included and require rough interpolations to derive. Generally, over 95% of all profiles have errors and omissions; therefore, using noise profile data for air quality requires an extensive engineering effort to derive incomplete and/or missing critical data points. See the Errors and Omissions Table to view the issues with the noise profiles data in this specific engineering analysis, for deriving Annual Representative Flight Operations Cycles, that required professional engineering judgement to resolve.

Data used outside of their intended purpose (e.g., noise data used for air analysis) must be inspected for anomalies (or outliers) to ensure the inclusion of these anomalies does not inadvertently and unwarrantedly bias the results of an air quality assessment. Given noise profile data is collected for capturing an “average busy day” (average worst-case day) versus air quality need for data representing an “average year”, the noise data is skewed which results in outliers (anomalies from the average) for air impact analyses. Identified outliers are generally not considered as “reassemble foreseeable” datapoints. As a result, as with all scientifically-sound modelling, these anomalies should normally be removed for an air analysis to ensure scientific integrity of the analysis results. However, the U.S. Air Force has chosen to include these anomalies in air impact analyses (i.e., use 100% of noise profiles regardless of potential bias).

Statistical analysis of emission results with and without inclusion of the anomalies was performed to assess the impact of the inclusion of the outliers (anomalies). The analysis indicated that the anomalies will be flown so infrequent that they will contribute no statistical difference (less than 1 ton/yr overall) to the estimated net annual emissions of any criteria pollutant.

Seguin - Randolph AFB Auxiliary T-7A Ground Idle Times

Taxi out (min)		Taxi in (min)
8.17		3.17

Taxi In/Out Times (min):

AIRCRAFT	BASE	RUNWAY #1	RW #1 CLOSEST DISTANCE (mile)	RW #1 FARTHEST DISTANCE (mile)	RUNWAY #2	RW #2 CLOSEST DISTANCE (mile)	RW #2 FARTHEST DISTANCE (mile)	AVERAGE IN OR OUT DISTANCE (mile)	AVERAGE IN OR OUT DISTANCE (nmi)	AVERAGE TAXI SPEED (Knt)	AVERAGE TAXI TIME IN OR OUT (Min)	LTO Taxi Distance (mile)	LTO Taxi Time (Min)
T-7	Seguin - Randolph AFB Auxiliary	13	0.32	1.87	31	0.32	1.87	1.095	0.952	18	3.17	2.19	6.34

Base-Specific Taxi-Time Study, 2020, Solutio Environmental Inc.

Ground Times Excluding Taxi (min):

MAJCOM	AIRCRAFT TYPE	AIRCRAFT	Pre-Taxi (e.g., startup)	Mid-Taxi Out (e.g., arm, hold, etc.)	RPM Run-up	Mid-Taxi In (e.g., de arm, hold, etc.)
AD	T	T-7A	0	5		0
Average	F	T-7	0	5		0

Mobile Source Engine Run Time Study, 2013, Prudent technologies Inc.

#075	T38 31S O1	Point "c" Power % RPM shows "88" as "Variable"	This data is erroneous and conflicts with itself as 88% power is "Climbout"	Assumed power setting is "Approach"
#076	T38 31S O1	Point "d" Power % RPM shows "80" as "Variable"	This data is erroneous and conflicts with itself as 80% power is "Climbout"	Assumed power setting is "Approach"
#077	T38 31S O1	Point "e" Power % RPM shows "88" as "Variable"	This data is erroneous and conflicts with itself as 88% power is "Climbout"	Assumed power setting is "Approach"
#078	T38 31S O1	Point "f" Power % RPM shows "88" as "Variable"	This data is erroneous and conflicts with itself as 88% power is "Climbout"	Assumed power setting is "Approach"
#079	T38 31S O1	Point "g" Power % RPM shows "80" as "Variable"	This data is erroneous and conflicts with itself as 80% power is "Climbout"	Assumed power setting is "Approach"
#080	T38 31S O1	Point "h" Power % RPM shows "95" as "Approach"	This data is erroneous and conflicts with itself as 95% power is "Military"	Assumed power setting is "Approach"
#081	T38 31S O1	Point "i" Power % RPM shows "89" as "Approach"	This data is erroneous and conflicts with itself as 89% power is "Climbout"	Assumed power setting is "Approach"
#082	T38 31S O1	Point "j" Power % RPM shows "88" as "Approach"	This data is erroneous and conflicts with itself as 88% power is "Climbout"	Assumed power setting is "Approach"
#083	T38 31S O1	Point "k" Power % RPM shows "88" as "Approach"	This data is erroneous and conflicts with itself as 88% power is "Climbout"	Assumed power setting is "Approach"
#084	T38 13S D1	Flight profile description of "Interfacility" should be "Departures"		Renamed "Departures"
#085	T38 31S D1	Flight profile description of "Interfacility" should be "Departures"		Renamed "Departures"
#086	T38 13S D2	Flight profile description of "Interfacility" should be "Departures"		Renamed "Departures"
#087	T38 31S D2	Flight profile description of "Interfacility" should be "Departures"		Renamed "Departures"

Outside Bexar County T-7 TIMs Summary						
	Idle In	Idle Out	Takeoff AB	Takeoff Mil	Climbout	Approach
LTO Flight Inside Bexar County	0.00	0.00	0.39	0.41	0.91	1.74
LTO Flight Total	0.00	0.00	0.39	0.51	1.43	6.26
LTO Flight Outside Bexar County	0.00	0.00	0.00	0.10	0.51	4.52
Closed Patterns Inside Bexar County	0.00	0.00	0.00	0.64	0.47	0.98
Closed Patterns Total	0.00	0.00	0.00	0.69	1.37	3.56
Closed Patterns Outside Bexar County	0.00	0.00	0.00	0.05	0.90	2.58

Outside Bexar County T-38 TIMs Summary						
	Idle In	Idle Out	Takeoff AB	Takeoff Mil	Climbout	Approach
LTO Flight Inside Bexar County	0.00	0.00	0.39	0.41	0.91	1.74
LTO Flight Total	0.00	0.00	0.39	0.51	1.43	6.26
LTO Flight Outside Bexar County	0.00	0.00	0.00	0.10	0.51	4.52
Closed Patterns Inside Bexar County	0.00	0.00	0.00	0.64	0.47	0.98
Closed Patterns Total	0.00	0.00	0.00	0.69	1.37	3.56
Closed Patterns Outside Bexar County	0.00	0.00	0.00	0.05	0.90	2.58

Methodology and Scientific Integrity

Methodology:

Air impact analyses are based on “reasonably foreseeable” estimated net annual emissions of criteria pollutants. Reasonably foreseeable actions include “activities not yet taken, but sufficiently likely to occur” and “do not include those actions that are highly speculative” (43 CFR 46.30). Estimated annual emissions from aircraft flight operations are determined from Annual Representative Flight Operations Cycles: Landing and Takeoff Cycle (LTO Cycle, includes arrivals and departures), Closed Pattern Cycle (CP Cycle), and Low Flight Pattern Cycle (LFP Cycle).

Within the U.S. Air Force, these Annual Representative Flight Operations Cycles are derived through weighted-averaging and utilizing the site-specific flight operational data (i.e., noise profile data) collected specifically for a location-specific noise analysis (for specific methodology see Standardized Procedures for Deriving Flight Operations Cycles from Noise Flight Profiles, AFCEC/CZTQ, 13 May 2020).

The current U.S. Air Force methodology for establishing site-specific flight operational data (i.e., noise profile data) is a single pilot interview where the pilot is asked to recollect and record flight parameter data by drawing points on a map and then estimating the distance flown, elevation, power setting, and airspeed at each point. Noise profile data collected from a single pilot recollection of specific flight parameter data is extremely imprecise and relatively speculative in nature at best. However, given the alternative is to use EPA default Annual Representative Flight Operations Cycles that are outdated and unverifiable; the U.S. Air Force believes the noise profile data is currently the best available data.

Professional and Scientific Integrity:

As with all modelling, air quality must apply a statistical approach to modelling for ensuring the scientific integrity of the results. In accordance with 40 CFR 1502.23 “agencies shall ensure the professional integrity, including scientific integrity, of the discussions and analyses” and “shall make use of reliable existing data and resources”.

Noise profile data, used for deriving Annual Representative Flight Operations Cycles (LTO, CP, and LFP Cycles), is far from perfect data for air impact analyses. Because noise profile data was not collected or intended for air impact analyses, it has errors and omissions (incomplete information needed for air quality); therefore, you cannot simply pull noise profile data into an air analysis. Noise

profile data collected from a single pilot recollection of specific flight parameter data is extremely imprecise and relatively speculative; therefore, this data has no quantifiable statistical validity. Additionally, most of the critical data points (e.g. at 500 and 3,000 ft AGL) are not included and require rough interpolations to derive. Generally, over 95% of all profiles have errors and omissions; therefore, using noise profile data for air quality requires an extensive engineering effort to derive incomplete and/or missing critical data points. See the Errors and Omissions Table to view the issues with the noise profiles data in this specific engineering analysis, for deriving Annual Representative Flight Operations Cycles, that required professional engineering judgement to resolve.

Data used outside of their intended purpose (e.g., noise data used for air analysis) must be inspected for anomalies (or outliers) to ensure the inclusion of these anomalies does not inadvertently and unwarrantedly bias the results of an air quality assessment. Given noise profile data is collected for capturing an “average busy day” (average worst-case day) versus air quality need for data representing an “average year”, the noise data is skewed which results in outliers (anomalies form the average) for air impact analyses. Identified outliers are generally not considered as “reassembly foreseeable” datapoints. As a result, as with all scientifically-sound modelling, these anomalies should normally be removed for an air analysis to ensure scientific integrity of the analysis results. However, the U.S. Air Force has chosen to include these anomalies in air impact analyses (i.e., use 100% of noise profiles regardless of potential bias).

Statistical analysis of emission results with and without inclusion of the anomalies was performed to assess the impact of the inclusion of the outliers (anomalies). The analysis indicated that the anomalies will be flown so infrequent that they will contribute no statistical difference (less than 1 ton/yr overall) to the estimated net annual emissions of any criteria pollutant.

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF AIR ANALYSIS (ROAA)

1. General Information: The Air Force's Air Conformity Applicability Model (ACAM) was used to perform an analysis to assess the potential air quality impact/s associated with the action in accordance with the Air Force Manual 32-7002, Environmental Compliance and Pollution Prevention; the Environmental Impact Analysis Process (EIAP, 32 CFR 989); and the General Conformity Rule (GCR, 40 CFR 93 Subpart B). This report provides a summary of the ACAM analysis.

a. Action Location:

Base: RANDOLPH AFB
State: Texas
County(s): Guadalupe
Regulatory Area(s): NOT IN A REGULATORY AREA

b. Action Title: Recapitalization of the T-38 Trainer At Randolph AFB - Proposed Action (Guadalupe County)

c. Project Number/s (if applicable):

d. Projected Action Start Date: 1 / 2023

e. Action Description:

The proposed action encompasses the recapitalize of the T-38 flight-training program with newer and more capable T-7A aircraft at JBSA-Randolph and Lackland. In addition to the phased introduction of the T-7A aircraft, five military construction projects and 17 facilities sustainment, restoration, and modernization projects are proposed at JBSA-Randolph at JBSA-Lackland to provide modern facilities and infrastructure to support the T-7A aircraft's maintenance, training, and operational requirements. The number of personnel on JBSA-Randolph would increase due to the proposed aircraft recapitalization. No changes to airspace configurations (i.e., size, shape, or location) would be required to support the proposed operations of the T-7A aircraft; however, the T-7A aircraft may have more flight operations than occurs with the T 38C aircraft at both JBSA-Randolph and JBSA-Lackland. This Applicability Analysis present the worst-case of three aircraft operational intensities as the worst-case action alternatives for the Proposed Action.

A Conformity Evaluation is required for every proposed action that will occur within an area designated by the U.S. Environmental Protection Agency (EPA) as nonattainment or maintenance for any National Ambient Air Quality Standard (NAAQS). The proposed T-7A Recapitalization action will occur at both JBSA-Randolph AFB and JBSA-Lackland AFB which both fall entirely within Bexar County that has been designated by the U.S. Environmental Protection Agency (EPA) as a marginal nonattainment area for the 2015 Ozone NAAQS in 2018. Given this recent designation of Bexar County, the proposed action (as well as all proposed actions from federal agencies) are subject to the General Conformity Rule (GCR, 40 CFR 93 Subpart B). As a marginal nonattainment area for ozone, the GCR has established de minimis significance threshold values of less than 100 ton/yr (for any given year) for both nitrogen oxides (NOx) and volatile organic compounds (VOC).

f. Point of Contact:

Name: [REDACTED]
Title: NEPA Contract Support
Organization: [REDACTED]
Email:
Phone Number:

2. Air Impact Analysis: Based on the attainment status at the action location, the requirements of the General Conformity Rule are:

_____ applicable
__X__ not applicable

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF AIR ANALYSIS (ROAA)

Total net direct and indirect emissions associated with the action were estimated through ACAM on a calendar-year basis for the start of the action through achieving “steady state” (i.e., net gain/loss upon action fully implemented) emissions. The ACAM analysis used the latest and most accurate emission estimation techniques available; all algorithms, emission factors, and methodologies used are described in detail in the USAF Air Emissions Guide for Air Force Stationary Sources, the USAF Air Emissions Guide for Air Force Mobile Sources, and the USAF Air Emissions Guide for Air Force Transitory Sources.

“Insignificance Indicators” were used in the analysis to provide an indication of the significance of potential impacts to air quality based on current ambient air quality relative to the National Ambient Air Quality Standards (NAAQSs). These insignificance indicators are the 250 ton/yr Prevention of Significant Deterioration (PSD) major source threshold for actions occurring in areas that are “Clearly Attainment” (i.e., not within 5% of any NAAQS) and the GCR de minimis values (25 ton/yr for lead and 100 ton/yr for all other criteria pollutants) for actions occurring in areas that are “Near Nonattainment” (i.e., within 5% of any NAAQS). These indicators do not define a significant impact; however, they do provide a threshold to identify actions that are insignificant. Any action with net emissions below the insignificance indicators for all criteria pollutant is considered so insignificant that the action will not cause or contribute to an exceedance on one or more NAAQSs. For further detail on insignificance indicators see chapter 4 of the Air Force Air Quality Environmental Impact Analysis Process (EIAP) Guide, Volume II - Advanced Assessments.

The action’s net emissions for every year through achieving steady state were compared against the Insignificance Indicator and are summarized below.

Analysis Summary:

2023

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	6.822	250	No
NO _x	7.947	250	No
CO	109.253	250	Yes
SO _x	2.163	250	No
PM 10	3.084	250	No
PM 2.5	1.424	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	6536.4		

2024

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	18.538	250	No
NO _x	20.527	250	No
CO	151.609	250	Yes
SO _x	3.448	250	No
PM 10	3.650	250	No
PM 2.5	1.990	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	10111.2		

2025

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF AIR ANALYSIS (ROAA)

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	17.851	250	No
NO _x	87.364	250	No
CO	39.012	250	No
SO _x	5.837	250	No
PM 10	0.650	250	No
PM 2.5	0.601	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	17347.6		

2026

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	18.699	250	No
NO _x	135.820	250	No
CO	-22.470	250	No
SO _x	8.130	250	No
PM 10	-1.006	250	No
PM 2.5	-0.130	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	24311.0		

2027

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	16.571	250	No
NO _x	198.407	250	No
CO	-153.605	250	No
SO _x	10.735	250	No
PM 10	-4.595	250	No
PM 2.5	-1.861	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	32245.9		

2028

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	13.627	250	No
NO _x	238.251	250	No
CO	-263.290	250	No
SO _x	12.233	250	No
PM 10	-7.594	250	No
PM 2.5	-3.378	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF AIR ANALYSIS (ROAA)

CO _{2e}	36798.1		
------------------	---------	--	--

2029

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	11.894	250	No
NO _x	255.117	250	Yes
CO	-317.450	250	No
SO _x	12.527	250	No
PM 10	-9.055	250	No
PM 2.5	-4.103	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	37693.4		

2030

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	7.950	250	No
NO _x	259.463	250	Yes
CO	-389.209	250	No
SO _x	11.873	250	No
PM 10	-11.028	250	No
PM 2.5	-5.115	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	35723.5		

2031

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	1.565	250	No
NO _x	259.848	250	Yes
CO	-494.603	250	No
SO _x	10.503	250	No
PM 10	-13.920	250	No
PM 2.5	-6.624	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	31579.3		

2032

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	1.794	250	No
NO _x	271.232	250	Yes
CO	-509.812	250	No
SO _x	11.144	250	No
PM 10	-14.364	250	No

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF AIR ANALYSIS (ROAA)

PM 2.5	-6.793	250	No
Pb	0.000	25	No
NH3	0.000	250	No
CO2e	33539.9		

2033 - (Steady State)

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	1.794	250	No
NOx	271.232	250	Yes
CO	-509.812	250	No
SOx	11.144	250	No
PM 10	-14.364	250	No
PM 2.5	-6.793	250	No
Pb	0.000	25	No
NH3	0.000	250	No
CO2e	33539.9		

The steady state estimated annual net emissions associated with this action exceed the insignificance indicators, indicating a potential for a significant impact to air quality. Therefore, the ACAM analysis is inconclusive and further air quality impact assessment is needed.

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1. General Information

- Action Location

Base: RANDOLPH AFB
State: Texas
County(s): Guadalupe
Regulatory Area(s): NOT IN A REGULATORY AREA

- Action Title: Recapitalization of the T-38 Trainer At Randolph AFB - Proposed Action (Guadalupe County)

- Project Number/s (if applicable):

- Projected Action Start Date: 1 / 2023

- Action Purpose and Need:

The T 38 Talon is a twin-engine, high-altitude, supersonic jet used by the USAF and other nations for pilot training. The aircraft originally was developed in the 1950s with production occurring between 1961 and 1972. The fleet has undergone periodic upgrades overtime. In 2001, the USAF upgraded several hundred T 38s with modern avionics and replaced propulsion components to provide increased performance and superior reliability.

The purpose of the Proposed Action is to allow the USAF T-7A to provide more efficient and effective pilot training to establish a T-7A pilot pipeline to allow for the transition to T-7A training throughout the entire USAF.

- Action Description:

The proposed action encompasses the recapitalize of the T-38 flight-training program with newer and more capable T-7A aircraft at JBSA-Randolph and Lackland. In addition to the phased introduction of the T-7A aircraft, five military construction projects and 17 facilities sustainment, restoration, and modernization projects are proposed at JBSA-Randolph at JBSA-Lackland to provide modern facilities and infrastructure to support the T-7A aircraft's maintenance, training, and operational requirements. The number of personnel on JBSA-Randolph would increase due to the proposed aircraft recapitalization. No changes to airspace configurations (i.e., size, shape, or location) would be required to support the proposed operations of the T-7A aircraft; however, the T-7A aircraft may have more flight operations than occurs with the T 38C aircraft at both JBSA-Randolph and JBSA-Lackland. This Applicability Analysis present the worst-case of three aircraft operational intensities as the worst-case action alternatives for the Proposed Action.

A Conformity Evaluation is required for every proposed action that will occur within an area designated by the U.S. Environmental Protection Agency (EPA) as nonattainment or maintenance for any National Ambient Air Quality Standard (NAAQS). The proposed T-7A Recapitalization action will occur at both JBSA-Randolph AFB and JBSA-Lackland AFB which both fall entirely within Bexar County that has been designated by the U.S. Environmental Protection Agency (EPA) as a marginal nonattainment area for the 2015 Ozone NAAQS in 2018. Given this recent designation of Bexar County, the proposed action (as well as all proposed actions from federal agencies) are subject to the General Conformity Rule (GCR, 40 CFR 93 Subpart B). As a marginal nonattainment area for ozone, the GCR has established de minimis significance threshold values of less than 100 ton/yr (for any given year) for both nitrogen oxides (NOx) and volatile organic compounds (VOC).

- Point of Contact

Name: [REDACTED]
Title: NEPA Contract Support
Organization: [REDACTED]
Email:
Phone Number:

- Activity List:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Activity Type		Activity Title
2.	Aircraft	T-7As and 759 LTOs OUTSIDE BEXAR COUNTY
3.	Aircraft	T-7A Increase 1,700 TGOs OUTSIDE BEXAR COUNTY
4.	Aircraft	T-38 Removal 5 TGOs OUTSIDE BEXAR COUNTY
5.	Aircraft	Add 10 T-7As and 1328 LTOs OUTSIDE BEXAR COUNTY
6.	Aircraft	Increase T-7A TGOs OUTSIDE BEXAR COUNTY
7.	Aircraft	Remove 11 T-38s and 2776LTOs OUTSIDE BEXAR COUNTY
8.	Aircraft	Remove 6142 T-38 TGOs OUTSIDE BEXAR COUNTY
9.	Aircraft	Add 7 new T-7As and 2836 LTOs OUTSIDE BEXAR COUNTY
10.	Aircraft	Increase T-7A TGOs by 6395 OUTSIDE BEXAR COUNTY
11.	Aircraft	Remove 7 T-38s and reduce LTOs by 1534 OUTSIDE BEXAR COUNTY
12.	Aircraft	Decrease T-38 TGOs by 3394 OUTSIDE BEXAR COUNTY
13.	Aircraft	Add T-7As and increase LTOs by 2698 OUTSIDE BEXAR COUNTY
14.	Aircraft	Increase T-7A TGOs by 6040 OUTSIDE BEXAR COUNTY
15.	Aircraft	Remove T-38s and decrease LTOs by 3767 OUTSIDE BEXAR COUNTY
16.	Aircraft	Decrease T-38 TGOs by 8,328 OUTSIDE BEXAR COUNTY
17.	Aircraft	Add 19 new T-7As and increase LTOs by 4918 OUTSIDE BEXAR COUNTY
18.	Aircraft	Increase T-7A TGOs by 10952 OUTSIDE BEXAR COUNTY
19.	Aircraft	Remove 21 T-38s and decrease LTOs by 3,667 OUTSIDE BEXAR COUNTY
20.	Aircraft	Decrease T-38 TGOs by 8093 OUTSIDE BEXAR COUNTY
21.	Aircraft	Add T-7As and increase LTOs by 4298 OUTSIDE BEXAR COUNTY
22.	Aircraft	Increase T-7A TGOs by 9527 OUTSIDE BEXAR COUNTY
23.	Aircraft	Remove T-38s and decrease LTOs by 1445 OUTSIDE BEXAR COUNTY
24.	Aircraft	Decrease T-38 TGOs by 3193 OUTSIDE BEXAR COUNTY
25.	Aircraft	Add T-7As and increase LTOs by 504 OUTSIDE BEXAR COUNTY
26.	Aircraft	Icrease T-7A TGOs by 1158 OUTSIDE OF BEXAR COUNTY
27.	Aircraft	RemoveT-38s and decrease LTOs by 1715 OUTSIDE OF BEXAR COUNTY
28.	Aircraft	Decrease T-38 TGOs by 3792 OUTSIDE OF BEXAR COUNTY
29.	Aircraft	increase LTOs by 261 OUTSIDE OF BEXAR COUNTY
30.	Aircraft	Increase TGOs by 590 OUTSIDE OF BEXAR COUNTY
31.	Aircraft	Remove 14 T-38s and decrease LTOs by 2636 OUTSIDE OF BEXAR COUNTY
32.	Aircraft	2031 T-38 Removal 5840 TGOs OUTSIDE BEXAR COUNTY
33.	Aircraft	decrease T-7A LTOs by 104 OUTSIDE BEXAR COUNTY
34.	Aircraft	decrease T-7A TGOs by 224 OUTSIDE BEXAR COUNTY
35.	Aircraft	Increase LTOs by 1242 OUTSIDE BEXAR COUNTY
36.	Aircraft	Increase T-7A TGOs by 2748 OUTSIDE BEXAR COUNTY
37.	Aircraft	2023 T-7A Seguin AAF Closed Patterns
38.	Aircraft	2023 T-38C Seguin AAF Closed Patterns
39.	Aircraft	2024 T-7A Seguin AAF Closed Patterns
40.	Aircraft	2024 T-38C Seguin AAF Closed Patterns
41.	Aircraft	2025 T-7A Seguin AAF Closed Patterns
42.	Aircraft	2025 T-38C Seguin AAF Closed Patterns
43.	Aircraft	2026 T-7A Seguin AAF Closed Patterns
44.	Aircraft	2026 T-38C Seguin AAF Closed Patterns
45.	Aircraft	2027 T-7A Seguin AAF Closed Patterns
46.	Aircraft	2027 T-38C Seguin AAF Closed Patterns
47.	Aircraft	2028 T-7A Seguin AAF Closed Patterns
48.	Aircraft	2028 T-38C Seguin AAF Closed Patterns
49.	Aircraft	2029 T-7A Seguin AAF Closed Patterns
50.	Aircraft	2029 T-38C seguin AAF Closed Patterns

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

51.	Aircraft	2030 T-7A Seguin AAF Closed Patterns
52.	Aircraft	2030 T-38C Seguin AAF Closed Patterns
53.	Aircraft	2031 T-7A Seguin AAF Closed Patterns
54.	Aircraft	2031 T-38C Seguin AAF Closed Patterns
55.	Aircraft	2032 T-7A Seguin AAF Closed Patterns
56.	Aircraft	2032 T-38C Seguin AAF Closed Patterns

Emission factors and air emission estimating methods come from the United States Air Force's Air Emissions Guide for Air Force Stationary Sources, Air Emissions Guide for Air Force Mobile Sources, and Air Emissions Guide for Air Force Transitory Sources.

2. Aircraft

2.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: T-7As and 759 LTOs OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2023 add 8 T-7As, and increase 759 LTOs

- Activity Start Date

Start Month: 1

Start Year: 2023

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.124692
SO _x	0.105199
NO _x	0.941128
CO	0.514749
PM 10	0.008812

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.007539
Pb	0.000000
NH ₃	0.000000
CO _{2e}	318.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.124692
SO _x	0.105199
NO _x	0.941128
CO	0.514749
PM 10	0.008812

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.007539
Pb	0.000000
NH ₃	0.000000
CO _{2e}	318.0

2.2 Aircraft & Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

2.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

2.3 Flight Operations

2.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 8
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 759
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.1
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.51
Approach [Approach] (mins): 4.52
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

2.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

2.4 Auxiliary Power Unit (APU)

2.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

2.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

2.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

3. Aircraft

3.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: T-7A Increase 1,700 TGOs OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2023 add 10 new T-7As, and increase 1,700TGOs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Start Date

Start Month: 1
Start Year: 2023

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.294061
SO _x	0.197961
NO _x	2.159129
CO	0.768998
PM 10	0.018946

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.016133
Pb	0.000000
NH ₃	0.000000
CO _{2e}	598.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.294061
SO _x	0.197961
NO _x	2.159129
CO	0.768998
PM 10	0.018946

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.016133
Pb	0.000000
NH ₃	0.000000
CO _{2e}	598.3

3.2 Aircraft & Engines

3.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

3.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

3.3 Flight Operations

3.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 10
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1700

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.05
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.9
Approach [Approach] (mins): 2.58
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

3.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
 AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
 AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
 AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
 AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
 AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
 AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
 AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
 AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

3.4 Auxiliary Power Unit (APU)

3.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

3.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

3.4.3 Auxiliary Power Unit (APU) Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

4. Aircraft

4.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: T-38 Removal 5 TGOs OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2024, remove 5 T-38 TGOs

- Activity Start Date

Start Month: 1

Start Year: 2024

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.001661
SO _x	-0.000289
NO _x	-0.000226
CO	-0.024829
PM 10	-0.000663

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.000393
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-0.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.001661
SO _x	-0.000289
NO _x	-0.000226
CO	-0.024829
PM 10	-0.000663

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.000393
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-0.9

4.2 Aircraft & Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

4.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

4.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

4.3 Flight Operations

4.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 91
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 5
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.05
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.9
Approach [Approach] (mins): 2.58
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

4.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

4.4 Auxiliary Power Unit (APU)

4.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

4.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

4.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

5. Aircraft

5.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Add 10 T-7As and 1328 LTOs OUTSIDE BEXAR COUNTY

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Description:

Starting in 2024 add 10 new T-7As, and increase 1328 LTO

- Activity Start Date

Start Month: 1
Start Year: 2024

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.218171
SO _x	0.184064
NO _x	1.646664
CO	0.900641
PM 10	0.015418

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.013191
Pb	0.000000
NH ₃	0.000000
CO _{2e}	556.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.218171
SO _x	0.184064
NO _x	1.646664
CO	0.900641
PM 10	0.015418

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.013191
Pb	0.000000
NH ₃	0.000000
CO _{2e}	556.3

5.2 Aircraft & Engines

5.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

5.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

5.3 Flight Operations

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

5.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	10
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	1328
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

5.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

5.4 Auxiliary Power Unit (APU)

5.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

5.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

5.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

6. Aircraft

6.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase T-7A TGOs OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2024 Increase T-7A TGOs 2931

- Activity Start Date

Start Month: 1

Start Year: 2024

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.510659
SO _x	0.425574
NO _x	4.228190
CO	1.717864
PM 10	0.032665

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.027814
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1302.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.510659
SO _x	0.425574

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.027814
Pb	0.000000

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NO _x	4.228190
CO	1.717864
PM 10	0.032665

NH ₃	0.000000
CO ₂ e	1302.9

6.2 Aircraft & Engines

6.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

6.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

6.3 Flight Operations

6.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 10
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 2931
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.05
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.9
Approach [Approach] (mins): 2.58
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AfterBurn (mins): 3

6.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

6.4 Auxiliary Power Unit (APU)

6.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

6.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

6.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

7. Aircraft

7.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove 11 T-38s and 2776LTOs OUTSIDE BEXAR COUNTY

- Activity Description:
 Starting in 2025 remove T-38s and 2776 LTOs

- Activity Start Date
 Start Month: 1
 Start Year: 2025

- Activity End Date
 Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.475438
SO _x	-0.228090
NO _x	-0.186752
CO	-20.882412
PM 10	-0.555171

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.347578
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-689.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.475438
SO _x	-0.228090
NO _x	-0.186752
CO	-20.882412
PM 10	-0.555171

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.347578
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-689.4

7.2 Aircraft & Engines

7.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

7.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

7.3 Flight Operations

7.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	11
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	2776
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

7.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)
AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

7.4 Auxiliary Power Unit (APU)

7.4.1 Auxiliary Power Unit (APU) Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

7.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

7.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

8. Aircraft

8.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove 6142 T-38 TGOs OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2025, remove 6142 T-38 TGOs

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-2.040612
SO _x	-0.355029
NO _x	-0.277701
CO	-30.500216

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.483192
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1073.1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

PM 10	-0.814230
-------	-----------

--	--

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-2.040612
SO _x	-0.355029
NO _x	-0.277701
CO	-30.500216
PM 10	-0.814230

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.483192
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1073.1

8.2 Aircraft & Engines

8.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

8.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

8.3 Flight Operations

8.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 11
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 6142
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.05
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.9
 Approach [Approach] (mins): 2.58

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

8.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
 AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
 AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

8.4 Auxiliary Power Unit (APU)

8.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

8.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

8.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

9. Aircraft

9.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Add 7 new T-7As and 2836 LTOs OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2025, add 7 new T-7As and 2836 LTOs

- Activity Start Date

Start Month: 1
 Start Year: 2025

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.469457
SO _x	0.474611
NO _x	4.005731
CO	2.302672
PM 10	0.032925

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.028169
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1450.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.469457
SO _x	0.474611
NO _x	4.005731
CO	2.302672
PM 10	0.032925

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.028169
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1450.5

9.2 Aircraft & Engines

9.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Aircraft Name:

Original Engine Name:

9.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

9.3 Flight Operations

9.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	7
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	2836
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

9.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

9.4 Auxiliary Power Unit (APU)

9.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

9.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

9.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

10. Aircraft

10.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase T-7A TGOs by 6395 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2025, increase T-7A TGOs by 6395

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.669170
SO _x	1.010052
NO _x	16.306460
CO	3.359047
PM 10	0.110952

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.095408
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3052.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.669170
SO _x	1.010052
NO _x	16.306460
CO	3.359047
PM 10	0.110952

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.095408
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3052.8

10.2 Aircraft & Engines

10.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

10.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

10.3 Flight Operations

10.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 7
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 6395
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.51

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

10.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

- AE_{TGO}: Aircraft Emissions (TONs)
- AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
- AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
- AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

- AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
- TD: Test Duration (min)
- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- NA: Number of Aircraft
- NTT: Number of Trim Test
- 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

10.4 Auxiliary Power Unit (APU)

10.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

10.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

10.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

11. Aircraft

11.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove 7 T-38s and reduce LTOs by 1534 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2026, remove 7 T-38s and reduce LTOs by 1534

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.815317
SO _x	-0.126041
NO _x	-0.103198
CO	-11.539488
PM 10	-0.306784

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.192069
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-381.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.815317
SO _x	-0.126041
NO _x	-0.103198
CO	-11.539488
PM 10	-0.306784

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.192069
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-381.0

11.2 Aircraft & Engines

11.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C

Engine Model: J85-GE-5R

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 2

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No
 - Original Aircraft Name:
 - Original Engine Name:

11.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

11.3 Flight Operations

11.3.1 Flight Operations Assumptions

- Flight Operations
 - Number of Aircraft: 7
 - Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1534
 - Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 - Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)
 - Taxi/Idle Out [Idle] (mins): 0
 - Takeoff [Military] (mins): 0.1
 - Takeoff [After Burn] (mins): 0
 - Climb Out [Intermediate] (mins): 0.51
 - Approach [Approach] (mins): 4.52
 - Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test
 - Idle (mins): 12
 - Approach (mins): 27
 - Intermediate (mins): 9
 - Military (mins): 9
 - AfterBurn (mins): 3

11.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
 TIM: Time in Mode (min)
 60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

11.4 Auxiliary Power Unit (APU)

11.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

11.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

11.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs
- EF_{POL}: Emission Factor for Pollutant (lb/hr)
- 2000: Conversion Factor pounds to tons

12. Aircraft

12.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove
- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA
- Activity Title: Decrease T-38 TGOs by 3394 OUTSIDE BEXAR COUNTY
- Activity Description:
 - Starting in 2026, decrease T-38 TGOs by 3394
- Activity Start Date
 - Start Month: 1
 - Start Year: 2026

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.127619
SO _x	-0.196185
NO _x	-0.153455
CO	-16.854076
PM 10	-0.449934

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.267007
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-593.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.127619
SO _x	-0.196185
NO _x	-0.153455
CO	-16.854076
PM 10	-0.449934

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.267007
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-593.0

12.2 Aircraft & Engines

12.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

12.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

12.3 Flight Operations

12.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 6
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3394

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.05
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.9
Approach [Approach] (mins): 2.58
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

12.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

12.4 Auxiliary Power Unit (APU)

12.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

12.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

12.4.3 Auxiliary Power Unit (APU) Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

13. Aircraft

13.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Add T-7As and increase LTOs by 2698 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2026, add T-7As and increase LTOs by 2698

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.443241
SO _x	0.373948
NO _x	3.345407
CO	1.829766
PM 10	0.031323

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.026799
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1130.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.443241
SO _x	0.373948
NO _x	3.345407
CO	1.829766
PM 10	0.031323

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.026799
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1130.2

13.2 Aircraft & Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

13.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

13.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

13.3 Flight Operations

13.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	2698
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

13.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

13.4 Auxiliary Power Unit (APU)

13.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

13.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

13.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

14. Aircraft

14.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase T-7A TGOs by 6040 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2026, increase T-7A TGOs by 6040

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Start Date

Start Month: 1
Start Year: 2026

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.052331
SO _x	0.876993
NO _x	8.713159
CO	3.540054
PM 10	0.067314

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.057318
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2684.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.052331
SO _x	0.876993
NO _x	8.713159
CO	3.540054
PM 10	0.067314

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.057318
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2684.8

14.2 Aircraft & Engines

14.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

14.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

14.3 Flight Operations

14.3.1 Flight Operations Assumptions

- Flight Operations

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Aircraft:	19
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	6040
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- **Default Settings Used:** No

- **Flight Operations TIMs (Time In Mode)**

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- **Trim Test**

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

14.3.2 Flight Operations Formula(s)

- **Aircraft Emissions per Mode for LTOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- **Aircraft Emissions for LTOs per Year**

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- **Aircraft Emissions per Mode for TGOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TIM: Time in Mode (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

14.4 Auxiliary Power Unit (APU)

14.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

14.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

14.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

15. Aircraft

15.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove T-38s and decrease LTOs by 3767 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2027, remove T-38s and decrease LTOs by 3,767

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-2.002152
SO _x	-0.309515
NO _x	-0.253420
CO	-28.337192
PM 10	-0.753361

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.471659
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-935.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-2.002152
SO _x	-0.309515
NO _x	-0.253420
CO	-28.337192

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.471659
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-935.5

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

PM 10	-0.753361
-------	-----------

--	--

15.2 Aircraft & Engines

15.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

15.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

15.3 Flight Operations

15.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 16
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3767
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.1
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.51
 Approach [Approach] (mins): 4.52
 Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

15.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

15.4 Auxiliary Power Unit (APU)

15.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

15.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

15.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

16. Aircraft

16.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Location

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Decrease T-38 TGOs by 8,328 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2027, decrease T-38 TGOs by 8,328

- Activity Start Date

Start Month: 1
 Start Year: 2027

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-2.766886
SO _x	-0.481388
NO _x	-0.376538
CO	-41.355552
PM 10	-1.104023

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.655165
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1455.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-2.766886
SO _x	-0.481388
NO _x	-0.376538
CO	-41.355552
PM 10	-1.104023

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.655165
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1455.0

16.2 Aircraft & Engines

16.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

16.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

16.3 Flight Operations

16.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	16
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	8328
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

16.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)
AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

16.4 Auxiliary Power Unit (APU)

16.4.1 Auxiliary Power Unit (APU) Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

16.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

16.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

17. Aircraft

17.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Add 19 new T-7As and increase LTOs by 4918 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2027, add 19 new T-7As and increase LTOs by 4918

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.807954
SO _x	0.681645
NO _x	6.098114

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.048849
Pb	0.000000
NH ₃	0.000000

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

CO	3.335356
PM 10	0.057096

CO _{2e}	2060.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.807954
SO _x	0.681645
NO _x	6.098114
CO	3.335356
PM 10	0.057096

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.048849
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2060.2

17.2 Aircraft & Engines

17.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

17.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

17.3 Flight Operations

17.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 19
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 4918
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.1
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.51
 Approach [Approach] (mins): 4.52
 Taxi/Idle In [Idle] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

17.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

17.4 Auxiliary Power Unit (APU)

17.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

17.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

17.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

18. Aircraft

18.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase T-7A TGOs by 10952 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2027, increase T-7A TGOs by 10952

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.908134
SO _x	1.590203
NO _x	15.799092
CO	6.418985
PM 10	0.122057

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.103932
Pb	0.000000
NH ₃	0.000000
CO _{2e}	4868.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.908134
SO _x	1.590203
NO _x	15.799092
CO	6.418985
PM 10	0.122057

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.103932
Pb	0.000000
NH ₃	0.000000
CO _{2e}	4868.3

18.2 Aircraft & Engines

18.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Aircraft Name:

Original Engine Name:

18.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

18.3 Flight Operations

18.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	19
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	10952
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

18.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

18.4 Auxiliary Power Unit (APU)

18.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

18.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

18.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

19. Aircraft

19.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove 21 T-38s and decrease LTOs by 3,667 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2028, remove 21 T-38s and decrease LTOs by 3,667

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.954317
SO _x	-0.302120
NO _x	-0.247365
CO	-27.660168
PM 10	-0.735361

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.460390
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-913.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.954317
SO _x	-0.302120
NO _x	-0.247365
CO	-27.660168
PM 10	-0.735361

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.460390
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-913.1

19.2 Aircraft & Engines

19.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

19.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

19.3 Flight Operations

19.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 21
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3677
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

19.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

19.4 Auxiliary Power Unit (APU)

19.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

19.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

19.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

20. Aircraft

20.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove
- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA
- Activity Title: Decrease T-38 TGOs by 8093 OUTSIDE BEXAR COUNTY
- Activity Description:
 - Starting in 2028, decrease T-38 TGOs by 8093
- Activity Start Date
 - Start Month: 1
 - Start Year: 2028
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-2.688810
SO _x	-0.467804
NO _x	-0.365913
CO	-40.188579
PM 10	-1.072870

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.636678
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1413.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-2.688810
SO _x	-0.467804
NO _x	-0.365913
CO	-40.188579
PM 10	-1.072870

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.636678
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1413.9

20.2 Aircraft & Engines

20.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-38C
 - Engine Model: J85-GE-5R

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No
 - Original Aircraft Name:
 - Original Engine Name:

20.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

20.3 Flight Operations

20.3.1 Flight Operations Assumptions

- Flight Operations
 - Number of Aircraft: 21
 - Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 8093
 - Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 - Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)
 - Taxi/Idle Out [Idle] (mins): 0
 - Takeoff [Military] (mins): 0.05
 - Takeoff [After Burn] (mins): 0
 - Climb Out [Intermediate] (mins): 0.9
 - Approach [Approach] (mins): 2.58
 - Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test
 - Idle (mins): 12
 - Approach (mins): 27
 - Intermediate (mins): 9
 - Military (mins): 9
 - AfterBurn (mins): 3

20.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year
 $AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

20.4 Auxiliary Power Unit (APU)

20.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

20.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

20.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs
- EF_{POL}: Emission Factor for Pollutant (lb/hr)
- 2000: Conversion Factor pounds to tons

21. Aircraft

21.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add
- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA
- Activity Title: Add T-7As and increase LTOs by 4298 OUTSIDE BEXAR COUNTY
- Activity Description:
 - Starting in 2028, add T-7As and increase LTOs by 4298

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Start Date

Start Month: 1
Start Year: 2028

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.711470
SO _x	0.719279
NO _x	6.070745
CO	3.489733
PM 10	0.049898

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.042691
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2198.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.711470
SO _x	0.719279
NO _x	6.070745
CO	3.489733
PM 10	0.049898

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.042691
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2198.3

21.2 Aircraft & Engines

21.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

21.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

21.3 Flight Operations

21.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 4298

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.1
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.51
Approach [Approach] (mins): 4.52
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

21.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

21.4 Auxiliary Power Unit (APU)

21.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

21.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

21.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

22. Aircraft

22.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase T-7A TGOs by 9527 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2028, increase T-7A TGOs by 9527

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.647952
SO _x	1.109395
NO _x	12.100014
CO	4.309554
PM 10	0.106176

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.090409
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3353.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.647952
SO _x	1.109395
NO _x	12.100014
CO	4.309554
PM 10	0.106176

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.090409
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3353.1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

22.2 Aircraft & Engines

22.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

22.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

22.3 Flight Operations

22.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 9527
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.05
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.9
Approach [Approach] (mins): 2.58
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

22.3.2 Flight Operations Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

22.4 Auxiliary Power Unit (APU)

22.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

22.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

22.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

23. Aircraft

23.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove T-38s and decrease LTOs by 1445 OUTSIDE BEXAR COUNTY

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Description:

Starting in 2029 T-38s and decrease LTOs by 1445

- Activity Start Date

Start Month: 1
Start Year: 2029

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.768014
SO _x	-0.118728
NO _x	-0.097210
CO	-10.869987
PM 10	-0.288985

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.180926
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-358.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.768014
SO _x	-0.118728
NO _x	-0.097210
CO	-10.869987
PM 10	-0.288985

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.180926
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-358.8

23.2 Aircraft & Engines

23.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

23.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

23.3 Flight Operations

23.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	3
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	1445
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

23.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

23.4 Auxiliary Power Unit (APU)

23.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
-------------------------------	---------------------------------	-------------------	-------------	--------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

23.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

23.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

24. Aircraft

24.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Decrease T-38 TGOs by 3193 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2029, decrease T-38 TGOs by 3193

- Activity Start Date

Start Month: 1

Start Year: 2029

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.060839
SO _x	-0.184567
NO _x	-0.144367
CO	-15.855941
PM 10	-0.423288

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.251194
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-557.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.060839

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.251194

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

SO _x	-0.184567
NO _x	-0.144367
CO	-15.855941
PM 10	-0.423288

Pb	0.000000
NH ₃	0.000000
CO _{2e}	-557.8

24.2 Aircraft & Engines

24.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

24.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

24.3 Flight Operations

24.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 7
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3193
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.05
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.9
 Approach [Approach] (mins): 2.58
 Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

24.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

24.4 Auxiliary Power Unit (APU)

24.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

24.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

24.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

25. Aircraft

25.1 General Information & Timeline Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe
Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Add T-7As and increase LTOs by 504 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2029, add T-7As and increase LTOs by 504

- Activity Start Date

Start Month: 1
Start Year: 2029

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.082800
SO _x	0.069855
NO _x	0.624939
CO	0.341810
PM 10	0.005851

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.005006
Pb	0.000000
NH ₃	0.000000
CO _{2e}	211.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.082800
SO _x	0.069855
NO _x	0.624939
CO	0.341810
PM 10	0.005851

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.005006
Pb	0.000000
NH ₃	0.000000
CO _{2e}	211.1

25.2 Aircraft & Engines

25.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

25.2.2 Aircraft & Engines Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

25.3 Flight Operations

25.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	0
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	504
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

25.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)
AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

25.4 Auxiliary Power Unit (APU)

25.4.1 Auxiliary Power Unit (APU) Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

25.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

25.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

26. Aircraft

26.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase T-7A TGOs by 1158 OUTSIDE OF BEXAR COUNTY

- Activity Description:

Starting in 2029, increase T-7A TGOs by 1158

- Activity Start Date

Start Month: 1

Start Year: 2029

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.201755
SO _x	0.168139
NO _x	1.670503

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.010989
Pb	0.000000
NH ₃	0.000000

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

CO	0.678706
PM 10	0.012906

CO _{2e}	514.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.201755
SO _x	0.168139
NO _x	1.670503
CO	0.678706
PM 10	0.012906

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.010989
Pb	0.000000
NH ₃	0.000000
CO _{2e}	514.7

26.2 Aircraft & Engines

26.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

26.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

26.3 Flight Operations

26.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 0
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1158
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.05
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.9
 Approach [Approach] (mins): 2.58
 Taxi/Idle In [Idle] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

26.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

26.4 Auxiliary Power Unit (APU)

26.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

26.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

26.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

27. Aircraft

27.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove T-38s and decrease LTOs by 1715 OUTSIDE OF BEXAR COUNTY

- Activity Description:

Starting in 2030, remove T-38s and decrease LTOs by 1715

- Activity Start Date

Start Month: 1
 Start Year: 2030

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.911519
SO _x	-0.140913
NO _x	-0.115374
CO	-12.901058
PM 10	-0.342982

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.214732
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-425.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.911519
SO _x	-0.140913
NO _x	-0.115374
CO	-12.901058
PM 10	-0.342982

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.214732
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-425.9

27.2 Aircraft & Engines

27.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Aircraft Name:

Original Engine Name:

27.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

27.3 Flight Operations

27.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	6
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	1715
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

27.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

27.4 Auxiliary Power Unit (APU)

27.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

27.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

27.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

28. Aircraft

28.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Decrease T-38 TGOs by 3792 OUTSIDE OF BEXAR COUNTY

- Activity Description:

Starting in 2030, decrease T-38 TGOs by 3,792

- Activity Start Date

Start Month: 1

Start Year: 2030

- Activity End Date

Indefinite: Yes

End Month: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.259850
SO _x	-0.219191
NO _x	-0.171450
CO	-18.830482
PM 10	-0.502696

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.298317
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-662.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.259850
SO _x	-0.219191
NO _x	-0.171450
CO	-18.830482
PM 10	-0.502696

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.298317
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-662.5

28.2 Aircraft & Engines

28.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

28.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

28.3 Flight Operations

28.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 6
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3792
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- **Default Settings Used:** No

- **Flight Operations TIMs (Time In Mode)**

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- **Trim Test**

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

28.3.2 Flight Operations Formula(s)

- **Aircraft Emissions per Mode for LTOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- **Aircraft Emissions for LTOs per Year**

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- **Aircraft Emissions per Mode for TGOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

28.4 Auxiliary Power Unit (APU)

28.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

28.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

28.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

29. Aircraft

29.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: increase LTOs by 261 OUTSIDE OF BEXAR COUNTY

- Activity Description:

Stating in 2030, increase LTOs by 261

- Activity Start Date

Start Month: 1

Start Year: 2030

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.043205
SO _x	0.043679
NO _x	0.368652
CO	0.211917
PM 10	0.003030

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.002592
Pb	0.000000
NH ₃	0.000000
CO _{2e}	133.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.043205
SO _x	0.043679
NO _x	0.368652
CO	0.211917
PM 10	0.003030

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.002592
Pb	0.000000
NH ₃	0.000000
CO _{2e}	133.5

29.2 Aircraft & Engines

29.2.1 Aircraft & Engines Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

29.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

29.3 Flight Operations

29.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	0
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	261
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

29.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

29.4 Auxiliary Power Unit (APU)

29.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

29.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

29.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

30. Aircraft

30.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase TGOs by 590 OUTSIDE OF BEXAR COUNTY

- Activity Description:

Starting in 2030, increase TGOs by 590

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Start Date

Start Month: 1
Start Year: 2030

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.102794
SO _x	0.085667
NO _x	0.851120
CO	0.345800
PM 10	0.006575

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.005599
Pb	0.000000
NH ₃	0.000000
CO _{2e}	262.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.102794
SO _x	0.085667
NO _x	0.851120
CO	0.345800
PM 10	0.006575

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.005599
Pb	0.000000
NH ₃	0.000000
CO _{2e}	262.3

30.2 Aircraft & Engines

30.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

30.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

30.3 Flight Operations

30.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:

0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 590
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.05
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.9
Approach [Approach] (mins): 2.58
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

30.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- TGO: Number of Touch-and-Go Cycles (for all aircraft)
- 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

- AE_{TGO}: Aircraft Emissions (TONs)
- AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
- AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
- AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

- AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
- TD: Test Duration (min)
- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- NA: Number of Aircraft
- NTT: Number of Trim Test
- 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

30.4 Auxiliary Power Unit (APU)

30.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

30.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4
----------	-------	-------	-------	-------	-------	--------	--------	-------

30.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

31. Aircraft

31.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove 14 T-38s and decrease LTOs by 2636 OUTSIDE OF BEXAR COUNTY

- Activity Description:

Starting in 2031, remove 14 T-38s and decrease TOs by 2,636

- Activity Start Date

Start Month: 1

Start Year: 2031

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.401028
SO _x	-0.216587
NO _x	-0.177333
CO	-19.829264
PM 10	-0.527172

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.330049
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-654.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.401028
SO _x	-0.216587
NO _x	-0.177333
CO	-19.829264
PM 10	-0.527172

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.330049
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-654.6

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

31.2 Aircraft & Engines

31.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

31.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

31.3 Flight Operations

31.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 2636
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.1
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.51
Approach [Approach] (mins): 4.52
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Military (mins): 9
AfterBurn (mins): 3

31.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

31.4 Auxiliary Power Unit (APU)

31.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

31.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

31.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

32. Aircraft

32.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Regulatory Area(s): NOT IN A REGULATORY AREA

- **Activity Title:** 2031 T-38 Removal 5840 TGOs OUTSIDE BEXAR COUNTY

- **Activity Description:**

Starting in 2031, decrease T-38 TGOs by 5840

- **Activity Start Date**

Start Month: 1

Start Year: 2031

- **Activity End Date**

Indefinite: Yes

End Month: N/A

End Year: N/A

- **Activity Emissions:**

Pollutant	Emissions Per Year (TONs)
VOC	-1.940276
SO _x	-0.337573
NO _x	-0.264047
CO	-29.000531
PM 10	-0.774195

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.459434
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1020.3

- **Activity Emissions [Flight Operations (includes Trim Test & APU) part]:**

Pollutant	Emissions Per Year (TONs)
VOC	-1.940276
SO _x	-0.337573
NO _x	-0.264047
CO	-29.000531
PM 10	-0.774195

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.459434
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1020.3

32.2 Aircraft & Engines

32.2.1 Aircraft & Engines Assumptions

- **Aircraft & Engine**

Aircraft Designation: T-38C

Engine Model: J85-GE-5R

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 2

- **Aircraft & Engine Surrogate**

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

32.2.2 Aircraft & Engines Emission Factor(s)

- **Aircraft & Engine Emissions Factors (lb/1000lb fuel)**

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

32.3 Flight Operations

32.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	5840
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

32.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

32.4 Auxiliary Power Unit (APU)

32.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

32.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

32.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

33. Aircraft

33.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: decrease T-7A LTOs by 104 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2031, decrease T-7A LTOs by 104

- Activity Start Date

Start Month: 1

Start Year: 2031

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.017086
SO _x	-0.014415
NO _x	-0.128956
CO	-0.070532

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.001033
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-43.6

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

PM 10	-0.001207
-------	-----------

--	--

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.017086
SO _x	-0.014415
NO _x	-0.128956
CO	-0.070532
PM 10	-0.001207

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.001033
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-43.6

33.2 Aircraft & Engines

33.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

33.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

33.3 Flight Operations

33.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 0
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 104
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.1
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.51
 Approach [Approach] (mins): 4.52
 Taxi/Idle In [Idle] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

33.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

33.4 Auxiliary Power Unit (APU)

33.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

33.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

33.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

34. Aircraft

34.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove
- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA
- Activity Title: decrease T-7A TGOs by 224 OUTSIDE BEXAR COUNTY
- Activity Description:
 - Starting in 2031, decrease T-7A TGOs by 224
- Activity Start Date
 - Start Month: 1
 - Start Year: 2031
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.039027
SO _x	-0.032524
NO _x	-0.323137
CO	-0.131287
PM 10	-0.002496

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.002126
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-99.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.039027
SO _x	-0.032524
NO _x	-0.323137
CO	-0.131287
PM 10	-0.002496

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.002126
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-99.6

34.2 Aircraft & Engines

34.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-7A
 - Engine Model: F404-GE-102
 - Primary Function: Trainer
 - Aircraft has After burn: Yes
 - Number of Engines: 1
- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Aircraft Name:

Original Engine Name:

34.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

34.3 Flight Operations

34.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	0
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	224
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

34.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

34.4 Auxiliary Power Unit (APU)

34.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

34.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

34.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

35. Aircraft

35.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase LTOs by 1242 OUTSIDE BEXAR COUNTY

- Activity Description:

increase LTOs by 1242

- Activity Start Date

Start Month: 1

Start Year: 2032

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.205595
SO _x	0.207851
NO _x	1.754273
CO	1.008434
PM 10	0.014419

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.012337
Pb	0.000000
NH ₃	0.000000
CO _{2e}	635.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.205595
SO _x	0.207851
NO _x	1.754273
CO	1.008434
PM 10	0.014419

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.012337
Pb	0.000000
NH ₃	0.000000
CO _{2e}	635.2

35.2 Aircraft & Engines

35.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

35.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

35.3 Flight Operations

35.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 0
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1242
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

35.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

35.4 Auxiliary Power Unit (APU)

35.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

35.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

35.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

36. Aircraft

36.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add
- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA
- Activity Title: Increase T-7A TGOs by 2748 OUTSIDE BEXAR COUNTY
- Activity Description:
 - Starting in 2032, increase T-7A TGOs by 2748
- Activity Start Date
 - Start Month: 1
 - Start Year: 2032
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.478776
SO _x	0.399003
NO _x	3.964199
CO	1.610607
PM 10	0.030626

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.026078
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1221.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.478776
SO _x	0.399003
NO _x	3.964199
CO	1.610607
PM 10	0.030626

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.026078
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1221.5

36.2 Aircraft & Engines

36.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-7A
 - Engine Model: F404-GE-102

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

36.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

36.3 Flight Operations

36.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	0
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	2748
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- **Default Settings Used:** No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

36.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

36.4 Auxiliary Power Unit (APU)

36.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

36.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

36.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

37. Aircraft

37.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2023 T-7A Seguin AAF Closed Patterns

- Activity Description:

Increase 645 Closed Patterns

- Activity Start Date

Start Month: 1

Start Year: 2023

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.305500
SO _x	0.165822
NO _x	3.015634
CO	0.445806
PM 10	0.019708

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.016934
Pb	0.000000
NH ₃	0.000000
CO _{2e}	501.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.305500
SO _x	0.165822
NO _x	3.015634
CO	0.445806
PM 10	0.019708

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.016934
Pb	0.000000
NH ₃	0.000000
CO _{2e}	501.2

37.2 Aircraft & Engines

37.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

37.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

37.3 Flight Operations

37.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 645
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- **Default Settings Used:** No

- **Flight Operations TIMs (Time In Mode)**

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- **Trim Test**

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

37.3.2 Flight Operations Formula(s)

- **Aircraft Emissions per Mode for LTOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- **Aircraft Emissions for LTOs per Year**

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- **Aircraft Emissions per Mode for TGOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

37.4 Auxiliary Power Unit (APU)

37.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

37.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

37.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

38. Aircraft

38.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add
- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA
- Activity Title: 2023 T-38C Seguin AAF Closed Patterns
- Activity Description:
 - increase 15400 CLosed Patterns
- Activity Start Date
 - Start Month: 1
 - Start Year: 2023
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	6.097359
SO _x	1.693636
NO _x	1.831199
CO	107.523651
PM 10	3.036999

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.383375
Pb	0.000000
NH ₃	0.000000
CO _{2e}	5118.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	6.097359
SO _x	1.693636
NO _x	1.831199
CO	107.523651
PM 10	3.036999

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.383375
Pb	0.000000
NH ₃	0.000000
CO _{2e}	5118.9

38.2 Aircraft & Engines

38.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

38.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

38.3 Flight Operations

38.3.1 Flight Operations Assumptions

- Flight Operations
 Number of Aircraft: 1
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 15400
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)
 Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.93
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 1.91
 Approach [Approach] (mins): 2.5
 Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test
 Idle (mins): 12
 Approach (mins): 27
 Intermediate (mins): 9
 Military (mins): 9
 AfterBurn (mins): 3

38.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

38.4 Auxiliary Power Unit (APU)

38.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

38.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

38.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

39. Aircraft

39.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2024 T-7A Seguin AAF Closed Patterns

- Activity Description:

increase 2235 Closed Patterns

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Start Date

Start Month: 1
Start Year: 2024

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	11.266155
SO _x	0.753242
NO _x	6.788309
CO	44.650047
PM 10	0.656407

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.587878
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1949.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	11.266155
SO _x	0.753242
NO _x	6.788309
CO	44.650047
PM 10	0.656407

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.587878
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1949.2

39.2 Aircraft & Engines

39.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

39.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

39.3 Flight Operations

39.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 2235
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 6.8
Takeoff [Military] (mins): 0.25
Takeoff [After Burn] (mins): 0.25
Climb Out [Intermediate] (mins): 1.4
Approach [Approach] (mins): 4
Taxi/Idle In [Idle] (mins): 4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

39.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- TGO: Number of Touch-and-Go Cycles (for all aircraft)
- 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

- AE_{TGO}: Aircraft Emissions (TONs)
- AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
- AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
- AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

- AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
- TD: Test Duration (min)
- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- NA: Number of Aircraft
- NTT: Number of Trim Test
- 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

39.4 Auxiliary Power Unit (APU)

39.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

39.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

39.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

40. Aircraft

40.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2024 T-38C Seguin AAF Closed Patterns

- Activity Description:

- Activity Start Date

Start Month: 1

Start Year: 2024

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.277153
SO _x	-0.076983
NO _x	-0.083236
CO	-4.887439
PM 10	-0.138045

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.062881
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-232.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.277153
SO _x	-0.076983
NO _x	-0.083236
CO	-4.887439
PM 10	-0.138045

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.062881
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-232.7

40.2 Aircraft & Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

40.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

40.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

40.3 Flight Operations

40.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 700
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.93
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 1.91
Approach [Approach] (mins): 2.5
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

40.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

40.4 Auxiliary Power Unit (APU)

40.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

40.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

40.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

41. Aircraft

41.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- **Activity Title:** 2025 T-7A Seguin AAF Closed Patterns

- **Activity Description:**
Increase 10320 closed patterns

- **Activity Start Date**
Start Month: 1
Start Year: 2025

- **Activity End Date**
Indefinite: Yes
End Month: N/A
End Year: N/A

- **Activity Emissions:**

Pollutant	Emissions Per Year (TONs)
VOC	4.887994
SO _x	2.653153
NO _x	48.250140
CO	7.132894
PM 10	0.315325

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.270949
Pb	0.000000
NH ₃	0.000000
CO _{2e}	8019.0

- **Activity Emissions [Flight Operations (includes Trim Test & APU) part]:**

Pollutant	Emissions Per Year (TONs)
VOC	4.887994
SO _x	2.653153
NO _x	48.250140
CO	7.132894
PM 10	0.315325

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.270949
Pb	0.000000
NH ₃	0.000000
CO _{2e}	8019.0

41.2 Aircraft & Engines

41.2.1 Aircraft & Engines Assumptions

- **Aircraft & Engine**
 Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- **Aircraft & Engine Surrogate**
 Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

41.2.2 Aircraft & Engines Emission Factor(s)

- **Aircraft & Engine Emissions Factors (lb/1000lb fuel)**
 Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

41.3 Flight Operations

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

41.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	10320
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

41.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

41.4 Auxiliary Power Unit (APU)

41.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
-------------------------------	---------------------------------	-------------------	-------------	--------------

41.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

41.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

42. Aircraft

42.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2025 T-38C Seguin AAF Closed Patterns

- Activity Description:

Decrease 10600 Closed Patterns

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-4.196883
SO _x	-1.165750
NO _x	-1.260436
CO	-74.009786
PM 10	-2.090402

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.952193
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-3523.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-4.196883
SO _x	-1.165750
NO _x	-1.260436

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.952193
Pb	0.000000
NH ₃	0.000000

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

CO	-74.009786
PM 10	-2.090402

CO _{2e}	-3523.4

42.2 Aircraft & Engines

42.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

42.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

42.3 Flight Operations

42.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 10600
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.93
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 1.91
Approach [Approach] (mins): 2.5
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

42.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

42.4 Auxiliary Power Unit (APU)

42.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

42.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

42.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

43. Aircraft

43.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Location

County: Guadalupe
Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2026 T-7A Seguin AAF Closed Patterns

- Activity Description:

Increase 8000 closed patterns.

- Activity Start Date

Start Month: 1
Start Year: 2026

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	3.789142
SO _x	2.056708
NO _x	37.403209
CO	5.529376
PM 10	0.244438

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.210038
Pb	0.000000
NH ₃	0.000000
CO _{2e}	6216.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	3.789142
SO _x	2.056708
NO _x	37.403209
CO	5.529376
PM 10	0.244438

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.210038
Pb	0.000000
NH ₃	0.000000
CO _{2e}	6216.3

43.2 Aircraft & Engines

43.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

43.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

43.3 Flight Operations

43.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	8000
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

43.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

43.4 Auxiliary Power Unit (APU)

43.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

43.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

43.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

44. Aircraft

44.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2026 T-38C Seguin AAF Closed Patterns

- Activity Description:

Decrease 6300 closed patterns.

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-2.494374
SO _x	-0.692851
NO _x	-0.749127
CO	-43.986948
PM 10	-1.242409

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.565926
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2094.1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-2.494374
SO _x	-0.692851
NO _x	-0.749127
CO	-43.986948
PM 10	-1.242409

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.565926
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2094.1

44.2 Aircraft & Engines

44.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

44.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

44.3 Flight Operations

44.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 6300
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.93
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 1.91
 Approach [Approach] (mins): 2.5
 Taxi/Idle In [Idle] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

44.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

44.4 Auxiliary Power Unit (APU)

44.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

44.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

44.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

45. Aircraft

45.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2027 T-7A Seguin AAF Closed Patterns

- Activity Description:
 - increase 9120 closed patterns.

- Activity Start Date
 - Start Month: 1
 - Start Year: 2027

- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	4.319622
SO _x	2.344647
NO _x	42.639658
CO	6.303488
PM 10	0.278659

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.239444
Pb	0.000000
NH ₃	0.000000
CO _{2e}	7086.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	4.319622
SO _x	2.344647
NO _x	42.639658
CO	6.303488
PM 10	0.278659

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.239444
Pb	0.000000
NH ₃	0.000000
CO _{2e}	7086.5

45.2 Aircraft & Engines

45.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-7A
 - Engine Model: F404-GE-102
 - Primary Function: Trainer
 - Aircraft has After burn: Yes
 - Number of Engines: 1

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No
 - Original Aircraft Name:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Engine Name:

45.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

45.3 Flight Operations

45.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	9120
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

45.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

45.4 Auxiliary Power Unit (APU)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

45.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

45.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

45.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

46. Aircraft

46.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2027 T-38C Seguin AAF Closed Patterns

- Activity Description:

Decrease 11100 closed patterns.

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-4.394850

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.997108

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

SO _x	-1.220738
NO _x	-1.319890
CO	-77.500813
PM 10	-2.189006

Pb	0.000000
NH ₃	0.000000
CO _{2e}	-3689.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-4.394850
SO _x	-1.220738
NO _x	-1.319890
CO	-77.500813
PM 10	-2.189006

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.997108
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-3689.6

46.2 Aircraft & Engines

46.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

46.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

46.3 Flight Operations

46.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 11100
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.93

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

46.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

- AE_{TGO}: Aircraft Emissions (TONs)
- AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
- AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
- AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

- AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
- TD: Test Duration (min)
- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- NA: Number of Aircraft
- NTT: Number of Trim Test
- 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

46.4 Auxiliary Power Unit (APU)

46.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

46.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

46.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

47. Aircraft

47.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2028 T-7A Seguin AAF Closed Patterns

- Activity Description:

increase 4960 closed patterns

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	2.349268
SO _x	1.275159
NO _x	23.189990
CO	3.428213
PM 10	0.151552

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.130224
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3854.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	2.349268
SO _x	1.275159
NO _x	23.189990
CO	3.428213
PM 10	0.151552

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.130224
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3854.1

47.2 Aircraft & Engines

47.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

47.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

47.3 Flight Operations

47.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	4960
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

47.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

47.4 Auxiliary Power Unit (APU)

47.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

47.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

47.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

48. Aircraft

48.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2028 T-38C Seguin AAF Closed Patterns

- Activity Description:

Decrease 7600 closed patterns.

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-3.009086
SO _x	-0.835821
NO _x	-0.903709
CO	-53.063620
PM 10	-1.498779

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.682704
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2526.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-3.009086
SO _x	-0.835821
NO _x	-0.903709
CO	-53.063620
PM 10	-1.498779

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.682704
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2526.2

48.2 Aircraft & Engines

48.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

48.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

48.3 Flight Operations

48.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 7600
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

48.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

48.4 Auxiliary Power Unit (APU)

48.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

48.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

48.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

49. Aircraft

49.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2029 T-7A Seguin AAF Closed Patterns

- Activity Description:

Increase 3280 Closed Patterns

- Activity Start Date

Start Month: 1

Start Year: 2029

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.553548
SO _x	0.843250
NO _x	15.335316
CO	2.267044
PM 10	0.100220

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.086116
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2548.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.553548
SO _x	0.843250
NO _x	15.335316
CO	2.267044
PM 10	0.100220

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.086116
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2548.7

49.2 Aircraft & Engines

49.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

49.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

49.3 Flight Operations

49.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	3280
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

49.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

49.4 Auxiliary Power Unit (APU)

49.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

49.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

49.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

50. Aircraft

50.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2029 T-38C seguin AAF Closed Patterns

- Activity Description:

decrease 4400 closed patterns.

- Activity Start Date

Start Month: 1

Start Year: 2029

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.742103
SO _x	-0.483896
NO _x	-0.523200
CO	-30.721043
PM 10	-0.867714

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.395250
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1462.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.742103
SO _x	-0.483896
NO _x	-0.523200
CO	-30.721043
PM 10	-0.867714

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.395250
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1462.5

50.2 Aircraft & Engines

50.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

50.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

50.3 Flight Operations

50.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 4400

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

50.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
 AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
 AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
 AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
 AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
 AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
 AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
 AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
 AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

50.4 Auxiliary Power Unit (APU)

50.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

50.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

50.4.3 Auxiliary Power Unit (APU) Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

51. Aircraft

51.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2030 T-7A Seguin AAF Closed Patterns

- Activity Description:

Increase 880 closed patterns

- Activity Start Date

Start Month: 1

Start Year: 2030

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.416806
SO _x	0.226238
NO _x	4.114353
CO	0.608231
PM 10	0.026888

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.023104
Pb	0.000000
NH ₃	0.000000
CO _{2e}	683.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.416806
SO _x	0.226238
NO _x	4.114353
CO	0.608231
PM 10	0.026888

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.023104
Pb	0.000000
NH ₃	0.000000
CO _{2e}	683.8

51.2 Aircraft & Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

51.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

51.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

51.3 Flight Operations

51.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 880
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.93
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 1.91
Approach [Approach] (mins): 2.5
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

51.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

51.4 Auxiliary Power Unit (APU)

51.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

51.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

51.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

52. Aircraft

52.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2030 T-38C Seguin AAF Closed Patterns

- Activity Description:

Decrease 5900 closed patterns

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Start Date

Start Month: 1
Start Year: 2030

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-2.336001
SO _x	-0.648861
NO _x	-0.701563
CO	-41.194126
PM 10	-1.163526

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.529994
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1961.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-2.336001
SO _x	-0.648861
NO _x	-0.701563
CO	-41.194126
PM 10	-1.163526

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.529994
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1961.1

52.2 Aircraft & Engines

52.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

52.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

52.3 Flight Operations

52.3.1 Flight Operations Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	5900
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

52.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

52.4 Auxiliary Power Unit (APU)

52.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

52.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

52.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

53. Aircraft

53.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2031 T-7A Seguin AAF Closed Patterns

- Activity Description:

increase 480 closed patterns

- Activity Start Date

Start Month: 1

Start Year: 2031

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.227349
SO _x	0.123402
NO _x	2.244193
CO	0.331763
PM 10	0.014666

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.012602
Pb	0.000000
NH ₃	0.000000
CO _{2e}	373.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.227349
SO _x	0.123402
NO _x	2.244193
CO	0.331763

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.012602
Pb	0.000000
NH ₃	0.000000
CO _{2e}	373.0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

PM 10	0.014666
-------	----------

--	--

53.2 Aircraft & Engines

53.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

53.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

53.3 Flight Operations

53.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 480
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.93
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 1.91
Approach [Approach] (mins): 2.5
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

53.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

53.4 Auxiliary Power Unit (APU)

53.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

53.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

53.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

54. Aircraft

54.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2031 T-38C Seguin AAF Closed PAtterns

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Description:
decrease 8120 closed patterns

- Activity Start Date
Start Month: 1
Start Year: 2031

- Activity End Date
Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-3.214971
SO _x	-0.893008
NO _x	-0.965541
CO	-56.694289
PM 10	-1.601327

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.729416
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2699.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-3.214971
SO _x	-0.893008
NO _x	-0.965541
CO	-56.694289
PM 10	-1.601327

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.729416
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2699.1

54.2 Aircraft & Engines

54.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

54.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

54.3 Flight Operations

54.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	8120
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

54.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

54.4 Auxiliary Power Unit (APU)

54.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU	Operation Hours	Exempt	Designation	Manufacturer
---------------	-----------------	--------	-------------	--------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

per Aircraft	for Each LTO	Source?	
--------------	--------------	---------	--

54.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

54.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

55. Aircraft

55.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2032 T-7A Seguin AAF Closed Patterns

- Activity Description:

increase 1280 closed patternd

- Activity Start Date

Start Month: 1

Start Year: 2032

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.606263
SO _x	0.329073
NO _x	5.984513
CO	0.884700
PM 10	0.039110

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.033606
Pb	0.000000
NH ₃	0.000000
CO _{2e}	994.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
-----------	---------------------------

Pollutant	Emissions Per Year (TONs)
-----------	---------------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

VOC	0.606263
SO _x	0.329073
NO _x	5.984513
CO	0.884700
PM 10	0.039110

PM 2.5	0.033606
Pb	0.000000
NH ₃	0.000000
CO ₂ e	994.6

55.2 Aircraft & Engines

55.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

55.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

55.3 Flight Operations

55.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1280
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.93
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 1.91
Approach [Approach] (mins): 2.5
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

55.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

55.4 Auxiliary Power Unit (APU)

55.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

55.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

55.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

56. Aircraft

56.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2032 T-38C Seguin AAF Closed Patterns

- Activity Description:
 Decrease 2680 Closed Patterns

- Activity Start Date
 Start Month: 1
 Start Year: 2032

- Activity End Date
 Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.061099
SO _x	-0.294737
NO _x	-0.318676
CO	-18.711908
PM 10	-0.528517

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.240743
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-890.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.061099
SO _x	-0.294737
NO _x	-0.318676
CO	-18.711908
PM 10	-0.528517

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.240743
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-890.8

56.2 Aircraft & Engines

56.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

56.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

56.3 Flight Operations

56.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	2680
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

56.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)
AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

56.4 Auxiliary Power Unit (APU)

56.4.1 Auxiliary Power Unit (APU) Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
-------------------------------	---------------------------------	-------------------	-------------	--------------

56.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

56.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF AIR ANALYSIS (ROAA)

1. General Information: The Air Force's Air Conformity Applicability Model (ACAM) was used to perform an analysis to assess the potential air quality impact/s associated with the action in accordance with the Air Force Manual 32-7002, Environmental Compliance and Pollution Prevention; the Environmental Impact Analysis Process (EIAP, 32 CFR 989); and the General Conformity Rule (GCR, 40 CFR 93 Subpart B). This report provides a summary of the ACAM analysis.

a. Action Location:

Base: RANDOLPH AFB
State: Texas
County(s): Guadalupe
Regulatory Area(s): NOT IN A REGULATORY AREA

b. Action Title: Recapitalization of the T-38 Trainer At Randolph AFB - Alternative 1 (Guadalupe County)

c. Project Number/s (if applicable):

d. Projected Action Start Date: 1 / 2023

e. Action Description:

The proposed action encompasses the recapitalize of the T-38 flight-training program with newer and more capable T-7A aircraft at JBSA-Randolph and Lackland. In addition to the phased introduction of the T-7A aircraft, five military construction projects and 17 facilities sustainment, restoration, and modernization projects are proposed at JBSA-Randolph at JBSA-Lackland to provide modern facilities and infrastructure to support the T-7A aircraft's maintenance, training, and operational requirements. The number of personnel on JBSA-Randolph would increase due to the proposed aircraft recapitalization. No changes to airspace configurations (i.e., size, shape, or location) would be required to support the proposed operations of the T-7A aircraft; however, the T-7A aircraft may have more flight operations than occurs with the T 38C aircraft at both JBSA-Randolph and JBSA-Lackland. This Applicability Analysis present the worst-case of three aircraft operational intensities as the worst-case action alternatives for the Proposed Action.

A Conformity Evaluation is required for every proposed action that will occur within an area designated by the U.S. Environmental Protection Agency (EPA) as nonattainment or maintenance for any National Ambient Air Quality Standard (NAAQS). The proposed T-7A Recapitalization action will occur at both JBSA-Randolph AFB and JBSA-Lackland AFB which both fall entirely within Bexar County that has been designated by the U.S. Environmental Protection Agency (EPA) as a marginal nonattainment area for the 2015 Ozone NAAQS in 2018. Given this recent designation of Bexar County, the proposed action (as well as all proposed actions from federal agencies) are subject to the General Conformity Rule (GCR, 40 CFR 93 Subpart B). As a marginal nonattainment area for ozone, the GCR has established de minimis significance threshold values of less than 100 ton/yr (for any given year) for both nitrogen oxides (NOx) and volatile organic compounds (VOC).

f. Point of Contact:

Name: [REDACTED]
Title: NEPA Contract Support
Organization: [REDACTED]

2. Air Impact Analysis: Based on the attainment status at the action location, the requirements of the General Conformity Rule are:

_____ applicable
__X__ not applicable

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF AIR ANALYSIS (ROAA)

Total net direct and indirect emissions associated with the action were estimated through ACAM on a calendar-year basis for the start of the action through achieving “steady state” (i.e., net gain/loss upon action fully implemented) emissions. The ACAM analysis used the latest and most accurate emission estimation techniques available; all algorithms, emission factors, and methodologies used are described in detail in the USAF Air Emissions Guide for Air Force Stationary Sources, the USAF Air Emissions Guide for Air Force Mobile Sources, and the USAF Air Emissions Guide for Air Force Transitory Sources.

“Insignificance Indicators” were used in the analysis to provide an indication of the significance of potential impacts to air quality based on current ambient air quality relative to the National Ambient Air Quality Standards (NAAQSs). These insignificance indicators are the 250 ton/yr Prevention of Significant Deterioration (PSD) major source threshold for actions occurring in areas that are “Clearly Attainment” (i.e., not within 5% of any NAAQS) and the GCR de minimis values (25 ton/yr for lead and 100 ton/yr for all other criteria pollutants) for actions occurring in areas that are “Near Nonattainment” (i.e., within 5% of any NAAQS). These indicators do not define a significant impact; however, they do provide a threshold to identify actions that are insignificant. Any action with net emissions below the insignificance indicators for all criteria pollutant is considered so insignificant that the action will not cause or contribute to an exceedance on one or more NAAQSs. For further detail on insignificance indicators see chapter 4 of the Air Force Air Quality Environmental Impact Analysis Process (EIAP) Guide, Volume II - Advanced Assessments.

The action’s net emissions for every year through achieving steady state were compared against the Insignificance Indicator and are summarized below.

Analysis Summary:

2023

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	6.822	250	No
NO _x	7.947	250	No
CO	109.253	250	No
SO _x	2.163	250	No
PM 10	3.084	250	No
PM 2.5	1.424	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	6536.4		

2024

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	8.330	250	No
NO _x	24.188	250	No
CO	108.504	250	No
SO _x	3.270	250	No
PM 10	3.062	250	No
PM 2.5	1.460	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	9898.7		

2025

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
-----------	---------------------------	--------------------------	--

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF AIR ANALYSIS (ROAA)

		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	7.081	250	No
NO _x	82.841	250	No
CO	-4.560	250	No
SO _x	5.393	250	No
PM 10	0.022	250	No
PM 2.5	0.037	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	16333.1		

2026

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	7.928	250	No
NO _x	131.297	250	No
CO	-66.041	250	No
SO _x	7.686	250	No
PM 10	-1.634	250	No
PM 2.5	-0.694	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	23296.4		

2027

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	5.248	250	No
NO _x	189.434	250	No
CO	-199.158	250	No
SO _x	9.829	250	No
PM 10	-5.259	250	No
PM 2.5	-2.456	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	29823.6		

2028

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	-20.188	250	No
NO _x	198.750	250	No
CO	-625.518	250	No
SO _x	5.080	250	No
PM 10	-16.927	250	No
PM 2.5	-8.653	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	15477.2		

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF AIR ANALYSIS (ROAA)

2029 - (Steady State)

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	-20.188	250	No
NO _x	198.750	250	No
CO	-625.518	250	No
SO _x	5.080	250	No
PM 10	-16.927	250	No
PM 2.5	-8.653	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	15477.2		

The steady state estimated annual net emissions associated with this action do not exceed the insignificance indicators, indicating no potential for a significant impact to air quality.

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1. General Information

- Action Location

Base: RANDOLPH AFB
State: Texas
County(s): Guadalupe
Regulatory Area(s): NOT IN A REGULATORY AREA

- Action Title: Recapitalization of the T-38 Trainer At Randolph AFB - Alternative 1 (Guadalupe County)

- Project Number/s (if applicable):

- Projected Action Start Date: 1 / 2023

- Action Purpose and Need:

The T 38 Talon is a twin-engine, high-altitude, supersonic jet used by the USAF and other nations for pilot training. The aircraft originally was developed in the 1950s with production occurring between 1961 and 1972. The fleet has undergone periodic upgrades overtime. In 2001, the USAF upgraded several hundred T 38s with modern avionics and replaced propulsion components to provide increased performance and superior reliability.

The purpose of the Proposed Action is to allow the USAF T-7A to provide more efficient and effective pilot training to establish a T-7A pilot pipeline to allow for the transition to T-7A training throughout the entire USAF.

- Action Description:

The proposed action encompasses the recapitalize of the T-38 flight-training program with newer and more capable T-7A aircraft at JBSA-Randolph and Lackland. In addition to the phased introduction of the T-7A aircraft, five military construction projects and 17 facilities sustainment, restoration, and modernization projects are proposed at JBSA-Randolph at JBSA-Lackland to provide modern facilities and infrastructure to support the T-7A aircraft's maintenance, training, and operational requirements. The number of personnel on JBSA-Randolph would increase due to the proposed aircraft recapitalization. No changes to airspace configurations (i.e., size, shape, or location) would be required to support the proposed operations of the T-7A aircraft; however, the T-7A aircraft may have more flight operations than occurs with the T 38C aircraft at both JBSA-Randolph and JBSA-Lackland. This Applicability Analysis present the worst-case of three aircraft operational intensities as the worst-case action alternatives for the Proposed Action.

A Conformity Evaluation is required for every proposed action that will occur within an area designated by the U.S. Environmental Protection Agency (EPA) as nonattainment or maintenance for any National Ambient Air Quality Standard (NAAQS). The proposed T-7A Recapitalization action will occur at both JBSA-Randolph AFB and JBSA-Lackland AFB which both fall entirely within Bexar County that has been designated by the U.S. Environmental Protection Agency (EPA) as a marginal nonattainment area for the 2015 Ozone NAAQS in 2018. Given this recent designation of Bexar County, the proposed action (as well as all proposed actions from federal agencies) are subject to the General Conformity Rule (GCR, 40 CFR 93 Subpart B). As a marginal nonattainment area for ozone, the GCR has established de minimis significance threshold values of less than 100 ton/yr (for any given year) for both nitrogen oxides (NOx) and volatile organic compounds (VOC).

- Point of Contact

Name:

[REDACTED]

Organization:

[REDACTED] Support

Email:

Phone Number:

- Activity List:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Activity Type		Activity Title
2.	Aircraft	T-7As and 759 LTOs OUTSIDE BEXAR COUNTY
3.	Aircraft	T-7A Increase 1,700 TGOs OUTSIDE BEXAR COUNTY
4.	Aircraft	T-38 Removal 5 TGOs OUTSIDE BEXAR COUNTY
5.	Aircraft	Add 10 T-7As and 1328 LTOs OUTSIDE BEXAR COUNTY
6.	Aircraft	Increase T-7A TGOs OUTSIDE BEXAR COUNTY
7.	Aircraft	Remove 11 T-38s and 2776LTOs OUTSIDE BEXAR COUNTY
8.	Aircraft	Remove 6142 T-38 TGOs OUTSIDE BEXAR COUNTY
9.	Aircraft	Add 7 new T-7As and 2836 LTOs OUTSIDE BEXAR COUNTY
10.	Aircraft	Increase T-7A TGOs by 6395 OUTSIDE BEXAR COUNTY
11.	Aircraft	Remove 7 T-38s and reduce LTOs by 1534 OUTSIDE BEXAR COUNTY
12.	Aircraft	Decrease T-38 TGOs by 3394 OUTSIDE BEXAR COUNTY
13.	Aircraft	Add T-7As and increase LTOs by 2698 OUTSIDE BEXAR COUNTY
14.	Aircraft	Increase T-7A TGOs by 6040 OUTSIDE BEXAR COUNTY
15.	Aircraft	Remove T-38s and decrease LTOs by 3767 OUTSIDE BEXAR COUNTY
16.	Aircraft	Decrease T-38 TGOs by 8,328 OUTSIDE BEXAR COUNTY
17.	Aircraft	Add 19 new T-7As and increase LTOs by 3927 OUTSIDE BEXAR COUNTY
18.	Aircraft	Increase T-7A TGOs by 8719 OUTSIDE BEXAR COUNTY
19.	Aircraft	Remove 21 T-38s and decrease LTOs by 12407 OUTSIDE BEXAR COUNTY
20.	Aircraft	Decrease T-38 TGOs by 27396 OUTSIDE BEXAR COUNTY
21.	Aircraft	Add T-7As and increase LTOs by 1012 OUTSIDE BEXAR COUNTY
22.	Aircraft	Increase T-7A TGOs by 2276 OUTSIDE BEXAR COUNTY
23.	Aircraft	2023 T-7A Seguin AAF Closed Patterns
24.	Aircraft	2023 T-38C Seguin AAF Closed Patterns
25.	Aircraft	2024 T-7A Seguin AAF Closed Patterns
26.	Aircraft	2024 T-38C Seguin AAF Closed Patterns
27.	Aircraft	2025 T-7A Seguin AAF Closed Patterns
28.	Aircraft	2025 T-38C Seguin AAF Closed Patterns
29.	Aircraft	2026 T-7A Seguin AAF Closed Patterns
30.	Aircraft	2026 T-38C Seguin AAF Closed Patterns
31.	Aircraft	2027 T-7A Seguin AAF Closed Patterns
32.	Aircraft	2027 T-38C Seguin AAF Closed Patterns
33.	Aircraft	2028 T-7A Seguin AAF Closed Patterns
34.	Aircraft	2028 T-38C Seguin AAF Closed Patterns

Emission factors and air emission estimating methods come from the United States Air Force's Air Emissions Guide for Air Force Stationary Sources, Air Emissions Guide for Air Force Mobile Sources, and Air Emissions Guide for Air Force Transitory Sources.

2. Aircraft

2.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

 County: Guadalupe

 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: T-7As and 759 LTOs OUTSIDE BEXAR COUNTY

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Description:

Starting in 2023 add 8 T-7As, and increase 759 LTOs

- Activity Start Date

Start Month: 1
Start Year: 2023

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.124692
SO _x	0.105199
NO _x	0.941128
CO	0.514749
PM 10	0.008812

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.007539
Pb	0.000000
NH ₃	0.000000
CO _{2e}	318.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.124692
SO _x	0.105199
NO _x	0.941128
CO	0.514749
PM 10	0.008812

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.007539
Pb	0.000000
NH ₃	0.000000
CO _{2e}	318.0

2.2 Aircraft & Engines

2.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

2.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

2.3 Flight Operations

2.3.1 Flight Operations Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations

Number of Aircraft:	8
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	759
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

2.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

2.4 Auxiliary Power Unit (APU)

2.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

2.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

2.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

3. Aircraft

3.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: T-7A Increase 1,700 TGOs OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2023 add 10 new T-7As, and increase 1,700TGOs

- Activity Start Date

Start Month: 1

Start Year: 2023

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.294061
SO _x	0.197961
NO _x	2.159129
CO	0.768998
PM 10	0.018946

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.016133
Pb	0.000000
NH ₃	0.000000
CO _{2e}	598.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.294061
SO _x	0.197961
NO _x	2.159129
CO	0.768998
PM 10	0.018946

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.016133
Pb	0.000000
NH ₃	0.000000
CO _{2e}	598.3

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

3.2 Aircraft & Engines

3.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

3.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

3.3 Flight Operations

3.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 10
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1700
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.05
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.9
Approach [Approach] (mins): 2.58
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

3.3.2 Flight Operations Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

3.4 Auxiliary Power Unit (APU)

3.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

3.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

3.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

4. Aircraft

4.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: T-38 Removal 5 TGOs OUTSIDE BEXAR COUNTY

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Description:

Starting in 2024, remove 5 T-38 TGOs

- Activity Start Date

Start Month: 1
Start Year: 2024

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.001661
SO _x	-0.000289
NO _x	-0.000226
CO	-0.024829
PM 10	-0.000663

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.000393
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-0.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.001661
SO _x	-0.000289
NO _x	-0.000226
CO	-0.024829
PM 10	-0.000663

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.000393
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-0.9

4.2 Aircraft & Engines

4.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

4.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

4.3 Flight Operations

4.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	91
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	5
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

4.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

- AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
- TIM: Time in Mode (min)
- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- TGO: Number of Touch-and-Go Cycles (for all aircraft)
- 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

- AE_{TGO}: Aircraft Emissions (TONs)
- AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
- AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
- AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

- AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
- TD: Test Duration (min)
- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- NA: Number of Aircraft
- NTT: Number of Trim Test
- 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

4.4 Auxiliary Power Unit (APU)

4.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
-------------------------------	---------------------------------	-------------------	-------------	--------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

4.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

4.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

5. Aircraft

5.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Add 10 T-7As and 1328 LTOs OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2024 add 10 new T-7As, and increase 1328 LTO

- Activity Start Date

Start Month: 1

Start Year: 2024

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.218171
SO _x	0.184064
NO _x	1.646664
CO	0.900641
PM 10	0.015418

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.013191
Pb	0.000000
NH ₃	0.000000
CO _{2e}	556.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
-----------	---------------------------

Pollutant	Emissions Per Year (TONs)
-----------	---------------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

VOC	0.218171
SO _x	0.184064
NO _x	1.646664
CO	0.900641
PM 10	0.015418

PM 2.5	0.013191
Pb	0.000000
NH ₃	0.000000
CO _{2e}	556.3

5.2 Aircraft & Engines

5.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

5.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

5.3 Flight Operations

5.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 10
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1328
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.1
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.51
Approach [Approach] (mins): 4.52
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

5.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

5.4 Auxiliary Power Unit (APU)

5.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

5.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

5.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

6. Aircraft

6.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase T-7A TGOs OUTSIDE BEXAR COUNTY

- Activity Description:
 Starting in 2024 Increase T-7A TGOs 2931

- Activity Start Date
 Start Month: 1
 Start Year: 2024

- Activity End Date
 Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.510659
SO _x	0.425574
NO _x	4.228190
CO	1.717864
PM 10	0.032665

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.027814
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1302.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.510659
SO _x	0.425574
NO _x	4.228190
CO	1.717864
PM 10	0.032665

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.027814
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1302.9

6.2 Aircraft & Engines

6.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate
 Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

6.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)
 Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

6.3 Flight Operations

6.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	10
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	2931
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

6.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

6.4 Auxiliary Power Unit (APU)

6.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU	Operation Hours	Exempt	Designation	Manufacturer
---------------	-----------------	--------	-------------	--------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

per Aircraft	for Each LTO	Source?		
1	0.25	No	4501687C	Hamilton Sundstrand

6.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

6.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

7. Aircraft

7.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove 11 T-38s and 2776LTOs OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2025 remove T-38s and 2776 LTOs

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.475438
SO _x	-0.228090
NO _x	-0.186752
CO	-20.882412
PM 10	-0.555171

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.347578
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-689.4

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.475438
SO _x	-0.228090
NO _x	-0.186752
CO	-20.882412
PM 10	-0.555171

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.347578
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-689.4

7.2 Aircraft & Engines

7.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

7.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

7.3 Flight Operations

7.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 11
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 2776
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.1
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.51
 Approach [Approach] (mins): 4.52
 Taxi/Idle In [Idle] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

7.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

7.4 Auxiliary Power Unit (APU)

7.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

7.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

7.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

8. Aircraft

8.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove 6142 T-38 TGOs OUTSIDE BEXAR COUNTY

- Activity Description:
 - Starting in 2025, remove 6142 T-38 TGOs

- Activity Start Date
 - Start Month: 1
 - Start Year: 2025

- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-2.040612
SO _x	-0.355029
NO _x	-0.277701
CO	-30.500216
PM 10	-0.814230

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.483192
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1073.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-2.040612
SO _x	-0.355029
NO _x	-0.277701
CO	-30.500216
PM 10	-0.814230

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.483192
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1073.1

8.2 Aircraft & Engines

8.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-38C
 - Engine Model: J85-GE-5R
 - Primary Function: Trainer
 - Aircraft has After burn: Yes
 - Number of Engines: 2

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No
 - Original Aircraft Name:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Engine Name:

8.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

8.3 Flight Operations

8.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	11
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	6142
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

8.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

8.4 Auxiliary Power Unit (APU)

8.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

8.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

8.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

9. Aircraft

9.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Add 7 new T-7As and 2836 LTOs OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2025, add 7 new T-7As and 2836 LTOs

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.469457
SO _x	0.474611
NO _x	4.005731
CO	2.302672
PM 10	0.032925

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.028169
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1450.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.469457
SO _x	0.474611
NO _x	4.005731
CO	2.302672
PM 10	0.032925

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.028169
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1450.5

9.2 Aircraft & Engines

9.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

9.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

9.3 Flight Operations

9.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 7
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 2836
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

9.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

9.4 Auxiliary Power Unit (APU)

9.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

9.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

9.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

10. Aircraft

10.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add
- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA
- Activity Title: Increase T-7A TGOs by 6395 OUTSIDE BEXAR COUNTY
- Activity Description:
 - Starting in 2025, increase T-7A TGOs by 6395
- Activity Start Date
 - Start Month: 1
 - Start Year: 2025
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.106188
SO _x	0.744682
NO _x	8.122136
CO	2.892788
PM 10	0.071271

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.060687
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2250.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.106188
SO _x	0.744682
NO _x	8.122136
CO	2.892788
PM 10	0.071271

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.060687
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2250.7

10.2 Aircraft & Engines

10.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-7A
 - Engine Model: F404-GE-102

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

10.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

10.3 Flight Operations

10.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	7
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	6395
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

10.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

10.4 Auxiliary Power Unit (APU)

10.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

10.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

10.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs
- EF_{POL}: Emission Factor for Pollutant (lb/hr)
- 2000: Conversion Factor pounds to tons

11. Aircraft

11.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

- County: Guadalupe
- Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove 7 T-38s and reduce LTOs by 1534 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2026, remove 7 T-38s and reduce LTOs by 1534

- Activity Start Date

- Start Month: 1
- Start Year: 2026

- Activity End Date

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.815317
SO _x	-0.126041
NO _x	-0.103198
CO	-11.539488
PM 10	-0.306784

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.192069
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-381.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.815317
SO _x	-0.126041
NO _x	-0.103198
CO	-11.539488
PM 10	-0.306784

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.192069
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-381.0

11.2 Aircraft & Engines

11.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

11.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

11.3 Flight Operations

11.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 7
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1534
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual Trim Test(s) per Aircraft:

0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

11.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

11.4 Auxiliary Power Unit (APU)

11.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

11.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

11.4.3 Auxiliary Power Unit (APU) Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

12. Aircraft

12.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Decrease T-38 TGOs by 3394 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2026, decrease T-38 TGOs by 3394

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.127619
SO _x	-0.196185
NO _x	-0.153455
CO	-16.854076
PM 10	-0.449934

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.267007
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-593.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.127619
SO _x	-0.196185
NO _x	-0.153455
CO	-16.854076
PM 10	-0.449934

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.267007
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-593.0

12.2 Aircraft & Engines

12.2.1 Aircraft & Engines Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

12.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

12.3 Flight Operations

12.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 6
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3394
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.05
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.9
 Approach [Approach] (mins): 2.58
 Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
 Approach (mins): 27
 Intermediate (mins): 9
 Military (mins): 9
 AfterBurn (mins): 3

12.3.2 Flight Operations Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

12.4 Auxiliary Power Unit (APU)

12.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

12.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

12.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

13. Aircraft

13.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Add T-7As and increase LTOs by 2698 OUTSIDE BEXAR COUNTY

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Description:

Starting in 2026, add T-7As and increase LTOs by 2698

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.443241
SO _x	0.373948
NO _x	3.345407
CO	1.829766
PM 10	0.031323

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.026799
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1130.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.443241
SO _x	0.373948
NO _x	3.345407
CO	1.829766
PM 10	0.031323

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.026799
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1130.2

13.2 Aircraft & Engines

13.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

13.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

13.3 Flight Operations

13.3.1 Flight Operations Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations

Number of Aircraft:	14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	2698
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

13.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

13.4 Auxiliary Power Unit (APU)

13.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

13.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

13.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

14. Aircraft

14.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase T-7A TGOs by 6040 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2026, increase T-7A TGOs by 6040

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.052331
SO _x	0.876993
NO _x	8.713159
CO	3.540054
PM 10	0.067314

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.057318
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2684.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.052331
SO _x	0.876993
NO _x	8.713159

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.057318
Pb	0.000000
NH ₃	0.000000

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

CO	3.540054
PM 10	0.067314

CO ₂ e	2684.8

14.2 Aircraft & Engines

14.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

14.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

14.3 Flight Operations

14.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 19
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 6040
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.05
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.9
Approach [Approach] (mins): 2.58
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

14.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

14.4 Auxiliary Power Unit (APU)

14.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

14.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

14.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

15. Aircraft

15.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Regulatory Area(s): NOT IN A REGULATORY AREA

- **Activity Title:** Remove T-38s and decrease LTOs by 3767 OUTSIDE BEXAR COUNTY

- **Activity Description:**

Starting in 2027, remove T-38s and decrease LTOs by 3,767

- **Activity Start Date**

Start Month: 1

Start Year: 2027

- **Activity End Date**

Indefinite: Yes

End Month: N/A

End Year: N/A

- **Activity Emissions:**

Pollutant	Emissions Per Year (TONs)
VOC	-2.002152
SO _x	-0.309515
NO _x	-0.253420
CO	-28.337192
PM 10	-0.753361

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.471659
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-935.5

- **Activity Emissions [Flight Operations (includes Trim Test & APU) part]:**

Pollutant	Emissions Per Year (TONs)
VOC	-2.002152
SO _x	-0.309515
NO _x	-0.253420
CO	-28.337192
PM 10	-0.753361

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.471659
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-935.5

15.2 Aircraft & Engines

15.2.1 Aircraft & Engines Assumptions

- **Aircraft & Engine**

Aircraft Designation: T-38C

Engine Model: J85-GE-5R

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 2

- **Aircraft & Engine Surrogate**

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

15.2.2 Aircraft & Engines Emission Factor(s)

- **Aircraft & Engine Emissions Factors (lb/1000lb fuel)**

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

15.3 Flight Operations

15.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	16
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	3767
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

15.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

15.4 Auxiliary Power Unit (APU)

15.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

15.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

15.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

16. Aircraft

16.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Decrease T-38 TGOs by 8,328 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2027, decrease T-38 TGOs by 8,328

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-2.766886
SO _x	-0.481388
NO _x	-0.376538
CO	-41.355552
PM 10	-1.104023

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.655165
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1455.0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-2.766886
SO _x	-0.481388
NO _x	-0.376538
CO	-41.355552
PM 10	-1.104023

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.655165
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1455.0

16.2 Aircraft & Engines

16.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

16.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

16.3 Flight Operations

16.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 16
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 8328
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.05
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.9
 Approach [Approach] (mins): 2.58
 Taxi/Idle In [Idle] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

16.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

16.4 Auxiliary Power Unit (APU)

16.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

16.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

16.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

17. Aircraft

17.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Add 19 new T-7As and increase LTOs by 3927 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2027, add 19 new T-7As and increase LTOs by 3927

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.645147
SO _x	0.544290
NO _x	4.869315
CO	2.663266
PM 10	0.045591

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.039006
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1645.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.645147
SO _x	0.544290
NO _x	4.869315
CO	2.663266
PM 10	0.045591

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.039006
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1645.1

17.2 Aircraft & Engines

17.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Aircraft Name:

Original Engine Name:

17.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

17.3 Flight Operations

17.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	19
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	3927
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

17.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

17.4 Auxiliary Power Unit (APU)

17.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

17.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

17.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

18. Aircraft

18.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase T-7A TGOs by 8719 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2027, increase T-7A TGOs by 8719

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Pollutant	Emissions Per Year (TONs)
VOC	1.519085
SO _x	1.265977
NO _x	12.577820
CO	5.110220
PM 10	0.097171

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.082741
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3875.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.519085
SO _x	1.265977
NO _x	12.577820
CO	5.110220
PM 10	0.097171

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.082741
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3875.7

18.2 Aircraft & Engines

18.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

18.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

18.3 Flight Operations

18.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 19
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 8719
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.05
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.9

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Approach [Approach] (mins): 2.58
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

18.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AE_{TCO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

18.4 Auxiliary Power Unit (APU)

18.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

18.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

18.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

19. Aircraft

19.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove 21 T-38s and decrease LTOs by 12407 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2028, remove 21 T-38s and decrease LTOs by 12407

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-6.594292
SO _x	-1.019420
NO _x	-0.834664
CO	-93.331441
PM 10	-2.481270

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.553457
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-3081.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-6.594292
SO _x	-1.019420
NO _x	-0.834664
CO	-93.331441
PM 10	-2.481270

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.553457
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-3081.1

19.2 Aircraft & Engines

19.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C

Engine Model: J85-GE-5R

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 2

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

19.4 Auxiliary Power Unit (APU)

19.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

19.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

19.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs
- EF_{POL}: Emission Factor for Pollutant (lb/hr)
- 2000: Conversion Factor pounds to tons

20. Aircraft

20.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

- County: Guadalupe
- Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Decrease T-38 TGOs by 27396 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2028, decrease T-38 TGOs by 27396

- Activity Start Date

- Start Month: 1
- Start Year: 2028

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-9.102019
SO _x	-1.583586
NO _x	-1.238668
CO	-136.044273
PM 10	-3.631822

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.155249
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-4786.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-9.102019
SO _x	-1.583586
NO _x	-1.238668
CO	-136.044273
PM 10	-3.631822

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.155249
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-4786.3

20.2 Aircraft & Engines

20.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

20.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

20.3 Flight Operations

20.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 21
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 27396

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.05
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.9
Approach [Approach] (mins): 2.58
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

20.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

20.4 Auxiliary Power Unit (APU)

20.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

20.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

20.4.3 Auxiliary Power Unit (APU) Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

21. Aircraft

21.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Add T-7As and increase LTOs by 1012 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2028, add T-7As and increase LTOs by 1012

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.167521
SO _x	0.169360
NO _x	1.429408
CO	0.821687
PM 10	0.011749

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.010052
Pb	0.000000
NH ₃	0.000000
CO _{2e}	517.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.167521
SO _x	0.169360
NO _x	1.429408
CO	0.821687
PM 10	0.011749

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.010052
Pb	0.000000
NH ₃	0.000000
CO _{2e}	517.6

21.2 Aircraft & Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

21.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

21.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

21.3 Flight Operations

21.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	1012
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

21.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

21.4 Auxiliary Power Unit (APU)

21.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

21.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

21.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

22. Aircraft

22.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase T-7A TGOs by 2276 OUTSIDE BEXAR COUNTY

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Description:

Starting in 2028, increase T-7A TGOs by 2276

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.393696
SO _x	0.265034
NO _x	2.890693
CO	1.029552
PM 10	0.025365

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.021599
Pb	0.000000
NH ₃	0.000000
CO _{2e}	801.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.393696
SO _x	0.265034
NO _x	2.890693
CO	1.029552
PM 10	0.025365

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.021599
Pb	0.000000
NH ₃	0.000000
CO _{2e}	801.0

22.2 Aircraft & Engines

22.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

22.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

22.3 Flight Operations

22.3.1 Flight Operations Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations

Number of Aircraft:	14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	2276
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

22.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

22.4 Auxiliary Power Unit (APU)

22.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

22.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

22.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

23. Aircraft

23.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2023 T-7A Seguin AAF Closed Patterns

- Activity Description:

Increase 645 Closed Patterns

- Activity Start Date

Start Month: 1

Start Year: 2023

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.305500
SO _x	0.165822
NO _x	3.015634
CO	0.445806
PM 10	0.019708

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.016934
Pb	0.000000
NH ₃	0.000000
CO _{2e}	501.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.305500
SO _x	0.165822
NO _x	3.015634
CO	0.445806

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.016934
Pb	0.000000
NH ₃	0.000000
CO _{2e}	501.2

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

PM 10	0.019708
-------	----------

--	--

23.2 Aircraft & Engines

23.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

23.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

23.3 Flight Operations

23.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 645
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.93
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 1.91
Approach [Approach] (mins): 2.5
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

23.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

23.4 Auxiliary Power Unit (APU)

23.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

23.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

23.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

24. Aircraft

24.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2023 T-38C Seguin AAF Closed Patterns

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- **Activity Description:**
increase 15400 CLosed Patterns

- **Activity Start Date**
Start Month: 1
Start Year: 2023

- **Activity End Date**
Indefinite: Yes
End Month: N/A
End Year: N/A

- **Activity Emissions:**

Pollutant	Emissions Per Year (TONs)
VOC	6.097359
SO _x	1.693636
NO _x	1.831199
CO	107.523651
PM 10	3.036999

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.383375
Pb	0.000000
NH ₃	0.000000
CO _{2e}	5118.9

- **Activity Emissions [Flight Operations (includes Trim Test & APU) part]:**

Pollutant	Emissions Per Year (TONs)
VOC	6.097359
SO _x	1.693636
NO _x	1.831199
CO	107.523651
PM 10	3.036999

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.383375
Pb	0.000000
NH ₃	0.000000
CO _{2e}	5118.9

24.2 Aircraft & Engines

24.2.1 Aircraft & Engines Assumptions

- **Aircraft & Engine**
Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- **Aircraft & Engine Surrogate**
Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

24.2.2 Aircraft & Engines Emission Factor(s)

- **Aircraft & Engine Emissions Factors (lb/1000lb fuel)**

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

24.3 Flight Operations

24.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	15400
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

24.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

24.4 Auxiliary Power Unit (APU)

24.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU	Operation Hours	Exempt	Designation	Manufacturer
---------------	-----------------	--------	-------------	--------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

per Aircraft	for Each LTO	Source?	
--------------	--------------	---------	--

24.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

24.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

25. Aircraft

25.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2024 T-7A Seguin AAF Closed Patterns

- Activity Description:

increase 2235 Closed Patterns

- Activity Start Date

Start Month: 1

Start Year: 2024

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.058592
SO _x	0.574593
NO _x	10.449522
CO	1.544769
PM 10	0.068290

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.058679
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1736.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
-----------	---------------------------

Pollutant	Emissions Per Year (TONs)
-----------	---------------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

VOC	1.058592
SO _x	0.574593
NO _x	10.449522
CO	1.544769
PM 10	0.068290

PM 2.5	0.058679
Pb	0.000000
NH ₃	0.000000
CO ₂ e	1736.7

25.2 Aircraft & Engines

25.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

25.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

25.3 Flight Operations

25.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 2235
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.93
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 1.91
Approach [Approach] (mins): 2.5
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

25.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

25.4 Auxiliary Power Unit (APU)

25.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

25.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

25.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

26. Aircraft

26.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2024 T-38C Seguin AAF Closed Patterns

- Activity Description:
 Decrease 700 closed patterns.

- Activity Start Date
 Start Month: 1
 Start Year: 2024

- Activity End Date
 Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.277153
SO _x	-0.076983
NO _x	-0.083236
CO	-4.887439
PM 10	-0.138045

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.062881
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-232.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.277153
SO _x	-0.076983
NO _x	-0.083236
CO	-4.887439
PM 10	-0.138045

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.062881
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-232.7

26.2 Aircraft & Engines

26.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

26.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

26.3 Flight Operations

26.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	700
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

26.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)
AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

26.4 Auxiliary Power Unit (APU)

26.4.1 Auxiliary Power Unit (APU) Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

26.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

26.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

27. Aircraft

27.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2025 T-7A Seguin AAF Closed Patterns

- Activity Description:

Increase 10320 closed patterns

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	4.887994
SO _x	2.653153
NO _x	48.250140
CO	7.132894

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.270949
Pb	0.000000
NH ₃	0.000000
CO _{2e}	8019.0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

PM 10	0.315325
-------	----------

--	--

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	4.887994
SO _x	2.653153
NO _x	48.250140
CO	7.132894
PM 10	0.315325

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.270949
Pb	0.000000
NH ₃	0.000000
CO _{2e}	8019.0

27.2 Aircraft & Engines

27.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

27.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

27.3 Flight Operations

27.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 10320
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.93
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 1.91
 Approach [Approach] (mins): 2.5
 Taxi/Idle In [Idle] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

27.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

27.4 Auxiliary Power Unit (APU)

27.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

27.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

27.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

28. Aircraft

28.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove
- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA
- Activity Title: 2025 T-38C Seguin AAF Closed Patterns
- Activity Description:
 - Decrease 10600 Closed Patterns
- Activity Start Date
 - Start Month: 1
 - Start Year: 2025
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-4.196883
SO _x	-1.165750
NO _x	-1.260436
CO	-74.009786
PM 10	-2.090402

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.952193
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-3523.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-4.196883
SO _x	-1.165750
NO _x	-1.260436
CO	-74.009786
PM 10	-2.090402

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.952193
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-3523.4

28.2 Aircraft & Engines

28.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-38C
 - Engine Model: J85-GE-5R
 - Primary Function: Trainer
 - Aircraft has After burn: Yes
 - Number of Engines: 2
- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No
 - Original Aircraft Name:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Engine Name:

28.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

28.3 Flight Operations

28.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	10600
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

28.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

28.4 Auxiliary Power Unit (APU)

28.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

28.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

28.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

29. Aircraft

29.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2026 T-7A Seguin AAF Closed Patterns

- Activity Description:

Increase 8000 closed patterns.

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	3.789142
SO _x	2.056708
NO _x	37.403209
CO	5.529376
PM 10	0.244438

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.210038
Pb	0.000000
NH ₃	0.000000
CO _{2e}	6216.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	3.789142
SO _x	2.056708
NO _x	37.403209
CO	5.529376
PM 10	0.244438

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.210038
Pb	0.000000
NH ₃	0.000000
CO _{2e}	6216.3

29.2 Aircraft & Engines

29.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

29.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

29.3 Flight Operations

29.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 8000
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.93

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

29.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

- AE_{TGO}: Aircraft Emissions (TONs)
- AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
- AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
- AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

- AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
- TD: Test Duration (min)
- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- NA: Number of Aircraft
- NTT: Number of Trim Test
- 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

29.4 Auxiliary Power Unit (APU)

29.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

29.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

29.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

30. Aircraft

30.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2026 T-38C Seguin AAF Closed Patterns

- Activity Description:
 - Decrease 6300 closed patterns.

- Activity Start Date
 - Start Month: 1
 - Start Year: 2026

- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-2.494374
SO _x	-0.692851
NO _x	-0.749127
CO	-43.986948
PM 10	-1.242409

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.565926
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2094.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-2.494374
SO _x	-0.692851
NO _x	-0.749127
CO	-43.986948
PM 10	-1.242409

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.565926
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2094.1

30.2 Aircraft & Engines

30.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-38C
 - Engine Model: J85-GE-5R
 - Primary Function: Trainer
 - Aircraft has After burn: Yes
 - Number of Engines: 2

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No
 - Original Aircraft Name:
 - Original Engine Name:

30.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

30.3 Flight Operations

30.3.1 Flight Operations Assumptions

- Flight Operations
 - Number of Aircraft: 1
 - Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 6300
 - Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 - Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)
 - Taxi/Idle Out [Idle] (mins): 0
 - Takeoff [Military] (mins): 0.93
 - Takeoff [After Burn] (mins): 0
 - Climb Out [Intermediate] (mins): 1.91
 - Approach [Approach] (mins): 2.5
 - Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test
 - Idle (mins): 12
 - Approach (mins): 27
 - Intermediate (mins): 9
 - Military (mins): 9
 - AfterBurn (mins): 3

30.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
 TIM: Time in Mode (min)
 60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

30.4 Auxiliary Power Unit (APU)

30.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

30.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

30.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs
- EF_{POL}: Emission Factor for Pollutant (lb/hr)
- 2000: Conversion Factor pounds to tons

31. Aircraft

31.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

- County: Guadalupe
- Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2027 T-7A Seguin AAF Closed Patterns

- Activity Description:

increase 9120 closed patterns.

- Activity Start Date

- Start Month: 1
- Start Year: 2027

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	4.319622
SO _x	2.344647
NO _x	42.639658
CO	6.303488
PM 10	0.278659

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.239444
Pb	0.000000
NH ₃	0.000000
CO _{2e}	7086.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	4.319622
SO _x	2.344647
NO _x	42.639658
CO	6.303488
PM 10	0.278659

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.239444
Pb	0.000000
NH ₃	0.000000
CO _{2e}	7086.5

31.2 Aircraft & Engines

31.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

31.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

31.3 Flight Operations

31.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 9120
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

31.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
 AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
 AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
 AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
 AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
 AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
 AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
 AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
 AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

31.4 Auxiliary Power Unit (APU)

31.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

31.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

31.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

32. Aircraft

32.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove
- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA
- Activity Title: 2027 T-38C Seguin AAF Closed Patterns
- Activity Description:
 - Decrease 11100 closed patterns.
- Activity Start Date
 - Start Month: 1
 - Start Year: 2027
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-4.394850
SO _x	-1.220738
NO _x	-1.319890
CO	-77.500813
PM 10	-2.189006

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.997108
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-3689.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-4.394850
SO _x	-1.220738
NO _x	-1.319890
CO	-77.500813
PM 10	-2.189006

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.997108
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-3689.6

32.2 Aircraft & Engines

32.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-38C

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No
 - Original Aircraft Name:
 - Original Engine Name:

32.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

32.3 Flight Operations

32.3.1 Flight Operations Assumptions

- Flight Operations
 - Number of Aircraft: 1
 - Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 11100
 - Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 - Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)
 - Taxi/Idle Out [Idle] (mins): 0
 - Takeoff [Military] (mins): 0.93
 - Takeoff [After Burn] (mins): 0
 - Climb Out [Intermediate] (mins): 1.91
 - Approach [Approach] (mins): 2.5
 - Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test
 - Idle (mins): 12
 - Approach (mins): 27
 - Intermediate (mins): 9
 - Military (mins): 9
 - AfterBurn (mins): 3

32.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year
 $AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

32.4 Auxiliary Power Unit (APU)

32.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

32.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

32.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

33. Aircraft

33.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2028 T-7A Seguin AAF Closed Patterns

- Activity Description:

increase 2242 closed patterns

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Start Date

Start Month: 1
Start Year: 2028

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.061907
SO _x	0.576392
NO _x	10.482249
CO	1.549607
PM 10	0.068504

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.058863
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1742.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.061907
SO _x	0.576392
NO _x	10.482249
CO	1.549607
PM 10	0.068504

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.058863
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1742.1

33.2 Aircraft & Engines

33.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

33.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

33.3 Flight Operations

33.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 2242

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

33.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
 AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
 AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
 AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
 AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
 AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
 AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
 AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
 AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

33.4 Auxiliary Power Unit (APU)

33.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

33.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

33.4.3 Auxiliary Power Unit (APU) Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

34. Aircraft

34.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2028 T-38C Seguin AAF Closed Patterns

- Activity Description:

Decrease 28700 closed patterns.

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-11.363260
SO _x	-3.156322
NO _x	-3.412689
CO	-200.384986
PM 10	-5.659862

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.578107
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-9539.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-11.363260
SO _x	-3.156322
NO _x	-3.412689
CO	-200.384986
PM 10	-5.659862

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.578107
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-9539.8

34.2 Aircraft & Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

34.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

34.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

34.3 Flight Operations

34.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 28700
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.93
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 1.91
Approach [Approach] (mins): 2.5
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

34.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

34.4 Auxiliary Power Unit (APU)

34.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

34.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

34.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF AIR ANALYSIS (ROAA)

1. General Information: The Air Force's Air Conformity Applicability Model (ACAM) was used to perform an analysis to assess the potential air quality impact/s associated with the action in accordance with the Air Force Manual 32-7002, Environmental Compliance and Pollution Prevention; the Environmental Impact Analysis Process (EIAP, 32 CFR 989); and the General Conformity Rule (GCR, 40 CFR 93 Subpart B). This report provides a summary of the ACAM analysis.

a. Action Location:

Base: RANDOLPH AFB
State: Texas
County(s): Guadalupe
Regulatory Area(s): NOT IN A REGULATORY AREA

b. Action Title: Recapitalization of the T-38 Trainer At Randolph AFB - Alternative 2 (Guadalupe County)

c. Project Number/s (if applicable):

d. Projected Action Start Date: 1 / 2023

e. Action Description:

The proposed action encompasses the recapitalize of the T-38 flight-training program with newer and more capable T-7A aircraft at JBSA-Randolph and Lackland. In addition to the phased introduction of the T-7A aircraft, five military construction projects and 17 facilities sustainment, restoration, and modernization projects are proposed at JBSA-Randolph at JBSA-Lackland to provide modern facilities and infrastructure to support the T-7A aircraft's maintenance, training, and operational requirements. The number of personnel on JBSA-Randolph would increase due to the proposed aircraft recapitalization. No changes to airspace configurations (i.e., size, shape, or location) would be required to support the proposed operations of the T-7A aircraft; however, the T-7A aircraft may have more flight operations than occurs with the T 38C aircraft at both JBSA-Randolph and JBSA-Lackland. This Applicability Analysis present the worst-case of three aircraft operational intensities as the worst-case action alternatives for the Proposed Action.

A Conformity Evaluation is required for every proposed action that will occur within an area designated by the U.S. Environmental Protection Agency (EPA) as nonattainment or maintenance for any National Ambient Air Quality Standard (NAAQS). The proposed T-7A Recapitalization action will occur at both JBSA-Randolph AFB and JBSA-Lackland AFB which both fall entirely within Bexar County that has been designated by the U.S. Environmental Protection Agency (EPA) as a marginal nonattainment area for the 2015 Ozone NAAQS in 2018. Given this recent designation of Bexar County, the proposed action (as well as all proposed actions from federal agencies) are subject to the General Conformity Rule (GCR, 40 CFR 93 Subpart B). As a marginal nonattainment area for ozone, the GCR has established de minimis significance threshold values of less than 100 ton/yr (for any given year) for both nitrogen oxides (NOx) and volatile organic compounds (VOC).

f. Point of Contact:

Name: [REDACTED]
Title: NEPA COntact Support
Organization: [REDACTED]
Email:
Phone Number:

2. Air Impact Analysis: Based on the attainment status at the action location, the requirements of the General Conformity Rule are:

_____ applicable
__X__ not applicable

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF AIR ANALYSIS (ROAA)

Total net direct and indirect emissions associated with the action were estimated through ACAM on a calendar-year basis for the start of the action through achieving “steady state” (i.e., net gain/loss upon action fully implemented) emissions. The ACAM analysis used the latest and most accurate emission estimation techniques available; all algorithms, emission factors, and methodologies used are described in detail in the USAF Air Emissions Guide for Air Force Stationary Sources, the USAF Air Emissions Guide for Air Force Mobile Sources, and the USAF Air Emissions Guide for Air Force Transitory Sources.

“Insignificance Indicators” were used in the analysis to provide an indication of the significance of potential impacts to air quality based on current ambient air quality relative to the National Ambient Air Quality Standards (NAAQSs). These insignificance indicators are the 250 ton/yr Prevention of Significant Deterioration (PSD) major source threshold for actions occurring in areas that are “Clearly Attainment” (i.e., not within 5% of any NAAQS) and the GCR de minimis values (25 ton/yr for lead and 100 ton/yr for all other criteria pollutants) for actions occurring in areas that are “Near Nonattainment” (i.e., within 5% of any NAAQS). These indicators do not define a significant impact; however, they do provide a threshold to identify actions that are insignificant. Any action with net emissions below the insignificance indicators for all criteria pollutant is considered so insignificant that the action will not cause or contribute to an exceedance on one or more NAAQSs. For further detail on insignificance indicators see chapter 4 of the Air Force Air Quality Environmental Impact Analysis Process (EIAP) Guide, Volume II - Advanced Assessments.

The action’s net emissions for every year through achieving steady state were compared against the Insignificance Indicator and are summarized below.

Analysis Summary:

2023

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	6.822	250	No
NO _x	7.948	250	No
CO	109.254	250	No
SO _x	2.163	250	No
PM 10	3.084	250	No
PM 2.5	1.424	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	6536.7		

2024

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	20.888	250	No
NO _x	23.228	250	No
CO	160.859	250	No
SO _x	3.738	250	No
PM 10	3.789	250	No
PM 2.5	2.113	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	10927.5		

2025

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF AIR ANALYSIS (ROAA)

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	20.608	250	No
NO _x	90.936	250	No
CO	49.643	250	No
SO _x	6.442	250	No
PM 10	0.811	250	No
PM 2.5	0.744	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	19119.3		

2026

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	22.246	250	No
NO _x	146.800	250	No
CO	-10.209	250	No
SO _x	9.230	250	No
PM 10	-0.794	250	No
PM 2.5	0.057	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	27583.7		

2027

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	21.174	250	No
NO _x	219.069	250	No
CO	-138.936	250	No
SO _x	12.527	250	No
PM 10	-4.313	250	No
PM 2.5	-1.616	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	37621.1		

2028

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	18.689	250	No
NO _x	263.299	250	Yes
CO	-247.584	250	No
SO _x	14.324	250	No
PM 10	-7.283	250	No
PM 2.5	-3.106	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF AIR ANALYSIS (ROAA)

CO _{2e}	43080.3		
------------------	---------	--	--

2029

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	17.232	250	No
NO _x	282.813	250	Yes
CO	-301.249	250	No
SO _x	14.781	250	No
PM 10	-8.726	250	No
PM 2.5	-3.816	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	44467.9		

2030

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	13.372	250	No
NO _x	287.958	250	Yes
CO	-372.834	250	No
SO _x	14.181	250	No
PM 10	-10.693	250	No
PM 2.5	-4.823	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	42659.6		

2031

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	7.013	250	No
NO _x	288.612	250	Yes
CO	-478.209	250	No
SO _x	12.821	250	No
PM 10	-13.583	250	No
PM 2.5	-6.331	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	38550.0		

2032

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	7.436	250	No
NO _x	301.753	250	Yes
CO	-492.891	250	No
SO _x	13.603	250	No
PM 10	-14.015	250	No

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF AIR ANALYSIS (ROAA)

PM 2.5	-6.489	250	No
Pb	0.000	25	No
NH3	0.000	250	No
CO2e	40938.5		

2033 - (Steady State)

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	7.436	250	No
NO _x	301.753	250	Yes
CO	-492.891	250	No
SO _x	13.603	250	No
PM 10	-14.015	250	No
PM 2.5	-6.489	250	No
Pb	0.000	25	No
NH3	0.000	250	No
CO2e	40938.5		

The steady state estimated annual net emissions associated with this action exceed the insignificance indicators, indicating a potential for a significant impact to air quality. Therefore, the ACAM analysis is inconclusive and further air quality impact assessment is needed.

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1. General Information

- Action Location

Base: RANDOLPH AFB
State: Texas
County(s): Guadalupe
Regulatory Area(s): NOT IN A REGULATORY AREA

- Action Title: Recapitalization of the T-38 Trainer At Randolph AFB - Alternative 2 (Guadalupe County)

- Project Number/s (if applicable):

- Projected Action Start Date: 1 / 2023

- Action Purpose and Need:

The T 38 Talon is a twin-engine, high-altitude, supersonic jet used by the USAF and other nations for pilot training. The aircraft originally was developed in the 1950s with production occurring between 1961 and 1972. The fleet has undergone periodic upgrades overtime. In 2001, the USAF upgraded several hundred T 38s with modern avionics and replaced propulsion components to provide increased performance and superior reliability.

The purpose of the Proposed Action is to allow the USAF T-7A to provide more efficient and effective pilot training to establish a T-7A pilot pipeline to allow for the transition to T-7A training throughout the entire USAF.

- Action Description:

The proposed action encompasses the recapitalize of the T-38 flight-training program with newer and more capable T-7A aircraft at JBSA-Randolph and Lackland. In addition to the phased introduction of the T-7A aircraft, five military construction projects and 17 facilities sustainment, restoration, and modernization projects are proposed at JBSA-Randolph at JBSA-Lackland to provide modern facilities and infrastructure to support the T-7A aircraft's maintenance, training, and operational requirements. The number of personnel on JBSA-Randolph would increase due to the proposed aircraft recapitalization. No changes to airspace configurations (i.e., size, shape, or location) would be required to support the proposed operations of the T-7A aircraft; however, the T-7A aircraft may have more flight operations than occurs with the T 38C aircraft at both JBSA-Randolph and JBSA-Lackland. This Applicability Analysis present the worst-case of three aircraft operational intensities as the worst-case action alternatives for the Proposed Action.

A Conformity Evaluation is required for every proposed action that will occur within an area designated by the U.S. Environmental Protection Agency (EPA) as nonattainment or maintenance for any National Ambient Air Quality Standard (NAAQS). The proposed T-7A Recapitalization action will occur at both JBSA-Randolph AFB and JBSA-Lackland AFB which both fall entirely within Bexar County that has been designated by the U.S. Environmental Protection Agency (EPA) as a marginal nonattainment area for the 2015 Ozone NAAQS in 2018. Given this recent designation of Bexar County, the proposed action (as well as all proposed actions from federal agencies) are subject to the General Conformity Rule (GCR, 40 CFR 93 Subpart B). As a marginal nonattainment area for ozone, the GCR has established de minimis significance threshold values of less than 100 ton/yr (for any given year) for both nitrogen oxides (NOx) and volatile organic compounds (VOC).

- Point of Contact

Name: [REDACTED]
Title: NEPA COntract Support
Organization: [REDACTED]
Email:
Phone Number:

- Activity List:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Activity Type		Activity Title
2.	Aircraft	T-7As and 759 LTOs OUTSIDE BEXAR COUNTY
3.	Aircraft	T-7A Increase 1,701 TGOs OUTSIDE BEXAR COUNTY
4.	Aircraft	T-38 Removal 5 TGOs OUTSIDE BEXAR COUNTY
5.	Aircraft	Add 10 T-7As and 1641 LTOs OUTSIDE BEXAR COUNTY
6.	Aircraft	Increase T-7A TGOs OUTSIDE BEXAR COUNTY
7.	Aircraft	Remove 11 T-38s and 2776LTOs OUTSIDE BEXAR COUNTY
8.	Aircraft	Remove 6142 T-38 TGOs OUTSIDE BEXAR COUNTY
9.	Aircraft	Add 7 new T-7As and 3261 LTOs OUTSIDE BEXAR COUNTY
10.	Aircraft	Increase T-7A TGOs by 7353 OUTSIDE BEXAR COUNTY
11.	Aircraft	Remove 7 T-38s and reduce LTOs by 1534 OUTSIDE BEXAR COUNTY
12.	Aircraft	Decrease T-38 TGOs by 3394 OUTSIDE BEXAR COUNTY
13.	Aircraft	Add T-7As and increase LTOs by 3093 OUTSIDE BEXAR COUNTY
14.	Aircraft	Increase T-7A TGOs by 6947 OUTSIDE BEXAR COUNTY
15.	Aircraft	Remove T-38s and decrease LTOs by 3767 OUTSIDE BEXAR COUNTY
16.	Aircraft	Decrease T-38 TGOs by 8,328 OUTSIDE BEXAR COUNTY
17.	Aircraft	Add 19 new T-7As and increase LTOs by 5656 OUTSIDE BEXAR COUNTY
18.	Aircraft	Increase T-7A TGOs by 12595 OUTSIDE BEXAR COUNTY
19.	Aircraft	Remove 21 T-38s and decrease LTOs by 3,667 OUTSIDE BEXAR COUNTY
20.	Aircraft	Decrease T-38 TGOs by 8093 OUTSIDE BEXAR COUNTY
21.	Aircraft	Add T-7As and increase LTOs by 4941 OUTSIDE BEXAR COUNTY
22.	Aircraft	Increase T-7A TGOs by 10954 OUTSIDE BEXAR COUNTY
23.	Aircraft	Remove T-38s and decrease LTOs by 1445 OUTSIDE BEXAR COUNTY
24.	Aircraft	Decrease T-38 TGOs by 3193 OUTSIDE BEXAR COUNTY
25.	Aircraft	Add T-7As and increase LTOs by 581 OUTSIDE BEXAR COUNTY
26.	Aircraft	Increase T-7A TGOs by 1333 OUTSIDE OF BEXAR COUNTY
27.	Aircraft	Remove T-38s and decrease LTOs by 1715 OUTSIDE OF BEXAR COUNTY
28.	Aircraft	Decrease T-38 TGOs by 3792 OUTSIDE OF BEXAR COUNTY
29.	Aircraft	increase LTOs by 300 OUTSIDE OF BEXAR COUNTY
30.	Aircraft	Increase TGOs by 678 OUTSIDE OF BEXAR COUNTY
31.	Aircraft	Remove 14 T-38s and decrease LTOs by 2636 OUTSIDE OF BEXAR COUNTY
32.	Aircraft	2031 T-38 Removal 5840 TGOs OUTSIDE BEXAR COUNTY
33.	Aircraft	decrease T-7A LTOs by 119 OUTSIDE BEXAR COUNTY
34.	Aircraft	decrease T-7A TGOs by 258 OUTSIDE BEXAR COUNTY
35.	Aircraft	Increase LTOs by 1428 OUTSIDE BEXAR COUNTY
36.	Aircraft	Increase T-7A TGOs by 3161 OUTSIDE BEXAR COUNTY
37.	Aircraft	2023 T-7A Seguin AAF Closed Patterns
38.	Aircraft	2023 T-38C Seguin AAF Closed Patterns
39.	Aircraft	2024 T-7A Seguin AAF Closed Patterns
40.	Aircraft	2024 T-38C Seguin AAF Closed Patterns
41.	Aircraft	2025 T-7A Seguin AAF Closed Patterns
42.	Aircraft	2025 T-38C Seguin AAF Closed Patterns
43.	Aircraft	2026 T-7A Seguin AAF Closed Patterns
44.	Aircraft	2026 T-38C Seguin AAF Closed Patterns
45.	Aircraft	2027 T-7A Seguin AAF Closed Patterns
46.	Aircraft	2027 T-38C Seguin AAF Closed Patterns
47.	Aircraft	2028 T-7A Seguin AAF Closed Patterns
48.	Aircraft	2028 T-38C Seguin AAF Closed Patterns
49.	Aircraft	2029 T-7A Seguin AAF Closed Patterns
50.	Aircraft	2029 T-38C seguin AAF Closed Patterns

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

51.	Aircraft	2030 T-7A Seguin AAF Closed Patterns
52.	Aircraft	2030 T-38C Seguin AAF Closed Patterns
53.	Aircraft	2031 T-7A Seguin AAF Closed Patterns
54.	Aircraft	2031 T-38C Seguin AAF Closed Patterns
55.	Aircraft	2032 T-7A Seguin AAF Closed Patterns
56.	Aircraft	2032 T-38C Seguin AAF Closed Patterns

Emission factors and air emission estimating methods come from the United States Air Force's Air Emissions Guide for Air Force Stationary Sources, Air Emissions Guide for Air Force Mobile Sources, and Air Emissions Guide for Air Force Transitory Sources.

2. Aircraft

2.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: T-7As and 759 LTOs OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2023 add 8 T-7As, and increase 759 LTOs

- Activity Start Date

Start Month: 1

Start Year: 2023

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.124692
SO _x	0.105199
NO _x	0.941128
CO	0.514749
PM 10	0.008812

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.007539
Pb	0.000000
NH ₃	0.000000
CO _{2e}	318.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.124692
SO _x	0.105199
NO _x	0.941128
CO	0.514749
PM 10	0.008812

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.007539
Pb	0.000000
NH ₃	0.000000
CO _{2e}	318.0

2.2 Aircraft & Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

2.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

2.3 Flight Operations

2.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 8
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 759
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.1
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.51
Approach [Approach] (mins): 4.52
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

2.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

2.4 Auxiliary Power Unit (APU)

2.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

2.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

2.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

3. Aircraft

3.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: T-7A Increase 1,701 TGOs OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2023 add 10 new T-7As, and increase 1,701 TGOs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Start Date

Start Month: 1
Start Year: 2023

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.294234
SO _x	0.198077
NO _x	2.160399
CO	0.769450
PM 10	0.018957

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.016142
Pb	0.000000
NH ₃	0.000000
CO _{2e}	598.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.294234
SO _x	0.198077
NO _x	2.160399
CO	0.769450
PM 10	0.018957

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.016142
Pb	0.000000
NH ₃	0.000000
CO _{2e}	598.7

3.2 Aircraft & Engines

3.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

3.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

3.3 Flight Operations

3.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 10
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1701

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.05
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.9
Approach [Approach] (mins): 2.58
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

3.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

3.4 Auxiliary Power Unit (APU)

3.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

3.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

3.4.3 Auxiliary Power Unit (APU) Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

4. Aircraft

4.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: T-38 Removal 5 TGOs OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2024, remove 5 T-38 TGOs

- Activity Start Date

Start Month: 1

Start Year: 2024

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.001628
SO _x	-0.000284
NO _x	-0.000222
CO	-0.024375
PM 10	-0.000651

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.000385
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-0.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.001628
SO _x	-0.000284
NO _x	-0.000222
CO	-0.024375
PM 10	-0.000651

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.000385
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-0.9

4.2 Aircraft & Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

4.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

4.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

4.3 Flight Operations

4.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 91
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 5
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.05
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.9
 Approach [Approach] (mins): 2.52
 Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
 Approach (mins): 27
 Intermediate (mins): 9
 Military (mins): 9
 AfterBurn (mins): 3

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

4.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

4.4 Auxiliary Power Unit (APU)

4.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

4.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

4.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

5. Aircraft

5.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Add 10 T-7As and 1641 LTOs OUTSIDE BEXAR COUNTY

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Description:

Starting in 2024 add 10 new T-7As, and increase 1641 LTO

- Activity Start Date

Start Month: 1
Start Year: 2024

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.269592
SO _x	0.227446
NO _x	2.034771
CO	1.112916
PM 10	0.019051

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.016300
Pb	0.000000
NH ₃	0.000000
CO _{2e}	687.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.269592
SO _x	0.227446
NO _x	2.034771
CO	1.112916
PM 10	0.019051

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.016300
Pb	0.000000
NH ₃	0.000000
CO _{2e}	687.4

5.2 Aircraft & Engines

5.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

5.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

5.3 Flight Operations

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

5.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	10
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	1641
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

5.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

5.4 Auxiliary Power Unit (APU)

5.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

5.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

5.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

6. Aircraft

6.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase T-7A TGOs OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2024 Increase T-7A TGOs 3634

- Activity Start Date

Start Month: 1

Start Year: 2024

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.631399
SO _x	0.526196
NO _x	5.227895
CO	2.124032
PM 10	0.040389

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.034391
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1610.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.631399
SO _x	0.526196

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.034391
Pb	0.000000

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NO _x	5.227895
CO	2.124032
PM 10	0.040389

NH ₃	0.000000
CO ₂ e	1610.9

6.2 Aircraft & Engines

6.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

6.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

6.3 Flight Operations

6.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 10
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3624
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.05
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.9
Approach [Approach] (mins): 2.58
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AfterBurn (mins): 3

6.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

6.4 Auxiliary Power Unit (APU)

6.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

6.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

6.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

7. Aircraft

7.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove 11 T-38s and 2776LTOs OUTSIDE BEXAR COUNTY

- Activity Description:
 Starting in 2025 remove T-38s and 2776 LTOs

- Activity Start Date
 Start Month: 1
 Start Year: 2025

- Activity End Date
 Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.475438
SO _x	-0.228090
NO _x	-0.186752
CO	-20.882412
PM 10	-0.555171

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.347578
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-689.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.475438
SO _x	-0.228090
NO _x	-0.186752
CO	-20.882412
PM 10	-0.555171

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.347578
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-689.4

7.2 Aircraft & Engines

7.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

7.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

7.3 Flight Operations

7.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	11
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	2776
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

7.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)
AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

7.4 Auxiliary Power Unit (APU)

7.4.1 Auxiliary Power Unit (APU) Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

7.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

7.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

8. Aircraft

8.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove 6142 T-38 TGOs OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2025, remove 6142 T-38 TGOs

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-2.040612
SO _x	-0.355029
NO _x	-0.277701
CO	-30.500216

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.483192
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1073.1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

PM 10	-0.814230
-------	-----------

--	--

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-2.040612
SO _x	-0.355029
NO _x	-0.277701
CO	-30.500216
PM 10	-0.814230

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.483192
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1073.1

8.2 Aircraft & Engines

8.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

8.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

8.3 Flight Operations

8.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 11
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 6142
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.05
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.9
 Approach [Approach] (mins): 2.58

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

8.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
 AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
 AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

8.4 Auxiliary Power Unit (APU)

8.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

8.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

8.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

9. Aircraft

9.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Add 7 new T-7As and 3261 LTOs OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2025, add 7 new T-7As and 3261 LTOs

- Activity Start Date

Start Month: 1
 Start Year: 2025

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.539810
SO _x	0.545735
NO _x	4.606026
CO	2.647748
PM 10	0.037859

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.032391
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1667.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.539810
SO _x	0.545735
NO _x	4.606026
CO	2.647748
PM 10	0.037859

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.032391
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1667.9

9.2 Aircraft & Engines

9.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Aircraft Name:

Original Engine Name:

9.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

9.3 Flight Operations

9.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	7
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	3261
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

9.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

9.4 Auxiliary Power Unit (APU)

9.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

9.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

9.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

10. Aircraft

10.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase T-7A TGOs by 7353 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2025, increase T-7A TGOs by 7353

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.271900
SO _x	0.856238
NO _x	9.338869
CO	3.326141
PM 10	0.081947

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.069778
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2587.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.271900
SO _x	0.856238
NO _x	9.338869
CO	3.326141
PM 10	0.081947

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.069778
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2587.9

10.2 Aircraft & Engines

10.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

10.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

10.3 Flight Operations

10.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 7
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 7353
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.05

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

10.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

- AE_{TGO}: Aircraft Emissions (TONs)
- AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
- AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
- AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

- AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
- TD: Test Duration (min)
- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- NA: Number of Aircraft
- NTT: Number of Trim Test
- 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

10.4 Auxiliary Power Unit (APU)

10.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

10.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

10.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

11. Aircraft

11.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove 7 T-38s and reduce LTOs by 1534 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2026, remove 7 T-38s and reduce LTOs by 1534

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.815317
SO _x	-0.126041
NO _x	-0.103198
CO	-11.539488
PM 10	-0.306784

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.192069
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-381.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.815317
SO _x	-0.126041
NO _x	-0.103198
CO	-11.539488
PM 10	-0.306784

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.192069
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-381.0

11.2 Aircraft & Engines

11.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C

Engine Model: J85-GE-5R

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 2

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No
 - Original Aircraft Name:
 - Original Engine Name:

11.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

11.3 Flight Operations

11.3.1 Flight Operations Assumptions

- Flight Operations
 - Number of Aircraft: 7
 - Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1534
 - Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 - Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)
 - Taxi/Idle Out [Idle] (mins): 0
 - Takeoff [Military] (mins): 0.1
 - Takeoff [After Burn] (mins): 0
 - Climb Out [Intermediate] (mins): 0.51
 - Approach [Approach] (mins): 4.52
 - Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test
 - Idle (mins): 12
 - Approach (mins): 27
 - Intermediate (mins): 9
 - Military (mins): 9
 - AfterBurn (mins): 3

11.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
 TIM: Time in Mode (min)
 60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

11.4 Auxiliary Power Unit (APU)

11.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

11.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

11.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs
- EF_{POL}: Emission Factor for Pollutant (lb/hr)
- 2000: Conversion Factor pounds to tons

12. Aircraft

12.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Decrease T-38 TGOs by 3394 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2026, decrease T-38 TGOs by 3394

- Activity Start Date

Start Month: 1

Start Year: 2026

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.127619
SO _x	-0.196185
NO _x	-0.153455
CO	-16.854076
PM 10	-0.449934

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.267007
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-593.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.127619
SO _x	-0.196185
NO _x	-0.153455
CO	-16.854076
PM 10	-0.449934

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.267007
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-593.0

12.2 Aircraft & Engines

12.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

12.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

12.3 Flight Operations

12.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 6
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3394

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.05
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.9
Approach [Approach] (mins): 2.58
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

12.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

12.4 Auxiliary Power Unit (APU)

12.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

12.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

12.4.3 Auxiliary Power Unit (APU) Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

13. Aircraft

13.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Add T-7As and increase LTOs by 3093 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2026, add T-7As and increase LTOs by 3093

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.508134
SO _x	0.428696
NO _x	3.835190
CO	2.097653
PM 10	0.035909

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.030722
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1295.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.508134
SO _x	0.428696
NO _x	3.835190
CO	2.097653
PM 10	0.035909

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.030722
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1295.7

13.2 Aircraft & Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

13.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

13.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

13.3 Flight Operations

13.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3093
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.1
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.51
Approach [Approach] (mins): 4.52
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

13.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

13.4 Auxiliary Power Unit (APU)

13.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

13.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

13.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

14. Aircraft

14.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase T-7A TGOs by 6947 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2026, increase T-7A TGOs by 6947

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Start Date

Start Month: 1
Start Year: 2026

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.210355
SO _x	1.008687
NO _x	10.021575
CO	4.071648
PM 10	0.077423

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.065925
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3088.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.210355
SO _x	1.008687
NO _x	10.021575
CO	4.071648
PM 10	0.077423

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.065925
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3088.0

14.2 Aircraft & Engines

14.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

14.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

14.3 Flight Operations

14.3.1 Flight Operations Assumptions

- Flight Operations

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Aircraft:	19
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	6947
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- **Default Settings Used:** No

- **Flight Operations TIMs (Time In Mode)**

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- **Trim Test**

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

14.3.2 Flight Operations Formula(s)

- **Aircraft Emissions per Mode for LTOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- **Aircraft Emissions for LTOs per Year**

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- **Aircraft Emissions per Mode for TGOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TIM: Time in Mode (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

14.4 Auxiliary Power Unit (APU)

14.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

14.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

14.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

15. Aircraft

15.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove T-38s and decrease LTOs by 3767 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2027, remove T-38s and decrease LTOs by 3,767

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-2.002152
SO _x	-0.309515
NO _x	-0.253420
CO	-28.337192
PM 10	-0.753361

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.471659
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-935.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-2.002152
SO _x	-0.309515
NO _x	-0.253420
CO	-28.337192

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.471659
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-935.5

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

PM 10	-0.753361
-------	-----------

--	--

15.2 Aircraft & Engines

15.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

15.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

15.3 Flight Operations

15.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 16
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3767
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.1
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.51
 Approach [Approach] (mins): 4.52
 Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

15.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

15.4 Auxiliary Power Unit (APU)

15.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

15.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

15.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

16. Aircraft

16.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Location

County: Guadalupe
Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Decrease T-38 TGOs by 8,328 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2027, decrease T-38 TGOs by 8,328

- Activity Start Date

Start Month: 1
Start Year: 2027

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-2.766886
SO _x	-0.481388
NO _x	-0.376538
CO	-41.355552
PM 10	-1.104023

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.655165
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1455.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-2.766886
SO _x	-0.481388
NO _x	-0.376538
CO	-41.355552
PM 10	-1.104023

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.655165
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1455.0

16.2 Aircraft & Engines

16.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

16.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

16.3 Flight Operations

16.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	16
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	8328
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

16.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)
AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

16.4 Auxiliary Power Unit (APU)

16.4.1 Auxiliary Power Unit (APU) Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

16.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

16.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

17. Aircraft

17.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Add 19 new T-7As and increase LTOs by 5656 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2027, add 19 new T-7As and increase LTOs by 5656

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.929196
SO _x	0.783933
NO _x	7.013203

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.056180
Pb	0.000000
NH ₃	0.000000

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

CO	3.835863
PM 10	0.065664

CO _{2e}	2369.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.929196
SO _x	0.783933
NO _x	7.013203
CO	3.835863
PM 10	0.065664

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.056180
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2369.4

17.2 Aircraft & Engines

17.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

17.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

17.3 Flight Operations

17.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 19
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 5656
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.1
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.51
 Approach [Approach] (mins): 4.52
 Taxi/Idle In [Idle] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

17.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

17.4 Auxiliary Power Unit (APU)

17.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

17.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

17.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

18. Aircraft

18.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase T-7A TGOs by 12595 OUTSIDE BEXAR COUNTY

- Activity Description:
 - Starting in 2027, increase T-7A TGOs by 12595

- Activity Start Date
 - Start Month: 1
 - Start Year: 2027

- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	2.194389
SO _x	1.828762
NO _x	18.169244
CO	7.381950
PM 10	0.140368

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.119523
Pb	0.000000
NH ₃	0.000000
CO _{2e}	5598.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	2.194389
SO _x	1.828762
NO _x	18.169244
CO	7.381950
PM 10	0.140368

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.119523
Pb	0.000000
NH ₃	0.000000
CO _{2e}	5598.6

18.2 Aircraft & Engines

18.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-7A
 - Engine Model: F404-GE-102
 - Primary Function: Trainer
 - Aircraft has After burn: Yes
 - Number of Engines: 1

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Aircraft Name:

Original Engine Name:

18.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

18.3 Flight Operations

18.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	19
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	12595
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

18.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

18.4 Auxiliary Power Unit (APU)

18.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

18.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

18.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

19. Aircraft

19.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove 21 T-38s and decrease LTOs by 3,667 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2028, remove 21 T-38s and decrease LTOs by 3,667

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.954317
SO _x	-0.302120
NO _x	-0.247365
CO	-27.660168
PM 10	-0.735361

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.460390
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-913.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.954317
SO _x	-0.302120
NO _x	-0.247365
CO	-27.660168
PM 10	-0.735361

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.460390
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-913.1

19.2 Aircraft & Engines

19.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

19.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

19.3 Flight Operations

19.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 21
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3677
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

19.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

19.4 Auxiliary Power Unit (APU)

19.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

19.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

19.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

20. Aircraft

20.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove
- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA
- Activity Title: Decrease T-38 TGOs by 8093 OUTSIDE BEXAR COUNTY
- Activity Description:
 - Starting in 2028, decrease T-38 TGOs by 8093
- Activity Start Date
 - Start Month: 1
 - Start Year: 2028
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-2.688810
SO _x	-0.467804
NO _x	-0.365913
CO	-40.188579
PM 10	-1.072870

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.636678
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1413.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-2.688810
SO _x	-0.467804
NO _x	-0.365913
CO	-40.188579
PM 10	-1.072870

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.636678
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1413.9

20.2 Aircraft & Engines

20.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-38C
 - Engine Model: J85-GE-5R

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No
 - Original Aircraft Name:
 - Original Engine Name:

20.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

20.3 Flight Operations

20.3.1 Flight Operations Assumptions

- Flight Operations
 - Number of Aircraft: 21
 - Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 8093
 - Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 - Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)
 - Taxi/Idle Out [Idle] (mins): 0
 - Takeoff [Military] (mins): 0.05
 - Takeoff [After Burn] (mins): 0
 - Climb Out [Intermediate] (mins): 0.9
 - Approach [Approach] (mins): 2.58
 - Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test
 - Idle (mins): 12
 - Approach (mins): 27
 - Intermediate (mins): 9
 - Military (mins): 9
 - AfterBurn (mins): 3

20.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year
 $AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)
AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)
AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

20.4 Auxiliary Power Unit (APU)

20.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

20.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

20.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

21. Aircraft

21.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Add T-7As and increase LTOs by 4941 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2028, add T-7As and increase LTOs by 4941

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Start Date

Start Month: 1
Start Year: 2028

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.817909
SO _x	0.826887
NO _x	6.978955
CO	4.011813
PM 10	0.057363

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.049078
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2527.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.817909
SO _x	0.826887
NO _x	6.978955
CO	4.011813
PM 10	0.057363

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.049078
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2527.2

21.2 Aircraft & Engines

21.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

21.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

21.3 Flight Operations

21.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 4941

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.1
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.51
Approach [Approach] (mins): 4.52
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

21.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
 AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
 AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
 AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
 AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
 AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
 AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
 AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
 AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

21.4 Auxiliary Power Unit (APU)

21.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

21.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

21.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

22. Aircraft

22.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase T-7A TGOs by 10954 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2028, increase T-7A TGOs by 10954

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.647952
SO _x	1.109395
NO _x	12.100014
CO	4.309554
PM 10	0.106176

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.090409
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3353.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.647952
SO _x	1.109395
NO _x	12.100014
CO	4.309554
PM 10	0.106176

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.090409
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3353.1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

22.2 Aircraft & Engines

22.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

22.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

22.3 Flight Operations

22.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 9527
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.05
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.9
Approach [Approach] (mins): 2.58
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

22.3.2 Flight Operations Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

22.4 Auxiliary Power Unit (APU)

22.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

22.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

22.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

23. Aircraft

23.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove T-38s and decrease LTOs by 1445 OUTSIDE BEXAR COUNTY

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Description:

Starting in 2029 T-38s and decrease LTOs by 1445

- Activity Start Date

Start Month: 1
Start Year: 2029

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.768014
SO _x	-0.118728
NO _x	-0.097210
CO	-10.869987
PM 10	-0.288985

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.180926
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-358.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.768014
SO _x	-0.118728
NO _x	-0.097210
CO	-10.869987
PM 10	-0.288985

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.180926
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-358.8

23.2 Aircraft & Engines

23.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

23.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

23.3 Flight Operations

23.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	3
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	1445
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

23.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

- AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
- TIM: Time in Mode (min)
- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- TGO: Number of Touch-and-Go Cycles (for all aircraft)
- 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

- AE_{TGO}: Aircraft Emissions (TONs)
- AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
- AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
- AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

- AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
- TD: Test Duration (min)
- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- NA: Number of Aircraft
- NTT: Number of Trim Test
- 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

23.4 Auxiliary Power Unit (APU)

23.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
-------------------------------	---------------------------------	-------------------	-------------	--------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

23.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

23.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

24. Aircraft

24.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Decrease T-38 TGOs by 3193 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2029, decrease T-38 TGOs by 3193

- Activity Start Date

Start Month: 1

Start Year: 2029

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.060839
SO _x	-0.184567
NO _x	-0.144367
CO	-15.855941
PM 10	-0.423288

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.251194
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-557.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.060839

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.251194

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

SO _x	-0.184567
NO _x	-0.144367
CO	-15.855941
PM 10	-0.423288

Pb	0.000000
NH ₃	0.000000
CO _{2e}	-557.8

24.2 Aircraft & Engines

24.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

24.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

24.3 Flight Operations

24.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 7
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3193
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.05
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.9
 Approach [Approach] (mins): 2.58
 Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

24.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

24.4 Auxiliary Power Unit (APU)

24.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

24.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

24.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

25. Aircraft

25.1 General Information & Timeline Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe
Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Add T-7As and increase LTOs by 581 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2029, add T-7As and increase LTOs by 581

- Activity Start Date

Start Month: 1
Start Year: 2029

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.095450
SO _x	0.080528
NO _x	0.720416
CO	0.394030
PM 10	0.006745

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.005771
Pb	0.000000
NH ₃	0.000000
CO _{2e}	243.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.095450
SO _x	0.080528
NO _x	0.720416
CO	0.394030
PM 10	0.006745

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.005771
Pb	0.000000
NH ₃	0.000000
CO _{2e}	243.4

25.2 Aircraft & Engines

25.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

25.2.2 Aircraft & Engines Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

25.3 Flight Operations

25.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	0
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	581
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

25.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)
AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

25.4 Auxiliary Power Unit (APU)

25.4.1 Auxiliary Power Unit (APU) Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

25.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

25.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

26. Aircraft

26.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase T-7A TGOs by 1333 OUTSIDE OF BEXAR COUNTY

- Activity Description:

Starting in 2029, increase T-7A TGOs by 1333

- Activity Start Date

Start Month: 1

Start Year: 2029

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.232245
SO _x	0.193548
NO _x	1.922954

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.012650
Pb	0.000000
NH ₃	0.000000

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

CO	0.781273
PM 10	0.014856

CO _{2e}	592.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.232245
SO _x	0.193548
NO _x	1.922954
CO	0.781273
PM 10	0.014856

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.012650
Pb	0.000000
NH ₃	0.000000
CO _{2e}	592.5

26.2 Aircraft & Engines

26.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

26.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

26.3 Flight Operations

26.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 0
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1333
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.05
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.9
 Approach [Approach] (mins): 2.58
 Taxi/Idle In [Idle] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

26.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

26.4 Auxiliary Power Unit (APU)

26.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

26.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

26.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

27. Aircraft

27.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe
Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove T-38s and decrease LTOs by 1715 OUTSIDE OF BEXAR COUNTY

- Activity Description:

Starting in 2030, remove T-38s and decrease LTOs by 1715

- Activity Start Date

Start Month: 1
Start Year: 2030

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.911519
SO _x	-0.140913
NO _x	-0.115374
CO	-12.901058
PM 10	-0.342982

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.214732
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-425.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.911519
SO _x	-0.140913
NO _x	-0.115374
CO	-12.901058
PM 10	-0.342982

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.214732
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-425.9

27.2 Aircraft & Engines

27.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Aircraft Name:

Original Engine Name:

27.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

27.3 Flight Operations

27.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	6
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	1715
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

27.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

27.4 Auxiliary Power Unit (APU)

27.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

27.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

27.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

28. Aircraft

28.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Decrease T-38 TGOs by 3792 OUTSIDE OF BEXAR COUNTY

- Activity Description:

Starting in 2030, decrease T-38 TGOs by 3,792

- Activity Start Date

Start Month: 1

Start Year: 2030

- Activity End Date

Indefinite: Yes

End Month: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.259850
SO _x	-0.219191
NO _x	-0.171450
CO	-18.830482
PM 10	-0.502696

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.298317
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-662.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.259850
SO _x	-0.219191
NO _x	-0.171450
CO	-18.830482
PM 10	-0.502696

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.298317
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-662.5

28.2 Aircraft & Engines

28.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

28.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

28.3 Flight Operations

28.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 6
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3792
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- **Default Settings Used:** No

- **Flight Operations TIMs (Time In Mode)**

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- **Trim Test**

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

28.3.2 Flight Operations Formula(s)

- **Aircraft Emissions per Mode for LTOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- **Aircraft Emissions for LTOs per Year**

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- **Aircraft Emissions per Mode for TGOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

28.4 Auxiliary Power Unit (APU)

28.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

28.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

28.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

29. Aircraft

29.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: increase LTOs by 300 OUTSIDE OF BEXAR COUNTY

- Activity Description:

Stating in 2030, increase LTOs by 300

- Activity Start Date

Start Month: 1

Start Year: 2030

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.049661
SO _x	0.050206
NO _x	0.423737
CO	0.243583
PM 10	0.003483

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.002980
Pb	0.000000
NH ₃	0.000000
CO _{2e}	153.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.049661
SO _x	0.050206
NO _x	0.423737
CO	0.243583
PM 10	0.003483

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.002980
Pb	0.000000
NH ₃	0.000000
CO _{2e}	153.4

29.2 Aircraft & Engines

29.2.1 Aircraft & Engines Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

29.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

29.3 Flight Operations

29.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	0
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	300
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

29.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

29.4 Auxiliary Power Unit (APU)

29.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

29.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

29.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

30. Aircraft

30.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase TGOs by 678 OUTSIDE OF BEXAR COUNTY

- Activity Description:

Starting in 2030, increase TGOs by 678

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Start Date

Start Month: 1
Start Year: 2030

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.118126
SO _x	0.098444
NO _x	0.978067
CO	0.397377
PM 10	0.007556

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.006434
Pb	0.000000
NH ₃	0.000000
CO _{2e}	301.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.118126
SO _x	0.098444
NO _x	0.978067
CO	0.397377
PM 10	0.007556

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.006434
Pb	0.000000
NH ₃	0.000000
CO _{2e}	301.4

30.2 Aircraft & Engines

30.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

30.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

30.3 Flight Operations

30.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:

0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 678
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.05
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.9
Approach [Approach] (mins): 2.58
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

30.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

30.4 Auxiliary Power Unit (APU)

30.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

30.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4
----------	-------	-------	-------	-------	-------	--------	--------	-------

30.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

31. Aircraft

31.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove 14 T-38s and decrease LTOs by 2636 OUTSIDE OF BEXAR COUNTY

- Activity Description:

Starting in 2031, remove 14 T-38s and decrease TOs by 2,636

- Activity Start Date

Start Month: 1

Start Year: 2031

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.401028
SO _x	-0.216587
NO _x	-0.177333
CO	-19.829264
PM 10	-0.527172

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.330049
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-654.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.401028
SO _x	-0.216587
NO _x	-0.177333
CO	-19.829264
PM 10	-0.527172

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.330049
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-654.6

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

31.2 Aircraft & Engines

31.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

31.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

31.3 Flight Operations

31.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 2636
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.1
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.51
Approach [Approach] (mins): 4.52
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Military (mins): 9
AfterBurn (mins): 3

31.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

31.4 Auxiliary Power Unit (APU)

31.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

31.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

31.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

32. Aircraft

32.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Regulatory Area(s): NOT IN A REGULATORY AREA

- **Activity Title:** 2031 T-38 Removal 5840 TGOs OUTSIDE BEXAR COUNTY

- **Activity Description:**

Starting in 2031, decrease T-38 TGOs by 5840

- **Activity Start Date**

Start Month: 1

Start Year: 2031

- **Activity End Date**

Indefinite: Yes

End Month: N/A

End Year: N/A

- **Activity Emissions:**

Pollutant	Emissions Per Year (TONs)
VOC	-1.940276
SO _x	-0.337573
NO _x	-0.264047
CO	-29.000531
PM 10	-0.774195

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.459434
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1020.3

- **Activity Emissions [Flight Operations (includes Trim Test & APU) part]:**

Pollutant	Emissions Per Year (TONs)
VOC	-1.940276
SO _x	-0.337573
NO _x	-0.264047
CO	-29.000531
PM 10	-0.774195

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.459434
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1020.3

32.2 Aircraft & Engines

32.2.1 Aircraft & Engines Assumptions

- **Aircraft & Engine**

Aircraft Designation: T-38C

Engine Model: J85-GE-5R

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 2

- **Aircraft & Engine Surrogate**

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

32.2.2 Aircraft & Engines Emission Factor(s)

- **Aircraft & Engine Emissions Factors (lb/1000lb fuel)**

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

32.3 Flight Operations

32.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	5840
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

32.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

32.4 Auxiliary Power Unit (APU)

32.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

32.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

32.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

33. Aircraft

33.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: decrease T-7A LTOs by 119 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2031, decrease T-7A LTOs by 119

- Activity Start Date

Start Month: 1

Start Year: 2031

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.019550
SO _x	-0.016494
NO _x	-0.147555
CO	-0.080705

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.001182
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-49.9

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

PM 10	-0.001382
-------	-----------

--	--

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.019550
SO _x	-0.016494
NO _x	-0.147555
CO	-0.080705
PM 10	-0.001382

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.001182
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-49.9

33.2 Aircraft & Engines

33.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

33.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

33.3 Flight Operations

33.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 0
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 119
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.1
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.51
 Approach [Approach] (mins): 4.52
 Taxi/Idle In [Idle] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

33.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

33.4 Auxiliary Power Unit (APU)

33.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

33.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

33.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

34. Aircraft

34.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: decrease T-7A TGOs by 258 OUTSIDE BEXAR COUNTY

- Activity Description:
 - Starting in 2031, decrease T-7A TGOs by 258

- Activity Start Date
 - Start Month: 1
 - Start Year: 2031

- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.044951
SO _x	-0.037461
NO _x	-0.372185
CO	-0.151214
PM 10	-0.002875

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.002448
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-114.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.044951
SO _x	-0.037461
NO _x	-0.372185
CO	-0.151214
PM 10	-0.002875

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.002448
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-114.7

34.2 Aircraft & Engines

34.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-7A
 - Engine Model: F404-GE-102
 - Primary Function: Trainer
 - Aircraft has After burn: Yes
 - Number of Engines: 1

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Aircraft Name:

Original Engine Name:

34.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

34.3 Flight Operations

34.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	0
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	258
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

34.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

34.4 Auxiliary Power Unit (APU)

34.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

34.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

34.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

35. Aircraft

35.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase LTOs by 1428 OUTSIDE BEXAR COUNTY

- Activity Description:

increase LTOs by 1428

- Activity Start Date

Start Month: 1

Start Year: 2032

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.236384
SO _x	0.238979
NO _x	2.016990
CO	1.159455
PM 10	0.016579

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.014184
Pb	0.000000
NH ₃	0.000000
CO _{2e}	730.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.236384
SO _x	0.238979
NO _x	2.016990
CO	1.159455
PM 10	0.016579

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.014184
Pb	0.000000
NH ₃	0.000000
CO _{2e}	730.4

35.2 Aircraft & Engines

35.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

35.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

35.3 Flight Operations

35.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 0
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1428
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

35.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

35.4 Auxiliary Power Unit (APU)

35.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

35.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

35.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

36. Aircraft

36.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add
- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA
- Activity Title: Increase T-7A TGOs by 3161 OUTSIDE BEXAR COUNTY
- Activity Description:
 - Starting in 2032, increase T-7A TGOs by 3161
- Activity Start Date
 - Start Month: 1
 - Start Year: 2032
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.550732
SO _x	0.458969
NO _x	4.559983
CO	1.852667
PM 10	0.035229

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.029997
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1405.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.550732
SO _x	0.458969
NO _x	4.559983
CO	1.852667
PM 10	0.035229

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.029997
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1405.1

36.2 Aircraft & Engines

36.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-7A
 - Engine Model: F404-GE-102

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

36.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

36.3 Flight Operations

36.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	0
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	3161
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- **Default Settings Used:** No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

36.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

36.4 Auxiliary Power Unit (APU)

36.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

36.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

36.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

37. Aircraft

37.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2023 T-7A Seguin AAF Closed Patterns

- Activity Description:

Increase 645 Closed Patterns

- Activity Start Date

Start Month: 1

Start Year: 2023

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.305500
SO _x	0.165822
NO _x	3.015634
CO	0.445806
PM 10	0.019708

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.016934
Pb	0.000000
NH ₃	0.000000
CO _{2e}	501.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.305500
SO _x	0.165822
NO _x	3.015634
CO	0.445806
PM 10	0.019708

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.016934
Pb	0.000000
NH ₃	0.000000
CO _{2e}	501.2

37.2 Aircraft & Engines

37.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

37.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

37.3 Flight Operations

37.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 645
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- **Default Settings Used:** No

- **Flight Operations TIMs (Time In Mode)**

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- **Trim Test**

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

37.3.2 Flight Operations Formula(s)

- **Aircraft Emissions per Mode for LTOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- **Aircraft Emissions for LTOs per Year**

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- **Aircraft Emissions per Mode for TGOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

37.4 Auxiliary Power Unit (APU)

37.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

37.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

37.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

38. Aircraft

38.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add
- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA
- Activity Title: 2023 T-38C Seguin AAF Closed Patterns
- Activity Description:
 - increase 15400 CLosed Patterns
- Activity Start Date
 - Start Month: 1
 - Start Year: 2023
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	6.097359
SO _x	1.693636
NO _x	1.831199
CO	107.523651
PM 10	3.036999

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.383375
Pb	0.000000
NH ₃	0.000000
CO _{2e}	5118.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	6.097359
SO _x	1.693636
NO _x	1.831199
CO	107.523651
PM 10	3.036999

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.383375
Pb	0.000000
NH ₃	0.000000
CO _{2e}	5118.9

38.2 Aircraft & Engines

38.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

38.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

38.3 Flight Operations

38.3.1 Flight Operations Assumptions

- Flight Operations
 Number of Aircraft: 1
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 15400
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)
 Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.93
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 1.91
 Approach [Approach] (mins): 2.5
 Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test
 Idle (mins): 12
 Approach (mins): 27
 Intermediate (mins): 9
 Military (mins): 9
 AfterBurn (mins): 3

38.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

38.4 Auxiliary Power Unit (APU)

38.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

38.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

38.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

39. Aircraft

39.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2024 T-7A Seguin AAF Closed Patterns

- Activity Description:

increase 2667 Closed Patterns

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Start Date

Start Month: 1
Start Year: 2024

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	13.443774
SO _x	0.898835
NO _x	8.100412
CO	53.280392
PM 10	0.783283

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.701508
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2325.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	13.443774
SO _x	0.898835
NO _x	8.100412
CO	53.280392
PM 10	0.783283

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.701508
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2325.9

39.2 Aircraft & Engines

39.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

39.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

39.3 Flight Operations

39.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 2667
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 6.8
Takeoff [Military] (mins): 0.25
Takeoff [After Burn] (mins): 0.25
Climb Out [Intermediate] (mins): 1.4
Approach [Approach] (mins): 4
Taxi/Idle In [Idle] (mins): 4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

39.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- TGO: Number of Touch-and-Go Cycles (for all aircraft)
- 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

- AE_{TGO}: Aircraft Emissions (TONs)
- AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
- AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
- AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

- AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
- TD: Test Duration (min)
- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- NA: Number of Aircraft
- NTT: Number of Trim Test
- 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

39.4 Auxiliary Power Unit (APU)

39.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

39.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

39.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

40. Aircraft

40.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2024 T-38C Seguin AAF Closed Patterns

- Activity Description:

Decrease 700 closed patterns.

- Activity Start Date

Start Month: 1

Start Year: 2024

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.277153
SO _x	-0.076983
NO _x	-0.083236
CO	-4.887439
PM 10	-0.138045

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.062881
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-232.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.277153
SO _x	-0.076983
NO _x	-0.083236
CO	-4.887439
PM 10	-0.138045

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.062881
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-232.7

40.2 Aircraft & Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

40.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

40.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO ₂ e
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

40.3 Flight Operations

40.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 700
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.93
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 1.91
Approach [Approach] (mins): 2.5
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

40.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

40.4 Auxiliary Power Unit (APU)

40.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

40.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

40.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

41. Aircraft

41.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- **Activity Title:** 2025 T-7A Seguin AAF Closed Patterns

- **Activity Description:**
Increase 11868 closed patterns

- **Activity Start Date**
Start Month: 1
Start Year: 2025

- **Activity End Date**
Indefinite: Yes
End Month: N/A
End Year: N/A

- **Activity Emissions:**

Pollutant	Emissions Per Year (TONs)
VOC	5.621193
SO _x	3.051126
NO _x	55.487661
CO	8.202829
PM 10	0.362624

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.311592
Pb	0.000000
NH ₃	0.000000
CO _{2e}	9221.8

- **Activity Emissions [Flight Operations (includes Trim Test & APU) part]:**

Pollutant	Emissions Per Year (TONs)
VOC	5.621193
SO _x	3.051126
NO _x	55.487661
CO	8.202829
PM 10	0.362624

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.311592
Pb	0.000000
NH ₃	0.000000
CO _{2e}	9221.8

41.2 Aircraft & Engines

41.2.1 Aircraft & Engines Assumptions

- **Aircraft & Engine**
 Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- **Aircraft & Engine Surrogate**
 Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

41.2.2 Aircraft & Engines Emission Factor(s)

- **Aircraft & Engine Emissions Factors (lb/1000lb fuel)**
 Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

41.3 Flight Operations

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

41.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	11868
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

41.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

41.4 Auxiliary Power Unit (APU)

41.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
-------------------------------	---------------------------------	-------------------	-------------	--------------

41.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

41.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

42. Aircraft

42.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2025 T-38C Seguin AAF Closed Patterns

- Activity Description:

Decrease 10600 Closed Patterns

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-4.196883
SO _x	-1.165750
NO _x	-1.260436
CO	-74.009786
PM 10	-2.090402

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.952193
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-3523.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-4.196883
SO _x	-1.165750
NO _x	-1.260436

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.952193
Pb	0.000000
NH ₃	0.000000

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

CO	-74.009786
PM 10	-2.090402

CO _{2e}	-3523.4

42.2 Aircraft & Engines

42.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

42.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

42.3 Flight Operations

42.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 10600
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.93
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 1.91
 Approach [Approach] (mins): 2.5
 Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

42.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

42.4 Auxiliary Power Unit (APU)

42.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

42.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

42.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

43. Aircraft

43.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Location

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2026 T-7A Seguin AAF Closed Patterns

- Activity Description:

Increase 9200 closed patterns.

- Activity Start Date

Start Month: 1
 Start Year: 2026

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	4.357514
SO _x	2.365214
NO _x	43.013690
CO	6.358782
PM 10	0.281104

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.241544
Pb	0.000000
NH ₃	0.000000
CO _{2e}	7148.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	4.357514
SO _x	2.365214
NO _x	43.013690
CO	6.358782
PM 10	0.281104

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.241544
Pb	0.000000
NH ₃	0.000000
CO _{2e}	7148.7

43.2 Aircraft & Engines

43.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

43.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

43.3 Flight Operations

43.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	9200
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

43.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

43.4 Auxiliary Power Unit (APU)

43.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

43.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

43.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

44. Aircraft

44.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2026 T-38C Seguin AAF Closed Patterns

- Activity Description:

Decrease 6300 closed patterns.

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-2.494374
SO _x	-0.692851
NO _x	-0.749127
CO	-43.986948
PM 10	-1.242409

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.565926
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2094.1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-2.494374
SO _x	-0.692851
NO _x	-0.749127
CO	-43.986948
PM 10	-1.242409

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.565926
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2094.1

44.2 Aircraft & Engines

44.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

44.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

44.3 Flight Operations

44.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 6300
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.93
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 1.91
 Approach [Approach] (mins): 2.5
 Taxi/Idle In [Idle] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

44.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

44.4 Auxiliary Power Unit (APU)

44.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

44.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

44.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

45. Aircraft

45.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2027 T-7A Seguin AAF Closed Patterns

- Activity Description:
 - increase 10488 closed patterns.

- Activity Start Date
 - Start Month: 1
 - Start Year: 2027

- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	4.967566
SO _x	2.696344
NO _x	49.035607
CO	7.249011
PM 10	0.320458

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.275360
Pb	0.000000
NH ₃	0.000000
CO _{2e}	8149.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	4.967566
SO _x	2.696344
NO _x	49.035607
CO	7.249011
PM 10	0.320458

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.275360
Pb	0.000000
NH ₃	0.000000
CO _{2e}	8149.5

45.2 Aircraft & Engines

45.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-7A
 - Engine Model: F404-GE-102
 - Primary Function: Trainer
 - Aircraft has After burn: Yes
 - Number of Engines: 1

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No
 - Original Aircraft Name:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Engine Name:

45.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

45.3 Flight Operations

45.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	10488
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

45.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

45.4 Auxiliary Power Unit (APU)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

45.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

45.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

45.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

46. Aircraft

46.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2027 T-38C Seguin AAF Closed Patterns

- Activity Description:

Decrease 11100 closed patterns.

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-4.394850

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.997108

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

SO _x	-1.220738
NO _x	-1.319890
CO	-77.500813
PM 10	-2.189006

Pb	0.000000
NH ₃	0.000000
CO _{2e}	-3689.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-4.394850
SO _x	-1.220738
NO _x	-1.319890
CO	-77.500813
PM 10	-2.189006

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.997108
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-3689.6

46.2 Aircraft & Engines

46.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

46.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

46.3 Flight Operations

46.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 11100
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.93

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

46.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

- AE_{TGO}: Aircraft Emissions (TONs)
- AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
- AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
- AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

- AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
- TD: Test Duration (min)
- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- NA: Number of Aircraft
- NTT: Number of Trim Test
- 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

46.4 Auxiliary Power Unit (APU)

46.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

46.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

46.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

47. Aircraft

47.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2028 T-7A Seguin AAF Closed Patterns

- Activity Description:

increase 5704 closed patterns

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	2.701658
SO _x	1.466433
NO _x	26.668488
CO	3.942445
PM 10	0.174284

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.149757
Pb	0.000000
NH ₃	0.000000
CO _{2e}	4432.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	2.701658
SO _x	1.466433
NO _x	26.668488
CO	3.942445
PM 10	0.174284

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.149757
Pb	0.000000
NH ₃	0.000000
CO _{2e}	4432.2

47.2 Aircraft & Engines

47.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

47.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

47.3 Flight Operations

47.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	5704
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

47.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

47.4 Auxiliary Power Unit (APU)

47.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

47.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

47.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

48. Aircraft

48.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2028 T-38C Seguin AAF Closed Patterns

- Activity Description:

Decrease 7600 closed patterns.

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-3.009086
SO _x	-0.835821
NO _x	-0.903709
CO	-53.063620
PM 10	-1.498779

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.682704
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2526.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-3.009086
SO _x	-0.835821
NO _x	-0.903709
CO	-53.063620
PM 10	-1.498779

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.682704
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2526.2

48.2 Aircraft & Engines

48.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

48.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

48.3 Flight Operations

48.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 7600
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

48.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

48.4 Auxiliary Power Unit (APU)

48.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

48.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

48.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

49. Aircraft

49.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2029 T-7A Seguin AAF Closed Patterns

- Activity Description:

Increase 3772 Closed Patterns

- Activity Start Date

Start Month: 1

Start Year: 2029

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.786581
SO _x	0.969738
NO _x	17.635613
CO	2.607101
PM 10	0.115253

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.099033
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2931.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.786581
SO _x	0.969738
NO _x	17.635613
CO	2.607101
PM 10	0.115253

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.099033
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2931.0

49.2 Aircraft & Engines

49.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

49.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

49.3 Flight Operations

49.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	3772
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

49.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

49.4 Auxiliary Power Unit (APU)

49.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

49.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

49.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

50. Aircraft

50.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2029 T-38C seguin AAF Closed Patterns

- Activity Description:

decrease 4400 closed patterns.

- Activity Start Date

Start Month: 1

Start Year: 2029

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.742103
SO _x	-0.483896
NO _x	-0.523200
CO	-30.721043
PM 10	-0.867714

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.395250
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1462.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.742103
SO _x	-0.483896
NO _x	-0.523200
CO	-30.721043
PM 10	-0.867714

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.395250
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1462.5

50.2 Aircraft & Engines

50.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

50.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

50.3 Flight Operations

50.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 4400

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

50.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

50.4 Auxiliary Power Unit (APU)

50.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

50.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

50.4.3 Auxiliary Power Unit (APU) Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

51. Aircraft

51.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2030 T-7A Seguin AAF Closed Patterns

- Activity Description:

Increase 1012 closed patterns

- Activity Start Date

Start Month: 1

Start Year: 2030

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.479327
SO _x	0.260174
NO _x	4.731506
CO	0.699466
PM 10	0.030921

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.026570
Pb	0.000000
NH ₃	0.000000
CO _{2e}	786.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.479327
SO _x	0.260174
NO _x	4.731506
CO	0.699466
PM 10	0.030921

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.026570
Pb	0.000000
NH ₃	0.000000
CO _{2e}	786.4

51.2 Aircraft & Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

51.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

51.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

51.3 Flight Operations

51.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1012
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.93
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 1.91
Approach [Approach] (mins): 2.5
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

51.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

51.4 Auxiliary Power Unit (APU)

51.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

51.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

51.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

52. Aircraft

52.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2030 T-38C Seguin AAF Closed Patterns

- Activity Description:

Decrease 5900 closed patterns

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Start Date

Start Month: 1
Start Year: 2030

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-2.336001
SO _x	-0.648861
NO _x	-0.701563
CO	-41.194126
PM 10	-1.163526

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.529994
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1961.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-2.336001
SO _x	-0.648861
NO _x	-0.701563
CO	-41.194126
PM 10	-1.163526

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.529994
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1961.1

52.2 Aircraft & Engines

52.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

52.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

52.3 Flight Operations

52.3.1 Flight Operations Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	5900
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

52.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

52.4 Auxiliary Power Unit (APU)

52.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

52.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

52.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

53. Aircraft

53.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2031 T-7A Seguin AAF Closed Patterns

- Activity Description:

increase 552 closed patterns

- Activity Start Date

Start Month: 1

Start Year: 2031

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.261451
SO _x	0.141913
NO _x	2.580821
CO	0.381527
PM 10	0.016866

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.014493
Pb	0.000000
NH ₃	0.000000
CO _{2e}	428.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.261451
SO _x	0.141913
NO _x	2.580821
CO	0.381527

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.014493
Pb	0.000000
NH ₃	0.000000
CO _{2e}	428.9

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

PM 10	0.016866
-------	----------

--	--

53.2 Aircraft & Engines

53.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

53.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

53.3 Flight Operations

53.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 552
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.93
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 1.91
Approach [Approach] (mins): 2.5
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

53.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

53.4 Auxiliary Power Unit (APU)

53.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

53.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

53.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

54. Aircraft

54.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2031 T-38C Seguin AAF Closed PAtterns

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Description:
decrease 8120 closed patterns

- Activity Start Date
Start Month: 1
Start Year: 2031

- Activity End Date
Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-3.214971
SO _x	-0.893008
NO _x	-0.965541
CO	-56.694289
PM 10	-1.601327

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.729416
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2699.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-3.214971
SO _x	-0.893008
NO _x	-0.965541
CO	-56.694289
PM 10	-1.601327

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.729416
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2699.1

54.2 Aircraft & Engines

54.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate
Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

54.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

54.3 Flight Operations

54.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	8120
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

54.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

54.4 Auxiliary Power Unit (APU)

54.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU	Operation Hours	Exempt	Designation	Manufacturer
---------------	-----------------	--------	-------------	--------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

per Aircraft	for Each LTO	Source?	
--------------	--------------	---------	--

54.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

54.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

55. Aircraft

55.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2032 T-7A Seguin AAF Closed Patterns

- Activity Description:

increase 1472 closed patternd

- Activity Start Date

Start Month: 1

Start Year: 2032

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.697202
SO _x	0.378434
NO _x	6.882190
CO	1.017405
PM 10	0.044977

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.038647
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1143.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
-----------	---------------------------

Pollutant	Emissions Per Year (TONs)
-----------	---------------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

VOC	0.697202
SO _x	0.378434
NO _x	6.882190
CO	1.017405
PM 10	0.044977

PM 2.5	0.038647
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1143.8

55.2 Aircraft & Engines

55.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

55.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

55.3 Flight Operations

55.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1472
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.93
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 1.91
Approach [Approach] (mins): 2.5
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

55.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

55.4 Auxiliary Power Unit (APU)

55.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

55.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

55.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

56. Aircraft

56.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2032 T-38C Seguin AAF Closed Patterns

- Activity Description:
 Decrease 2680 Closed Patterns

- Activity Start Date
 Start Month: 1
 Start Year: 2032

- Activity End Date
 Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.061099
SO _x	-0.294737
NO _x	-0.318676
CO	-18.711908
PM 10	-0.528517

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.240743
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-890.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.061099
SO _x	-0.294737
NO _x	-0.318676
CO	-18.711908
PM 10	-0.528517

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.240743
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-890.8

56.2 Aircraft & Engines

56.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

56.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

56.3 Flight Operations

56.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	2680
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

56.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)
AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

56.4 Auxiliary Power Unit (APU)

56.4.1 Auxiliary Power Unit (APU) Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
-------------------------------	---------------------------------	-------------------	-------------	--------------

56.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

56.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF AIR ANALYSIS (ROAA)

1. General Information: The Air Force's Air Conformity Applicability Model (ACAM) was used to perform an analysis to assess the potential air quality impact/s associated with the action in accordance with the Air Force Manual 32-7002, Environmental Compliance and Pollution Prevention; the Environmental Impact Analysis Process (EIAP, 32 CFR 989); and the General Conformity Rule (GCR, 40 CFR 93 Subpart B). This report provides a summary of the ACAM analysis.

a. Action Location:

Base: RANDOLPH AFB
State: Texas
County(s): Guadalupe
Regulatory Area(s): NOT IN A REGULATORY AREA

b. Action Title: Recapitalization of the T-38 Trainer At Randolph AFB - Alternative 3 (Guadalupe County)

c. Project Number/s (if applicable):

d. Projected Action Start Date: 1 / 2023

e. Action Description:

The proposed action encompasses the recapitalize of the T-38 flight-training program with newer and more capable T-7A aircraft at JBSA-Randolph and Lackland. In addition to the phased introduction of the T-7A aircraft, five military construction projects and 17 facilities sustainment, restoration, and modernization projects are proposed at JBSA-Randolph at JBSA-Lackland to provide modern facilities and infrastructure to support the T-7A aircraft's maintenance, training, and operational requirements. The number of personnel on JBSA-Randolph would increase due to the proposed aircraft recapitalization. No changes to airspace configurations (i.e., size, shape, or location) would be required to support the proposed operations of the T-7A aircraft; however, the T-7A aircraft may have more flight operations than occurs with the T 38C aircraft at both JBSA-Randolph and JBSA-Lackland. This Applicability Analysis present the worst-case of three aircraft operational intensities as the worst-case action alternatives for the Proposed Action.

A Conformity Evaluation is required for every proposed action that will occur within an area designated by the U.S. Environmental Protection Agency (EPA) as nonattainment or maintenance for any National Ambient Air Quality Standard (NAAQS). The proposed T-7A Recapitalization action will occur at both JBSA-Randolph AFB and JBSA-Lackland AFB which both fall entirely within Bexar County that has been designated by the U.S. Environmental Protection Agency (EPA) as a marginal nonattainment area for the 2015 Ozone NAAQS in 2018. Given this recent designation of Bexar County, the proposed action (as well as all proposed actions from federal agencies) are subject to the General Conformity Rule (GCR, 40 CFR 93 Subpart B). As a marginal nonattainment area for ozone, the GCR has established de minimis significance threshold values of less than 100 ton/yr (for any given year) for both nitrogen oxides (NOx) and volatile organic compounds (VOC).

f. Point of Contact:

Name: [REDACTED]
Title: NEPA Contract Support
Organization: [REDACTED]
Email:
Phone Number:

2. Air Impact Analysis: Based on the attainment status at the action location, the requirements of the General Conformity Rule are:

applicable
 not applicable

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF AIR ANALYSIS (ROAA)

Total net direct and indirect emissions associated with the action were estimated through ACAM on a calendar-year basis for the start of the action through achieving “steady state” (i.e., net gain/loss upon action fully implemented) emissions. The ACAM analysis used the latest and most accurate emission estimation techniques available; all algorithms, emission factors, and methodologies used are described in detail in the USAF Air Emissions Guide for Air Force Stationary Sources, the USAF Air Emissions Guide for Air Force Mobile Sources, and the USAF Air Emissions Guide for Air Force Transitory Sources.

“Insignificance Indicators” were used in the analysis to provide an indication of the significance of potential impacts to air quality based on current ambient air quality relative to the National Ambient Air Quality Standards (NAAQSs). These insignificance indicators are the 250 ton/yr Prevention of Significant Deterioration (PSD) major source threshold for actions occurring in areas that are “Clearly Attainment” (i.e., not within 5% of any NAAQS) and the GCR de minimis values (25 ton/yr for lead and 100 ton/yr for all other criteria pollutants) for actions occurring in areas that are “Near Nonattainment” (i.e., within 5% of any NAAQS). These indicators do not define a significant impact; however, they do provide a threshold to identify actions that are insignificant. Any action with net emissions below the insignificance indicators for all criteria pollutant is considered so insignificant that the action will not cause or contribute to an exceedance on one or more NAAQSs. For further detail on insignificance indicators see chapter 4 of the Air Force Air Quality Environmental Impact Analysis Process (EIAP) Guide, Volume II - Advanced Assessments.

The action’s net emissions for every year through achieving steady state were compared against the Insignificance Indicator and are summarized below.

Analysis Summary:

2023

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	6.822	250	No
NO _x	7.950	250	No
CO	109.254	250	No
SO _x	2.163	250	No
PM 10	3.084	250	No
PM 2.5	1.424	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	6537.1		

2024

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	22.454	250	No
NO _x	25.028	250	No
CO	167.025	250	No
SO _x	3.931	250	No
PM 10	3.881	250	No
PM 2.5	2.195	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	11471.5		

2025

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF AIR ANALYSIS (ROAA)

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	21.392	250	No
NO _x	96.668	250	No
CO	39.783	250	No
SO _x	6.438	250	No
PM 10	0.462	250	No
PM 2.5	0.631	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	19068.9		

2026

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	22.348	250	No
NO _x	145.947	250	No
CO	-21.249	250	No
SO _x	8.823	250	No
PM 10	-1.186	250	No
PM 2.5	-0.093	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	26310.0		

2027

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	21.250	250	No
NO _x	217.896	250	No
CO	-147.634	250	No
SO _x	12.389	250	No
PM 10	-4.699	250	No
PM 2.5	-1.760	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	37166.1		

2028

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	19.484	250	No
NO _x	268.078	250	Yes
CO	-254.513	250	No
SO _x	14.663	250	No
PM 10	-7.622	250	No
PM 2.5	-3.211	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF AIR ANALYSIS (ROAA)

CO _{2e}	44069.1		
------------------	---------	--	--

2029

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	18.210	250	No
NO _x	289.351	250	Yes
CO	-307.850	250	No
SO _x	15.227	250	No
PM 10	-9.053	250	No
PM 2.5	-3.911	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	45782.8		

2030

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	14.406	250	No
NO _x	295.029	250	Yes
CO	-379.319	250	No
SO _x	14.662	250	No
PM 10	-11.017	250	No
PM 2.5	-4.915	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	44082.4		

2031

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	8.064	250	No
NO _x	295.862	250	Yes
CO	-484.681	250	No
SO _x	13.311	250	No
PM 10	-13.906	250	No
PM 2.5	-6.422	250	No
Pb	0.000	25	No
NH ₃	0.000	250	No
CO _{2e}	39995.7		

2032

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	8.617	250	No
NO _x	310.175	250	Yes
CO	-499.012	250	No
SO _x	14.186	250	No
PM 10	-14.329	250	No

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF AIR ANALYSIS (ROAA)

PM 2.5	-6.572	250	No
Pb	0.000	25	No
NH3	0.000	250	No
CO2e	42669.8		

2033 - (Steady State)

Pollutant	Action Emissions (ton/yr)	INSIGNIFICANCE INDICATOR	
		Indicator (ton/yr)	Exceedance (Yes or No)
NOT IN A REGULATORY AREA			
VOC	8.617	250	No
NOx	310.175	250	Yes
CO	-499.012	250	No
SOx	14.186	250	No
PM 10	-14.329	250	No
PM 2.5	-6.572	250	No
Pb	0.000	25	No
NH3	0.000	250	No
CO2e	42669.8		

The steady state estimated annual net emissions associated with this action exceed the insignificance indicators, indicating a potential for a significant impact to air quality. Therefore, the ACAM analysis is inconclusive and further air quality impact assessment is needed.

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1. General Information

- Action Location

Base: RANDOLPH AFB
State: Texas
County(s): Guadalupe
Regulatory Area(s): NOT IN A REGULATORY AREA

- Action Title: Recapitalization of the T-38 Trainer At Randolph AFB - Alternative 3 (Guadalupe County)

- Project Number/s (if applicable):

- Projected Action Start Date: 1 / 2023

- Action Purpose and Need:

The T 38 Talon is a twin-engine, high-altitude, supersonic jet used by the USAF and other nations for pilot training. The aircraft originally was developed in the 1950s with production occurring between 1961 and 1972. The fleet has undergone periodic upgrades overtime. In 2001, the USAF upgraded several hundred T 38s with modern avionics and replaced propulsion components to provide increased performance and superior reliability.

The purpose of the Proposed Action is to allow the USAF T-7A to provide more efficient and effective pilot training to establish a T-7A pilot pipeline to allow for the transition to T-7A training throughout the entire USAF.

- Action Description:

The proposed action encompasses the recapitalize of the T-38 flight-training program with newer and more capable T-7A aircraft at JBSA-Randolph and Lackland. In addition to the phased introduction of the T-7A aircraft, five military construction projects and 17 facilities sustainment, restoration, and modernization projects are proposed at JBSA-Randolph at JBSA-Lackland to provide modern facilities and infrastructure to support the T-7A aircraft's maintenance, training, and operational requirements. The number of personnel on JBSA-Randolph would increase due to the proposed aircraft recapitalization. No changes to airspace configurations (i.e., size, shape, or location) would be required to support the proposed operations of the T-7A aircraft; however, the T-7A aircraft may have more flight operations than occurs with the T 38C aircraft at both JBSA-Randolph and JBSA-Lackland. This Applicability Analysis present the worst-case of three aircraft operational intensities as the worst-case action alternatives for the Proposed Action.

A Conformity Evaluation is required for every proposed action that will occur within an area designated by the U.S. Environmental Protection Agency (EPA) as nonattainment or maintenance for any National Ambient Air Quality Standard (NAAQS). The proposed T-7A Recapitalization action will occur at both JBSA-Randolph AFB and JBSA-Lackland AFB which both fall entirely within Bexar County that has been designated by the U.S. Environmental Protection Agency (EPA) as a marginal nonattainment area for the 2015 Ozone NAAQS in 2018. Given this recent designation of Bexar County, the proposed action (as well as all proposed actions from federal agencies) are subject to the General Conformity Rule (GCR, 40 CFR 93 Subpart B). As a marginal nonattainment area for ozone, the GCR has established de minimis significance threshold values of less than 100 ton/yr (for any given year) for both nitrogen oxides (NOx) and volatile organic compounds (VOC).

- Point of Contact

Name: [REDACTED]
Title: NEPA Contract Support
Organization: [REDACTED]
Email:
Phone Number:

- Activity List:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Activity Type		Activity Title
2.	Aircraft	T-7As and 759 LTOs OUTSIDE BEXAR COUNTY
3.	Aircraft	T-7A Increase 1,702 TGOs OUTSIDE BEXAR COUNTY
4.	Aircraft	T-38 Removal 5 TGOs OUTSIDE BEXAR COUNTY
5.	Aircraft	Add 10 T-7As and 1849 LTOs OUTSIDE BEXAR COUNTY
6.	Aircraft	Increase T-7A TGOs OUTSIDE BEXAR COUNTY
7.	Aircraft	Remove 11 T-38s and 2776LTOs OUTSIDE BEXAR COUNTY
8.	Aircraft	Remove 6142 T-38 TGOs OUTSIDE BEXAR COUNTY
9.	Aircraft	Add 7 new T-7As and 3545 LTOs OUTSIDE BEXAR COUNTY
10.	Aircraft	Increase T-7A TGOs by 7993 OUTSIDE BEXAR COUNTY
11.	Aircraft	Remove 7 T-38s and reduce LTOs by 1534 OUTSIDE BEXAR COUNTY
12.	Aircraft	Decrease T-38 TGOs by 3394 OUTSIDE BEXAR COUNTY
13.	Aircraft	Add T-7As and increase LTOs by 3361 OUTSIDE BEXAR COUNTY
14.	Aircraft	Increase T-7A TGOs by 7550 OUTSIDE BEXAR COUNTY
15.	Aircraft	Remove T-38s and decrease LTOs by 3767 OUTSIDE BEXAR COUNTY
16.	Aircraft	Decrease T-38 TGOs by 8,328 OUTSIDE BEXAR COUNTY
17.	Aircraft	Add 19 new T-7As and increase LTOs by 6148 OUTSIDE BEXAR COUNTY
18.	Aircraft	Increase T-7A TGOs by 13690 OUTSIDE BEXAR COUNTY
19.	Aircraft	Remove 21 T-38s and decrease LTOs by 3,667 OUTSIDE BEXAR COUNTY
20.	Aircraft	Decrease T-38 TGOs by 8093 OUTSIDE BEXAR COUNTY
21.	Aircraft	Add T-7As and increase LTOs by 5372 OUTSIDE BEXAR COUNTY
22.	Aircraft	Increase T-7A TGOs by 11908 OUTSIDE BEXAR COUNTY
23.	Aircraft	Remove T-38s and decrease LTOs by 1445 OUTSIDE BEXAR COUNTY
24.	Aircraft	Decrease T-38 TGOs by 3193 OUTSIDE BEXAR COUNTY
25.	Aircraft	Add T-7As and increase LTOs by 630 OUTSIDE BEXAR COUNTY
26.	Aircraft	Icrease T-7A TGOs by 1447 OUTSIDE OF BEXAR COUNTY
27.	Aircraft	RemoveT-38s and decrease LTOs by 1715 OUTSIDE OF BEXAR COUNTY
28.	Aircraft	Decrease T-38 TGOs by 3792 OUTSIDE OF BEXAR COUNTY
29.	Aircraft	increase LTOs by 326 OUTSIDE OF BEXAR COUNTY
30.	Aircraft	Increase TGOs by 737 OUTSIDE OF BEXAR COUNTY
31.	Aircraft	Remove 14 T-38s and decrease LTOs by 2636 OUTSIDE OF BEXAR COUNTY
32.	Aircraft	2031 T-38 Removal 5840 TGOs OUTSIDE BEXAR COUNTY
33.	Aircraft	decrease T-7A LTOs by 130 OUTSIDE BEXAR COUNTY
34.	Aircraft	decrease T-7A TGOs by 280 OUTSIDE BEXAR COUNTY
35.	Aircraft	Increase LTOs by 1553 OUTSIDE BEXAR COUNTY
36.	Aircraft	Increase T-7A TGOs by 3436 OUTSIDE BEXAR COUNTY
37.	Aircraft	2023 T-7A Seguin AAF Closed Patterns
38.	Aircraft	2023 T-38C Seguin AAF Closed Patterns
39.	Aircraft	2024 T-7A Seguin AAF Closed Patterns
40.	Aircraft	2024 T-38C Seguin AAF Closed Patterns
41.	Aircraft	2025 T-7A Seguin AAF Closed Patterns
42.	Aircraft	2025 T-38C Seguin AAF Closed Patterns
43.	Aircraft	2026 T-7A Seguin AAF Closed Patterns
44.	Aircraft	2026 T-38C Seguin AAF Closed Patterns
45.	Aircraft	2027 T-7A Seguin AAF Closed Patterns
46.	Aircraft	2027 T-38C Seguin AAF Closed Patterns
47.	Aircraft	2028 T-7A Seguin AAF Closed Patterns
48.	Aircraft	2028 T-38C Seguin AAF Closed Patterns
49.	Aircraft	2029 T-7A Seguin AAF Closed Patterns
50.	Aircraft	2029 T-38C seguin AAF Closed Patterns

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

51.	Aircraft	2030 T-7A Seguin AAF Closed Patterns
52.	Aircraft	2030 T-38C Seguin AAF Closed Patterns
53.	Aircraft	2031 T-7A Seguin AAF Closed Patterns
54.	Aircraft	2031 T-38C Seguin AAF Closed Patterns
55.	Aircraft	2032 T-7A Seguin AAF Closed Patterns
56.	Aircraft	2032 T-38C Seguin AAF Closed Patterns

Emission factors and air emission estimating methods come from the United States Air Force's Air Emissions Guide for Air Force Stationary Sources, Air Emissions Guide for Air Force Mobile Sources, and Air Emissions Guide for Air Force Transitory Sources.

2. Aircraft

2.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: T-7As and 759 LTOs OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2023 add 8 T-7As, and increase 759 LTOs

- Activity Start Date

Start Month: 1

Start Year: 2023

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.124692
SO _x	0.105199
NO _x	0.941128
CO	0.514749
PM 10	0.008812

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.007539
Pb	0.000000
NH ₃	0.000000
CO _{2e}	318.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.124692
SO _x	0.105199
NO _x	0.941128
CO	0.514749
PM 10	0.008812

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.007539
Pb	0.000000
NH ₃	0.000000
CO _{2e}	318.0

2.2 Aircraft & Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

2.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

2.3 Flight Operations

2.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 8
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 759
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.1
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.51
Approach [Approach] (mins): 4.52
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

2.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

2.4 Auxiliary Power Unit (APU)

2.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

2.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

2.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

3. Aircraft

3.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: T-7A Increase 1,702 TGOs OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2023 add 10 new T-7As, and increase 1,702 TGOs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Start Date

Start Month: 1
Start Year: 2023

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.294407
SO _x	0.198194
NO _x	2.161669
CO	0.769902
PM 10	0.018968

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.016152
Pb	0.000000
NH ₃	0.000000
CO _{2e}	599.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.294407
SO _x	0.198194
NO _x	2.161669
CO	0.769902
PM 10	0.018968

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.016152
Pb	0.000000
NH ₃	0.000000
CO _{2e}	599.0

3.2 Aircraft & Engines

3.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

3.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

3.3 Flight Operations

3.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 10
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1702

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.05
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.9
Approach [Approach] (mins): 2.58
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

3.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
 AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
 AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
 AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
 AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
 AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
 AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
 AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
 AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

3.4 Auxiliary Power Unit (APU)

3.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

3.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

3.4.3 Auxiliary Power Unit (APU) Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

4. Aircraft

4.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: T-38 Removal 5 TGOs OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2024, remove 5 T-38 TGOs

- Activity Start Date

Start Month: 1

Start Year: 2024

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.001661
SO _x	-0.000289
NO _x	-0.000226
CO	-0.024829
PM 10	-0.000663

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.000393
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-0.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.001661
SO _x	-0.000289
NO _x	-0.000226
CO	-0.024829
PM 10	-0.000663

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.000393
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-0.9

4.2 Aircraft & Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

4.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

4.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

4.3 Flight Operations

4.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 91
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 5
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.05
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.9
 Approach [Approach] (mins): 2.58
 Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
 Approach (mins): 27
 Intermediate (mins): 9
 Military (mins): 9
 AfterBurn (mins): 3

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

4.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

4.4 Auxiliary Power Unit (APU)

4.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

4.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

4.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

5. Aircraft

5.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Add 10 T-7As and 1849 LTOs OUTSIDE BEXAR COUNTY

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Description:

Starting in 2024 add 10 new T-7As, and increase 1849 LTO

- Activity Start Date

Start Month: 1
Start Year: 2024

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.303763
SO _x	0.256275
NO _x	2.292682
CO	1.253980
PM 10	0.021466

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.018366
Pb	0.000000
NH ₃	0.000000
CO _{2e}	774.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.303763
SO _x	0.256275
NO _x	2.292682
CO	1.253980
PM 10	0.021466

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.018366
Pb	0.000000
NH ₃	0.000000
CO _{2e}	774.6

5.2 Aircraft & Engines

5.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

5.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

5.3 Flight Operations

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

5.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	10
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	1849
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

5.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

5.4 Auxiliary Power Unit (APU)

5.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

5.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

5.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

6. Aircraft

6.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase T-7A TGOs OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2024 Increase T-7A TGOs 4086

- Activity Start Date

Start Month: 1

Start Year: 2024

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.711892
SO _x	0.593277
NO _x	5.894365
CO	2.394811
PM 10	0.045537

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.038775
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1816.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.711892
SO _x	0.593277

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.038775
Pb	0.000000

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NO _x	5.894365
CO	2.394811
PM 10	0.045537

NH ₃	0.000000
CO ₂ e	1816.3

6.2 Aircraft & Engines

6.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

6.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

6.3 Flight Operations

6.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 10
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 4086
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.05
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.9
Approach [Approach] (mins): 2.58
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AfterBurn (mins): 3

6.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

6.4 Auxiliary Power Unit (APU)

6.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

6.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

6.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

7. Aircraft

7.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove 11 T-38s and 2776LTOs OUTSIDE BEXAR COUNTY

- Activity Description:
 Starting in 2025 remove T-38s and 2776 LTOs

- Activity Start Date
 Start Month: 1
 Start Year: 2025

- Activity End Date
 Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.475438
SO _x	-0.228090
NO _x	-0.186752
CO	-20.882412
PM 10	-0.555171

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.347578
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-689.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.475438
SO _x	-0.228090
NO _x	-0.186752
CO	-20.882412
PM 10	-0.555171

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.347578
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-689.4

7.2 Aircraft & Engines

7.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

7.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

7.3 Flight Operations

7.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	11
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	2776
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

7.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)
AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

7.4 Auxiliary Power Unit (APU)

7.4.1 Auxiliary Power Unit (APU) Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

7.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

7.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

8. Aircraft

8.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove 6142 T-38 TGOs OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2025, remove 6142 T-38 TGOs

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-2.040612
SO _x	-0.355029
NO _x	-0.277701
CO	-30.500216

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.483192
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1073.1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

PM 10	-0.814230
-------	-----------

--	--

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-2.040612
SO _x	-0.355029
NO _x	-0.277701
CO	-30.500216
PM 10	-0.814230

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.483192
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1073.1

8.2 Aircraft & Engines

8.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

8.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

8.3 Flight Operations

8.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 11
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 6142
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.05
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.9
 Approach [Approach] (mins): 2.58

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

8.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
 AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
 AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

8.4 Auxiliary Power Unit (APU)

8.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

8.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

8.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

9. Aircraft

9.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Add 7 new T-7As and 3545 LTOs OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2025, add 7 new T-7As and 3545 LTOs

- Activity Start Date

Start Month: 1
 Start Year: 2025

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.586822
SO _x	0.593263
NO _x	5.007164
CO	2.878340
PM 10	0.041156

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.035212
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1813.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.586822
SO _x	0.593263
NO _x	5.007164
CO	2.878340
PM 10	0.041156

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.035212
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1813.2

9.2 Aircraft & Engines

9.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Aircraft Name:

Original Engine Name:

9.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

9.3 Flight Operations

9.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	7
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	3545
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

9.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

9.4 Auxiliary Power Unit (APU)

9.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

9.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

9.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

10. Aircraft

10.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase T-7A TGOs by 7993 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2025, increase T-7A TGOs by 7993

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	2.086267
SO _x	1.262447
NO _x	20.381163
CO	4.198415
PM 10	0.138677

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.119249
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3815.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	2.086267
SO _x	1.262447
NO _x	20.381163
CO	4.198415
PM 10	0.138677

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.119249
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3815.7

10.2 Aircraft & Engines

10.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

10.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

10.3 Flight Operations

10.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 7
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 7993
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.51

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

10.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

- AE_{TGO}: Aircraft Emissions (TONs)
- AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
- AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
- AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

- AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
- TD: Test Duration (min)
- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- NA: Number of Aircraft
- NTT: Number of Trim Test
- 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

10.4 Auxiliary Power Unit (APU)

10.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

10.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

10.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

11. Aircraft

11.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove 7 T-38s and reduce LTOs by 1534 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2026, remove 7 T-38s and reduce LTOs by 1534

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.815317
SO _x	-0.126041
NO _x	-0.103198
CO	-11.539488
PM 10	-0.306784

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.192069
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-381.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.815317
SO _x	-0.126041
NO _x	-0.103198
CO	-11.539488
PM 10	-0.306784

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.192069
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-381.0

11.2 Aircraft & Engines

11.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C

Engine Model: J85-GE-5R

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 2

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No
 - Original Aircraft Name:
 - Original Engine Name:

11.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

11.3 Flight Operations

11.3.1 Flight Operations Assumptions

- Flight Operations
 - Number of Aircraft: 7
 - Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1534
 - Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 - Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)
 - Taxi/Idle Out [Idle] (mins): 0
 - Takeoff [Military] (mins): 0.1
 - Takeoff [After Burn] (mins): 0
 - Climb Out [Intermediate] (mins): 0.51
 - Approach [Approach] (mins): 4.52
 - Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test
 - Idle (mins): 12
 - Approach (mins): 27
 - Intermediate (mins): 9
 - Military (mins): 9
 - AfterBurn (mins): 3

11.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year
 $AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
 TIM: Time in Mode (min)
 60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

11.4 Auxiliary Power Unit (APU)

11.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

11.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

11.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs
- EF_{POL}: Emission Factor for Pollutant (lb/hr)
- 2000: Conversion Factor pounds to tons

12. Aircraft

12.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove
- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA
- Activity Title: Decrease T-38 TGOs by 3394 OUTSIDE BEXAR COUNTY
- Activity Description:
 - Starting in 2026, decrease T-38 TGOs by 3394
- Activity Start Date
 - Start Month: 1
 - Start Year: 2026

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.127619
SO _x	-0.196185
NO _x	-0.153455
CO	-16.854076
PM 10	-0.449934

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.267007
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-593.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.127619
SO _x	-0.196185
NO _x	-0.153455
CO	-16.854076
PM 10	-0.449934

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.267007
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-593.0

12.2 Aircraft & Engines

12.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

12.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

12.3 Flight Operations

12.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 6
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3394

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.05
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.9
Approach [Approach] (mins): 2.58
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

12.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

12.4 Auxiliary Power Unit (APU)

12.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

12.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

12.4.3 Auxiliary Power Unit (APU) Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

13. Aircraft

13.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Add T-7As and increase LTOs by 3361 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2026, add T-7As and increase LTOs by 3361

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.552162
SO _x	0.465842
NO _x	4.167499
CO	2.279409
PM 10	0.039020

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.033384
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1408.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.552162
SO _x	0.465842
NO _x	4.167499
CO	2.279409
PM 10	0.039020

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.033384
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1408.0

13.2 Aircraft & Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

13.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

13.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

13.3 Flight Operations

13.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3361
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.1
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.51
Approach [Approach] (mins): 4.52
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

13.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

13.4 Auxiliary Power Unit (APU)

13.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

13.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

13.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

14. Aircraft

14.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase T-7A TGOs by 7550 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2026, increase T-7A TGOs by 7550

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Start Date

Start Month: 1
Start Year: 2026

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.052331
SO _x	0.876993
NO _x	8.713159
CO	3.540054
PM 10	0.067314

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.057318
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2684.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.052331
SO _x	0.876993
NO _x	8.713159
CO	3.540054
PM 10	0.067314

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.057318
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2684.8

14.2 Aircraft & Engines

14.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

14.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

14.3 Flight Operations

14.3.1 Flight Operations Assumptions

- Flight Operations

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Aircraft:	19
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	6040
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- **Default Settings Used:** No

- **Flight Operations TIMs (Time In Mode)**

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- **Trim Test**

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

14.3.2 Flight Operations Formula(s)

- **Aircraft Emissions per Mode for LTOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- **Aircraft Emissions for LTOs per Year**

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- **Aircraft Emissions per Mode for TGOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TIM: Time in Mode (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

14.4 Auxiliary Power Unit (APU)

14.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

14.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

14.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

15. Aircraft

15.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove T-38s and decrease LTOs by 3767 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2027, remove T-38s and decrease LTOs by 3,767

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-2.002152
SO _x	-0.309515
NO _x	-0.253420
CO	-28.337192
PM 10	-0.753361

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.471659
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-935.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-2.002152
SO _x	-0.309515
NO _x	-0.253420
CO	-28.337192

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.471659
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-935.5

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

PM 10	-0.753361
-------	-----------

--	--

15.2 Aircraft & Engines

15.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

15.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

15.3 Flight Operations

15.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 16
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3767
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.1
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.51
 Approach [Approach] (mins): 4.52
 Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

15.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

15.4 Auxiliary Power Unit (APU)

15.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

15.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

15.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

16. Aircraft

16.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Location

County: Guadalupe
Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Decrease T-38 TGOs by 8,328 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2027, decrease T-38 TGOs by 8,328

- Activity Start Date

Start Month: 1
Start Year: 2027

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-2.766886
SO _x	-0.481388
NO _x	-0.376538
CO	-41.355552
PM 10	-1.104023

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.655165
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1455.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-2.766886
SO _x	-0.481388
NO _x	-0.376538
CO	-41.355552
PM 10	-1.104023

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.655165
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1455.0

16.2 Aircraft & Engines

16.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

16.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

16.3 Flight Operations

16.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	16
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	8328
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

16.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)
AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

16.4 Auxiliary Power Unit (APU)

16.4.1 Auxiliary Power Unit (APU) Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

16.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

16.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

17. Aircraft

17.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Add 19 new T-7As and increase LTOs by 6148 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2027, add 19 new T-7As and increase LTOs by 6148

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.063463
SO _x	0.715919
NO _x	7.808427

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.058343
Pb	0.000000
NH ₃	0.000000

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

CO	2.781058
PM 10	0.068518

CO _{2e}	2163.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.063463
SO _x	0.715919
NO _x	7.808427
CO	2.781058
PM 10	0.068518

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.058343
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2163.8

17.2 Aircraft & Engines

17.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

17.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

17.3 Flight Operations

17.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 19
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 6148
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.05
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.9
 Approach [Approach] (mins): 2.58
 Taxi/Idle In [Idle] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

17.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

17.4 Auxiliary Power Unit (APU)

17.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

17.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

17.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

18. Aircraft

18.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe
Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase T-7A TGOs by 13690 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2027, increase T-7A TGOs by 13690

- Activity Start Date

Start Month: 1
Start Year: 2027

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	2.266175
SO _x	2.291050
NO _x	19.336551
CO	11.115507
PM 10	0.158936

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.135980
Pb	0.000000
NH ₃	0.000000
CO _{2e}	7002.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	2.266175
SO _x	2.291050
NO _x	19.336551
CO	11.115507
PM 10	0.158936

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.135980
Pb	0.000000
NH ₃	0.000000
CO _{2e}	7002.0

18.2 Aircraft & Engines

18.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Aircraft Name:

Original Engine Name:

18.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

18.3 Flight Operations

18.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	19
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	13690
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

18.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

18.4 Auxiliary Power Unit (APU)

18.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

18.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

18.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

19. Aircraft

19.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove 21 T-38s and decrease LTOs by 3,667 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2028, remove 21 T-38s and decrease LTOs by 3,667

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.954317
SO _x	-0.302120
NO _x	-0.247365
CO	-27.660168
PM 10	-0.735361

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.460390
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-913.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.954317
SO _x	-0.302120
NO _x	-0.247365
CO	-27.660168
PM 10	-0.735361

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.460390
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-913.1

19.2 Aircraft & Engines

19.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

19.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

19.3 Flight Operations

19.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 21
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3677
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

19.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

19.4 Auxiliary Power Unit (APU)

19.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

19.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

19.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

20. Aircraft

20.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove
- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA
- Activity Title: Decrease T-38 TGOs by 8093 OUTSIDE BEXAR COUNTY
- Activity Description:
 - Starting in 2028, decrease T-38 TGOs by 8093
- Activity Start Date
 - Start Month: 1
 - Start Year: 2028
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-2.688810
SO _x	-0.467804
NO _x	-0.365913
CO	-40.188579
PM 10	-1.072870

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.636678
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1413.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-2.688810
SO _x	-0.467804
NO _x	-0.365913
CO	-40.188579
PM 10	-1.072870

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.636678
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1413.9

20.2 Aircraft & Engines

20.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-38C
 - Engine Model: J85-GE-5R

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No
 - Original Aircraft Name:
 - Original Engine Name:

20.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

20.3 Flight Operations

20.3.1 Flight Operations Assumptions

- Flight Operations
 - Number of Aircraft: 21
 - Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 8093
 - Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 - Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)
 - Taxi/Idle Out [Idle] (mins): 0
 - Takeoff [Military] (mins): 0.05
 - Takeoff [After Burn] (mins): 0
 - Climb Out [Intermediate] (mins): 0.9
 - Approach [Approach] (mins): 2.58
 - Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test
 - Idle (mins): 12
 - Approach (mins): 27
 - Intermediate (mins): 9
 - Military (mins): 9
 - AfterBurn (mins): 3

20.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year
 $AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

20.4 Auxiliary Power Unit (APU)

20.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
-------------------------------	---------------------------------	-------------------	-------------	--------------

20.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

20.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

21. Aircraft

21.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Add T-7As and increase LTOs by 5372 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2028, add T-7As and increase LTOs by 5372

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Start Date

Start Month: 1
Start Year: 2028

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.889254
SO _x	0.899015
NO _x	7.587725
CO	4.361761
PM 10	0.062367

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.053359
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2747.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.889254
SO _x	0.899015
NO _x	7.587725
CO	4.361761
PM 10	0.062367

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.053359
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2747.6

21.2 Aircraft & Engines

21.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

21.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

21.3 Flight Operations

21.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 5372

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.1
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.51
Approach [Approach] (mins): 4.52
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

21.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
 AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
 AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
 AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
 AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
 AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
 AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
 AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
 AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

21.4 Auxiliary Power Unit (APU)

21.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

21.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

21.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

22. Aircraft

22.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase T-7A TGOs by 11908 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2028, increase T-7A TGOs by 11908

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	2.059810
SO _x	1.386657
NO _x	15.124065
CO	5.386603
PM 10	0.132712

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.113004
Pb	0.000000
NH ₃	0.000000
CO _{2e}	4191.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	2.059810
SO _x	1.386657
NO _x	15.124065
CO	5.386603
PM 10	0.132712

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.113004
Pb	0.000000
NH ₃	0.000000
CO _{2e}	4191.1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

22.2 Aircraft & Engines

22.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

22.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

22.3 Flight Operations

22.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 11908
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.05
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.9
Approach [Approach] (mins): 2.58
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

22.3.2 Flight Operations Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

22.4 Auxiliary Power Unit (APU)

22.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

22.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

22.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

23. Aircraft

23.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove T-38s and decrease LTOs by 1445 OUTSIDE BEXAR COUNTY

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Description:

Starting in 2029 T-38s and decrease LTOs by 1445

- Activity Start Date

Start Month: 1
Start Year: 2029

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.768014
SO _x	-0.118728
NO _x	-0.097210
CO	-10.869987
PM 10	-0.288985

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.180926
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-358.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.768014
SO _x	-0.118728
NO _x	-0.097210
CO	-10.869987
PM 10	-0.288985

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.180926
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-358.8

23.2 Aircraft & Engines

23.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

23.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

23.3 Flight Operations

23.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	3
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	1445
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

23.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

- AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
- TIM: Time in Mode (min)
- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- TGO: Number of Touch-and-Go Cycles (for all aircraft)
- 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

- AE_{TGO}: Aircraft Emissions (TONs)
- AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
- AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
- AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

- AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
- TD: Test Duration (min)
- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- NA: Number of Aircraft
- NTT: Number of Trim Test
- 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

23.4 Auxiliary Power Unit (APU)

23.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
-------------------------------	---------------------------------	-------------------	-------------	--------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

23.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

23.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

24. Aircraft

24.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Decrease T-38 TGOs by 3193 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2029, decrease T-38 TGOs by 3193

- Activity Start Date

Start Month: 1

Start Year: 2029

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.060839
SO _x	-0.184567
NO _x	-0.144367
CO	-15.855941
PM 10	-0.423288

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.251194
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-557.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.060839

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.251194

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

SO _x	-0.184567
NO _x	-0.144367
CO	-15.855941
PM 10	-0.423288

Pb	0.000000
NH ₃	0.000000
CO _{2e}	-557.8

24.2 Aircraft & Engines

24.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

24.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

24.3 Flight Operations

24.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 7
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3193
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.05
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.9
 Approach [Approach] (mins): 2.58
 Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

24.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

24.4 Auxiliary Power Unit (APU)

24.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

24.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

24.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

25. Aircraft

25.1 General Information & Timeline Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Add T-7As and increase LTOs by 630 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2029, add T-7As and increase LTOs by 630

- Activity Start Date

Start Month: 1
 Start Year: 2029

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.103500
SO _x	0.087319
NO _x	0.781174
CO	0.427262
PM 10	0.007314

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.006258
Pb	0.000000
NH ₃	0.000000
CO _{2e}	263.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.103500
SO _x	0.087319
NO _x	0.781174
CO	0.427262
PM 10	0.007314

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.006258
Pb	0.000000
NH ₃	0.000000
CO _{2e}	263.9

25.2 Aircraft & Engines

25.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

25.2.2 Aircraft & Engines Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

25.3 Flight Operations

25.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	0
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	630
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

25.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)
AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

25.4 Auxiliary Power Unit (APU)

25.4.1 Auxiliary Power Unit (APU) Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

25.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

25.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

26. Aircraft

26.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase T-7A TGOs by 1447 OUTSIDE OF BEXAR COUNTY

- Activity Description:

Starting in 2029, increase T-7A TGOs by 1447

- Activity Start Date

Start Month: 1

Start Year: 2029

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.252106
SO _x	0.210101
NO _x	2.087407

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.013732
Pb	0.000000
NH ₃	0.000000

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

CO	0.848089
PM 10	0.016126

CO _{2e}	643.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.252106
SO _x	0.210101
NO _x	2.087407
CO	0.848089
PM 10	0.016126

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.013732
Pb	0.000000
NH ₃	0.000000
CO _{2e}	643.2

26.2 Aircraft & Engines

26.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

26.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

26.3 Flight Operations

26.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 0
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1447
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.05
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.9
 Approach [Approach] (mins): 2.58
 Taxi/Idle In [Idle] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

26.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

26.4 Auxiliary Power Unit (APU)

26.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

26.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

26.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

27. Aircraft

27.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove T-38s and decrease LTOs by 1715 OUTSIDE OF BEXAR COUNTY

- Activity Description:

Starting in 2030, remove T-38s and decrease LTOs by 1715

- Activity Start Date

Start Month: 1
 Start Year: 2030

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.911519
SO _x	-0.140913
NO _x	-0.115374
CO	-12.901058
PM 10	-0.342982

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.214732
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-425.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.911519
SO _x	-0.140913
NO _x	-0.115374
CO	-12.901058
PM 10	-0.342982

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.214732
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-425.9

27.2 Aircraft & Engines

27.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Aircraft Name:

Original Engine Name:

27.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

27.3 Flight Operations

27.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	6
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	1715
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

27.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

27.4 Auxiliary Power Unit (APU)

27.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

27.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

27.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

28. Aircraft

28.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Decrease T-38 TGOs by 3792 OUTSIDE OF BEXAR COUNTY

- Activity Description:

Starting in 2030, decrease T-38 TGOs by 3,792

- Activity Start Date

Start Month: 1

Start Year: 2030

- Activity End Date

Indefinite: Yes

End Month: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.259850
SO _x	-0.219191
NO _x	-0.171450
CO	-18.830482
PM 10	-0.502696

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.298317
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-662.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.259850
SO _x	-0.219191
NO _x	-0.171450
CO	-18.830482
PM 10	-0.502696

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.298317
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-662.5

28.2 Aircraft & Engines

28.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

28.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

28.3 Flight Operations

28.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 6
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3792
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- **Default Settings Used:** No

- **Flight Operations TIMs (Time In Mode)**

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- **Trim Test**

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

28.3.2 Flight Operations Formula(s)

- **Aircraft Emissions per Mode for LTOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- **Aircraft Emissions for LTOs per Year**

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- **Aircraft Emissions per Mode for TGOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

28.4 Auxiliary Power Unit (APU)

28.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

28.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

28.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

29. Aircraft

29.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: increase LTOs by 326 OUTSIDE OF BEXAR COUNTY

- Activity Description:

Stating in 2030, increase LTOs by 326

- Activity Start Date

Start Month: 1

Start Year: 2030

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.053964
SO _x	0.054557
NO _x	0.460461
CO	0.264694
PM 10	0.003785

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.003238
Pb	0.000000
NH ₃	0.000000
CO _{2e}	166.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.053964
SO _x	0.054557
NO _x	0.460461
CO	0.264694
PM 10	0.003785

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.003238
Pb	0.000000
NH ₃	0.000000
CO _{2e}	166.7

29.2 Aircraft & Engines

29.2.1 Aircraft & Engines Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

29.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

29.3 Flight Operations

29.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	0
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	326
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.1
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

29.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

29.4 Auxiliary Power Unit (APU)

29.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

29.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

29.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

30. Aircraft

30.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase TGOs by 737 OUTSIDE OF BEXAR COUNTY

- Activity Description:

Starting in 2030, increase TGOs by 737

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Start Date

Start Month: 1
Start Year: 2030

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.128405
SO _x	0.107011
NO _x	1.063178
CO	0.431957
PM 10	0.008214

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.006994
Pb	0.000000
NH ₃	0.000000
CO _{2e}	327.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.128405
SO _x	0.107011
NO _x	1.063178
CO	0.431957
PM 10	0.008214

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.006994
Pb	0.000000
NH ₃	0.000000
CO _{2e}	327.6

30.2 Aircraft & Engines

30.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

30.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

30.3 Flight Operations

30.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:

0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 737
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.05
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.9
Approach [Approach] (mins): 2.58
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

30.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

30.4 Auxiliary Power Unit (APU)

30.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

30.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4
----------	-------	-------	-------	-------	-------	--------	--------	-------

30.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

31. Aircraft

31.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Remove 14 T-38s and decrease LTOs by 2636 OUTSIDE OF BEXAR COUNTY

- Activity Description:

Starting in 2031, remove 14 T-38s and decrease TOs by 2,636

- Activity Start Date

Start Month: 1

Start Year: 2031

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.401028
SO _x	-0.216587
NO _x	-0.177333
CO	-19.829264
PM 10	-0.527172

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.330049
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-654.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.401028
SO _x	-0.216587
NO _x	-0.177333
CO	-19.829264
PM 10	-0.527172

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.330049
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-654.6

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

31.2 Aircraft & Engines

31.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

31.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

31.3 Flight Operations

31.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 2636
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.1
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.51
Approach [Approach] (mins): 4.52
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Military (mins): 9
AfterBurn (mins): 3

31.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

31.4 Auxiliary Power Unit (APU)

31.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

31.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

31.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

32. Aircraft

32.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Regulatory Area(s): NOT IN A REGULATORY AREA

- **Activity Title:** 2031 T-38 Removal 5840 TGOs OUTSIDE BEXAR COUNTY

- **Activity Description:**

Starting in 2031, decrease T-38 TGOs by 5840

- **Activity Start Date**

Start Month: 1

Start Year: 2031

- **Activity End Date**

Indefinite: Yes

End Month: N/A

End Year: N/A

- **Activity Emissions:**

Pollutant	Emissions Per Year (TONs)
VOC	-1.940276
SO _x	-0.337573
NO _x	-0.264047
CO	-29.000531
PM 10	-0.774195

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.459434
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1020.3

- **Activity Emissions [Flight Operations (includes Trim Test & APU) part]:**

Pollutant	Emissions Per Year (TONs)
VOC	-1.940276
SO _x	-0.337573
NO _x	-0.264047
CO	-29.000531
PM 10	-0.774195

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.459434
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1020.3

32.2 Aircraft & Engines

32.2.1 Aircraft & Engines Assumptions

- **Aircraft & Engine**

Aircraft Designation: T-38C

Engine Model: J85-GE-5R

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 2

- **Aircraft & Engine Surrogate**

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

32.2.2 Aircraft & Engines Emission Factor(s)

- **Aircraft & Engine Emissions Factors (lb/1000lb fuel)**

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

32.3 Flight Operations

32.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	5840
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

32.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

32.4 Auxiliary Power Unit (APU)

32.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

32.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

32.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

33. Aircraft

33.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: decrease T-7A LTOs by 130 OUTSIDE BEXAR COUNTY

- Activity Description:

Starting in 2031, decrease T-7A LTOs by 103

- Activity Start Date

Start Month: 1

Start Year: 2031

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.021357
SO _x	-0.018018
NO _x	-0.161195
CO	-0.088165

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.001291
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-54.5

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

PM 10	-0.001509
-------	-----------

--	--

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.021357
SO _x	-0.018018
NO _x	-0.161195
CO	-0.088165
PM 10	-0.001509

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.001291
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-54.5

33.2 Aircraft & Engines

33.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

33.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

33.3 Flight Operations

33.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 0
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 130
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.1
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.51
 Approach [Approach] (mins): 4.52
 Taxi/Idle In [Idle] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

33.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

33.4 Auxiliary Power Unit (APU)

33.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

33.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

33.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

34. Aircraft

34.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: decrease T-7A TGOs by 280 OUTSIDE BEXAR COUNTY

- Activity Description:
 - Starting in 2031, decrease T-7A TGOs by 280

- Activity Start Date
 - Start Month: 1
 - Start Year: 2031

- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.048784
SO _x	-0.040655
NO _x	-0.403921
CO	-0.164108
PM 10	-0.003121

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.002657
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-124.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.048784
SO _x	-0.040655
NO _x	-0.403921
CO	-0.164108
PM 10	-0.003121

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.002657
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-124.5

34.2 Aircraft & Engines

34.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-7A
 - Engine Model: F404-GE-102
 - Primary Function: Trainer
 - Aircraft has After burn: Yes
 - Number of Engines: 1

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Aircraft Name:

Original Engine Name:

34.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

34.3 Flight Operations

34.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	0
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	280
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

34.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

34.4 Auxiliary Power Unit (APU)

34.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

34.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

34.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

35. Aircraft

35.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase LTOs by 1553 OUTSIDE BEXAR COUNTY

- Activity Description:

increase LTOs by 1553

- Activity Start Date

Start Month: 1

Start Year: 2032

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.257076
SO _x	0.259898
NO _x	2.193547
CO	1.260948
PM 10	0.018030

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.015426
Pb	0.000000
NH ₃	0.000000
CO _{2e}	794.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.257076
SO _x	0.259898
NO _x	2.193547
CO	1.260948
PM 10	0.018030

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.015426
Pb	0.000000
NH ₃	0.000000
CO _{2e}	794.3

35.2 Aircraft & Engines

35.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

35.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

35.3 Flight Operations

35.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 0
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1553
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.51
Approach [Approach] (mins):	4.52
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

35.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

35.4 Auxiliary Power Unit (APU)

35.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

35.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

35.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

36. Aircraft

36.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: Increase T-7A TGOs by 3436 OUTSIDE BEXAR COUNTY

- Activity Description:
 - Starting in 2032, increase T-7A TGOs by 3436

- Activity Start Date
 - Start Month: 1
 - Start Year: 2032

- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.598644
SO _x	0.498899
NO _x	4.956691
CO	2.013845
PM 10	0.038293

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.032607
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1527.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.598644
SO _x	0.498899
NO _x	4.956691
CO	2.013845
PM 10	0.038293

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.032607
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1527.3

36.2 Aircraft & Engines

36.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-7A
 - Engine Model: F404-GE-102

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

36.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

36.3 Flight Operations

36.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	0
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	3436
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.05
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	2.58
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

36.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

36.4 Auxiliary Power Unit (APU)

36.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

36.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

36.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

37. Aircraft

37.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2023 T-7A Seguin AAF Closed Patterns

- Activity Description:

Increase 645 Closed Patterns

- Activity Start Date

Start Month: 1

Start Year: 2023

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.305500
SO _x	0.165822
NO _x	3.015634
CO	0.445806
PM 10	0.019708

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.016934
Pb	0.000000
NH ₃	0.000000
CO _{2e}	501.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.305500
SO _x	0.165822
NO _x	3.015634
CO	0.445806
PM 10	0.019708

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.016934
Pb	0.000000
NH ₃	0.000000
CO _{2e}	501.2

37.2 Aircraft & Engines

37.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

37.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

37.3 Flight Operations

37.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 645
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- **Default Settings Used:** No

- **Flight Operations TIMs (Time In Mode)**

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- **Trim Test**

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

37.3.2 Flight Operations Formula(s)

- **Aircraft Emissions per Mode for LTOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- **Aircraft Emissions for LTOs per Year**

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- **Aircraft Emissions per Mode for TGOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

37.4 Auxiliary Power Unit (APU)

37.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

37.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

37.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

38. Aircraft

38.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add
- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA
- Activity Title: 2023 T-38C Seguin AAF Closed Patterns
- Activity Description:
 - increase 15400 CLosed Patterns
- Activity Start Date
 - Start Month: 1
 - Start Year: 2023
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	6.097359
SO _x	1.693636
NO _x	1.831199
CO	107.523651
PM 10	3.036999

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.383375
Pb	0.000000
NH ₃	0.000000
CO _{2e}	5118.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	6.097359
SO _x	1.693636
NO _x	1.831199
CO	107.523651
PM 10	3.036999

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.383375
Pb	0.000000
NH ₃	0.000000
CO _{2e}	5118.9

38.2 Aircraft & Engines

38.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

38.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

38.3 Flight Operations

38.3.1 Flight Operations Assumptions

- Flight Operations
 Number of Aircraft: 1
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 15400
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)
 Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.93
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 1.91
 Approach [Approach] (mins): 2.5
 Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test
 Idle (mins): 12
 Approach (mins): 27
 Intermediate (mins): 9
 Military (mins): 9
 AfterBurn (mins): 3

38.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

38.4 Auxiliary Power Unit (APU)

38.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

38.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

38.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

39. Aircraft

39.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2024 T-7A Seguin AAF Closed Patterns

- Activity Description:

increase 2955 Closed Patterns

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Start Date

Start Month: 1
Start Year: 2024

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	14.895520
SO _x	0.995897
NO _x	8.975147
CO	59.033955
PM 10	0.867868

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.777262
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2577.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	14.895520
SO _x	0.995897
NO _x	8.975147
CO	59.033955
PM 10	0.867868

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.777262
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2577.1

39.2 Aircraft & Engines

39.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

39.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

39.3 Flight Operations

39.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 2955
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 6.8
Takeoff [Military] (mins): 0.25
Takeoff [After Burn] (mins): 0.25
Climb Out [Intermediate] (mins): 1.4
Approach [Approach] (mins): 4
Taxi/Idle In [Idle] (mins): 4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

39.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- TGO: Number of Touch-and-Go Cycles (for all aircraft)
- 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

- AE_{TGO}: Aircraft Emissions (TONs)
- AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
- AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
- AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

- AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
- TD: Test Duration (min)
- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- NA: Number of Aircraft
- NTT: Number of Trim Test
- 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

39.4 Auxiliary Power Unit (APU)

39.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

39.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

39.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

40. Aircraft

40.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2024 T-38C Seguin AAF Closed Patterns

- Activity Description:

Decrease 700 Closed Patterns.

- Activity Start Date

Start Month: 1

Start Year: 2024

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.277153
SO _x	-0.076983
NO _x	-0.083236
CO	-4.887439
PM 10	-0.138045

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.062881
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-232.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.277153
SO _x	-0.076983
NO _x	-0.083236
CO	-4.887439
PM 10	-0.138045

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.062881
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-232.7

40.2 Aircraft & Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

40.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

40.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

40.3 Flight Operations

40.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 700
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.93
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 1.91
Approach [Approach] (mins): 2.5
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

40.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

40.4 Auxiliary Power Unit (APU)

40.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

40.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

40.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

41. Aircraft

41.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- **Activity Title:** 2025 T-7A Seguin AAF Closed Patterns

- **Activity Description:**
Increase 10320 closed patterns

- **Activity Start Date**
Start Month: 1
Start Year: 2025

- **Activity End Date**
Indefinite: Yes
End Month: N/A
End Year: N/A

- **Activity Emissions:**

Pollutant	Emissions Per Year (TONs)
VOC	4.887994
SO _x	2.653153
NO _x	48.250140
CO	7.132894
PM 10	0.315325

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.270949
Pb	0.000000
NH ₃	0.000000
CO _{2e}	8019.0

- **Activity Emissions [Flight Operations (includes Trim Test & APU) part]:**

Pollutant	Emissions Per Year (TONs)
VOC	4.887994
SO _x	2.653153
NO _x	48.250140
CO	7.132894
PM 10	0.315325

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.270949
Pb	0.000000
NH ₃	0.000000
CO _{2e}	8019.0

41.2 Aircraft & Engines

41.2.1 Aircraft & Engines Assumptions

- **Aircraft & Engine**
 Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- **Aircraft & Engine Surrogate**
 Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

41.2.2 Aircraft & Engines Emission Factor(s)

- **Aircraft & Engine Emissions Factors (lb/1000lb fuel)**
 Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

41.3 Flight Operations

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

41.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	10320
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

41.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

41.4 Auxiliary Power Unit (APU)

41.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer

41.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

41.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

42. Aircraft

42.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2025 T-38C Seguin AAF Closed Patterns

- Activity Description:

Decrease 12900 Closed Patterns

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-5.107528
SO _x	-1.418695
NO _x	-1.533927
CO	-90.068513
PM 10	-2.543980

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.158801
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-4287.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-5.107528
SO _x	-1.418695
NO _x	-1.533927

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.158801
Pb	0.000000
NH ₃	0.000000

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

CO	-90.068513
PM 10	-2.543980

CO _{2e}	-4287.9

42.2 Aircraft & Engines

42.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

42.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

42.3 Flight Operations

42.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 12900
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.93
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 1.91
 Approach [Approach] (mins): 2.5
 Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

42.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

42.4 Auxiliary Power Unit (APU)

42.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

42.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

42.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

43. Aircraft

43.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Location

County: Guadalupe
Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2026 T-7A Seguin AAF Closed Patterns

- Activity Description:

Increase 8000 closed patterns.

- Activity Start Date

Start Month: 1
Start Year: 2026

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	3.789142
SO _x	2.056708
NO _x	37.403209
CO	5.529376
PM 10	0.244438

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.210038
Pb	0.000000
NH ₃	0.000000
CO _{2e}	6216.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	3.789142
SO _x	2.056708
NO _x	37.403209
CO	5.529376
PM 10	0.244438

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.210038
Pb	0.000000
NH ₃	0.000000
CO _{2e}	6216.3

43.2 Aircraft & Engines

43.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

43.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

43.3 Flight Operations

43.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	8000
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

43.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

43.4 Auxiliary Power Unit (APU)

43.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

43.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

43.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

44. Aircraft

44.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2026 T-38C Seguin AAF Closed Patterns

- Activity Description:

Decrease 6300 closed patterns.

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-2.494374
SO _x	-0.692851
NO _x	-0.749127
CO	-43.986948
PM 10	-1.242409

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.565926
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2094.1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-2.494374
SO _x	-0.692851
NO _x	-0.749127
CO	-43.986948
PM 10	-1.242409

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.565926
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2094.1

44.2 Aircraft & Engines

44.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

44.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

44.3 Flight Operations

44.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 6300
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.93
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 1.91
 Approach [Approach] (mins): 2.5
 Taxi/Idle In [Idle] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

44.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

44.4 Auxiliary Power Unit (APU)

44.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

44.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

44.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

45. Aircraft

45.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add
- Activity Location
 - County: Guadalupe
 - Regulatory Area(s): NOT IN A REGULATORY AREA
- Activity Title: 2027 T-7A Seguin AAF Closed Patterns
- Activity Description:
 - increase 10000 closed patterns.
- Activity Start Date
 - Start Month: 1
 - Start Year: 2027
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	4.736428
SO _x	2.570885
NO _x	46.754011
CO	6.911719
PM 10	0.305547

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.262548
Pb	0.000000
NH ₃	0.000000
CO _{2e}	7770.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	4.736428
SO _x	2.570885
NO _x	46.754011
CO	6.911719
PM 10	0.305547

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.262548
Pb	0.000000
NH ₃	0.000000
CO _{2e}	7770.3

45.2 Aircraft & Engines

45.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-7A
 - Engine Model: F404-GE-102
 - Primary Function: Trainer
 - Aircraft has After burn: Yes
 - Number of Engines: 1
- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No
 - Original Aircraft Name:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Engine Name:

45.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

45.3 Flight Operations

45.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	10000
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

45.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

45.4 Auxiliary Power Unit (APU)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

45.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

45.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

45.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

46. Aircraft

46.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2027 T-38C Seguin AAF Closed Patterns

- Activity Description:

Decrease 11100 closed patterns.

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-4.394850

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.997108

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

SO _x	-1.220738
NO _x	-1.319890
CO	-77.500813
PM 10	-2.189006

Pb	0.000000
NH ₃	0.000000
CO _{2e}	-3689.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-4.394850
SO _x	-1.220738
NO _x	-1.319890
CO	-77.500813
PM 10	-2.189006

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.997108
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-3689.6

46.2 Aircraft & Engines

46.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

46.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

46.3 Flight Operations

46.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 11100
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.93

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

46.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

- AE_{TGO}: Aircraft Emissions (TONs)
- AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
- AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
- AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

- AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
- TD: Test Duration (min)
- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- NA: Number of Aircraft
- NTT: Number of Trim Test
- 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

46.4 Auxiliary Power Unit (APU)

46.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

46.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

46.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

47. Aircraft

47.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2028 T-7A Seguin AAF Closed Patterns

- Activity Description:

increase 6200 closed patterns

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	2.936585
SO _x	1.593948
NO _x	28.987487
CO	4.285266
PM 10	0.189439

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.162780
Pb	0.000000
NH ₃	0.000000
CO _{2e}	4817.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	2.936585
SO _x	1.593948
NO _x	28.987487
CO	4.285266
PM 10	0.189439

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.162780
Pb	0.000000
NH ₃	0.000000
CO _{2e}	4817.6

47.2 Aircraft & Engines

47.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

47.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

47.3 Flight Operations

47.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	6200
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

47.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

47.4 Auxiliary Power Unit (APU)

47.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

47.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

47.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

48. Aircraft

48.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2028 T-38C Seguin AAF Closed Patterns

- Activity Description:

Decrease 7600 closed patterns.

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-3.009086
SO _x	-0.835821
NO _x	-0.903709
CO	-53.063620
PM 10	-1.498779

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.682704
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2526.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-3.009086
SO _x	-0.835821
NO _x	-0.903709
CO	-53.063620
PM 10	-1.498779

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.682704
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2526.2

48.2 Aircraft & Engines

48.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

48.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

48.3 Flight Operations

48.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 7600
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

48.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

48.4 Auxiliary Power Unit (APU)

48.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

48.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

48.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

49. Aircraft

49.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2029 T-7A Seguin AAF Closed Patterns

- Activity Description:

Increase 4100 Closed Patterns

- Activity Start Date

Start Month: 1

Start Year: 2029

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.941935
SO _x	1.054063
NO _x	19.169145
CO	2.833805
PM 10	0.125274

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.107645
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3185.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.941935
SO _x	1.054063
NO _x	19.169145
CO	2.833805
PM 10	0.125274

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.107645
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3185.8

49.2 Aircraft & Engines

49.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

49.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

49.3 Flight Operations

49.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	4100
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

49.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

49.4 Auxiliary Power Unit (APU)

49.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

49.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

49.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

50. Aircraft

50.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2029 T-38C seguin AAF Closed Patterns

- Activity Description:

decrease 4400 closed patterns.

- Activity Start Date

Start Month: 1

Start Year: 2029

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.742103
SO _x	-0.483896
NO _x	-0.523200
CO	-30.721043
PM 10	-0.867714

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.395250
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1462.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.742103
SO _x	-0.483896
NO _x	-0.523200
CO	-30.721043
PM 10	-0.867714

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.395250
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1462.5

50.2 Aircraft & Engines

50.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

50.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

50.3 Flight Operations

50.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 4400

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.93
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 1.91
Approach [Approach] (mins): 2.5
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

50.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

50.4 Auxiliary Power Unit (APU)

50.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

50.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

50.4.3 Auxiliary Power Unit (APU) Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

51. Aircraft

51.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2030 T-7A Seguin AAF Closed Patterns

- Activity Description:

Increase 1100 closed patterns

- Activity Start Date

Start Month: 1

Start Year: 2030

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.521007
SO _x	0.282797
NO _x	5.142941
CO	0.760289
PM 10	0.033610

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.028880
Pb	0.000000
NH ₃	0.000000
CO _{2e}	854.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.521007
SO _x	0.282797
NO _x	5.142941
CO	0.760289
PM 10	0.033610

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.028880
Pb	0.000000
NH ₃	0.000000
CO _{2e}	854.7

51.2 Aircraft & Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

51.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

51.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

51.3 Flight Operations

51.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1100
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.93
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 1.91
Approach [Approach] (mins): 2.5
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

51.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

51.4 Auxiliary Power Unit (APU)

51.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

51.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

51.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

52. Aircraft

52.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2030 T-38C Seguin AAF Closed Patterns

- Activity Description:

Decrease 5900 closed patterns

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Start Date

Start Month: 1
Start Year: 2030

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-2.336001
SO _x	-0.648861
NO _x	-0.701563
CO	-41.194126
PM 10	-1.163526

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.529994
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1961.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-2.336001
SO _x	-0.648861
NO _x	-0.701563
CO	-41.194126
PM 10	-1.163526

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.529994
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1961.1

52.2 Aircraft & Engines

52.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

52.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

52.3 Flight Operations

52.3.1 Flight Operations Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	5900
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

52.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

52.4 Auxiliary Power Unit (APU)

52.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

52.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

52.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

53. Aircraft

53.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2031 T-7A Seguin AAF Closed Patterns

- Activity Description:

increase 600 closed patterns

- Activity Start Date

Start Month: 1

Start Year: 2031

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.284186
SO _x	0.154253
NO _x	2.805241
CO	0.414703
PM 10	0.018333

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.015753
Pb	0.000000
NH ₃	0.000000
CO _{2e}	466.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.284186
SO _x	0.154253
NO _x	2.805241
CO	0.414703

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.015753
Pb	0.000000
NH ₃	0.000000
CO _{2e}	466.2

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

PM 10	0.018333
-------	----------

--	--

53.2 Aircraft & Engines

53.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

53.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

53.3 Flight Operations

53.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 600
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.93
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 1.91
Approach [Approach] (mins): 2.5
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

53.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

53.4 Auxiliary Power Unit (APU)

53.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

53.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

53.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

54. Aircraft

54.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2031 T-38C Seguin AAF Closed PAtterns

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Description:
decrease 8120 closed patterns

- Activity Start Date
Start Month: 1
Start Year: 2031

- Activity End Date
Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-3.214971
SO _x	-0.893008
NO _x	-0.965541
CO	-56.694289
PM 10	-1.601327

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.729416
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2699.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-3.214971
SO _x	-0.893008
NO _x	-0.965541
CO	-56.694289
PM 10	-1.601327

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.729416
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2699.1

54.2 Aircraft & Engines

54.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

54.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

54.3 Flight Operations

54.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	8120
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

54.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

54.4 Auxiliary Power Unit (APU)

54.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU	Operation Hours	Exempt	Designation	Manufacturer
---------------	-----------------	--------	-------------	--------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

per Aircraft	for Each LTO	Source?	
--------------	--------------	---------	--

54.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

54.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

55. Aircraft

55.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Guadalupe

Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2032 T-7A Seguin AAF Closed Patterns

- Activity Description:

increase 1600 closed patternd

- Activity Start Date

Start Month: 1

Start Year: 2032

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.757828
SO _x	0.411342
NO _x	7.480642
CO	1.105875
PM 10	0.048888

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.042008
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1243.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
-----------	---------------------------

Pollutant	Emissions Per Year (TONs)
-----------	---------------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

VOC	0.757828
SO _x	0.411342
NO _x	7.480642
CO	1.105875
PM 10	0.048888

PM 2.5	0.042008
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1243.3

55.2 Aircraft & Engines

55.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

55.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

55.3 Flight Operations

55.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1600
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.93
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 1.91
Approach [Approach] (mins): 2.5
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

55.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

55.4 Auxiliary Power Unit (APU)

55.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

55.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

55.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

56. Aircraft

56.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

County: Guadalupe
 Regulatory Area(s): NOT IN A REGULATORY AREA

- Activity Title: 2032 T-38C Seguin AAF Closed Patterns

- Activity Description:
 Decrease 2680 Closed Patterns

- Activity Start Date
 Start Month: 1
 Start Year: 2032

- Activity End Date
 Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.061099
SO _x	-0.294737
NO _x	-0.318676
CO	-18.711908
PM 10	-0.528517

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.240743
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-890.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.061099
SO _x	-0.294737
NO _x	-0.318676
CO	-18.711908
PM 10	-0.528517

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.240743
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-890.8

56.2 Aircraft & Engines

56.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

56.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

56.3 Flight Operations

56.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	1
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	2680
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.93
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	1.91
Approach [Approach] (mins):	2.5
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

56.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)
AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

56.4 Auxiliary Power Unit (APU)

56.4.1 Auxiliary Power Unit (APU) Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

56.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

56.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons