



E

Air Quality Supporting
Documentation



Appendix E provides air quality backup data and ACAM reports for all activities and operations associated with JBSA-Randolph, JBSA-Lackland, Seguin AAF, operations with airspace for region of influence (ROI) 1 and ROI 2.

Appendix E is presented in four sections to enable activities and operations in particular geographic boundaries to be analyzed in manner that allows for determination of significance of specific locations. The four sections of Appendix E and respective locations include:

E-1 JBSA-Randolph and JBSA-Lackland; Air Quality: Bexar County ROI

E-2 Seguin AAF; Air Quality: Guadalupe County ROI

E-3 Airspace ROI 1 (includes Brady MOA); Air Quality: Brady ROI

Counties included:

McCulloch	San Saba	Llano
-----------	----------	-------

E-4 Airspace ROI 2 (includes MTRs and McMullen Range R-6132); Air Quality: MTR ROI

Counties included:

Atascosa	De Witt	Kendall
Bandera	Dimmit	La Salle
Bastrop	Frio	Live Oak
Bee	Gonzales	McMullen
Blanco	Hays	Uvalde
Caldwell	Jim Wells	Webb
Comal	Karnes	Zavala

E-1 JBSA-RANDOLPH & JBSA-LACKLAND (AIR QUALITY: BEXAR COUNTYROI)

The content of Section E-1 presents the data and methodology used for preparing aircraft operations data for the ACAM modeling followed by the ACAM results. The data in Section E-1 represents all operations that occur in Bexar County associated with the Proposed Action and Action Alternatives.

This section includes the following:

- Randolph T-7 TIMs Summary
- Randolph T-7 TIMS Arrivals
- Randolph T-7 Closed Patterns
- Randolph T-7 TIMS Departures
- Randolph T-7 TIMS Errors and Omissions
- Proposed Action ACAM Report
- Proposed Action ACAM Detailed Report
- Alternative 1 ACAM Report
- Alternative 1 ACAM Detailed Report
- Alternative 2 ACAM Report
- Alternative 2 ACAM Detailed Report
- Alternative 3 ACAM Report
- Alternative 3 ACAM Detailed Report

Randolph AFB T-7 TIMs Summary					
	Idle In/Out	Takeoff AB	Takeoff Mil	Climbout	Approach
LTO Flight	0.00	0.39	0.41	0.91	1.74
LTO Taxi	0.00	0.00	0.00	0.00	0.00
Total LTO	9.74	0.39	0.41	0.91	1.74
Closed Patterns	0.00	0.00	0.64	0.47	0.98

Randolph AFB T-38 TIMs Summary						
	Idle In	Idle Out	Takeoff AB	Takeoff Mil	Climbout	Approach
LTO Flight	0.00	0.00	0.39	0.41	0.91	1.74
LTO Taxi	12.80	6.40	0.00	0.00	0.00	0.00
Total LTO	12.80	6.40	0.39	0.41	0.91	1.74
Closed Patterns	0.00	0.00	0.00	0.64	0.47	0.98

Methodology and Scientific Integrity

Methodology:

Air impact analyses are based on “reasonably foreseeable” estimated net annual emissions of criteria pollutants. Reasonably foreseeable actions include “activities not yet taken, but sufficiently likely to occur” and “do not include those actions that are highly speculative” (43 CFR 46.30). Estimated annual emissions from aircraft flight operations are determined from Annual Representative Flight Operations Cycles: Landing and Takeoff Cycle (LTO Cycle, includes arrivals and departures), Closed Pattern Cycle (CP Cycle), and Low Flight Pattern Cycle (LFP Cycle).

Within the U.S. Air Force, these Annual Representative Flight Operations Cycles are derived through weighted-averaging and utilizing the site-specific flight operational data (i.e., noise profile data) collected specifically for a location-specific noise analysis (for specific methodology see Standardized Procedures for Deriving Flight Operations Cycles from Noise Flight Profiles, AFCEC/CZTQ, 13 May 2020).

The current U.S. Air Force methodology for establishing site-specific flight operational data (i.e., noise profile data) is a single pilot interview where the pilot is asked to recollect and record flight parameter data by drawing points on a map and then estimating the distance flown, elevation, power setting, and airspeed at each point. Noise profile data collected from a single pilot recollection of specific flight parameter data is extremely imprecise and relatively speculative in nature at best. However, given the alternative is to use EPA default Annual Representative Flight Operations Cycles that are outdated and unverifiable; the U.S. Air Force believes the noise profile data is currently the best available data.

Professional and Scientific Integrity

As with all modelling, air quality must apply a statistical approach to modelling for ensuring the scientific integrity of the results. In accordance with 40 CFR 1502.23 “agencies shall ensure the professional integrity, including scientific integrity, of the discussions and analyses” and “shall make use of reliable existing data and resources”.

Noise profile data, used for deriving Annual Representative Flight Operations Cycles (LTO, CP, and LFP Cycles), is far from perfect data for air impact analyses. Because noise profile data was not collected or intended for air impact analyses, it has errors and omissions (incomplete information needed for air quality); therefore, you cannot simply pull noise profile data into an air analysis. Noise profile data collected from a single pilot recollection of specific flight parameter data is extremely imprecise and relatively speculative; therefore, this data has no quantifiable statistical validity. Additionally, most of the critical data points (e.g. at 500 and 3,000 ft AGL) are not included and require rough interpolations to derive. Generally, over 95% of all profiles have errors and omissions; therefore, using noise profile data for air quality requires an extensive engineering effort to derive incomplete and/or missing critical data points. See the Errors and Omissions Table to view the issues with the noise profiles data in this specific engineering analysis, for deriving Annual Representative Flight Operations Cycles, that required professional engineering judgement to resolve.

Data used outside of their intended purpose (e.g., noise data used for air analysis) must be inspected for anomalies (or outliers) to ensure the inclusion of these anomalies does not inadvertently and unwarrantedly bias the results of an air quality assessment. Given noise profile data is collected for capturing an “average busy day” (average worst-case day) versus air quality need for data representing an “average year”, the noise data is skewed which results in outliers (anomalies from the average) for air impact analyses. Identified outliers are generally not considered as “reassembly foreseeable” datapoints. As a result, as with all scientifically-sound modelling, these anomalies should normally be removed for an air analysis to ensure scientific integrity of the analysis results. However, the U.S. Air Force has chosen to include these anomalies in air impact analyses (i.e., use 100% of noise profiles regardless of potential bias).

Statistical analysis of emission results with and without inclusion of the anomalies was performed to assess the impact of the inclusion of the outliers (anomalies). The analysis indicated that the anomalies will be flown so infrequent that they will contribute no statistical difference (less than 1 ton/yr overall) to the estimated net annual emissions of any criteria pollutant.

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF CONFORMITY ANALYSIS (ROCA)

1. General Information: The Air Force's Air Conformity Applicability Model (ACAM) was used to perform an analysis to assess the potential air quality impact/s associated with the action in accordance with the Air Force Manual 32-7002, Environmental Compliance and Pollution Prevention; the Environmental Impact Analysis Process (EIAP, 32 CFR 989); and the General Conformity Rule (GCR, 40 CFR 93 Subpart B). This report provides a summary of the ACAM analysis.

a. Action Location:

Base: RANDOLPH AFB
State: Texas
County(s): Bexar
Regulatory Area(s): San Antonio, TX

b. Action Title: Recapitalization of the T-38 Trainer At Randolph AFB - Proposed Action (Bexar County and Guadalupe County ROIs)

c. Project Number/s (if applicable):

d. Projected Action Start Date: 1 / 2022

e. Action Description:

The proposed action encompasses the recapitalize of the T-38 flight-training program with newer and more capable T-7A aircraft at JBSA-Randolph and Lackland. In addition to the phased introduction of the T-7A aircraft, five military construction projects and 17 facilities sustainment, restoration, and modernization projects are proposed at JBSA-Randolph at JBSA-Lackland to provide modern facilities and infrastructure to support the T-7A aircraft's maintenance, training, and operational requirements. The number of personnel on JBSA-Randolph would increase due to the proposed aircraft recapitalization. No changes to airspace configurations (i.e., size, shape, or location) would be required to support the proposed operations of the T-7A aircraft; however, the T-7A aircraft may have more flight operations than occurs with the T 38C aircraft at both JBSA-Randolph and JBSA-Lackland. This Applicability Analysis present the worst-case of three aircraft operational intensities as the worst-case action alternatives for the Proposed Action.

A Conformity Evaluation is required for every proposed action that will occur within an area designated by the U.S. Environmental Protection Agency (EPA) as nonattainment or maintenance for any National Ambient Air Quality Standard (NAAQS). The proposed T-7A Recapitalization action will occur at both JBSA-Randolph AFB and JBSA-Lackland AFB which both fall entirely within Bexar County that has been designated by the U.S. Environmental Protection Agency (EPA) as a marginal nonattainment area for the 2015 Ozone NAAQS in 2018. Given this recent designation of Bexar County, the proposed action (as well as all proposed actions from federal agencies) are subject to the General Conformity Rule (GCR, 40 CFR 93 Subpart B). As a marginal nonattainment area for ozone, the GCR has established de minimis significance threshold values of less than 100 ton/yr (for any given year) for both nitrogen oxides (NO_x) and volatile organic compounds (VOC).

f. Point of Contact:

Name: [REDACTED]
Title: NEPA Contract Support
Organization: [REDACTED]
Email:
Phone Number:

2. Analysis: Total combined direct and indirect emissions associated with the action were estimated through ACAM on a calendar-year basis for the "worst-case" and "steady state" (net gain/loss upon action fully implemented) emissions. General Conformity under the Clean Air Act, Section 1.76 has been evaluated for the action described above according to the requirements of 40 CFR 93, Subpart B.

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF CONFORMITY ANALYSIS (ROCA)

Based on the analysis, the requirements of this rule are: X applicable
 not applicable

Conformity Analysis Summary:

2022

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	0.527	100	No
NOx	2.123	100	No
CO	2.304		
SOx	0.005		
PM 10	3.636		
PM 2.5	0.095		
Pb	0.000		
NH3	0.002		
CO2e	506.5		

2023

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	4.579	100	No
NOx	7.911	100	No
CO	28.479		
SOx	0.471		
PM 10	0.425		
PM 2.5	0.384		
Pb	0.000		
NH3	0.042		
CO2e	2523.3		

2024

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	11.408	100	No
NOx	20.089	100	No
CO	64.406		
SOx	1.347		
PM 10	1.059		
PM 2.5	0.952		
Pb	0.000		
NH3	0.042		
CO2e	4891.2		

2025

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	15.280	100	No
NOx	43.497	100	No

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF CONFORMITY ANALYSIS (ROCA)

CO	17.781		
SOx	2.018		
PM 10	-0.727		
PM 2.5	-0.138		
Pb	0.000		
NH3	0.042		
CO2e	6643.0		

2026

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	23.293	100	No
NOx	67.021	100	No
CO	23.480		
SOx	3.152		
PM 10	-1.154		
PM 2.5	-0.242		
Pb	0.000		
NH3	0.042		
CO2e	9679.7		

2027

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	36.858	100	No
NOx	108.475	100	Yes
CO	-5.094		
SOx	4.809		
PM 10	-3.034		
PM 2.5	-1.240		
Pb	0.000		
NH3	0.042		
CO2e	14088.2		

2028

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	44.686	100	No
NOx	144.087	100	Yes
CO	-52.938		
SOx	6.023		
PM 10	-5.156		
PM 2.5	-2.457		
Pb	0.000		
NH3	0.042		
CO2e	17275.3		

2029

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF CONFORMITY ANALYSIS (ROCA)

San Antonio, TX			
VOC	41.723	100	No
NOx	147.499	100	Yes
CO	-103.030		
SOx	5.737		
PM 10	-6.539		
PM 2.5	-3.428		
Pb	0.000		
NH3	0.042		
CO2e	16471.1		

2030

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	36.575	100	No
NOx	148.566	100	Yes
CO	-170.096		
SOx	5.198		
PM 10	-8.308		
PM 2.5	-4.708		
Pb	0.000		
NH3	0.042		
CO2e	14986.6		

2031

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	25.963	100	No
NOx	145.658	100	Yes
CO	-287.926		
SOx	4.015		
PM 10	-11.292		
PM 2.5	-6.891		
Pb	0.000		
NH3	0.042		
CO2e	11734.8		

2032

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	29.082	100	No
NOx	154.317	100	Yes
CO	-273.027		
SOx	4.575		
PM 10	-11.023		
PM 2.5	-6.651		
Pb	0.000		
NH3	0.042		
CO2e	13320.4		

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF CONFORMITY ANALYSIS (ROCA)

2033 - (Steady State)

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	29.082	100	No
NOx	154.317	100	Yes
CO	-273.027		
SOx	4.575		
PM 10	-11.023		
PM 2.5	-6.651		
Pb	0.000		
NH3	0.042		
CO2e	13320.4		

Some estimated emissions associated with this action are above the conformity threshold values established at 40 CFR 93.153 (b); Therefore, the requirements of the General Conformity Rule are applicable.

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1. General Information

- Action Location

Base: RANDOLPH AFB
State: Texas
County(s): Bexar
Regulatory Area(s): San Antonio, TX

- Action Title: Recapitalization of the T-38 Trainer At Randolph AFB - Proposed Action

- Project Number/s (if applicable):

- Projected Action Start Date: 1 / 2022

- Action Purpose and Need:

The T 38 Talon is a twin-engine, high-altitude, supersonic jet used by the USAF and other nations for pilot training. The aircraft originally was developed in the 1950s with production occurring between 1961 and 1972. The fleet has undergone periodic upgrades overtime. In 2001, the USAF upgraded several hundred T 38s with modern avionics and replaced propulsion components to provide increased performance and superior reliability.

The purpose of the Proposed Action is to allow the USAF T-7A to provide more efficient and effective pilot training to establish a T-7A pilot pipeline to allow for the transition to T-7A training throughout the entire USAF.

- Action Description:

The proposed action encompasses the recapitalize of the T-38 flight-training program with newer and more capable T-7A aircraft at JBSA-Randolph and Lackland. In addition to the phased introduction of the T-7A aircraft, five military construction projects and 17 facilities sustainment, restoration, and modernization projects are proposed at JBSA-Randolph at JBSA-Lackland to provide modern facilities and infrastructure to support the T-7A aircraft's maintenance, training, and operational requirements. The number of personnel on JBSA-Randolph would increase due to the proposed aircraft recapitalization. No changes to airspace configurations (i.e., size, shape, or location) would be required to support the proposed operations of the T-7A aircraft; however, the T-7A aircraft may have more flight operations than occurs with the T 38C aircraft at both JBSA-Randolph and JBSA-Lackland. This Applicability Analysis present the worst-case of three aircraft operational intensities as the worst-case action alternatives for the Proposed Action.

A Conformity Evaluation is required for every proposed action that will occur within an area designated by the U.S. Environmental Protection Agency (EPA) as nonattainment or maintenance for any National Ambient Air Quality Standard (NAAQS). The proposed T-7A Recapitalization action will occur at both JBSA-Randolph AFB and JBSA-Lackland AFB which both fall entirely within Bexar County that has been designated by the U.S. Environmental Protection Agency (EPA) as a marginal nonattainment area for the 2015 Ozone NAAQS in 2018. Given this recent designation of Bexar County, the proposed action (as well as all proposed actions from federal agencies) are subject to the General Conformity Rule (GCR, 40 CFR 93 Subpart B). As a marginal nonattainment area for ozone, the GCR has established de minimis significance threshold values of less than 100 ton/yr (for any given year) for both nitrogen oxides (NOx) and volatile organic compounds (VOC).

- Point of Contact

Name: [REDACTED]
Title: NEPA Contract Support
Organization: [REDACTED]
Email:
Phone Number:

- Activity List:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Activity Type		Activity Title
2.	Aircraft	T-7As and 759 LTOs
3.	Aircraft	T-7A Increase 1,700 TGOs
4.	Aircraft	T-38 Removal 5 TGOs
5.	Aircraft	Add 10 T-7As and 1328LTOs
6.	Aircraft	Increase T-7A TGOs
7.	Aircraft	Remove 11 T-38s and 2776LTOs
8.	Aircraft	Remove 6142 T-38 TGOs
9.	Aircraft	Add 7 new T-7As and 2836 LTOs
10.	Aircraft	Increase T-7A TGOs by 6395
11.	Aircraft	Remove 7 T-38s and reduce LTOs by 1534
12.	Aircraft	Decrease T-38 TGOs by 3394
13.	Aircraft	Add T-7As and increase LTOs by 2698
14.	Aircraft	Increase T-7A TGOs by 6040
15.	Aircraft	Remove T-38s and decrease LTOs by 3767
16.	Aircraft	Decrease T-38 TGOs by 8,328
17.	Aircraft	Add 19 new T-7As and increase LTOs by 4918
18.	Aircraft	Increase T-7A TGOs by 10952
19.	Aircraft	Remove 21 T-38s and decrease LTOs by 3,667
20.	Aircraft	Decrease T-38 TGOs by 8093
21.	Aircraft	Add T-7As and increase LTOs by 4298
22.	Aircraft	Increase T-7A TGOs by 9527
23.	Aircraft	Remove T-38s and decrease LTOs by 1445
24.	Aircraft	Decrease T-38 TGOs by 3193
25.	Aircraft	Add T-7As and increase LTOs by 504
26.	Aircraft	Increase T-7A TGOs by 1158
27.	Aircraft	Remove T-38s and decrease LTOs by 1715
28.	Aircraft	Decrease T-38 TGOs by 3792
29.	Aircraft	increase LTOs by 261
30.	Aircraft	Increase TGOs by 590
31.	Aircraft	Remove 14 T-38s and decrease LTOs by 2636
32.	Aircraft	2031 T-38 Removal 5840 TGOs
33.	Aircraft	decrease T-7A LTOs by 104
34.	Aircraft	decrease T-7A TGOs by 224
35.	Aircraft	Increase LTOs by 1242
36.	Aircraft	Increase T-7A TGOs by 2748
37.	Aircraft	2023 T-7A Increase Trim Test and Test Cell
38.	Aircraft	2024 T-7A Increase Trim Test and Engine Test Cell
39.	Aircraft	2025 T-38 Removal Trim Test and Test Cell
40.	Aircraft	2025 T-7A Increase Trim Test and Test Cell
41.	Aircraft	2026 T-38 Removal Trim Test and Test Cell
42.	Aircraft	2026 T-7A Increase Trim Test and Engine Test Cell
43.	Aircraft	2027 T-38 Removal Trim Test and Test Cell
44.	Aircraft	2027 T-7A Increase Trim Test and Test Cell
45.	Aircraft	2028 T-38 Removal Trim Test and Test Cell
46.	Aircraft	2028 T-7A Increase Trim Test and Test Cell
47.	Aircraft	2029 T-38 Removal Trim Test and Test Cell
48.	Aircraft	2030 T-38 Removal Trim Test and Test Cell
49.	Aircraft	2031 T-38 Removal Trim Test and Test Cell
50.	Personnel	2023 Increase 303 Personnel INDEFINITE
51.	Heating	2023 Heating for Buildings INDEFINITE
52.	Construction / Demolition	Construction and Demolition

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Emission factors and air emission estimating methods come from the United States Air Force's Air Emissions Guide for Air Force Stationary Sources, Air Emissions Guide for Air Force Mobile Sources, and Air Emissions Guide for Air Force Transitory Sources.

2. Aircraft

2.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: T-7As and 759 LTOs

- Activity Description:

Starting in 2023 add 8 T-7As, and increase 759 LTOs

- Activity Start Date

Start Month: 1

Start Year: 2023

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	3.503273
SO _x	0.251578
NO _x	2.428146
CO	18.804690
PM 10	0.316361

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.283894
Pb	0.000000
NH ₃	0.000000
CO _{2e}	591.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	3.503273
SO _x	0.251578
NO _x	2.428146
CO	18.804690
PM 10	0.316361

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.283894
Pb	0.000000
NH ₃	0.000000
CO _{2e}	591.2

2.2 Aircraft & Engines

2.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

2.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

2.3 Flight Operations

2.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	8
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	759
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	9.74
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

2.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

2.4 Auxiliary Power Unit (APU)

2.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

2.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

2.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

3. Aircraft

3.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: T-7A Increase 1,700 TGOs

- Activity Description:

Starting in 2023 add 10 new T-7As, and increase 1,700TGOs

- Activity Start Date

Start Month: 1

Start Year: 2023

- Activity End Date

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.342560
SO _x	0.184015
NO _x	3.965532
CO	0.483172
PM 10	0.023088

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.019985
Pb	0.000000
NH ₃	0.000000
CO _{2e}	556.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.342560
SO _x	0.184015
NO _x	3.965532
CO	0.483172
PM 10	0.023088

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.019985
Pb	0.000000
NH ₃	0.000000
CO _{2e}	556.2

3.2 Aircraft & Engines

3.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

3.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

3.3 Flight Operations

3.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 10
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1700
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

3.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

3.4 Auxiliary Power Unit (APU)

3.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

3.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

3.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU: Number of Auxiliary Power Units
OH: Operation Hours for Each LTO (hour)
LTO: Number of LTOs
EF_{POL}: Emission Factor for Pollutant (lb/hr)
2000: Conversion Factor pounds to tons

4. Aircraft

4.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar
Regulatory Area(s): San Antonio, TX

- Activity Title: T-38 Removal 5 TGOs

- Activity Description:

Starting in 2024, remove 5 T-38 TGOs

- Activity Start Date

Start Month: 1
Start Year: 2024

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.000748
SO _x	-0.000244
NO _x	-0.000314
CO	-0.013707
PM 10	-0.000401

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.000162
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-0.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.000748
SO _x	-0.000244
NO _x	-0.000314
CO	-0.013707
PM 10	-0.000401

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.000162
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-0.7

4.2 Aircraft & Engines

4.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No
 - Original Aircraft Name:
 - Original Engine Name:

4.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

4.3 Flight Operations

4.3.1 Flight Operations Assumptions

- Flight Operations
 - Number of Aircraft: 91
 - Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 5
 - Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 - Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)
 - Taxi/Idle Out [Idle] (mins): 0
 - Takeoff [Military] (mins): 0.64
 - Takeoff [After Burn] (mins): 0
 - Climb Out [Intermediate] (mins): 0.47
 - Approach [Approach] (mins): 0.98
 - Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test
 - Idle (mins): 12
 - Approach (mins): 27
 - Intermediate (mins): 9
 - Military (mins): 9
 - AfterBurn (mins): 3

4.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year
 $AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

4.4 Auxiliary Power Unit (APU)

4.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

4.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

4.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

5. Aircraft

5.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Add 10 T-7As and 1328LTOs

- Activity Description:

Starting in 2024 add 10 new T-7As, and increase 1328 LTO

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Start Date

Start Month: 1
Start Year: 2024

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	6.129575
SO _x	0.440178
NO _x	4.248455
CO	32.902013
PM 10	0.553528

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.496721
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1034.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	6.129575
SO _x	0.440178
NO _x	4.248455
CO	32.902013
PM 10	0.553528

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.496721
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1034.4

5.2 Aircraft & Engines

5.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

5.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

5.3 Flight Operations

5.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 10
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1328

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	9.74
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

5.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

5.4 Auxiliary Power Unit (APU)

5.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

5.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

5.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

6. Aircraft

6.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs

- Activity Description:

Starting in 2024 Increase T-7A TGOs 2931

- Activity Start Date

Start Month: 1

Start Year: 2024

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.594278
SO _x	0.401530
NO _x	7.342641
CO	1.225067
PM 10	0.039806

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.034457
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1230.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.594278
SO _x	0.401530
NO _x	7.342641
CO	1.225067
PM 10	0.039806

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.034457
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1230.2

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

6.2 Aircraft & Engines

6.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

6.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

6.3 Flight Operations

6.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 10
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 2931
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.64
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.47
Approach [Approach] (mins): 0.98
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

6.3.2 Flight Operations Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

6.4 Auxiliary Power Unit (APU)

6.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

6.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

6.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

7. Aircraft

7.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Title: Remove 11 T-38s and 2776LTOs

- Activity Description:

Starting in 2025 remove T-38s and 2776 LTOs

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-9.419282
SO _x	-0.807853
NO _x	-1.532868
CO	-100.821859
PM 10	-2.523479

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.028236
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2122.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-9.419282
SO _x	-0.807853
NO _x	-1.532868
CO	-100.821859
PM 10	-2.523479

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.028236
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2122.2

7.2 Aircraft & Engines

7.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C

Engine Model: J85-GE-5R

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

7.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234
------------	---------	------	------	------	-------	------	------	------

7.3 Flight Operations

7.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	11
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	2776
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	12.8
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

7.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

7.4 Auxiliary Power Unit (APU)

7.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

7.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

7.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

8. Aircraft

8.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Remove 6142 T-38 TGOs

- Activity Description:

Starting in 2025, remove 6142 T-38 TGOs

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.918521
SO _x	-0.300318
NO _x	-0.385904
CO	-16.838007
PM 10	-0.492938

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.198506
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-907.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Pollutant	Emissions Per Year (TONs)
VOC	-0.918521
SO _x	-0.300318
NO _x	-0.385904
CO	-16.838007
PM 10	-0.492938

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.198506
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-907.7

8.2 Aircraft & Engines

8.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

8.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

8.3 Flight Operations

8.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 11
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 6142
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.64
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.47
 Approach [Approach] (mins): 0.98
 Taxi/Idle In [Idle] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

8.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

8.4 Auxiliary Power Unit (APU)

8.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

8.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

8.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

9. Aircraft

9.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Add 7 new T-7As and 2836 LTOs

- Activity Description:

Starting in 2025, add 7 new T-7As and 2836 LTOs

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	13.089965
SO _x	0.940019
NO _x	9.072755
CO	70.263637
PM 10	1.182083

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.060768
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2209.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	13.089965
SO _x	0.940019
NO _x	9.072755
CO	70.263637
PM 10	1.182083

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.060768
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2209.0

9.2 Aircraft & Engines

9.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Engine Name:

9.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

9.3 Flight Operations

9.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	7
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	2836
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	9.74
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

9.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

9.4 Auxiliary Power Unit (APU)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

9.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

9.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

9.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

10. Aircraft

10.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs by 6395

- Activity Description:

Starting in 2025, increase T-7A TGOs by 6395

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.296625
SO _x	0.876078
NO _x	16.020536
CO	2.672911
PM 10	0.086851

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.075180
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2684.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.296625
SO _x	0.876078
NO _x	16.020536
CO	2.672911
PM 10	0.086851

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.075180
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2684.1

10.2 Aircraft & Engines

10.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

10.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

10.3 Flight Operations

10.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 7
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 6395
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.64
 Takeoff [After Burn] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

10.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AE_{TCO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

10.4 Auxiliary Power Unit (APU)

10.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

10.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

10.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

LTO: Number of LTOs
 EFPOL: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

11. Aircraft

11.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove
- Activity Location
 - County: Bexar
 - Regulatory Area(s): San Antonio, TX
- Activity Title: Remove 7 T-38s and reduce LTOs by 1534
- Activity Description:
 - Starting in 2026, remove 7 T-38s and reduce LTOs by 1534
- Activity Start Date
 - Start Month: 1
 - Start Year: 2026
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-5.205036
SO _x	-0.446415
NO _x	-0.847053
CO	-55.713520
PM 10	-1.394458

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.120790
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1172.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-5.205036
SO _x	-0.446415
NO _x	-0.847053
CO	-55.713520
PM 10	-1.394458

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.120790
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1172.7

11.2 Aircraft & Engines

11.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-38C
 - Engine Model: J85-GE-5R
 - Primary Function: Trainer
 - Aircraft has After burn: Yes

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

11.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

11.3 Flight Operations

11.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 7
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1534
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 12.8
 Takeoff [Military] (mins): 0.41
 Takeoff [After Burn] (mins): 0.39
 Climb Out [Intermediate] (mins): 0.91
 Approach [Approach] (mins): 1.74
 Taxi/Idle In [Idle] (mins): 6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
 Approach (mins): 27
 Intermediate (mins): 9
 Military (mins): 9
 AfterBurn (mins): 3

11.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

11.4 Auxiliary Power Unit (APU)

11.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

11.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

11.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

12. Aircraft

12.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Decrease T-38 TGOs by 3394

- Activity Description:

Starting in 2026, decrease T-38 TGOs by 3394

- Activity Start Date

Start Month: 1

Start Year: 2026

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.507564
SO _x	-0.165952
NO _x	-0.213246
CO	-9.304493
PM 10	-0.272392

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.109692
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-501.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.507564
SO _x	-0.165952
NO _x	-0.213246
CO	-9.304493
PM 10	-0.272392

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.109692
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-501.6

12.2 Aircraft & Engines

12.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

12.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

12.3 Flight Operations

12.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3394
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.64
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.47
Approach [Approach] (mins): 0.98
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

12.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

12.4 Auxiliary Power Unit (APU)

12.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

12.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

12.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

13. Aircraft

13.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Add T-7As and increase LTOs by 2698

- Activity Description:

Starting in 2026, add T-7As and increase LTOs by 2698

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	12.453006
SO _x	0.894277
NO _x	8.631274
CO	66.844602
PM 10	1.124563

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.009151
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2101.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	12.453006
SO _x	0.894277
NO _x	8.631274
CO	66.844602
PM 10	1.124563

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.009151
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2101.5

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

13.2 Aircraft & Engines

13.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

13.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

13.3 Flight Operations

13.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 2698
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 9.74
Takeoff [Military] (mins): 0.41
Takeoff [After Burn] (mins): 0.39
Climb Out [Intermediate] (mins): 0.91
Approach [Approach] (mins): 1.74
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

13.3.2 Flight Operations Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

13.4 Auxiliary Power Unit (APU)

13.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

13.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

13.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

14. Aircraft

14.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs by 6040

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Description:

Starting in 2026, increase T-7A TGOs by 6040

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.224647
SO _x	0.827445
NO _x	15.131202
CO	2.524532
PM 10	0.082030

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.071006
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2535.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.224647
SO _x	0.827445
NO _x	15.131202
CO	2.524532
PM 10	0.082030

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.071006
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2535.1

14.2 Aircraft & Engines

14.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

14.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

14.3 Flight Operations

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

14.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	19
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	6040
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

14.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

14.4 Auxiliary Power Unit (APU)

14.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

14.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

14.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

15. Aircraft

15.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Remove T-38s and decrease LTOs by 3767

- Activity Description:

Starting in 2027, remove T-38s and decrease LTOs by 3,767

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-12.781857
SO _x	-1.096248
NO _x	-2.080085
CO	-136.814100
PM 10	-3.424331

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.752292
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2879.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-12.781857

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.752292

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

SO _x	-1.096248
NO _x	-2.080085
CO	-136.814100
PM 10	-3.424331

Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2879.8

15.2 Aircraft & Engines

15.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

15.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

15.3 Flight Operations

15.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 16
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3767
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 12.8
 Takeoff [Military] (mins): 0.41
 Takeoff [After Burn] (mins): 0.39
 Climb Out [Intermediate] (mins): 0.91
 Approach [Approach] (mins): 1.74
 Taxi/Idle In [Idle] (mins): 6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

15.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

15.4 Auxiliary Power Unit (APU)

15.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

15.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

15.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

16. Aircraft

16.1 General Information & Timeline Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar
Regulatory Area(s): San Antonio, TX

- Activity Title: Decrease T-38 TGOs by 8,328

- Activity Description:

Starting in 2027, decrease T-38 TGOs by 8,328

- Activity Start Date

Start Month: 1
Start Year: 2027

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.245432
SO _x	-0.407204
NO _x	-0.523251
CO	-22.830824
PM 10	-0.668380

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.269156
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1230.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.245432
SO _x	-0.407204
NO _x	-0.523251
CO	-22.830824
PM 10	-0.668380

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.269156
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1230.7

16.2 Aircraft & Engines

16.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

16.2.2 Aircraft & Engines Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

16.3 Flight Operations

16.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	16
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	8328
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

16.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

16.4 Auxiliary Power Unit (APU)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

16.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

16.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

16.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

17. Aircraft

17.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Add 19 new T-7As and increase LTOs by 4918

- Activity Description:

Starting in 2027, add 19 new T-7As and increase LTOs by 4918

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
-----------	---------------------------

Pollutant	Emissions Per Year (TONs)
-----------	---------------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

VOC	25.492332
SO _x	1.674742
NO _x	15.805093
CO	127.217291
PM 10	2.073661

PM 2.5	1.860782
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3965.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	25.492332
SO _x	1.674742
NO _x	15.805093
CO	127.217291
PM 10	2.073661

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.860782
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3965.6

17.2 Aircraft & Engines

17.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

17.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

17.3 Flight Operations

17.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 19
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 4918
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 6.8
 Takeoff [Military] (mins): 0.41
 Takeoff [After Burn] (mins): 0.39
 Climb Out [Intermediate] (mins): 0.91
 Approach [Approach] (mins): 1.74

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Taxi/Idle In [Idle] (mins): 4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

17.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
 AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
 AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

17.4 Auxiliary Power Unit (APU)

17.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

17.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

17.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to tons

18. Aircraft

18.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs by 10952

- Activity Description:

Starting in 2027, increase T-7A TGOs by 10952

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	2.220585
SO _x	1.500361
NO _x	27.436577
CO	4.577595
PM 10	0.148741

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.128752
Pb	0.000000
NH ₃	0.000000
CO _{2e}	4596.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	2.220585
SO _x	1.500361
NO _x	27.436577
CO	4.577595
PM 10	0.148741

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.128752
Pb	0.000000
NH ₃	0.000000
CO _{2e}	4596.7

18.2 Aircraft & Engines

18.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

18.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

18.3 Flight Operations

18.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	19
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	10952
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

18.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

18.4 Auxiliary Power Unit (APU)

18.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

18.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

18.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

19. Aircraft

19.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Remove 21 T-38s and decrease LTOs by 3,667

- Activity Description:

Starting in 2028, remove 21 T-38s and decrease LTOs by 3,667

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-12.476477
SO _x	-1.070056
NO _x	-2.030388
CO	-133.545380
PM 10	-3.342518

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.686535
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2811.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-12.476477
SO _x	-1.070056
NO _x	-2.030388
CO	-133.545380
PM 10	-3.342518

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.686535
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2811.0

19.2 Aircraft & Engines

19.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

19.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

19.3 Flight Operations

19.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 21
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3677
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- **Default Settings Used:** No

- **Flight Operations TIMs (Time In Mode)**

Taxi/Idle Out [Idle] (mins):	12.8
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- **Trim Test**

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

19.3.2 Flight Operations Formula(s)

- **Aircraft Emissions per Mode for LTOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- **Aircraft Emissions for LTOs per Year**

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- **Aircraft Emissions per Mode for TGOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

19.4 Auxiliary Power Unit (APU)

19.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

19.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

19.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

20. Aircraft

20.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Decrease T-38 TGOs by 8093

- Activity Description:

Starting in 2028, decrease T-38 TGOs by 8093

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.210288
SO _x	-0.395714
NO _x	-0.508486
CO	-22.186583
PM 10	-0.649520

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.261561
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1196.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.210288
SO _x	-0.395714
NO _x	-0.508486
CO	-22.186583
PM 10	-0.649520

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.261561
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1196.0

20.2 Aircraft & Engines

20.2.1 Aircraft & Engines Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

20.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

20.3 Flight Operations

20.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 21
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 8093
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.64
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.47
 Approach [Approach] (mins): 0.98
 Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
 Approach (mins): 27
 Intermediate (mins): 9
 Military (mins): 9
 AfterBurn (mins): 3

20.3.2 Flight Operations Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

20.4 Auxiliary Power Unit (APU)

20.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

20.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

20.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

21. Aircraft

21.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

- Activity Title: Add T-7As and increase LTOs by 4298

- Activity Description:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Starting in 2028, add T-7As and increase LTOs by 4298

- Activity Start Date

Start Month: 1
Start Year: 2028

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	19.838036
SO _x	1.424612
NO _x	13.749895
CO	106.485582
PM 10	1.791464

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.607610
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3347.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	19.838036
SO _x	1.424612
NO _x	13.749895
CO	106.485582
PM 10	1.791464

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.607610
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3347.8

21.2 Aircraft & Engines

21.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

21.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

21.3 Flight Operations

21.3.1 Flight Operations Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations

Number of Aircraft:	14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	4298
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	9.74
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

21.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

21.4 Auxiliary Power Unit (APU)

21.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

21.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

21.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

22. Aircraft

22.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs by 9527

- Activity Description:

Starting in 2028, increase T-7A TGOs by 9527

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.931658
SO _x	1.305144
NO _x	23.866716
CO	3.981990
PM 10	0.129388

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.112000
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3998.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.931658
SO _x	1.305144

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.112000
Pb	0.000000

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NO _x	23.866716
CO	3.981990
PM 10	0.129388

NH ₃	0.000000
CO ₂ e	3998.6

22.2 Aircraft & Engines

22.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

22.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

22.3 Flight Operations

22.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 9527
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.64
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.47
Approach [Approach] (mins): 0.98
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AfterBurn (mins): 3

22.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

22.4 Auxiliary Power Unit (APU)

22.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

22.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

22.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

23. Aircraft

23.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

County: Bexar
 Regulatory Area(s): San Antonio, TX

- Activity Title: Remove T-38s and decrease LTOs by 1445

- Activity Description:
 Starting in 2029 T-38s and decrease LTOs by 1445

- Activity Start Date
 Start Month: 1
 Start Year: 2029

- Activity End Date
 Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-4.903048
SO _x	-0.420514
NO _x	-0.797909
CO	-52.481119
PM 10	-1.313554

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.055764
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1104.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-4.903048
SO _x	-0.420514
NO _x	-0.797909
CO	-52.481119
PM 10	-1.313554

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.055764
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1104.7

23.2 Aircraft & Engines

23.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

23.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

23.3 Flight Operations

23.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	3
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	1445
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	12.8
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

23.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)
AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

23.4 Auxiliary Power Unit (APU)

23.4.1 Auxiliary Power Unit (APU) Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

23.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

23.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

24. Aircraft

24.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Decrease T-38 TGOs by 3193

- Activity Description:

Starting in 2029, decrease T-38 TGOs by 3193

- Activity Start Date

Start Month: 1

Start Year: 2029

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.477505
SO _x	-0.156124
NO _x	-0.200617
CO	-8.753461

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.103196
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-471.9

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

PM 10	-0.256261
-------	-----------

--	--

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.477505
SO _x	-0.156124
NO _x	-0.200617
CO	-8.753461
PM 10	-0.256261

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.103196
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-471.9

24.2 Aircraft & Engines

24.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

24.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

24.3 Flight Operations

24.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 7
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3193
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.64
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.47
 Approach [Approach] (mins): 0.98

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

24.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
 AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
 AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

24.4 Auxiliary Power Unit (APU)

24.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

24.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

24.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

25. Aircraft

25.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Add T-7As and increase LTOs by 504

- Activity Description:

Starting in 2029, add T-7As and increase LTOs by 504

- Activity Start Date

Start Month: 1

Start Year: 2029

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	2.326284
SO _x	0.167056
NO _x	1.612365
CO	12.486909
PM 10	0.210074

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.188515
Pb	0.000000
NH ₃	0.000000
CO _{2e}	392.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	2.326284
SO _x	0.167056
NO _x	1.612365
CO	12.486909
PM 10	0.210074

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.188515
Pb	0.000000
NH ₃	0.000000
CO _{2e}	392.6

25.2 Aircraft & Engines

25.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 1

- Aircraft & Engine Surrogate

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

25.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

25.3 Flight Operations

25.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	0
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	504
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	9.74
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

25.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

25.4 Auxiliary Power Unit (APU)

25.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

25.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

25.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

26. Aircraft

26.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs by 1158

- Activity Description:

Starting in 2029, increase T-7A TGOs by 1158

- Activity Start Date

Start Month: 1

Start Year: 2029

- Activity End Date

Indefinite: Yes

End Month: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.234792
SO _x	0.158639
NO _x	2.900982
CO	0.484008
PM 10	0.015727

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.013613
Pb	0.000000
NH ₃	0.000000
CO _{2e}	486.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.234792
SO _x	0.158639
NO _x	2.900982
CO	0.484008
PM 10	0.015727

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.013613
Pb	0.000000
NH ₃	0.000000
CO _{2e}	486.0

26.2 Aircraft & Engines

26.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

26.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

26.3 Flight Operations

26.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 0
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1158
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

26.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

26.4 Auxiliary Power Unit (APU)

26.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

26.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

26.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

27. Aircraft

27.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove
- Activity Location
 - County: Bexar
 - Regulatory Area(s): San Antonio, TX
- Activity Title: Remove T-38s and decrease LTOs by 1715
- Activity Description:
 - Starting in 2030, remove T-38s and decrease LTOs by 1715
- Activity Start Date
 - Start Month: 1
 - Start Year: 2030
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-5.819189
SO _x	-0.499088
NO _x	-0.946999
CO	-62.287279
PM 10	-1.558993

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.253035
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1311.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-5.819189
SO _x	-0.499088
NO _x	-0.946999
CO	-62.287279
PM 10	-1.558993

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.253035
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1311.1

27.2 Aircraft & Engines

27.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-38C
 - Engine Model: J85-GE-5R

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No
 - Original Aircraft Name:
 - Original Engine Name:

27.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

27.3 Flight Operations

27.3.1 Flight Operations Assumptions

- Flight Operations
 - Number of Aircraft: 6
 - Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1715
 - Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 - Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)
 - Taxi/Idle Out [Idle] (mins): 12.8
 - Takeoff [Military] (mins): 0.41
 - Takeoff [After Burn] (mins): 0.39
 - Climb Out [Intermediate] (mins): 0.91
 - Approach [Approach] (mins): 1.74
 - Taxi/Idle In [Idle] (mins): 6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test
 - Idle (mins): 12
 - Approach (mins): 27
 - Intermediate (mins): 9
 - Military (mins): 9
 - AfterBurn (mins): 3

27.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year
 $AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

27.4 Auxiliary Power Unit (APU)

27.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

27.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

27.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs
- EF_{POL}: Emission Factor for Pollutant (lb/hr)
- 2000: Conversion Factor pounds to tons

28. Aircraft

28.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

- Activity Title: Decrease T-38 TGOs by 3792

- Activity Description:

Starting in 2030, decrease T-38 TGOs by 3,792

- Activity Start Date

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Start Month: 1
Start Year: 2030

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.567084
SO _x	-0.185413
NO _x	-0.238253
CO	-10.395591
PM 10	-0.304334

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.122555
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-560.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.567084
SO _x	-0.185413
NO _x	-0.238253
CO	-10.395591
PM 10	-0.304334

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.122555
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-560.4

28.2 Aircraft & Engines

28.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

28.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

28.3 Flight Operations

28.3.1 Flight Operations Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations

Number of Aircraft:	6
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	3792
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

28.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

28.4 Auxiliary Power Unit (APU)

28.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

28.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

28.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

29. Aircraft

29.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: increase LTOs by 261

- Activity Description:

Stating in 2030, increase LTOs by 261

- Activity Start Date

Start Month: 1

Start Year: 2030

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.204683
SO _x	0.086511
NO _x	0.834975
CO	6.466435
PM 10	0.108788

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.097624
Pb	0.000000
NH ₃	0.000000
CO _{2e}	203.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.204683
SO _x	0.086511
NO _x	0.834975
CO	6.466435

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.097624
Pb	0.000000
NH ₃	0.000000
CO _{2e}	203.3

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

PM 10	0.108788
-------	----------

--	--

29.2 Aircraft & Engines

29.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

29.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

29.3 Flight Operations

29.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 0
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 261
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 9.74
Takeoff [Military] (mins): 0.41
Takeoff [After Burn] (mins): 0.39
Climb Out [Intermediate] (mins): 0.91
Approach [Approach] (mins): 1.74
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

29.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

29.4 Auxiliary Power Unit (APU)

29.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

29.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

29.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

30. Aircraft

30.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- **Activity Title:** Increase TGOs by 590

- **Activity Description:**
Starting in 2030, increase TGOs by 590

- **Activity Start Date**

Start Month: 1

Start Year: 2030

- **Activity End Date**

Indefinite: Yes

End Month: N/A

End Year: N/A

- **Activity Emissions:**

Pollutant	Emissions Per Year (TONs)
VOC	0.119626
SO _x	0.080827
NO _x	1.478048
CO	0.246602
PM 10	0.008013

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.006936
Pb	0.000000
NH ₃	0.000000
CO _{2e}	247.6

- **Activity Emissions [Flight Operations (includes Trim Test & APU) part]:**

Pollutant	Emissions Per Year (TONs)
VOC	0.119626
SO _x	0.080827
NO _x	1.478048
CO	0.246602
PM 10	0.008013

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.006936
Pb	0.000000
NH ₃	0.000000
CO _{2e}	247.6

30.2 Aircraft & Engines

30.2.1 Aircraft & Engines Assumptions

- **Aircraft & Engine**

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 1

- **Aircraft & Engine Surrogate**

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

30.2.2 Aircraft & Engines Emission Factor(s)

- **Aircraft & Engine Emissions Factors (lb/1000lb fuel)**

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

30.3 Flight Operations

30.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	0
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	590
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

30.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

30.4 Auxiliary Power Unit (APU)

30.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1	0.25	No	4501687C	Hamilton Sundstrand
---	------	----	----------	---------------------

30.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

30.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

31. Aircraft

31.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Remove 14 T-38s and decrease LTOs by 2636

- Activity Description:

Starting in 2031, remove 14 T-38s and decrease TOs by 2,636

- Activity Start Date

Start Month: 1

Start Year: 2031

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-8.944246
SO _x	-0.767111
NO _x	-1.455562
CO	-95.737183
PM 10	-2.396214

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.925947
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2015.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Pollutant	Emissions Per Year (TONs)
VOC	-8.944246
SO _x	-0.767111
NO _x	-1.455562
CO	-95.737183
PM 10	-2.396214

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.925947
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2015.2

31.2 Aircraft & Engines

31.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

31.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

31.3 Flight Operations

31.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 14
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 2636
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 12.8
 Takeoff [Military] (mins): 0.41
 Takeoff [After Burn] (mins): 0.39
 Climb Out [Intermediate] (mins): 0.91
 Approach [Approach] (mins): 1.74
 Taxi/Idle In [Idle] (mins): 6.4

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

31.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

31.4 Auxiliary Power Unit (APU)

31.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

31.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

31.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

32. Aircraft

32.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2031 T-38 Removal 5840 TGOs

- Activity Description:

Starting in 2031, decrease T-38 TGOs by 5840

- Activity Start Date

Start Month: 1

Start Year: 2031

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.873357
SO _x	-0.285551
NO _x	-0.366929
CO	-16.010088
PM 10	-0.468701

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.188745
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-863.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.873357
SO _x	-0.285551
NO _x	-0.366929
CO	-16.010088
PM 10	-0.468701

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.188745
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-863.1

32.2 Aircraft & Engines

32.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C

Engine Model: J85-GE-5R

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Engine Name:

32.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

32.3 Flight Operations

32.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	5840
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

32.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

32.4 Auxiliary Power Unit (APU)

32.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

32.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

32.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

33. Aircraft

33.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: decrease T-7A LTOs by 104

- Activity Description:

Starting in 2031, decrease T-7A LTOs by 104

- Activity Start Date

Start Month: 1

Start Year: 2031

- Activity End Date

Indefinite: Yes

End Month: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.480027
SO _x	-0.034472
NO _x	-0.332710
CO	-2.576664
PM 10	-0.043349

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.038900
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-81.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.480027
SO _x	-0.034472
NO _x	-0.332710
CO	-2.576664
PM 10	-0.043349

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.038900
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-81.0

33.2 Aircraft & Engines

33.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

33.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

33.3 Flight Operations

33.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 0
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 104
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 9.74

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

33.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

- AE_{TGO}: Aircraft Emissions (TONs)
- AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
- AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
- AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

- AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
- TD: Test Duration (min)
- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- NA: Number of Aircraft
- NTT: Number of Trim Test
- 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

33.4 Auxiliary Power Unit (APU)

33.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

33.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

33.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

34. Aircraft

34.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

- Activity Title: decrease T-7A TGOs by 224

- Activity Description:

Starting in 2031, decrease T-7A TGOs by 224

- Activity Start Date

Start Month: 1
 Start Year: 2031

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.045417
SO _x	-0.030687
NO _x	-0.561157
CO	-0.093625
PM 10	-0.003042

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.002633
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-94.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.045417
SO _x	-0.030687
NO _x	-0.561157
CO	-0.093625
PM 10	-0.003042

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.002633
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-94.0

34.2 Aircraft & Engines

34.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

34.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

34.3 Flight Operations

34.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	0
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	224
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

34.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

34.4 Auxiliary Power Unit (APU)

34.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

34.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

34.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

35. Aircraft

35.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase LTOs by 1242

- Activity Description:

increase LTOs by 1242

- Activity Start Date

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Start Month: 1
Start Year: 2032

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	2.561682
SO _x	0.183960
NO _x	1.775522
CO	13.750465
PM 10	0.231331

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.207590
Pb	0.000000
NH ₃	0.000000
CO _{2e}	432.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	2.561682
SO _x	0.183960
NO _x	1.775522
CO	13.750465
PM 10	0.231331

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.207590
Pb	0.000000
NH ₃	0.000000
CO _{2e}	432.3

35.2 Aircraft & Engines

35.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

35.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

35.3 Flight Operations

35.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 0
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 555
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual Trim Test(s) per Aircraft:

0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	9.74
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

35.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

35.4 Auxiliary Power Unit (APU)

35.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

35.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

35.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

36. Aircraft

36.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs by 2748

- Activity Description:

Starting in 2032, increase T-7A TGOs by 2748

- Activity Start Date

Start Month: 1

Start Year: 2032

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.557174
SO _x	0.376460
NO _x	6.884196
CO	1.148579
PM 10	0.037321

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.032306
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1153.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.557174
SO _x	0.376460
NO _x	6.884196
CO	1.148579
PM 10	0.037321

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.032306
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1153.4

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

36.2 Aircraft & Engines

36.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

36.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

36.3 Flight Operations

36.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 0
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 2748
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.64
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.47
Approach [Approach] (mins): 0.98
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

36.3.2 Flight Operations Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

36.4 Auxiliary Power Unit (APU)

36.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

36.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

36.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

37. Aircraft

37.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

- Activity Title: 2023 T-7A Increase Trim Test and Test Cell

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Description:

- Activity Start Date

Start Month: 1
Start Year: 2023

- Activity End Date

Indefinite: No
End Month: 12
End Year: 2023

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.084558
SO _x	0.027537
NO _x	0.469887
CO	1.450657
PM 10	0.032987

Pollutant	Total Emissions (TONs)
PM 2.5	0.029582
Pb	0.000000
NH ₃	0.000000
CO _{2e}	83.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	0.046147
SO _x	0.015141
NO _x	0.251550
CO	0.731888
PM 10	0.016822

Pollutant	Total Emissions (TONs)
PM 2.5	0.015074
Pb	0.000000
NH ₃	0.000000
CO _{2e}	45.8

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	0.038410
SO _x	0.012396
NO _x	0.218337
CO	0.718770
PM 10	0.016165

Pollutant	Total Emissions (TONs)
PM 2.5	0.014509
Pb	0.000000
NH ₃	0.000000
CO _{2e}	37.5

37.2 Aircraft & Engines

37.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

37.2.2 Aircraft & Engines Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

37.3 Flight Operations

37.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	8
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	0
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	1

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	6.8
Takeoff [Military] (mins):	0.25
Takeoff [After Burn] (mins):	0.25
Climb Out [Intermediate] (mins):	1.4
Approach [Approach] (mins):	4
Taxi/Idle In [Idle] (mins):	4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

37.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)
AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

37.4 Auxiliary Power Unit (APU)

37.4.1 Auxiliary Power Unit (APU) Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

37.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

37.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

37.5 Aircraft Engine Test Cell

37.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 8

- Default Settings Used: No

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine):	1
Idle Duration (mins):	0
Approach Duration (mins):	12
Intermediate Duration (mins):	0
Military Duration (mins):	8
After Burner Duration (mins):	2

37.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

37.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

EF: Emission Factor (lb/1000lb fuel)
 NE: Total Number of Engines (For All Aircraft)
 ARU: Annual Run-ups (Per Aircraft Engine)
 2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

TestCell: Aircraft Engine Test Cell Emissions (TONs)
 TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)
 TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)
 TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)
 TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)
 TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

38. Aircraft

38.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

- Activity Title: 2024 T-7A Increase Trim Test and Engine Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1
 Start Year: 2024

- Activity End Date

Indefinite: No
 End Month: 12
 End Year: 2024

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.190255
SO _x	0.061958
NO _x	1.057247
CO	3.263979
PM 10	0.074222

Pollutant	Total Emissions (TONs)
PM 2.5	0.066560
Pb	0.000000
NH ₃	0.000000
CO _{2e}	187.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	0.103831
SO _x	0.034068
NO _x	0.565988

Pollutant	Total Emissions (TONs)
PM 2.5	0.033916
Pb	0.000000
NH ₃	0.000000

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

CO	1.646748
PM 10	0.037849

CO _{2e}	103.0

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	0.086424
SO _x	0.027890
NO _x	0.491259
CO	1.617231
PM 10	0.036372

Pollutant	Total Emissions (TONs)
PM 2.5	0.032645
Pb	0.000000
NH ₃	0.000000
CO _{2e}	84.3

38.2 Aircraft & Engines

38.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

38.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

38.3 Flight Operations

38.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 18
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 1

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 6.8
 Takeoff [Military] (mins): 0.25
 Takeoff [After Burn] (mins): 0.25
 Climb Out [Intermediate] (mins): 1.4
 Approach [Approach] (mins): 4
 Taxi/Idle In [Idle] (mins): 4.4

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

38.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

38.4 Auxiliary Power Unit (APU)

38.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

38.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

38.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

38.5 Aircraft Engine Test Cell

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

38.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 18

- Default Settings Used: No

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 1
Idle Duration (mins): 0
Approach Duration (mins): 12
Intermediate Duration (mins): 0
Military Duration (mins): 8
After Burner Duration (mins): 2

38.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

38.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$TestCell = TestCellPS_{IDLE} + TestCellPS_{APPROACH} + TestCellPS_{INTERMEDIATE} + TestCellPS_{MILITARY} + TestCellPS_{AFTERBURN}$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

39. Aircraft

39.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Regulatory Area(s): San Antonio, TX

- Activity Title: 2025 T-38 Removal Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1
Start Year: 2025

- Activity End Date

Indefinite: No
End Month: 12
End Year: 2025

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	-0.250354
SO _x	-0.060969
NO _x	-0.178052
CO	-3.170952
PM 10	-0.067114

Pollutant	Total Emissions (TONs)
PM 2.5	-0.025080
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-184.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	-0.109701
SO _x	-0.028464
NO _x	-0.081041
CO	-1.447601
PM 10	-0.030287

Pollutant	Total Emissions (TONs)
PM 2.5	-0.010342
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-86.0

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	-0.140653
SO _x	-0.032505
NO _x	-0.097011
CO	-1.723351
PM 10	-0.036827

Pollutant	Total Emissions (TONs)
PM 2.5	-0.014738
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-98.2

39.2 Aircraft & Engines

39.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

39.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

39.3 Flight Operations

39.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	12
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	0
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	3

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	12.8
Takeoff [Military] (mins):	0.2
Takeoff [After Burn] (mins):	0.2
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	3.8
Taxi/Idle In [Idle] (mins):	6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

39.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

39.4 Auxiliary Power Unit (APU)

39.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

39.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

39.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

39.5 Aircraft Engine Test Cell

39.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 28

- Default Settings Used: Yes

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine):	3 (default)
Idle Duration (mins):	0 (default)
Approach Duration (mins):	12 (default)
Intermediate Duration (mins):	0 (default)
Military Duration (mins):	8 (default)
After Burner Duration (mins):	2 (default)

39.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

39.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

TestCell = TestCellPS_{IDLE} + TestCellPS_{APPROACH} + TestCellPS_{INTERMEDIATE} + TestCellPS_{MILITARY} + TestCellPS_{AFTERBURN}

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

40. Aircraft

40.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2025 T-7A Increase Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: No

End Month: 12

End Year: 2025

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.264243
SO _x	0.086053
NO _x	1.468398
CO	4.533304
PM 10	0.103086

Pollutant	Total Emissions (TONs)
PM 2.5	0.092445
Pb	0.000000
NH ₃	0.000000
CO _{2e}	260.1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	0.144210
SO _x	0.047317
NO _x	0.786095
CO	2.287149
PM 10	0.052569

Pollutant	Total Emissions (TONs)
PM 2.5	0.047105
Pb	0.000000
NH ₃	0.000000
CO _{2e}	143.0

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	0.120033
SO _x	0.038737
NO _x	0.682304
CO	2.246155
PM 10	0.050517

Pollutant	Total Emissions (TONs)
PM 2.5	0.045340
Pb	0.000000
NH ₃	0.000000
CO _{2e}	117.1

40.2 Aircraft & Engines

40.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

40.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

40.3 Flight Operations

40.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 25
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 1

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 6.8
 Takeoff [Military] (mins): 0.25

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Takeoff [After Burn] (mins):	0.25
Climb Out [Intermediate] (mins):	1.4
Approach [Approach] (mins):	4
Taxi/Idle In [Idle] (mins):	4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

40.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

- AE_{TGO}: Aircraft Emissions (TONs)
- AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
- AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
- AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

- AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
- TD: Test Duration (min)
- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- NA: Number of Aircraft
- NTT: Number of Trim Test
- 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

40.4 Auxiliary Power Unit (APU)

40.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

40.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

40.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

40.5 Aircraft Engine Test Cell

40.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 25

- Default Settings Used: No

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine):	1
Idle Duration (mins):	0
Approach Duration (mins):	12
Intermediate Duration (mins):	0
Military Duration (mins):	8
After Burner Duration (mins):	2

40.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

40.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$\text{TestCellPS}_{\text{POL}} = (\text{TD} / 60) * (\text{FC} / 1000) * \text{EF} * \text{NE} * \text{ARU} / 2000$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} +$

$\text{TestCellPS}_{\text{AFTERBURN}}$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

41. Aircraft

41.1 General Information & Timeline Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2026 T-38 Removal Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: No

End Month: 12

End Year: 2026

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	-0.364579
SO _x	-0.089182
NO _x	-0.259973
CO	-4.630868
PM 10	-0.097934

Pollutant	Total Emissions (TONs)
PM 2.5	-0.036377
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-269.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	-0.173693
SO _x	-0.045068
NO _x	-0.128315
CO	-2.292035
PM 10	-0.047954

Pollutant	Total Emissions (TONs)
PM 2.5	-0.016375
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-136.2

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	-0.190886
SO _x	-0.044114
NO _x	-0.131658
CO	-2.338834
PM 10	-0.049980

Pollutant	Total Emissions (TONs)
PM 2.5	-0.020002
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-133.3

41.2 Aircraft & Engines

41.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C

Engine Model: J85-GE-5R

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 2

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

41.4 Auxiliary Power Unit (APU)

41.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

41.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

41.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs
- EF_{POL}: Emission Factor for Pollutant (lb/hr)
- 2000: Conversion Factor pounds to tons

41.5 Aircraft Engine Test Cell

41.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 38

- Default Settings Used: No

- Annual Run-ups / Test Durations

- Annual Run-ups (Per Aircraft Engine): 3
- Idle Duration (mins): 0
- Approach Duration (mins): 12
- Intermediate Duration (mins): 0
- Military Duration (mins): 8
- After Burner Duration (mins): 2

41.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

41.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$\text{TestCellPS}_{\text{POL}} = (\text{TD} / 60) * (\text{FC} / 1000) * \text{EF} * \text{NE} * \text{ARU} / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

42. Aircraft

42.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2026 T-7A Increase Trim Test and Engine Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: No

End Month: 12

End Year: 2026

- Activity Emissions:

Pollutant	Total Emissions (TONs)
-----------	------------------------

Pollutant	Total Emissions (TONs)
-----------	------------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

VOC	0.426622
SO _x	0.138892
NO _x	2.372578
CO	7.341493
PM 10	0.166876

PM 2.5	0.149655
Pb	0.000000
NH ₃	0.000000
CO _{2e}	419.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	0.224967
SO _x	0.073814
NO _x	1.226308
CO	3.567953
PM 10	0.082007

Pollutant	Total Emissions (TONs)
PM 2.5	0.073484
Pb	0.000000
NH ₃	0.000000
CO _{2e}	223.1

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	0.201655
SO _x	0.065078
NO _x	1.146270
CO	3.773540
PM 10	0.084869

Pollutant	Total Emissions (TONs)
PM 2.5	0.076171
Pb	0.000000
NH ₃	0.000000
CO _{2e}	196.7

42.2 Aircraft & Engines

42.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

42.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

42.3 Flight Operations

42.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 39
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- **Default Settings Used:** No

- **Flight Operations TIMs (Time In Mode)**

Taxi/Idle Out [Idle] (mins):	6.8
Takeoff [Military] (mins):	0.25
Takeoff [After Burn] (mins):	0.25
Climb Out [Intermediate] (mins):	1.4
Approach [Approach] (mins):	4
Taxi/Idle In [Idle] (mins):	4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- **Trim Test**

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

42.3.2 Flight Operations Formula(s)

- **Aircraft Emissions per Mode for LTOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- **Aircraft Emissions for LTOs per Year**

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- **Aircraft Emissions per Mode for TGOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

42.4 Auxiliary Power Unit (APU)

42.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

42.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

42.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
APU: Number of Auxiliary Power Units
OH: Operation Hours for Each LTO (hour)
LTO: Number of LTOs
EF_{POL}: Emission Factor for Pollutant (lb/hr)
2000: Conversion Factor pounds to tons

42.5 Aircraft Engine Test Cell

42.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 42

- Default Settings Used: Yes

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 1 (default)
Idle Duration (mins): 0 (default)
Approach Duration (mins): 12 (default)
Intermediate Duration (mins): 0 (default)
Military Duration (mins): 8 (default)
After Burner Duration (mins): 2 (default)

42.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

42.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$\text{TestCellPS}_{\text{POL}} = (\text{TD} / 60) * (\text{FC} / 1000) * \text{EF} * \text{NE} * \text{ARU} / 2000$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Total Number of Engines (For All Aircraft)
ARU: Annual Run-ups (Per Aircraft Engine)
2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$

TestCell: Aircraft Engine Test Cell Emissions (TONs)
TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)
TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)
TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)
TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)
TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

43. Aircraft

43.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location
 - County: Bexar
 - Regulatory Area(s): San Antonio, TX

- Activity Title: 2027 T-38 Removal Trim Test and Test Cell

- Activity Description:

- Activity Start Date
 - Start Month: 1
 - Start Year: 2027

- Activity End Date
 - Indefinite: No
 - End Month: 12
 - End Year: 2027

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	-0.671594
SO _x	-0.164283
NO _x	-0.478897
CO	-8.530547
PM 10	-0.180406

Pollutant	Total Emissions (TONs)
PM 2.5	-0.067010
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-496.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	-0.319962
SO _x	-0.083020
NO _x	-0.236369
CO	-4.222169
PM 10	-0.088337

Pollutant	Total Emissions (TONs)
PM 2.5	-0.030165
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-250.9

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	-0.351632
SO _x	-0.081263
NO _x	-0.242528
CO	-4.308378
PM 10	-0.092069

Pollutant	Total Emissions (TONs)
PM 2.5	-0.036845
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-245.6

43.2 Aircraft & Engines

43.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

43.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

43.3 Flight Operations

43.3.1 Flight Operations Assumptions

- Flight Operations
 Number of Aircraft: 35
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 3

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)
 Taxi/Idle Out [Idle] (mins): 6.8
 Takeoff [Military] (mins): 0.25
 Takeoff [After Burn] (mins): 0.25
 Climb Out [Intermediate] (mins): 1.4
 Approach [Approach] (mins): 4
 Taxi/Idle In [Idle] (mins): 4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test
 Idle (mins): 0
 Approach (mins): 4.97
 Intermediate (mins): 10.45
 Military (mins): 6.14
 AfterBurn (mins): 2.04

43.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{\text{TRIM}} = AEPS_{\text{IDLE}} + AEPS_{\text{APPROACH}} + AEPS_{\text{INTERMEDIATE}} + AEPS_{\text{MILITARY}} + AEPS_{\text{AFTERBURN}}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{\text{IDLE}}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{\text{APPROACH}}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{\text{INTERMEDIATE}}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{\text{MILITARY}}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{\text{AFTERBURN}}$: Aircraft Emissions for After Burner Power Setting (TONs)

43.4 Auxiliary Power Unit (APU)

43.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

43.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

43.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{\text{POL}} = \text{APU} * \text{OH} * \text{LTO} * EF_{\text{POL}} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

43.5 Aircraft Engine Test Cell

43.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 70

- Default Settings Used: No

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine):	3
Idle Duration (mins):	0
Approach Duration (mins):	12
Intermediate Duration (mins):	0
Military Duration (mins):	8

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

After Burner Duration (mins): 2

43.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

43.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$\text{TestCellPS}_{\text{POL}} = (\text{TD} / 60) * (\text{FC} / 1000) * \text{EF} * \text{NE} * \text{ARU} / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

44. Aircraft

44.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2027 T-7A Increase Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

End Month: 12
End Year: 2027

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.613043
SO _x	0.199644
NO _x	3.406684
CO	10.517266
PM 10	0.239159

Pollutant	Total Emissions (TONs)
PM 2.5	0.214473
Pb	0.000000
NH ₃	0.000000
CO _{2e}	603.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	0.334567
SO _x	0.109775
NO _x	1.823740
CO	5.306186
PM 10	0.121959

Pollutant	Total Emissions (TONs)
PM 2.5	0.109284
Pb	0.000000
NH ₃	0.000000
CO _{2e}	331.8

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	0.278476
SO _x	0.089869
NO _x	1.582944
CO	5.211079
PM 10	0.117200

Pollutant	Total Emissions (TONs)
PM 2.5	0.105189
Pb	0.000000
NH ₃	0.000000
CO _{2e}	271.6

44.2 Aircraft & Engines

44.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

44.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

44.3 Flight Operations

44.3.1 Flight Operations Assumptions

- Flight Operations

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Aircraft:	58
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	0
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	1

- **Default Settings Used:** No

- **Flight Operations TIMs (Time In Mode)**

Taxi/Idle Out [Idle] (mins):	6.8
Takeoff [Military] (mins):	0.25
Takeoff [After Burn] (mins):	0.25
Climb Out [Intermediate] (mins):	1.4
Approach [Approach] (mins):	4
Taxi/Idle In [Idle] (mins):	4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- **Trim Test**

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

44.3.2 Flight Operations Formula(s)

- **Aircraft Emissions per Mode for LTOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- **Aircraft Emissions for LTOs per Year**

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- **Aircraft Emissions per Mode for TGOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TIM: Time in Mode (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

44.4 Auxiliary Power Unit (APU)

44.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

44.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

44.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$\text{APU}_{\text{POL}} = \text{APU} * \text{OH} * \text{LTO} * \text{EF}_{\text{POL}} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

44.5 Aircraft Engine Test Cell

44.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 58

- Default Settings Used: No

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine):	1
Idle Duration (mins):	0
Approach Duration (mins):	12
Intermediate Duration (mins):	0
Military Duration (mins):	8
After Burner Duration (mins):	2

44.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

44.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$\text{TestCellPS}_{\text{POL}} = (\text{TD} / 60) * (\text{FC} / 1000) * \text{EF} * \text{NE} * \text{ARU} / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONS

- Aircraft Engine Test Cell Emissions per Year

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)
 TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)
 TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)
 TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

45. Aircraft

45.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove
- Activity Location
 - County: Bexar; Bexar
 - Regulatory Area(s): San Antonio, TX
- Activity Title: 2028 T-38 Removal Trim Test and Test Cell
- Activity Description:
- Activity Start Date
 - Start Month: 1
 - Start Year: 2028
- Activity End Date
 - Indefinite: No
 - End Month: 12
 - End Year: 2028

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	-1.074550
SO _x	-0.262853
NO _x	-0.766235
CO	-13.648875
PM 10	-0.288649

Pollutant	Total Emissions (TONs)
PM 2.5	-0.107216
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-794.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	-0.511939
SO _x	-0.132832
NO _x	-0.378191
CO	-6.755471
PM 10	-0.141339

Pollutant	Total Emissions (TONs)
PM 2.5	-0.048263
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-401.5

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	-0.562611
SO _x	-0.130020
NO _x	-0.388044
CO	-6.893404
PM 10	-0.147310

Pollutant	Total Emissions (TONs)
PM 2.5	-0.058952
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-393.0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

45.2 Aircraft & Engines

45.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

45.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

45.3 Flight Operations

45.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 56
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 3

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 6.8
 Takeoff [Military] (mins): 0.25
 Takeoff [After Burn] (mins): 0.25
 Climb Out [Intermediate] (mins): 1.4
 Approach [Approach] (mins): 4
 Taxi/Idle In [Idle] (mins): 4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 0
 Approach (mins): 4.97
 Intermediate (mins): 10.45
 Military (mins): 6.14

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AfterBurn (mins): 2.04

45.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

45.4 Auxiliary Power Unit (APU)

45.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

45.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

45.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

45.5 Aircraft Engine Test Cell

45.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 112

- Default Settings Used: No

- Annual Run-ups / Test Durations

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Annual Run-ups (Per Aircraft Engine):	3
Idle Duration (mins):	0
Approach Duration (mins):	12
Intermediate Duration (mins):	0
Military Duration (mins):	8
After Burner Duration (mins):	2

45.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

45.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$\text{TestCellPS}_{\text{POL}} = (\text{TD} / 60) * (\text{FC} / 1000) * \text{EF} * \text{NE} * \text{ARU} / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

46. Aircraft

46.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2028 T-7A Increase Trim Test and Test Cell

- Activity Description:

- Activity Start Date

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Start Month: 1
Start Year: 2028

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.761018
SO _x	0.247833
NO _x	4.228987
CO	13.055916
PM 10	0.296887

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.266242
Pb	0.000000
NH ₃	0.000000
CO _{2e}	749.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.415324
SO _x	0.136272
NO _x	2.263953
CO	6.586990
PM 10	0.151397

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.135663
Pb	0.000000
NH ₃	0.000000
CO _{2e}	411.9

- Activity Emissions [Test Cell part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.345694
SO _x	0.111562
NO _x	1.965034
CO	6.468926
PM 10	0.145489

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.130579
Pb	0.000000
NH ₃	0.000000
CO _{2e}	337.2

46.2 Aircraft & Engines

46.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

46.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

46.3 Flight Operations

46.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	72
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	0
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	1

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	6.8
Takeoff [Military] (mins):	0.25
Takeoff [After Burn] (mins):	0.25
Climb Out [Intermediate] (mins):	1.4
Approach [Approach] (mins):	4
Taxi/Idle In [Idle] (mins):	4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

46.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

46.4 Auxiliary Power Unit (APU)

46.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
-------------------------------	---------------------------------	-------------------	-------------	--------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

46.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

46.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

46.5 Aircraft Engine Test Cell

46.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 72

- Default Settings Used: No

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 1
 Idle Duration (mins): 0
 Approach Duration (mins): 12
 Intermediate Duration (mins): 0
 Military Duration (mins): 8
 After Burner Duration (mins): 2

46.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

46.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

- TestCell: Aircraft Engine Test Cell Emissions (TONs)
- TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)
- TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)
- TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)
- TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)
- TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

47. Aircraft

47.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove
- Activity Location
 - County: Bexar
 - Regulatory Area(s): San Antonio, TX
- Activity Title: 2029 T-38 Removal Trim Test and Test Cell
- Activity Description:
- Activity Start Date
 - Start Month: 1
 - Start Year: 2029
- Activity End Date
 - Indefinite: No
 - End Month: 12
 - End Year: 2029

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	-1.218915
SO _x	-0.298031
NO _x	-0.868944
CO	-15.478080
PM 10	-0.327361

Pollutant	Total Emissions (TONs)
PM 2.5	-0.121670
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-900.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	-0.575931
SO _x	-0.149436
NO _x	-0.425465
CO	-7.599904
PM 10	-0.159006

Pollutant	Total Emissions (TONs)
PM 2.5	-0.054296
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-451.7

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	-0.642984

Pollutant	Total Emissions (TONs)
PM 2.5	-0.067374

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

SO _x	-0.148595
NO _x	-0.443479
CO	-7.878176
PM 10	-0.168354

Pb	0.000000
NH ₃	0.000000
CO _{2e}	-449.1

47.2 Aircraft & Engines

47.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

47.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

47.3 Flight Operations

47.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 63
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 3

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 12.8
 Takeoff [Military] (mins): 0.2
 Takeoff [After Burn] (mins): 0.2
 Climb Out [Intermediate] (mins): 0.9
 Approach [Approach] (mins): 3.8
 Taxi/Idle In [Idle] (mins): 6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

47.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

47.4 Auxiliary Power Unit (APU)

47.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

47.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

47.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

47.5 Aircraft Engine Test Cell

47.5.1 Aircraft Engine Test Cell Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 128

- Default Settings Used: Yes

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 3 (default)
Idle Duration (mins): 0 (default)
Approach Duration (mins): 12 (default)
Intermediate Duration (mins): 0 (default)
Military Duration (mins): 8 (default)
After Burner Duration (mins): 2 (default)

47.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

47.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$\text{TestCellPS}_{\text{POL}} = (\text{TD} / 60) * (\text{FC} / 1000) * \text{EF} * \text{NE} * \text{ARU} / 2000$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

48. Aircraft

48.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Title: 2030 T-38 Removal Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1
Start Year: 2030

- Activity End Date

Indefinite: No
End Month: 12
End Year: 2030

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	-1.304811
SO _x	-0.319178
NO _x	-0.930428
CO	-16.573633
PM 10	-0.350502

Pollutant	Total Emissions (TONs)
PM 2.5	-0.130190
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-964.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	-0.621640
SO _x	-0.161296
NO _x	-0.459232
CO	-8.203071
PM 10	-0.171626

Pollutant	Total Emissions (TONs)
PM 2.5	-0.058606
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-487.5

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	-0.683171
SO _x	-0.157882
NO _x	-0.471197
CO	-8.370562
PM 10	-0.178876

Pollutant	Total Emissions (TONs)
PM 2.5	-0.071585
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-477.2

48.2 Aircraft & Engines

48.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

48.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

48.3 Flight Operations

48.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	68
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	0
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	3

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	12.8
Takeoff [Military] (mins):	0.2
Takeoff [After Burn] (mins):	0.2
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	3.8
Taxi/Idle In [Idle] (mins):	6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

48.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

48.4 Auxiliary Power Unit (APU)

48.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

48.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

48.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

48.5 Aircraft Engine Test Cell

48.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 136

- Default Settings Used: No

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine):	3
Idle Duration (mins):	0
Approach Duration (mins):	12
Intermediate Duration (mins):	0
Military Duration (mins):	8
After Burner Duration (mins):	2

48.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

48.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

TestCell = TestCellPS_{IDLE} + TestCellPS_{APPROACH} + TestCellPS_{INTERMEDIATE} + TestCellPS_{MILITARY} + TestCellPS_{AFTERBURN}

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

49. Aircraft

49.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2031 T-38 Removal Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1

Start Year: 2031

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.573448
SO _x	-0.384891
NO _x	-1.121987
CO	-19.985852
PM 10	-0.422664

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.156994
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1163.3

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.749624
SO _x	-0.194504
NO _x	-0.553779
CO	-9.891939
PM 10	-0.206961

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.070672
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-587.9

- Activity Emissions [Test Cell part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.823824
SO _x	-0.190387
NO _x	-0.568208
CO	-10.093913
PM 10	-0.215704

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.086323
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-575.4

49.2 Aircraft & Engines

49.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

49.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

49.3 Flight Operations

49.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 82
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 3

- Default Settings Used: No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	12.8
Takeoff [Military] (mins):	0.2
Takeoff [After Burn] (mins):	0.2
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	3.8
Taxi/Idle In [Idle] (mins):	6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

49.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

49.4 Auxiliary Power Unit (APU)

49.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

49.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

49.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU: Number of Auxiliary Power Units
OH: Operation Hours for Each LTO (hour)
LTO: Number of LTOs
EF_{POL}: Emission Factor for Pollutant (lb/hr)
2000: Conversion Factor pounds to tons

49.5 Aircraft Engine Test Cell

49.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 164

- **Default Settings Used:** No

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine):	3
Idle Duration (mins):	0
Approach Duration (mins):	12
Intermediate Duration (mins):	0
Military Duration (mins):	8
After Burner Duration (mins):	2

49.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

49.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$\text{TestCellPS}_{\text{POL}} = (\text{TD} / 60) * (\text{FC} / 1000) * \text{EF} * \text{NE} * \text{ARU} / 2000$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

50. Personnel

50.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add
- Activity Location
 - County: Bexar
 - Regulatory Area(s): San Antonio, TX
- Activity Title: 2023 Increase 303 Personnel INDEFINITE
- Activity Description:
- Activity Start Date
 - Start Month: 1
 - Start Year: 2023
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.620085
SO _x	0.004562
NO _x	0.528932
CO	7.305354
PM 10	0.013181

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.011378
Pb	0.000000
NH ₃	0.041964
CO ₂ e	668.7

50.2 Personnel Assumptions

- Number of Personnel
 - Active Duty Personnel: 303
 - Civilian Personnel: 0
 - Support Contractor Personnel: 0
 - Air National Guard (ANG) Personnel: 0
 - Reserve Personnel: 0
- Default Settings Used: Yes
- Average Personnel Round Trip Commute (mile): 20 (default)
- Personnel Work Schedule
 - Active Duty Personnel: 5 Days Per Week (default)
 - Civilian Personnel: 5 Days Per Week (default)
 - Support Contractor Personnel: 5 Days Per Week (default)
 - Air National Guard (ANG) Personnel: 4 Days Per Week (default)
 - Reserve Personnel: 4 Days Per Month (default)

50.3 Personnel On Road Vehicle Mixture

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- On Road Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	37.55	60.32	0	0.03	0.2	0	1.9
GOVs	54.49	37.73	4.67	0	0	3.11	0

50.4 Personnel Emission Factor(s)

- On Road Vehicle Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
LDGV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859
LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HDCV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007
LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

50.5 Personnel Formula(s)

- Personnel Vehicle Miles Travel for Work Days per Year

$$VMT_p = NP * WD * AC$$

VMT_p: Personnel Vehicle Miles Travel (miles/year)
 NP: Number of Personnel
 WD: Work Days per Year
 AC: Average Commute (miles)

- Total Vehicle Miles Travel per Year

$$VMT_{Total} = VMT_{AD} + VMT_C + VMT_{SC} + VMT_{ANG} + VMT_{AFRC}$$

VMT_{Total}: Total Vehicle Miles Travel (miles)
 VMT_{AD}: Active Duty Personnel Vehicle Miles Travel (miles)
 VMT_C: Civilian Personnel Vehicle Miles Travel (miles)
 VMT_{SC}: Support Contractor Personnel Vehicle Miles Travel (miles)
 VMT_{ANG}: Air National Guard Personnel Vehicle Miles Travel (miles)
 VMT_{AFRC}: Reserve Personnel Vehicle Miles Travel (miles)

- Vehicle Emissions per Year

$$V_{POL} = (VMT_{Total} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
 VMT_{Total}: Total Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL}: Emission Factor for Pollutant (grams/mile)
 VM: Personnel On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

51. Heating

51.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Location

County: Bexar
Regulatory Area(s): San Antonio, TX

- Activity Title: 2023 Heating for Buildings INDEFINITE

- Activity Description:

- Activity Start Date

Start Month: 1
Start Year: 2023

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.028510
SO _x	0.003110
NO _x	0.518357
CO	0.435420
PM 10	0.039395

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.039395
Pb	0.000000
NH ₃	0.000000
CO _{2e}	624.0

51.2 Heating Assumptions

- Heating

Heating Calculation Type: Heat Energy Requirement Method

- Heat Energy Requirement Method

Area of floorspace to be heated (ft²): 100885
Type of fuel: Natural Gas
Type of boiler/furnace: Industrial (10 - 250 MMBtu/hr)
Heat Value (MMBtu/ft³): 0.00105
Energy Intensity (MMBtu/ft²): 0.1079

- Default Settings Used: Yes

- Boiler/Furnace Usage

Operating Time Per Year (hours): 900 (default)

51.3 Heating Emission Factor(s)

- Heating Emission Factors (lb/1000000 scf)

VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
5.5	0.6	100	84	7.6	7.6			120390

51.4 Heating Formula(s)

- Heating Fuel Consumption ft³ per Year

$$FC_{HER} = HA * EI / HV / 1000000$$

FC_{HER}: Fuel Consumption for Heat Energy Requirement Method

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

HA: Area of floorspace to be heated (ft²)
EI: Energy Intensity Requirement (MMBtu/ft²)
HV: Heat Value (MMBTU/ft³)
1000000: Conversion Factor

- Heating Emissions per Year

$$HE_{POL} = FC * EF_{POL} / 2000$$

HE_{POL}: Heating Emission Emissions (TONs)
FC: Fuel Consumption
EF_{POL}: Emission Factor for Pollutant
2000: Conversion Factor pounds to tons

52. Construction / Demolition

52.1 General Information & Timeline Assumptions

- Activity Location

County: Bexar
Regulatory Area(s): San Antonio, TX

- Activity Title: Construction and Demolition

- Activity Description:

- Activity Start Date

Start Month: 1
Start Month: 2022

- Activity End Date

Indefinite: False
End Month: 12
End Month: 2022

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.526940
SO _x	0.005198
NO _x	2.123360
CO	2.303931
PM 10	3.635660

Pollutant	Total Emissions (TONs)
PM 2.5	0.094714
Pb	0.000000
NH ₃	0.001988
CO ₂ e	506.5

52.1 Site Grading Phase

52.1.1 Site Grading Phase Timeline Assumptions

- Phase Start Date

Start Month: 1
Start Quarter: 1
Start Year: 2022

- Phase Duration

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Month: 1
 Number of Days: 0

52.1.2 Site Grading Phase Assumptions

- General Site Grading Information

Area of Site to be Graded (ft²): 322910
 Amount of Material to be Hauled On-Site (yd³): 0
 Amount of Material to be Hauled Off-Site (yd³): 0

- Site Grading Default Settings

Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Graders Composite	1	8
Other Construction Equipment Composite	1	8
Rubber Tired Dozers Composite	1	8
Tractors/Loaders/Backhoes Composite	2	7

- Vehicle Exhaust

Average Hauling Truck Capacity (yd³): 20 (default)
 Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

52.1.3 Site Grading Phase Emission Factor(s)

- Construction Exhaust Emission Factors (lb/hour) (default)

Graders Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0806	0.0014	0.4657	0.5731	0.0217	0.0217	0.0072	132.92
Other Construction Equipment Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0507	0.0012	0.2785	0.3488	0.0105	0.0105	0.0045	122.61
Rubber Tired Dozers Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.1919	0.0024	1.3611	0.7352	0.0536	0.0536	0.0173	239.51
Tractors/Loaders/Backhoes Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0383	0.0007	0.2301	0.3598	0.0095	0.0095	0.0034	66.884

- Vehicle Exhaust & Worker Trips Emission Factors (grams/mile)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
LDGV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859
LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HDGV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007
LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

52.1.4 Site Grading Phase Formula(s)

- Fugitive Dust Emissions per Phase

$$PM10_{FD} = (20 * ACRE * WD) / 2000$$

PM10_{FD}: Fugitive Dust PM 10 Emissions (TONs)

20: Conversion Factor Acre Day to pounds (20 lb / 1 Acre Day)

ACRE: Total acres (acres)

WD: Number of Total Work Days (days)

2000: Conversion Factor pounds to tons

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * EF_{POL}) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)

NE: Number of Equipment

WD: Number of Total Work Days (days)

H: Hours Worked per Day (hours)

EF_{POL}: Emission Factor for Pollutant (lb/hour)

2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = (HA_{OnSite} + HA_{OffSite}) * (1 / HC) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

HA_{OnSite}: Amount of Material to be Hauled On-Site (yd³)

HA_{OffSite}: Amount of Material to be Hauled Off-Site (yd³)

HC: Average Hauling Truck Capacity (yd³)

(1 / HC): Conversion Factor cubic yards to trips (1 trip / HC yd³)

HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Vehicle Exhaust On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)

WD: Number of Total Work Days (days)

WT: Average Worker Round Trip Commute (mile)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1.25: Conversion Factor Number of Construction Equipment to Number of Works

NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)

VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL} : Emission Factor for Pollutant (grams/mile)

VM: Worker Trips On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

52.2 Trenching/Excavating Phase

52.2.1 Trenching / Excavating Phase Timeline Assumptions

- Phase Start Date

Start Month: 2

Start Quarter: 1

Start Year: 2022

- Phase Duration

Number of Month: 1

Number of Days: 0

52.2.2 Trenching / Excavating Phase Assumptions

- General Trenching/Excavating Information

Area of Site to be Trenched/Excavated (ft²): 33000

Amount of Material to be Hauled On-Site (yd³): 0

Amount of Material to be Hauled Off-Site (yd³): 0

- Trenching Default Settings

Default Settings Used: Yes

Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Excavators Composite	2	8
Other General Industrial Equipmen Composite	1	8
Tractors/Loaders/Backhoes Composite	1	8

- Vehicle Exhaust

Average Hauling Truck Capacity (yd³): 20 (default)

Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HdGV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

	LDGV	LDGT	HdGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

52.2.3 Trenching / Excavating Phase Emission Factor(s)

- Construction Exhaust Emission Factors (lb/hour) (default)

Graders Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0806	0.0014	0.4657	0.5731	0.0217	0.0217	0.0072	132.92
Other Construction Equipment Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0507	0.0012	0.2785	0.3488	0.0105	0.0105	0.0045	122.61
Rubber Tired Dozers Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.1919	0.0024	1.3611	0.7352	0.0536	0.0536	0.0173	239.51
Tractors/Loaders/Backhoes Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0383	0.0007	0.2301	0.3598	0.0095	0.0095	0.0034	66.884

- Vehicle Exhaust & Worker Trips Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
LDGV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859
LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HdGV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007
LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

52.2.4 Trenching / Excavating Phase Formula(s)

- Fugitive Dust Emissions per Phase

$$PM10_{FD} = (20 * ACRE * WD) / 2000$$

PM10_{FD}: Fugitive Dust PM 10 Emissions (TONs)

20: Conversion Factor Acre Day to pounds (20 lb / 1 Acre Day)

ACRE: Total acres (acres)

WD: Number of Total Work Days (days)

2000: Conversion Factor pounds to tons

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * EF_{POL}) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)

NE: Number of Equipment

WD: Number of Total Work Days (days)

H: Hours Worked per Day (hours)

EF_{POL}: Emission Factor for Pollutant (lb/hour)

2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = (HA_{OnSite} + HA_{OffSite}) * (1 / HC) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

HA_{OnSite}: Amount of Material to be Hauled On-Site (yd³)
HA_{OffSite}: Amount of Material to be Hauled Off-Site (yd³)
HC: Average Hauling Truck Capacity (yd³)
(1 / HC): Conversion Factor cubic yards to trips (1 trip / HC yd³)
HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)
0.002205: Conversion Factor grams to pounds
EF_{POL}: Emission Factor for Pollutant (grams/mile)
VM: Vehicle Exhaust On Road Vehicle Mixture (%)
2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)
WD: Number of Total Work Days (days)
WT: Average Worker Round Trip Commute (mile)
1.25: Conversion Factor Number of Construction Equipment to Number of Works
NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
VMT_{VE}: Worker Trips Vehicle Miles Travel (miles)
0.002205: Conversion Factor grams to pounds
EF_{POL}: Emission Factor for Pollutant (grams/mile)
VM: Worker Trips On Road Vehicle Mixture (%)
2000: Conversion Factor pounds to tons

52.3 Building Construction Phase

52.3.1 Building Construction Phase Timeline Assumptions

- Phase Start Date

Start Month: 3
Start Quarter: 1
Start Year: 2022

- Phase Duration

Number of Month: 10
Number of Days: 0

52.3.2 Building Construction Phase Assumptions

- General Building Construction Information

Building Category: Office or Industrial
Area of Building (ft²): 101000
Height of Building (ft): 12
Number of Units: N/A

- Building Construction Default Settings

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Cranes Composite	1	6
Forklifts Composite	2	6
Generator Sets Composite	1	8
Tractors/Loaders/Backhoes Composite	1	8
Welders Composite	3	8

- Vehicle Exhaust

Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

- Vendor Trips

Average Vendor Round Trip Commute (mile): 40 (default)

- Vendor Trips Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

52.3.3 Building Construction Phase Emission Factor(s)

- Construction Exhaust Emission Factors (lb/hour) (default)

Cranes Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0797	0.0013	0.5505	0.3821	0.0203	0.0203	0.0071	128.81
Forklifts Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0274	0.0006	0.1265	0.2146	0.0043	0.0043	0.0024	54.457
Generator Sets Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0340	0.0006	0.2783	0.2694	0.0116	0.0116	0.0030	61.069
Tractors/Loaders/Backhoes Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0383	0.0007	0.2301	0.3598	0.0095	0.0095	0.0034	66.884
Welders Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0260	0.0003	0.1557	0.1772	0.0077	0.0077	0.0023	25.661

- Vehicle Exhaust & Worker Trips Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
--	-----	-----------------	-----------------	----	-------	--------	----	-----------------	------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

LDGV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859
LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HDGV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007
LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

52.3.4 Building Construction Phase Formula(s)

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * EF_{POL}) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)

NE: Number of Equipment

WD: Number of Total Work Days (days)

H: Hours Worked per Day (hours)

EF_{POL}: Emission Factor for Pollutant (lb/hour)

2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = BA * BH * (0.42 / 1000) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

BA: Area of Building (ft²)

BH: Height of Building (ft)

(0.42 / 1000): Conversion Factor ft³ to trips (0.42 trip / 1000 ft³)

HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Worker Trips On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)

WD: Number of Total Work Days (days)

WT: Average Worker Round Trip Commute (mile)

1.25: Conversion Factor Number of Construction Equipment to Number of Works

NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Worker Trips On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Vender Trips Emissions per Phase

$$VMT_{VT} = BA * BH * (0.38 / 1000) * HT$$

- VMT_{VT}: Vender Trips Vehicle Miles Travel (miles)
- BA: Area of Building (ft²)
- BH: Height of Building (ft)
- (0.38 / 1000): Conversion Factor ft³ to trips (0.38 trip / 1000 ft³)
- HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VT} * 0.002205 * EF_{POL} * VM) / 2000$$

- V_{POL}: Vehicle Emissions (TONs)
- VMT_{VT}: Vender Trips Vehicle Miles Travel (miles)
- 0.002205: Conversion Factor grams to pounds
- EF_{POL}: Emission Factor for Pollutant (grams/mile)
- VM: Worker Trips On Road Vehicle Mixture (%)
- 2000: Conversion Factor pounds to tons

52.4 Architectural Coatings Phase

52.4.1 Architectural Coatings Phase Timeline Assumptions

- Phase Start Date

Start Month: 12
 Start Quarter: 1
 Start Year: 2022

- Phase Duration

Number of Month: 1
 Number of Days: 0

52.4.2 Architectural Coatings Phase Assumptions

- General Architectural Coatings Information

Building Category: Non-Residential
 Total Square Footage (ft²): 15200
 Number of Units: N/A

- Architectural Coatings Default Settings

Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

52.4.3 Architectural Coatings Phase Emission Factor(s)

- Worker Trips Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
LDGV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HDGV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007
LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

52.4.4 Architectural Coatings Phase Formula(s)

- Worker Trips Emissions per Phase

$$VMT_{WT} = (1 * WT * PA) / 800$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)

1: Conversion Factor man days to trips (1 trip / 1 man * day)

WT: Average Worker Round Trip Commute (mile)

PA: Paint Area (ft²)

800: Conversion Factor square feet to man days (1 ft² / 1 man * day)

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Worker Trips On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

- Off-Gassing Emissions per Phase

$$VOC_{AC} = (AB * 2.0 * 0.0116) / 2000.0$$

VOC_{AC}: Architectural Coating VOC Emissions (TONs)

BA: Area of Building (ft²)

2.0: Conversion Factor total area to coated area (2.0 ft² coated area / total area)

0.0116: Emission Factor (lb/ft²)

2000: Conversion Factor pounds to tons

52.5 Paving Phase

52.5.1 Paving Phase Timeline Assumptions

- Phase Start Date

Start Month: 12

Start Quarter: 1

Start Year: 2022

- Phase Duration

Number of Month: 1

Number of Days: 0

52.5.2 Paving Phase Assumptions

- General Paving Information

Paving Area (ft²): 244000

- Paving Default Settings

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Pavers Composite	1	8
Paving Equipment Composite	2	6
Rollers Composite	2	6

- Vehicle Exhaust

Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

52.5.3 Paving Phase Emission Factor(s)

- Construction Exhaust Emission Factors (lb/hour) (default)

Graders Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0806	0.0014	0.4657	0.5731	0.0217	0.0217	0.0072	132.92
Other Construction Equipment Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0507	0.0012	0.2785	0.3488	0.0105	0.0105	0.0045	122.61
Rubber Tired Dozers Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.1919	0.0024	1.3611	0.7352	0.0536	0.0536	0.0173	239.51
Tractors/Loaders/Backhoes Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0383	0.0007	0.2301	0.3598	0.0095	0.0095	0.0034	66.884

- Vehicle Exhaust & Worker Trips Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
LDGV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859
LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HDCV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007
LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

52.5.4 Paving Phase Formula(s)

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * EF_{POL}) / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

CEE_{POL}: Construction Exhaust Emissions (TONs)

NE: Number of Equipment

WD: Number of Total Work Days (days)

H: Hours Worked per Day (hours)

EF_{POL}: Emission Factor for Pollutant (lb/hour)

2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = PA * 0.25 * (1 / 27) * (1 / HC) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

PA: Paving Area (ft²)

0.25: Thickness of Paving Area (ft)

(1 / 27): Conversion Factor cubic feet to cubic yards (1 yd³ / 27 ft³)

HC: Average Hauling Truck Capacity (yd³)

(1 / HC): Conversion Factor cubic yards to trips (1 trip / HC yd³)

HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Vehicle Exhaust On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)

WD: Number of Total Work Days (days)

WT: Average Worker Round Trip Commute (mile)

1.25: Conversion Factor Number of Construction Equipment to Number of Works

NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{VE}: Worker Trips Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Worker Trips On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

- Off-Gassing Emissions per Phase

$$VOC_P = (2.62 * PA) / 43560$$

VOC_P: Paving VOC Emissions (TONs)

2.62: Emission Factor (lb/acre)

PA: Paving Area (ft²)

43560: Conversion Factor square feet to acre (43560 ft² / acre)² / acre)

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF CONFORMITY ANALYSIS (ROCA)

1. General Information: The Air Force's Air Conformity Applicability Model (ACAM) was used to perform an analysis to assess the potential air quality impact/s associated with the action in accordance with the Air Force Manual 32-7002, Environmental Compliance and Pollution Prevention; the Environmental Impact Analysis Process (EIAP, 32 CFR 989); and the General Conformity Rule (GCR, 40 CFR 93 Subpart B). This report provides a summary of the ACAM analysis.

a. Action Location:

Base: RANDOLPH AFB
State: Texas
County(s): Bexar
Regulatory Area(s): San Antonio, TX

b. Action Title: Recapitalization of the T-38 Trainer At Randolph AFB - Alternative 1 (Bexar County and Guadalupe County ROIs)

c. Project Number/s (if applicable):

d. Projected Action Start Date: 1 / 2022

e. Action Description:

The proposed action encompasses the recapitalize of the T-38 flight-training program with newer and more capable T-7A aircraft at JBSA-Randolph and Lackland. In addition to the phased introduction of the T-7A aircraft, five military construction projects and 17 facilities sustainment, restoration, and modernization projects are proposed at JBSA-Randolph at JBSA-Lackland to provide modern facilities and infrastructure to support the T-7A aircraft's maintenance, training, and operational requirements. The number of personnel on JBSA-Randolph would increase due to the proposed aircraft recapitalization. No changes to airspace configurations (i.e., size, shape, or location) would be required to support the proposed operations of the T-7A aircraft; however, the T-7A aircraft may have more flight operations than occurs with the T 38C aircraft at both JBSA-Randolph and JBSA-Lackland. This Applicability Analysis present the worst-case of three aircraft operational intensities as the worst-case action alternatives for the Proposed Action.

A Conformity Evaluation is required for every proposed action that will occur within an area designated by the U.S. Environmental Protection Agency (EPA) as nonattainment or maintenance for any National Ambient Air Quality Standard (NAAQS). The proposed T-7A Recapitalization action will occur at both JBSA-Randolph AFB and JBSA-Lackland AFB which both fall entirely within Bexar County that has been designated by the U.S. Environmental Protection Agency (EPA) as a marginal nonattainment area for the 2015 Ozone NAAQS in 2018. Given this recent designation of Bexar County, the proposed action (as well as all proposed actions from federal agencies) are subject to the General Conformity Rule (GCR, 40 CFR 93 Subpart B). As a marginal nonattainment area for ozone, the GCR has established de minimis significance threshold values of less than 100 ton/yr (for any given year) for both nitrogen oxides (NO_x) and volatile organic compounds (VOC).

f. Point of Contact:

Name: [REDACTED]
Title: NEPA Contract Support
Organization: [REDACTED]

2. Analysis: Total combined direct and indirect emissions associated with the action were estimated through ACAM on a calendar-year basis for the "worst-case" and "steady state" (net gain/loss upon action fully implemented) emissions. General Conformity under the Clean Air Act, Section 1.76 has been evaluated for the action described above according to the requirements of 40 CFR 93, Subpart B. Based on the analysis, the requirements of this rule are not applicable. None of estimated emissions associated with this action are above the conformity threshold values established at 40 CFR 93.153 (b); Therefore, the requirements of the General Conformity Rule are not applicable.

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF CONFORMITY ANALYSIS (ROCA)

Conformity Analysis Summary:

2022

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	0.527	100	No
NO _x	2.123	100	No
CO	2.304		
SO _x	0.005		
PM 10	3.636		
PM 2.5	0.095		
Pb	0.000		
NH ₃	0.002		
CO _{2e}	506.5		

2023

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	4.579	100	No
NO _x	7.911	100	No
CO	28.479		
SO _x	0.471		
PM 10	0.425		
PM 2.5	0.384		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	2523.3		

2024

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	11.408	100	No
NO _x	20.089	100	No
CO	64.406		
SO _x	1.347		
PM 10	1.059		
PM 2.5	0.952		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	4891.2		

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF CONFORMITY ANALYSIS (ROCA)

2025

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	15.361	100	No
NO _x	43.552	100	No
CO	18.766		
SO _x	2.036		
PM 10	-0.706		
PM 2.5	-0.129		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	6699.1		

2026

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	23.374	100	No
NO _x	67.005	100	No
CO	24.380		
SO _x	3.169		
PM 10	-1.135		
PM 2.5	-0.238		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	9732.4		

2027

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	31.381	100	No
NO _x	99.465	100	No
CO	-30.596		
SO _x	4.186		
PM 10	-3.461		
PM 2.5	-1.645		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	12412.3		

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF CONFORMITY ANALYSIS (ROCA)

2028

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	-10.518	100	No
NO _x	99.433	100	No
CO	-540.857		
SO _x	-0.323		
PM 10	-16.707		
PM 2.5	-11.261		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	1.8		

2029 - (Steady State)

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	-10.518	100	No
NO _x	99.433	100	No
CO	-540.857		
SO _x	-0.323		
PM 10	-16.707		
PM 2.5	-11.261		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	1.8		

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1. General Information

- Action Location

Base: RANDOLPH AFB
State: Texas
County(s): Bexar
Regulatory Area(s): San Antonio, TX

- Action Title: Recapitalization of the T-38 Trainer At Randolph AFB - Alternative 1

- Project Number/s (if applicable):

- Projected Action Start Date: 1 / 2022

- Action Purpose and Need:

The T 38 Talon is a twin-engine, high-altitude, supersonic jet used by the USAF and other nations for pilot training. The aircraft originally was developed in the 1950s with production occurring between 1961 and 1972. The fleet has undergone periodic upgrades overtime. In 2001, the USAF upgraded several hundred T 38s with modern avionics and replaced propulsion components to provide increased performance and superior reliability.

The purpose of the Proposed Action is to allow the USAF T-7A to provide more efficient and effective pilot training to establish a T-7A pilot pipeline to allow for the transition to T-7A training throughout the entire USAF.

- Action Description:

The proposed action encompasses the recapitalize of the T-38 flight-training program with newer and more capable T-7A aircraft at JBSA-Randolph and Lackland. In addition to the phased introduction of the T-7A aircraft, five military construction projects and 17 facilities sustainment, restoration, and modernization projects are proposed at JBSA-Randolph at JBSA-Lackland to provide modern facilities and infrastructure to support the T-7A aircraft's maintenance, training, and operational requirements. The number of personnel on JBSA-Randolph would increase due to the proposed aircraft recapitalization. No changes to airspace configurations (i.e., size, shape, or location) would be required to support the proposed operations of the T-7A aircraft; however, the T-7A aircraft may have more flight operations than occurs with the T 38C aircraft at both JBSA-Randolph and JBSA-Lackland. This Applicability Analysis present the worst-case of three aircraft operational intensities as the worst-case action alternatives for the Proposed Action.

A Conformity Evaluation is required for every proposed action that will occur within an area designated by the U.S. Environmental Protection Agency (EPA) as nonattainment or maintenance for any National Ambient Air Quality Standard (NAAQS). The proposed T-7A Recapitalization action will occur at both JBSA-Randolph AFB and JBSA-Lackland AFB which both fall entirely within Bexar County that has been designated by the U.S. Environmental Protection Agency (EPA) as a marginal nonattainment area for the 2015 Ozone NAAQS in 2018. Given this recent designation of Bexar County, the proposed action (as well as all proposed actions from federal agencies) are subject to the General Conformity Rule (GCR, 40 CFR 93 Subpart B). As a marginal nonattainment area for ozone, the GCR has established de minimis significance threshold values of less than 100 ton/yr (for any given year) for both nitrogen oxides (NOx) and volatile organic compounds (VOC).

- Point of Contact

Name: [REDACTED]
Title: NEPA Contract Support
Organization: [REDACTED]
Email:
Phone Number:

- Activity List:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Activity Type		Activity Title
2.	Aircraft	T-7As and 759 LTOs
3.	Aircraft	T-7A Increase 1,700 TGOs
4.	Aircraft	T-38 Removal 5 TGOs
5.	Aircraft	Add 10 T-7As and 1328LTOs
6.	Aircraft	Increase T-7A TGOs
7.	Aircraft	Remove 11 T-38s and 2776LTOs
8.	Aircraft	Remove 6142 T-38 TGOs
9.	Aircraft	Add 7 new T-7As and 2836 LTOs
10.	Aircraft	Increase T-7A TGOs by 6395
11.	Aircraft	Remove 7 T-38s and reduce LTOs by 1534
12.	Aircraft	Decrease T-38 TGOs by 3394
13.	Aircraft	Add T-7As and increase LTOs by 2698
14.	Aircraft	Increase T-7A TGOs by 6040
15.	Aircraft	Remove T-38s and decrease LTOs by 3767
16.	Aircraft	Decrease T-38 TGOs by 8,328
17.	Aircraft	Add 19 new T-7As and increase LTOs by 3927
18.	Aircraft	Increase T-7A TGOs by 8719
19.	Aircraft	Remove 21 T-38s and decrease LTOs by 12407
20.	Aircraft	Decrease T-38 TGOs by 27396
21.	Aircraft	Add T-7As and increase LTOs by 1012
22.	Aircraft	2023 T-7A Increase Trim Test and Test Cell
23.	Aircraft	2024 T-7A Increase Trim Test and Engine Test Cell
24.	Aircraft	2025 T-38 Removal Trim Test and Test Cell
25.	Aircraft	2025 T-7A Increase Trim Test and Test Cell
26.	Aircraft	2026 T-38 Removal Trim Test and Test Cell
27.	Aircraft	2026 T-7A Increase Trim Test and Engine Test Cell
28.	Aircraft	2027 T-38 Removal Trim Test and Test Cell
29.	Aircraft	2027 T-7A Increase Trim Test and Test Cell
30.	Aircraft	2028 T-38 Removal Trim Test and Test Cell
31.	Aircraft	2028 T-7A Increase Trim Test and Test Cell
32.	Personnel	2023 Increase 303 Personnel INDEFINITE
33.	Heating	2023 Heating for Buildings INDEFINITE
34.	Construction / Demolition	Construction and Demolition
35.	Aircraft	Starting in 2028, add T-7As and increase TGOs by 2276

Emission factors and air emission estimating methods come from the United States Air Force's Air Emissions Guide for Air Force Stationary Sources, Air Emissions Guide for Air Force Mobile Sources, and Air Emissions Guide for Air Force Transitory Sources.

2. Aircraft

2.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

 County: Bexar

 Regulatory Area(s): San Antonio, TX

- Activity Title: T-7As and 759 LTOs

- Activity Description:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Starting in 2023 add 8 T-7As, and increase 759 LTOs

- Activity Start Date

Start Month: 1
Start Year: 2023

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	3.503273
SO _x	0.251578
NO _x	2.428146
CO	18.804690
PM 10	0.316361

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.283894
Pb	0.000000
NH ₃	0.000000
CO _{2e}	591.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	3.503273
SO _x	0.251578
NO _x	2.428146
CO	18.804690
PM 10	0.316361

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.283894
Pb	0.000000
NH ₃	0.000000
CO _{2e}	591.2

2.2 Aircraft & Engines

2.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

2.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

2.3 Flight Operations

2.3.1 Flight Operations Assumptions

- Flight Operations

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Aircraft:	8
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	759
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- **Default Settings Used:** No

- **Flight Operations TIMs (Time In Mode)**

Taxi/Idle Out [Idle] (mins):	9.74
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- **Trim Test**

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

2.3.2 Flight Operations Formula(s)

- **Aircraft Emissions per Mode for LTOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- **Aircraft Emissions for LTOs per Year**

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- **Aircraft Emissions per Mode for TGOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TIM: Time in Mode (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

2.4 Auxiliary Power Unit (APU)

2.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

2.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

2.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

3. Aircraft

3.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: T-7A Increase 1,700 TGOs

- Activity Description:

Starting in 2023 add 10 new T-7As, and increase 1,700TGOs

- Activity Start Date

Start Month: 1

Start Year: 2023

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.342560
SO _x	0.184015
NO _x	3.965532
CO	0.483172
PM 10	0.023088

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.019985
Pb	0.000000
NH ₃	0.000000
CO _{2e}	556.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.342560
SO _x	0.184015
NO _x	3.965532
CO	0.483172

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.019985
Pb	0.000000
NH ₃	0.000000
CO _{2e}	556.2

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

PM 10	0.023088
-------	----------

--	--

3.2 Aircraft & Engines

3.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

3.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

3.3 Flight Operations

3.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 10
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1700
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.64
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.47
Approach [Approach] (mins): 0.98
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

3.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

3.4 Auxiliary Power Unit (APU)

3.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

3.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

3.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

4. Aircraft

4.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

- Activity Title: T-38 Removal 5 TGOs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Description:

Starting in 2024, remove 5 T-38 TGOs

- Activity Start Date

Start Month: 1

Start Year: 2024

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.000748
SO _x	-0.000244
NO _x	-0.000314
CO	-0.013707
PM 10	-0.000401

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.000162
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-0.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.000748
SO _x	-0.000244
NO _x	-0.000314
CO	-0.013707
PM 10	-0.000401

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.000162
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-0.7

4.2 Aircraft & Engines

4.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C

Engine Model: J85-GE-5R

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

4.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

4.3 Flight Operations

4.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	91
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	5
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

4.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

4.4 Auxiliary Power Unit (APU)

4.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU	Operation Hours	Exempt	Designation	Manufacturer
---------------	-----------------	--------	-------------	--------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

per Aircraft	for Each LTO	Source?	
--------------	--------------	---------	--

4.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

4.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

5. Aircraft

5.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Add 10 T-7As and 1328LTOs

- Activity Description:

Starting in 2024 add 10 new T-7As, and increase 1328 LTO

- Activity Start Date

Start Month: 1

Start Year: 2024

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	6.129575
SO _x	0.440178
NO _x	4.248455
CO	32.902013
PM 10	0.553528

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.496721
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1034.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Pollutant	Emissions Per Year (TONs)
VOC	6.129575
SO _x	0.440178
NO _x	4.248455
CO	32.902013
PM 10	0.553528

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.496721
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1034.4

5.2 Aircraft & Engines

5.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

5.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

5.3 Flight Operations

5.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 10
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1328
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 9.74
 Takeoff [Military] (mins): 0.41
 Takeoff [After Burn] (mins): 0.39
 Climb Out [Intermediate] (mins): 0.91
 Approach [Approach] (mins): 1.74
 Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

5.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

5.4 Auxiliary Power Unit (APU)

5.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

5.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

5.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

6. Aircraft

6.1 General Information & Timeline Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar
Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs

- Activity Description:

Starting in 2024 Increase T-7A TGOs 2931

- Activity Start Date

Start Month: 1
Start Year: 2024

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.594278
SO _x	0.401530
NO _x	7.342641
CO	1.225067
PM 10	0.039806

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.034457
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1230.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.594278
SO _x	0.401530
NO _x	7.342641
CO	1.225067
PM 10	0.039806

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.034457
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1230.2

6.2 Aircraft & Engines

6.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

6.2.2 Aircraft & Engines Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

6.3 Flight Operations

6.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	10
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	2931
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

6.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

6.4 Auxiliary Power Unit (APU)

6.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

6.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

6.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

7. Aircraft

7.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Remove 11 T-38s and 2776LTOs

- Activity Description:

Starting in 2025 remove T-38s and 2776 LTOs

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-9.419282
SO _x	-0.807853
NO _x	-1.532868

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.028236
Pb	0.000000
NH ₃	0.000000

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

CO	-100.821859
PM 10	-2.523479

CO _{2e}	-2122.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-9.419282
SO _x	-0.807853
NO _x	-1.532868
CO	-100.821859
PM 10	-2.523479

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.028236
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2122.2

7.2 Aircraft & Engines

7.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

7.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

7.3 Flight Operations

7.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 11
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 2776
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 12.8
 Takeoff [Military] (mins): 0.41
 Takeoff [After Burn] (mins): 0.39
 Climb Out [Intermediate] (mins): 0.91

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Approach [Approach] (mins): 1.74
Taxi/Idle In [Idle] (mins): 6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

7.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AE_{TCO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

7.4 Auxiliary Power Unit (APU)

7.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

7.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

7.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

8. Aircraft

8.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Remove 6142 T-38 TGOs

- Activity Description:

Starting in 2025, remove 6142 T-38 TGOs

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.918521
SO _x	-0.300318
NO _x	-0.385904
CO	-16.838007
PM 10	-0.492938

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.198506
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-907.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.918521
SO _x	-0.300318
NO _x	-0.385904
CO	-16.838007
PM 10	-0.492938

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.198506
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-907.7

8.2 Aircraft & Engines

8.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C

Engine Model: J85-GE-5R

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 2

- Aircraft & Engine Surrogate

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

8.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

8.3 Flight Operations

8.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 11
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 6142
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.64
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.47
 Approach [Approach] (mins): 0.98
 Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
 Approach (mins): 27
 Intermediate (mins): 9
 Military (mins): 9
 AfterBurn (mins): 3

8.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
 TIM: Time in Mode (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

8.4 Auxiliary Power Unit (APU)

8.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

8.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

8.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

9. Aircraft

9.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Add 7 new T-7As and 2836 LTOs

- Activity Description:

Starting in 2025, add 7 new T-7As and 2836 LTOs

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	13.089965
SO _x	0.940019
NO _x	9.072755
CO	70.263637
PM 10	1.182083

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.060768
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2209.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	13.089965
SO _x	0.940019
NO _x	9.072755
CO	70.263637
PM 10	1.182083

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.060768
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2209.0

9.2 Aircraft & Engines

9.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

9.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

9.3 Flight Operations

9.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 7
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 2836
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Taxi/Idle Out [Idle] (mins):	9.74
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

9.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

9.4 Auxiliary Power Unit (APU)

9.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

9.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

9.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

10. Aircraft

10.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

 County: Bexar

 Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs by 6395

- Activity Description:

 Starting in 2025, increase T-7A TGOs by 6395

- Activity Start Date

 Start Month: 1

 Start Year: 2025

- Activity End Date

 Indefinite: Yes

 End Month: N/A

 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.296625
SO _x	0.876078
NO _x	16.020536
CO	2.672911
PM 10	0.086851

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.075180
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2684.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.296625
SO _x	0.876078
NO _x	16.020536
CO	2.672911
PM 10	0.086851

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.075180
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2684.1

10.2 Aircraft & Engines

10.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- **Aircraft & Engine Surrogate**
Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

10.2.2 Aircraft & Engines Emission Factor(s)

- **Aircraft & Engine Emissions Factors (lb/1000lb fuel)**
Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

10.3 Flight Operations

10.3.1 Flight Operations Assumptions

- **Flight Operations**
Number of Aircraft: 7
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 6395
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0
- **Default Settings Used:** No
- **Flight Operations TIMs (Time In Mode)**
Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.64
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.47
Approach [Approach] (mins): 0.98
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- **Trim Test**
Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

10.3.2 Flight Operations Formula(s)

- **Aircraft Emissions per Mode for LTOs per Year**
 $AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

10.4 Auxiliary Power Unit (APU)

10.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

10.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

10.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs
- EF_{POL}: Emission Factor for Pollutant (lb/hr)
- 2000: Conversion Factor pounds to tons

11. Aircraft

11.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove
- Activity Location
 - County: Bexar
 - Regulatory Area(s): San Antonio, TX
- Activity Title: Remove 7 T-38s and reduce LTOs by 1534
- Activity Description:
 - Starting in 2026, remove 7 T-38s and reduce LTOs by 1534
- Activity Start Date

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Start Month: 1
Start Year: 2026

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-5.205036
SO _x	-0.446415
NO _x	-0.847053
CO	-55.713520
PM 10	-1.394458

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.120790
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1172.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-5.205036
SO _x	-0.446415
NO _x	-0.847053
CO	-55.713520
PM 10	-1.394458

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.120790
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1172.7

11.2 Aircraft & Engines

11.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

11.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

11.3 Flight Operations

11.3.1 Flight Operations Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations

Number of Aircraft:	7
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	1534
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	12.8
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

11.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

11.4 Auxiliary Power Unit (APU)

11.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer

11.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

11.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

12. Aircraft

12.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Decrease T-38 TGOs by 3394

- Activity Description:

Starting in 2026, decrease T-38 TGOs by 3394

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.507564
SO _x	-0.165952
NO _x	-0.213246
CO	-9.304493
PM 10	-0.272392

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.109692
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-501.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.507564
SO _x	-0.165952
NO _x	-0.213246
CO	-9.304493
PM 10	-0.272392

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.109692
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-501.6

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

12.2 Aircraft & Engines

12.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

12.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

12.3 Flight Operations

12.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 6
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3394
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.64
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.47
Approach [Approach] (mins): 0.98
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Military (mins): 9
AfterBurn (mins): 3

12.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

12.4 Auxiliary Power Unit (APU)

12.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

12.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

12.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

13. Aircraft

13.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Regulatory Area(s): San Antonio, TX

- Activity Title: Add T-7As and increase LTOs by 2698

- Activity Description:
Starting in 2026, add T-7As and increase LTOs by 2698

- Activity Start Date
Start Month: 1
Start Year: 2026

- Activity End Date
Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	12.453006
SO _x	0.894277
NO _x	8.631274
CO	66.844602
PM 10	1.124563

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.009151
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2101.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	12.453006
SO _x	0.894277
NO _x	8.631274
CO	66.844602
PM 10	1.124563

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.009151
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2101.5

13.2 Aircraft & Engines

13.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate
Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

13.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)
Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

13.3 Flight Operations

13.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	2698
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	9.74
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

13.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

- AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
- TIM: Time in Mode (min)
- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- TGO: Number of Touch-and-Go Cycles (for all aircraft)
- 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

- AE_{TGO}: Aircraft Emissions (TONs)
- AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
- AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
- AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

- AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
- TD: Test Duration (min)
- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- NA: Number of Aircraft
- NTT: Number of Trim Test
- 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

13.4 Auxiliary Power Unit (APU)

13.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1	0.25	No	4501687C	Hamilton Sundstrand
---	------	----	----------	---------------------

13.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

13.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

14. Aircraft

14.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs by 6040

- Activity Description:

Starting in 2026, increase T-7A TGOs by 6040

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.224647
SO _x	0.827445
NO _x	15.131202
CO	2.524532
PM 10	0.082030

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.071006
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2535.1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.224647
SO _x	0.827445
NO _x	15.131202
CO	2.524532
PM 10	0.082030

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.071006
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2535.1

14.2 Aircraft & Engines

14.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

14.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

14.3 Flight Operations

14.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 19
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 6040
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.64
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.47
 Approach [Approach] (mins): 0.98
 Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

14.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
 AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
 AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
 AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
 AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
 AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

14.4 Auxiliary Power Unit (APU)

14.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

14.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

14.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

15. Aircraft

15.1 General Information & Timeline Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar
Regulatory Area(s): San Antonio, TX

- Activity Title: Remove T-38s and decrease LTOs by 3767

- Activity Description:

Starting in 2027, remove T-38s and decrease LTOs by 3,767

- Activity Start Date

Start Month: 1
Start Year: 2027

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-12.781857
SO _x	-1.096248
NO _x	-2.080085
CO	-136.814100
PM 10	-3.424331

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.752292
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2879.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-12.781857
SO _x	-1.096248
NO _x	-2.080085
CO	-136.814100
PM 10	-3.424331

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.752292
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2879.8

15.2 Aircraft & Engines

15.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

15.2.2 Aircraft & Engines Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

15.3 Flight Operations

15.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	16
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	3767
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	12.8
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

15.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

15.4 Auxiliary Power Unit (APU)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

15.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

15.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

15.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

16. Aircraft

16.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Decrease T-38 TGOs by 8,328

- Activity Description:

Starting in 2027, decrease T-38 TGOs by 8,328

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.245432

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.269156

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

SO _x	-0.407204
NO _x	-0.523251
CO	-22.830824
PM 10	-0.668380

Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1230.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.245432
SO _x	-0.407204
NO _x	-0.523251
CO	-22.830824
PM 10	-0.668380

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.269156
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1230.7

16.2 Aircraft & Engines

16.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

16.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

16.3 Flight Operations

16.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 16
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 8328
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.64

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

16.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

- AE_{TGO}: Aircraft Emissions (TONs)
- AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
- AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
- AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

- AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
- TD: Test Duration (min)
- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- NA: Number of Aircraft
- NTT: Number of Trim Test
- 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

16.4 Auxiliary Power Unit (APU)

16.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

16.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

16.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

17. Aircraft

17.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Add 19 new T-7As and increase LTOs by 3927

- Activity Description:

Starting in 2027, add 19 new T-7As and increase LTOs by 3927

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	20.355508
SO _x	1.337274
NO _x	12.620293
CO	101.582412
PM 10	1.655809

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.485826
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3166.5

- Activity Emissions [Flight Operations (includes Trim Test & APU part)]:

Pollutant	Emissions Per Year (TONs)
VOC	20.355508
SO _x	1.337274
NO _x	12.620293
CO	101.582412
PM 10	1.655809

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.485826
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3166.5

17.2 Aircraft & Engines

17.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

17.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

17.3 Flight Operations

17.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	19
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	3927
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	6.8
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

17.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

17.4 Auxiliary Power Unit (APU)

17.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

17.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

17.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

18. Aircraft

18.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs by 8719

- Activity Description:

Starting in 2027, increase T-7A TGOs by 8719

- Activity Start Date

Start Month: 1

Start Year: 2027

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.767831
SO _x	1.194453
NO _x	21.842542
CO	3.644271
PM 10	0.118414

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.102501
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3659.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.767831
SO _x	1.194453
NO _x	21.842542
CO	3.644271
PM 10	0.118414

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.102501
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3659.5

18.2 Aircraft & Engines

18.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

18.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

18.3 Flight Operations

18.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 19
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 8719
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

18.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

18.4 Auxiliary Power Unit (APU)

18.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

18.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

18.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs
- EF_{POL}: Emission Factor for Pollutant (lb/hr)
- 2000: Conversion Factor pounds to tons

19. Aircraft

19.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove
- Activity Location
 - County: Bexar
 - Regulatory Area(s): San Antonio, TX
- Activity Title: Remove 21 T-38s and decrease LTOs by 12407
- Activity Description:
 - Starting in 2028, remove 21 T-38s and decrease LTOs by 12407
- Activity Start Date
 - Start Month: 1
 - Start Year: 2028
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-42.098355
SO _x	-3.610604
NO _x	-6.850972
CO	-450.611239
PM 10	-11.278386

Pollutant	Emissions Per Year (TONs)
PM 2.5	-9.064956
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-9484.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-42.098355
SO _x	-3.610604
NO _x	-6.850972
CO	-450.611239
PM 10	-11.278386

Pollutant	Emissions Per Year (TONs)
PM 2.5	-9.064956
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-9484.9

19.2 Aircraft & Engines

19.2.1 Aircraft & Engines Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

19.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

19.3 Flight Operations

19.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 21
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 12407
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 12.8
 Takeoff [Military] (mins): 0.41
 Takeoff [After Burn] (mins): 0.39
 Climb Out [Intermediate] (mins): 0.91
 Approach [Approach] (mins): 1.74
 Taxi/Idle In [Idle] (mins): 6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
 Approach (mins): 27
 Intermediate (mins): 9
 Military (mins): 9
 AfterBurn (mins): 3

19.3.2 Flight Operations Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

19.4 Auxiliary Power Unit (APU)

19.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

19.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

19.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

20. Aircraft

20.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

- Activity Title: Decrease T-38 TGOs by 27396

- Activity Description:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Starting in 2028, decrease T-38 TGOs by 27396

- Activity Start Date

Start Month: 1
Start Year: 2028

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-4.097004
SO _x	-1.339549
NO _x	-1.721299
CO	-75.104858
PM 10	-2.198720

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.885422
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-4048.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-4.097004
SO _x	-1.339549
NO _x	-1.721299
CO	-75.104858
PM 10	-2.198720

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.885422
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-4048.7

20.2 Aircraft & Engines

20.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

20.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

20.3 Flight Operations

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

20.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	21
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	27396
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

20.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

20.4 Auxiliary Power Unit (APU)

20.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
-------------------------------	---------------------------------	-------------------	-------------	--------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

20.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

20.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

21. Aircraft

21.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Add T-7As and increase LTOs by 1012

- Activity Description:

Starting in 2028, add T-7As and increase LTOs by 1012

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	4.671031
SO _x	0.335437
NO _x	3.237528
CO	25.072920
PM 10	0.421815

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.378525
Pb	0.000000
NH ₃	0.000000
CO _{2e}	788.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	4.671031

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.378525

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

SO _x	0.335437
NO _x	3.237528
CO	25.072920
PM 10	0.421815

Pb	0.000000
NH ₃	0.000000
CO _{2e}	788.3

21.2 Aircraft & Engines

21.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

21.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

21.3 Flight Operations

21.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1012
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 9.74
Takeoff [Military] (mins): 0.41
Takeoff [After Burn] (mins): 0.39
Climb Out [Intermediate] (mins): 0.91
Approach [Approach] (mins): 1.74
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Military (mins): 9
AfterBurn (mins): 3

21.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

21.4 Auxiliary Power Unit (APU)

21.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

21.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

21.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

22. Aircraft

22.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Location

County: Bexar
Regulatory Area(s): San Antonio, TX

- Activity Title: 2023 T-7A Increase Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1
Start Year: 2023

- Activity End Date

Indefinite: No
End Month: 12
End Year: 2023

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.084558
SO _x	0.027537
NO _x	0.469887
CO	1.450657
PM 10	0.032987

Pollutant	Total Emissions (TONs)
PM 2.5	0.029582
Pb	0.000000
NH ₃	0.000000
CO _{2e}	83.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	0.046147
SO _x	0.015141
NO _x	0.251550
CO	0.731888
PM 10	0.016822

Pollutant	Total Emissions (TONs)
PM 2.5	0.015074
Pb	0.000000
NH ₃	0.000000
CO _{2e}	45.8

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	0.038410
SO _x	0.012396
NO _x	0.218337
CO	0.718770
PM 10	0.016165

Pollutant	Total Emissions (TONs)
PM 2.5	0.014509
Pb	0.000000
NH ₃	0.000000
CO _{2e}	37.5

22.2 Aircraft & Engines

22.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Aircraft Name:

Original Engine Name:

22.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

22.3 Flight Operations

22.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	8
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	0
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	1

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	6.8
Takeoff [Military] (mins):	0.25
Takeoff [After Burn] (mins):	0.25
Climb Out [Intermediate] (mins):	1.4
Approach [Approach] (mins):	4
Taxi/Idle In [Idle] (mins):	4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

22.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

22.4 Auxiliary Power Unit (APU)

22.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

22.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

22.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

22.5 Aircraft Engine Test Cell

22.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 8

- Default Settings Used: No

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 1

Idle Duration (mins): 0

Approach Duration (mins): 12

Intermediate Duration (mins): 0

Military Duration (mins): 8

After Burner Duration (mins): 2

22.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

22.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Total Number of Engines (For All Aircraft)
 ARU: Annual Run-ups (Per Aircraft Engine)
 2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

TestCell: Aircraft Engine Test Cell Emissions (TONs)
 TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)
 TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)
 TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)
 TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)
 TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

23. Aircraft

23.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

- Activity Title: 2024 T-7A Increase Trim Test and Engine Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1
 Start Year: 2024

- Activity End Date

Indefinite: No
 End Month: 12
 End Year: 2024

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.190255
SO _x	0.061958
NO _x	1.057247
CO	3.263979
PM 10	0.074222

Pollutant	Total Emissions (TONs)
PM 2.5	0.066560
Pb	0.000000
NH ₃	0.000000
CO _{2e}	187.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Pollutant	Total Emissions (TONs)
VOC	0.103831
SO _x	0.034068
NO _x	0.565988
CO	1.646748
PM 10	0.037849

Pollutant	Total Emissions (TONs)
PM 2.5	0.033916
Pb	0.000000
NH ₃	0.000000
CO _{2e}	103.0

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	0.086424
SO _x	0.027890
NO _x	0.491259
CO	1.617231
PM 10	0.036372

Pollutant	Total Emissions (TONs)
PM 2.5	0.032645
Pb	0.000000
NH ₃	0.000000
CO _{2e}	84.3

23.2 Aircraft & Engines

23.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

23.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

23.3 Flight Operations

23.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 18
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 1

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 6.8
 Takeoff [Military] (mins): 0.25
 Takeoff [After Burn] (mins): 0.25
 Climb Out [Intermediate] (mins): 1.4

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Approach [Approach] (mins):	4
Taxi/Idle In [Idle] (mins):	4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

23.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AE_{TCO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

23.4 Auxiliary Power Unit (APU)

23.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

23.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

23.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

23.5 Aircraft Engine Test Cell

23.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 18

- Default Settings Used: No

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine):	1
Idle Duration (mins):	0
Approach Duration (mins):	12
Intermediate Duration (mins):	0
Military Duration (mins):	8
After Burner Duration (mins):	2

23.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

23.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$TestCell = TestCellPS_{IDLE} + TestCellPS_{APPROACH} + TestCellPS_{INTERMEDIATE} + TestCellPS_{MILITARY} + TestCellPS_{AFTERBURN}$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

24. Aircraft

24.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Location

County: Bexar
Regulatory Area(s): San Antonio, TX

- Activity Title: 2025 T-38 Removal Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1
Start Year: 2025

- Activity End Date

Indefinite: No
End Month: 12
End Year: 2025

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	-0.169981
SO _x	-0.042395
NO _x	-0.122617
CO	-2.186180
PM 10	-0.046070

Pollutant	Total Emissions (TONs)
PM 2.5	-0.016658
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-128.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	-0.109701
SO _x	-0.028464
NO _x	-0.081041
CO	-1.447601
PM 10	-0.030287

Pollutant	Total Emissions (TONs)
PM 2.5	-0.010342
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-86.0

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	-0.060280
SO _x	-0.013931
NO _x	-0.041576
CO	-0.738579
PM 10	-0.015783

Pollutant	Total Emissions (TONs)
PM 2.5	-0.006316
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-42.1

24.2 Aircraft & Engines

24.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

24.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

24.3 Flight Operations

24.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 12
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 3

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 12.8
 Takeoff [Military] (mins): 0.2
 Takeoff [After Burn] (mins): 0.2
 Climb Out [Intermediate] (mins): 0.9
 Approach [Approach] (mins): 3.8
 Taxi/Idle In [Idle] (mins): 6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 0
 Approach (mins): 4.97
 Intermediate (mins): 10.45
 Military (mins): 6.14
 AfterBurn (mins): 2.04

24.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
 AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
 AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
 AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

24.4 Auxiliary Power Unit (APU)

24.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

24.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

24.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

24.5 Aircraft Engine Test Cell

24.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 12

- Default Settings Used: Yes

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 3 (default)

Idle Duration (mins): 0 (default)

Approach Duration (mins): 12 (default)

Intermediate Duration (mins): 0 (default)

Military Duration (mins): 8 (default)

After Burner Duration (mins): 2 (default)

24.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

24.5.3 Aircraft Engine Test Cell Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$\text{TestCellPS}_{\text{POL}} = (\text{TD} / 60) * (\text{FC} / 1000) * \text{EF} * \text{NE} * \text{ARU} / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONS

- Aircraft Engine Test Cell Emissions per Year

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

25. Aircraft

25.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2025 T-7A Increase Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: No

End Month: 12

End Year: 2025

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.264243
SO _x	0.086053
NO _x	1.468398

Pollutant	Total Emissions (TONs)
PM 2.5	0.092445
Pb	0.000000
NH ₃	0.000000

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

CO	4.533304
PM 10	0.103086

CO _{2e}	260.1
------------------	-------

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	0.144210
SO _x	0.047317
NO _x	0.786095
CO	2.287149
PM 10	0.052569

Pollutant	Total Emissions (TONs)
PM 2.5	0.047105
Pb	0.000000
NH ₃	0.000000
CO _{2e}	143.0

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	0.120033
SO _x	0.038737
NO _x	0.682304
CO	2.246155
PM 10	0.050517

Pollutant	Total Emissions (TONs)
PM 2.5	0.045340
Pb	0.000000
NH ₃	0.000000
CO _{2e}	117.1

25.2 Aircraft & Engines

25.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

25.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

25.3 Flight Operations

25.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 25
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 1

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Taxi/Idle Out [Idle] (mins):	6.8
Takeoff [Military] (mins):	0.25
Takeoff [After Burn] (mins):	0.25
Climb Out [Intermediate] (mins):	1.4
Approach [Approach] (mins):	4
Taxi/Idle In [Idle] (mins):	4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

25.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

- AE_{TGO}: Aircraft Emissions (TONs)
- AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
- AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
- AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

- AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
- TD: Test Duration (min)
- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Number of Engines
- NA: Number of Aircraft
- NTT: Number of Trim Test
- 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

25.4 Auxiliary Power Unit (APU)

25.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

25.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

25.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

OH: Operation Hours for Each LTO (hour)
LTO: Number of LTOs
EF_{POL}: Emission Factor for Pollutant (lb/hr)
2000: Conversion Factor pounds to tons

25.5 Aircraft Engine Test Cell

25.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 25

- **Default Settings Used:** No

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine):	1
Idle Duration (mins):	0
Approach Duration (mins):	12
Intermediate Duration (mins):	0
Military Duration (mins):	8
After Burner Duration (mins):	2

25.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

25.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$\text{TestCellPS}_{\text{POL}} = (\text{TD} / 60) * (\text{FC} / 1000) * \text{EF} * \text{NE} * \text{ARU} / 2000$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

26. Aircraft

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

26.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location
 - County: Bexar
 - Regulatory Area(s): San Antonio, TX

- Activity Title: 2026 T-38 Removal Trim Test and Test Cell

- Activity Description:

- Activity Start Date
 - Start Month: 1
 - Start Year: 2026

- Activity End Date
 - Indefinite: No
 - End Month: 12
 - End Year: 2026

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	-0.269136
SO _x	-0.067125
NO _x	-0.194144
CO	-3.461451
PM 10	-0.072944

Pollutant	Total Emissions (TONs)
PM 2.5	-0.026376
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-202.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	-0.173693
SO _x	-0.045068
NO _x	-0.128315
CO	-2.292035
PM 10	-0.047954

Pollutant	Total Emissions (TONs)
PM 2.5	-0.016375
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-136.2

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	-0.095443
SO _x	-0.022057
NO _x	-0.065829
CO	-1.169417
PM 10	-0.024990

Pollutant	Total Emissions (TONs)
PM 2.5	-0.010001
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-66.7

26.2 Aircraft & Engines

26.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-38C
 - Engine Model: J85-GE-5R

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No
 - Original Aircraft Name:
 - Original Engine Name:

26.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

26.3 Flight Operations

26.3.1 Flight Operations Assumptions

- Flight Operations
 - Number of Aircraft: 19
 - Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 - Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 - Number of Annual Trim Test(s) per Aircraft: 3

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)
 - Taxi/Idle Out [Idle] (mins): 12.8
 - Takeoff [Military] (mins): 0.2
 - Takeoff [After Burn] (mins): 0.2
 - Climb Out [Intermediate] (mins): 0.9
 - Approach [Approach] (mins): 3.8
 - Taxi/Idle In [Idle] (mins): 6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test
 - Idle (mins): 0
 - Approach (mins): 4.97
 - Intermediate (mins): 10.45
 - Military (mins): 6.14
 - AfterBurn (mins): 2.04

26.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year
 $AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

26.4 Auxiliary Power Unit (APU)

26.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

26.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

26.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

26.5 Aircraft Engine Test Cell

26.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 19

- Default Settings Used: Yes

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 3 (default)

Idle Duration (mins): 0 (default)

Approach Duration (mins): 12 (default)

Intermediate Duration (mins): 0 (default)

Military Duration (mins): 8 (default)

After Burner Duration (mins): 2 (default)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

26.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

26.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$\text{TestCellPS}_{\text{POL}} = (\text{TD} / 60) * (\text{FC} / 1000) * \text{EF} * \text{NE} * \text{ARU} / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

27. Aircraft

27.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2026 T-7A Increase Trim Test and Engine Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: No

End Month: 12

End Year: 2026

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.412218
SO _x	0.134243
NO _x	2.290701
CO	7.071954
PM 10	0.160814

Pollutant	Total Emissions (TONs)
PM 2.5	0.144214
Pb	0.000000
NH ₃	0.000000
CO _{2e}	405.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	0.224967
SO _x	0.073814
NO _x	1.226308
CO	3.567953
PM 10	0.082007

Pollutant	Total Emissions (TONs)
PM 2.5	0.073484
Pb	0.000000
NH ₃	0.000000
CO _{2e}	223.1

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	0.187251
SO _x	0.060429
NO _x	1.064393
CO	3.504001
PM 10	0.078807

Pollutant	Total Emissions (TONs)
PM 2.5	0.070730
Pb	0.000000
NH ₃	0.000000
CO _{2e}	182.6

27.2 Aircraft & Engines

27.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

27.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

27.3 Flight Operations

27.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 39
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 1

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	6.8
Takeoff [Military] (mins):	0.25
Takeoff [After Burn] (mins):	0.25
Climb Out [Intermediate] (mins):	1.4
Approach [Approach] (mins):	4
Taxi/Idle In [Idle] (mins):	4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

27.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
 AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
 AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
 AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
 AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
 AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
 AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
 AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
 AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

27.4 Auxiliary Power Unit (APU)

27.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

27.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

27.4.3 Auxiliary Power Unit (APU) Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

27.5 Aircraft Engine Test Cell

27.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 39

- Default Settings Used: Yes

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 1 (default)

Idle Duration (mins): 0 (default)

Approach Duration (mins): 12 (default)

Intermediate Duration (mins): 0 (default)

Military Duration (mins): 8 (default)

After Burner Duration (mins): 2 (default)

27.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

27.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$$TestCell = TestCellPS_{IDLE} + TestCellPS_{APPROACH} + TestCellPS_{INTERMEDIATE} + TestCellPS_{MILITARY} + TestCellPS_{AFTERBURN}$$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

28. Aircraft

28.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2027 T-38 Removal Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: No

End Month: 12

End Year: 2027

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	-0.495778
SO _x	-0.123651
NO _x	-0.357633
CO	-6.376358
PM 10	-0.134371

Pollutant	Total Emissions (TONs)
PM 2.5	-0.048587
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-373.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	-0.319962
SO _x	-0.083020
NO _x	-0.236369
CO	-4.222169
PM 10	-0.088337

Pollutant	Total Emissions (TONs)
PM 2.5	-0.030165
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-250.9

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	-0.175816
SO _x	-0.040631
NO _x	-0.121264
CO	-2.154189
PM 10	-0.046034

Pollutant	Total Emissions (TONs)
PM 2.5	-0.018423
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-122.8

28.2 Aircraft & Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

28.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

28.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

28.3 Flight Operations

28.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 35
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 3

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 6.8
 Takeoff [Military] (mins): 0.25
 Takeoff [After Burn] (mins): 0.25
 Climb Out [Intermediate] (mins): 1.4
 Approach [Approach] (mins): 4
 Taxi/Idle In [Idle] (mins): 4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 0
 Approach (mins): 4.97
 Intermediate (mins): 10.45
 Military (mins): 6.14
 AfterBurn (mins): 2.04

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

28.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

28.4 Auxiliary Power Unit (APU)

28.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

28.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

28.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

28.5 Aircraft Engine Test Cell

28.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 35

- Default Settings Used: Yes

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 3 (default)
 Idle Duration (mins): 0 (default)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Approach Duration (mins):	12 (default)
Intermediate Duration (mins):	0 (default)
Military Duration (mins):	8 (default)
After Burner Duration (mins):	2 (default)

28.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

28.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$\text{TestCellPS}_{\text{POL}} = (\text{TD} / 60) * (\text{FC} / 1000) * \text{EF} * \text{NE} * \text{ARU} / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

29. Aircraft

29.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2027 T-7A Increase Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1

Start Year: 2027

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity End Date

Indefinite: No
 End Month: 12
 End Year: 2027

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.549624
SO _x	0.178991
NO _x	3.054268
CO	9.429273
PM 10	0.214418

Pollutant	Total Emissions (TONs)
PM 2.5	0.192286
Pb	0.000000
NH ₃	0.000000
CO _{2e}	541.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	0.299956
SO _x	0.098419
NO _x	1.635077
CO	4.757271
PM 10	0.109343

Pollutant	Total Emissions (TONs)
PM 2.5	0.097979
Pb	0.000000
NH ₃	0.000000
CO _{2e}	297.5

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	0.249668
SO _x	0.080572
NO _x	1.419191
CO	4.672002
PM 10	0.105076

Pollutant	Total Emissions (TONs)
PM 2.5	0.094307
Pb	0.000000
NH ₃	0.000000
CO _{2e}	243.5

29.2 Aircraft & Engines

29.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

29.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

29.3 Flight Operations

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

29.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	52
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	0
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	1

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	6.8
Takeoff [Military] (mins):	0.25
Takeoff [After Burn] (mins):	0.25
Climb Out [Intermediate] (mins):	1.4
Approach [Approach] (mins):	4
Taxi/Idle In [Idle] (mins):	4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

29.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

29.4 Auxiliary Power Unit (APU)

29.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

29.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

29.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

29.5 Aircraft Engine Test Cell

29.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 52

- Default Settings Used: No

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 1
 Idle Duration (mins): 0
 Approach Duration (mins): 12
 Intermediate Duration (mins): 0
 Military Duration (mins): 8
 After Burner Duration (mins): 2

29.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

29.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$TestCellIPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$$

TestCellIPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

- TestCell: Aircraft Engine Test Cell Emissions (TONs)
- TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)
- TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)
- TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)
- TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)
- TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

30. Aircraft

30.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove
- Activity Location
 - County: Bexar; Bexar
 - Regulatory Area(s): San Antonio, TX
- Activity Title: 2028 T-38 Removal Trim Test and Test Cell
- Activity Description:
- Activity Start Date
 - Start Month: 1
 - Start Year: 2028
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.374012
SO _x	-0.342691
NO _x	-0.991155
CO	-17.671620
PM 10	-0.372400

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.134656
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1035.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.886751
SO _x	-0.230084
NO _x	-0.655081
CO	-11.701440
PM 10	-0.244819

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.083599
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-695.4

- Activity Emissions [Test Cell part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.487262

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.051057

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

SO _x	-0.112607
NO _x	-0.336074
CO	-5.970180
PM 10	-0.127581

Pb	0.000000
NH ₃	0.000000
CO _{2e}	-340.3

30.2 Aircraft & Engines

30.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

30.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

30.3 Flight Operations

30.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 97
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 3

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 6.8
 Takeoff [Military] (mins): 0.25
 Takeoff [After Burn] (mins): 0.25
 Climb Out [Intermediate] (mins): 1.4
 Approach [Approach] (mins): 4
 Taxi/Idle In [Idle] (mins): 4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

30.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

30.4 Auxiliary Power Unit (APU)

30.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

30.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

30.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

30.5 Aircraft Engine Test Cell

30.5.1 Aircraft Engine Test Cell Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 97

- Default Settings Used: Yes

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 3 (default)
Idle Duration (mins): 0 (default)
Approach Duration (mins): 12 (default)
Intermediate Duration (mins): 0 (default)
Military Duration (mins): 8 (default)
After Burner Duration (mins): 2 (default)

30.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

30.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$\text{TestCellPS}_{\text{POL}} = (\text{TD} / 60) * (\text{FC} / 1000) * \text{EF} * \text{NE} * \text{ARU} / 2000$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

31. Aircraft

31.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Title: 2028 T-7A Increase Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1
Start Year: 2028

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.591903
SO _x	0.192759
NO _x	3.289212
CO	10.154601
PM 10	0.230912

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.207077
Pb	0.000000
NH ₃	0.000000
CO _{2e}	582.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.323030
SO _x	0.105989
NO _x	1.760852
CO	5.123215
PM 10	0.117753

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.105516
Pb	0.000000
NH ₃	0.000000
CO _{2e}	320.3

- Activity Emissions [Test Cell part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.268873
SO _x	0.086770
NO _x	1.528360
CO	5.031387
PM 10	0.113158

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.101562
Pb	0.000000
NH ₃	0.000000
CO _{2e}	262.3

31.2 Aircraft & Engines

31.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

31.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

31.3 Flight Operations

31.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	56
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	0
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	1

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	6.8
Takeoff [Military] (mins):	0.25
Takeoff [After Burn] (mins):	0.25
Climb Out [Intermediate] (mins):	1.4
Approach [Approach] (mins):	4
Taxi/Idle In [Idle] (mins):	4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

31.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEL_{TGO}: Aircraft Emissions (TONs)
AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)
AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AET_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AETR_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

31.4 Auxiliary Power Unit (APU)

31.4.1 Auxiliary Power Unit (APU) Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

31.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

31.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

31.5 Aircraft Engine Test Cell

31.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 56

- Default Settings Used: No

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine):	1
Idle Duration (mins):	0
Approach Duration (mins):	12
Intermediate Duration (mins):	0
Military Duration (mins):	8
After Burner Duration (mins):	2

31.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

31.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- 60: Conversion Factor minutes to hours
- FC: Fuel Flow Rate (lb/hr)
- 1000: Conversion Factor pounds to 1000pounds
- EF: Emission Factor (lb/1000lb fuel)
- NE: Total Number of Engines (For All Aircraft)
- ARU: Annual Run-ups (Per Aircraft Engine)
- 2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

- TestCell: Aircraft Engine Test Cell Emissions (TONs)
- TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)
- TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)
- TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)
- TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)
- TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

32. Personnel

32.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add
- Activity Location
 - County: Bexar
 - Regulatory Area(s): San Antonio, TX
- Activity Title: 2023 Increase 303 Personnel INDEFINITE
- Activity Description:
- Activity Start Date
 - Start Month: 1
 - Start Year: 2023
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A
- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.620085
SO _x	0.004562
NO _x	0.528932
CO	7.305354
PM 10	0.013181

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.011378
Pb	0.000000
NH ₃	0.041964
CO _{2e}	668.7

32.2 Personnel Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Number of Personnel

Active Duty Personnel: 303
 Civilian Personnel: 0
 Support Contractor Personnel: 0
 Air National Guard (ANG) Personnel: 0
 Reserve Personnel: 0

- Default Settings Used: Yes

- Average Personnel Round Trip Commute (mile): 20 (default)

- Personnel Work Schedule

Active Duty Personnel: 5 Days Per Week (default)
 Civilian Personnel: 5 Days Per Week (default)
 Support Contractor Personnel: 5 Days Per Week (default)
 Air National Guard (ANG) Personnel: 4 Days Per Week (default)
 Reserve Personnel: 4 Days Per Month (default)

32.3 Personnel On Road Vehicle Mixture

- On Road Vehicle Mixture (%)

	LDCV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	37.55	60.32	0	0.03	0.2	0	1.9
GOVs	54.49	37.73	4.67	0	0	3.11	0

32.4 Personnel Emission Factor(s)

- On Road Vehicle Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
LDCV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859
LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HDCV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007
LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

32.5 Personnel Formula(s)

- Personnel Vehicle Miles Travel for Work Days per Year

$$VMT_p = NP * WD * AC$$

VMT_p: Personnel Vehicle Miles Travel (miles/year)
 NP: Number of Personnel
 WD: Work Days per Year
 AC: Average Commute (miles)

- Total Vehicle Miles Travel per Year

$$VMT_{Total} = VMT_{AD} + VMT_C + VMT_{SC} + VMT_{ANG} + VMT_{AFRC}$$

VMT_{Total}: Total Vehicle Miles Travel (miles)
 VMT_{AD}: Active Duty Personnel Vehicle Miles Travel (miles)
 VMT_C: Civilian Personnel Vehicle Miles Travel (miles)
 VMT_{SC}: Support Contractor Personnel Vehicle Miles Travel (miles)
 VMT_{ANG}: Air National Guard Personnel Vehicle Miles Travel (miles)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

VMT_{AFRC}: Reserve Personnel Vehicle Miles Travel (miles)

- Vehicle Emissions per Year

$$V_{POL} = (VMT_{Total} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{Total}: Total Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Personnel On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

33. Heating

33.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2023 Heating for Buildings INDEFINITE

- Activity Description:

- Activity Start Date

Start Month: 1

Start Year: 2023

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.028510
SO _x	0.003110
NO _x	0.518357
CO	0.435420
PM 10	0.039395

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.039395
Pb	0.000000
NH ₃	0.000000
CO _{2e}	624.0

33.2 Heating Assumptions

- Heating

Heating Calculation Type: Heat Energy Requirement Method

- Heat Energy Requirement Method

Area of floorspace to be heated (ft²):

100885

Type of fuel:

Natural Gas

Type of boiler/furnace:

Industrial (10 - 250 MMBtu/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Heat Value (MMBtu/ft³): 0.00105
Energy Intensity (MMBtu/ft²): 0.1079

- Default Settings Used: Yes
- Boiler/Furnace Usage
Operating Time Per Year (hours): 900 (default)

33.3 Heating Emission Factor(s)

- Heating Emission Factors (lb/1000000 scf)

VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
5.5	0.6	100	84	7.6	7.6			120390

33.4 Heating Formula(s)

- Heating Fuel Consumption ft³ per Year
 $FC_{HER} = HA * EI / HV / 1000000$

FC_{HER}: Fuel Consumption for Heat Energy Requirement Method
HA: Area of floorspace to be heated (ft²)
EI: Energy Intensity Requirement (MMBtu/ft²)
HV: Heat Value (MMBTU/ft³)
1000000: Conversion Factor

- Heating Emissions per Year
 $HE_{POL} = FC * EF_{POL} / 2000$

HE_{POL}: Heating Emission Emissions (TONs)
FC: Fuel Consumption
EF_{POL}: Emission Factor for Pollutant
2000: Conversion Factor pounds to tons

34. Construction / Demolition

34.1 General Information & Timeline Assumptions

- Activity Location
County: Bexar
Regulatory Area(s): San Antonio, TX
- Activity Title: Construction and Demolition
- Activity Description:
- Activity Start Date
Start Month: 1
Start Month: 2022
- Activity End Date
Indefinite: False
End Month: 12

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

End Month: 2022

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.526940
SO _x	0.005198
NO _x	2.123360
CO	2.303931
PM 10	3.635660

Pollutant	Total Emissions (TONs)
PM 2.5	0.094714
Pb	0.000000
NH ₃	0.001988
CO _{2e}	506.5

34.1 Site Grading Phase

34.1.1 Site Grading Phase Timeline Assumptions

- Phase Start Date

Start Month: 1
 Start Quarter: 1
 Start Year: 2022

- Phase Duration

Number of Month: 1
 Number of Days: 0

34.1.2 Site Grading Phase Assumptions

- General Site Grading Information

Area of Site to be Graded (ft²): 322910
 Amount of Material to be Hauled On-Site (yd³): 0
 Amount of Material to be Hauled Off-Site (yd³): 0

- Site Grading Default Settings

Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Graders Composite	1	8
Other Construction Equipment Composite	1	8
Rubber Tired Dozers Composite	1	8
Tractors/Loaders/Backhoes Composite	2	7

- Vehicle Exhaust

Average Hauling Truck Capacity (yd³): 20 (default)
 Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

	LDGV	LDGT	HdGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

34.1.3 Site Grading Phase Emission Factor(s)

- Construction Exhaust Emission Factors (lb/hour) (default)

Graders Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0806	0.0014	0.4657	0.5731	0.0217	0.0217	0.0072	132.92
Other Construction Equipment Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0507	0.0012	0.2785	0.3488	0.0105	0.0105	0.0045	122.61
Rubber Tired Dozers Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.1919	0.0024	1.3611	0.7352	0.0536	0.0536	0.0173	239.51
Tractors/Loaders/Backhoes Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0383	0.0007	0.2301	0.3598	0.0095	0.0095	0.0034	66.884

- Vehicle Exhaust & Worker Trips Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
LDGV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859
LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HdGV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007
LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

34.1.4 Site Grading Phase Formula(s)

- Fugitive Dust Emissions per Phase

$$PM10_{FD} = (20 * ACRE * WD) / 2000$$

PM10_{FD}: Fugitive Dust PM 10 Emissions (TONs)

20: Conversion Factor Acre Day to pounds (20 lb / 1 Acre Day)

ACRE: Total acres (acres)

WD: Number of Total Work Days (days)

2000: Conversion Factor pounds to tons

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * EF_{POL}) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)

NE: Number of Equipment

WD: Number of Total Work Days (days)

H: Hours Worked per Day (hours)

EF_{POL}: Emission Factor for Pollutant (lb/hour)

2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = (HA_{OnSite} + HA_{OffSite}) * (1 / HC) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

HA_{OnSite}: Amount of Material to be Hauled On-Site (yd³)
HA_{OffSite}: Amount of Material to be Hauled Off-Site (yd³)
HC: Average Hauling Truck Capacity (yd³)
(1 / HC): Conversion Factor cubic yards to trips (1 trip / HC yd³)
HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)
0.002205: Conversion Factor grams to pounds
EF_{POL}: Emission Factor for Pollutant (grams/mile)
VM: Vehicle Exhaust On Road Vehicle Mixture (%)
2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)
WD: Number of Total Work Days (days)
WT: Average Worker Round Trip Commute (mile)
1.25: Conversion Factor Number of Construction Equipment to Number of Works
NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)
0.002205: Conversion Factor grams to pounds
EF_{POL}: Emission Factor for Pollutant (grams/mile)
VM: Worker Trips On Road Vehicle Mixture (%)
2000: Conversion Factor pounds to tons

34.2 Trenching/Excavating Phase

34.2.1 Trenching / Excavating Phase Timeline Assumptions

- Phase Start Date

Start Month: 2
Start Quarter: 1
Start Year: 2022

- Phase Duration

Number of Month: 1
Number of Days: 0

34.2.2 Trenching / Excavating Phase Assumptions

- General Trenching/Excavating Information

Area of Site to be Trenched/Excavated (ft²): 33000
Amount of Material to be Hauled On-Site (yd³): 0
Amount of Material to be Hauled Off-Site (yd³): 0

- Trenching Default Settings

Default Settings Used: Yes

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Excavators Composite	2	8
Other General Industrial Equipmen Composite	1	8
Tractors/Loaders/Backhoes Composite	1	8

- Vehicle Exhaust

Average Hauling Truck Capacity (yd³): 20 (default)

Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

34.2.3 Trenching / Excavating Phase Emission Factor(s)

- Construction Exhaust Emission Factors (lb/hour) (default)

Graders Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0806	0.0014	0.4657	0.5731	0.0217	0.0217	0.0072	132.92
Other Construction Equipment Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0507	0.0012	0.2785	0.3488	0.0105	0.0105	0.0045	122.61
Rubber Tired Dozers Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.1919	0.0024	1.3611	0.7352	0.0536	0.0536	0.0173	239.51
Tractors/Loaders/Backhoes Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0383	0.0007	0.2301	0.3598	0.0095	0.0095	0.0034	66.884

- Vehicle Exhaust & Worker Trips Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
LDGV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859
LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HDCV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007
LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

34.2.4 Trenching / Excavating Phase Formula(s)

- Fugitive Dust Emissions per Phase

$$PM_{10FD} = (20 * ACRE * WD) / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

PM10_{FD}: Fugitive Dust PM 10 Emissions (TONs)
20: Conversion Factor Acre Day to pounds (20 lb / 1 Acre Day)
ACRE: Total acres (acres)
WD: Number of Total Work Days (days)
2000: Conversion Factor pounds to tons

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * EF_{POL}) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)
NE: Number of Equipment
WD: Number of Total Work Days (days)
H: Hours Worked per Day (hours)
EF_{POL}: Emission Factor for Pollutant (lb/hour)
2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = (HA_{OnSite} + HA_{OffSite}) * (1 / HC) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)
HA_{OnSite}: Amount of Material to be Hauled On-Site (yd³)
HA_{OffSite}: Amount of Material to be Hauled Off-Site (yd³)
HC: Average Hauling Truck Capacity (yd³)
(1 / HC): Conversion Factor cubic yards to trips (1 trip / HC yd³)
HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)
0.002205: Conversion Factor grams to pounds
EF_{POL}: Emission Factor for Pollutant (grams/mile)
VM: Vehicle Exhaust On Road Vehicle Mixture (%)
2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)
WD: Number of Total Work Days (days)
WT: Average Worker Round Trip Commute (mile)
1.25: Conversion Factor Number of Construction Equipment to Number of Works
NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
VMT_{VE}: Worker Trips Vehicle Miles Travel (miles)
0.002205: Conversion Factor grams to pounds
EF_{POL}: Emission Factor for Pollutant (grams/mile)
VM: Worker Trips On Road Vehicle Mixture (%)
2000: Conversion Factor pounds to tons

34.3 Building Construction Phase

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

34.3.1 Building Construction Phase Timeline Assumptions

- Phase Start Date

Start Month: 3
 Start Quarter: 1
 Start Year: 2022

- Phase Duration

Number of Month: 10
 Number of Days: 0

34.3.2 Building Construction Phase Assumptions

- General Building Construction Information

Building Category: Office or Industrial
 Area of Building (ft²): 101000
 Height of Building (ft): 12
 Number of Units: N/A

- Building Construction Default Settings

Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Cranes Composite	1	6
Forklifts Composite	2	6
Generator Sets Composite	1	8
Tractors/Loaders/Backhoes Composite	1	8
Welders Composite	3	8

- Vehicle Exhaust

Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

- Vendor Trips

Average Vendor Round Trip Commute (mile): 40 (default)

- Vendor Trips Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

34.3.3 Building Construction Phase Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Construction Exhaust Emission Factors (lb/hour) (default)

Cranes Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0797	0.0013	0.5505	0.3821	0.0203	0.0203	0.0071	128.81
Forklifts Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0274	0.0006	0.1265	0.2146	0.0043	0.0043	0.0024	54.457
Generator Sets Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0340	0.0006	0.2783	0.2694	0.0116	0.0116	0.0030	61.069
Tractors/Loaders/Backhoes Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0383	0.0007	0.2301	0.3598	0.0095	0.0095	0.0034	66.884
Welders Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0260	0.0003	0.1557	0.1772	0.0077	0.0077	0.0023	25.661

- Vehicle Exhaust & Worker Trips Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
LDGV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859
LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HDGV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007
LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

34.3.4 Building Construction Phase Formula(s)

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * EF_{POL}) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)

NE: Number of Equipment

WD: Number of Total Work Days (days)

H: Hours Worked per Day (hours)

EF_{POL}: Emission Factor for Pollutant (lb/hour)

2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = BA * BH * (0.42 / 1000) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

BA: Area of Building (ft²)

BH: Height of Building (ft)

(0.42 / 1000): Conversion Factor ft³ to trips (0.42 trip / 1000 ft³)

HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

VM: Worker Trips On Road Vehicle Mixture (%)
2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)
WD: Number of Total Work Days (days)
WT: Average Worker Round Trip Commute (mile)
1.25: Conversion Factor Number of Construction Equipment to Number of Works
NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)
0.002205: Conversion Factor grams to pounds
EF_{POL}: Emission Factor for Pollutant (grams/mile)
VM: Worker Trips On Road Vehicle Mixture (%)
2000: Conversion Factor pounds to tons

- Vender Trips Emissions per Phase

$$VMT_{VT} = BA * BH * (0.38 / 1000) * HT$$

VMT_{VT}: Vender Trips Vehicle Miles Travel (miles)
BA: Area of Building (ft²)
BH: Height of Building (ft)
(0.38 / 1000): Conversion Factor ft³ to trips (0.38 trip / 1000 ft³)
HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
VMT_{VT}: Vender Trips Vehicle Miles Travel (miles)
0.002205: Conversion Factor grams to pounds
EF_{POL}: Emission Factor for Pollutant (grams/mile)
VM: Worker Trips On Road Vehicle Mixture (%)
2000: Conversion Factor pounds to tons

34.4 Architectural Coatings Phase

34.4.1 Architectural Coatings Phase Timeline Assumptions

- Phase Start Date

Start Month: 12
Start Quarter: 1
Start Year: 2022

- Phase Duration

Number of Month: 1
Number of Days: 0

34.4.2 Architectural Coatings Phase Assumptions

- General Architectural Coatings Information

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Building Category: Non-Residential
Total Square Footage (ft²): 15200
Number of Units: N/A

- Architectural Coatings Default Settings

Default Settings Used: Yes
Average Day(s) worked per week: 5 (default)

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDBGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

34.4.3 Architectural Coatings Phase Emission Factor(s)

- Worker Trips Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
LDGV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859
LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HDBGV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007
LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

34.4.4 Architectural Coatings Phase Formula(s)

- Worker Trips Emissions per Phase

$$VMT_{WT} = (1 * WT * PA) / 800$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)
 1: Conversion Factor man days to trips (1 trip / 1 man * day)
 WT: Average Worker Round Trip Commute (mile)
 PA: Paint Area (ft²)
 800: Conversion Factor square feet to man days (1 ft² / 1 man * day)

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
 VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)
 0.002205: Conversion Factor grams to pounds
 EF_{POL}: Emission Factor for Pollutant (grams/mile)
 VM: Worker Trips On Road Vehicle Mixture (%)
 2000: Conversion Factor pounds to tons

- Off-Gassing Emissions per Phase

$$VOC_{AC} = (AB * 2.0 * 0.0116) / 2000.0$$

VOC_{AC}: Architectural Coating VOC Emissions (TONs)
 BA: Area of Building (ft²)
 2.0: Conversion Factor total area to coated area (2.0 ft² coated area / total area)
 0.0116: Emission Factor (lb/ft²)
 2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

34.5 Paving Phase

34.5.1 Paving Phase Timeline Assumptions

- Phase Start Date

Start Month: 12
 Start Quarter: 1
 Start Year: 2022

- Phase Duration

Number of Month: 1
 Number of Days: 0

34.5.2 Paving Phase Assumptions

- General Paving Information

Paving Area (ft²): 244000

- Paving Default Settings

Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Pavers Composite	1	8
Paving Equipment Composite	2	6
Rollers Composite	2	6

- Vehicle Exhaust

Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

34.5.3 Paving Phase Emission Factor(s)

- Construction Exhaust Emission Factors (lb/hour) (default)

Graders Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0806	0.0014	0.4657	0.5731	0.0217	0.0217	0.0072	132.92
Other Construction Equipment Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0507	0.0012	0.2785	0.3488	0.0105	0.0105	0.0045	122.61
Rubber Tired Dozers Composite								

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.1919	0.0024	1.3611	0.7352	0.0536	0.0536	0.0173	239.51
Tractors/Loaders/Backhoes Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0383	0.0007	0.2301	0.3598	0.0095	0.0095	0.0034	66.884

- Vehicle Exhaust & Worker Trips Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
LDGV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859
LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HdGV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007
LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

34.5.4 Paving Phase Formula(s)

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * EF_{POL}) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)

NE: Number of Equipment

WD: Number of Total Work Days (days)

H: Hours Worked per Day (hours)

EF_{POL}: Emission Factor for Pollutant (lb/hour)

2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = PA * 0.25 * (1 / 27) * (1 / HC) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

PA: Paving Area (ft²)

0.25: Thickness of Paving Area (ft)

(1 / 27): Conversion Factor cubic feet to cubic yards (1 yd³ / 27 ft³)

HC: Average Hauling Truck Capacity (yd³)

(1 / HC): Conversion Factor cubic yards to trips (1 trip / HC yd³)

HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Vehicle Exhaust On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)

WD: Number of Total Work Days (days)

WT: Average Worker Round Trip Commute (mile)

1.25: Conversion Factor Number of Construction Equipment to Number of Works

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

- V_{POL}: Vehicle Emissions (TONs)
- VMT_{VE}: Worker Trips Vehicle Miles Travel (miles)
- 0.002205: Conversion Factor grams to pounds
- EF_{POL}: Emission Factor for Pollutant (grams/mile)
- VM: Worker Trips On Road Vehicle Mixture (%)
- 2000: Conversion Factor pounds to tons

- Off-Gassing Emissions per Phase

$$VOC_P = (2.62 * PA) / 43560$$

- VOC_P: Paving VOC Emissions (TONs)
- 2.62: Emission Factor (lb/acre)
- PA: Paving Area (ft²)
- 43560: Conversion Factor square feet to acre (43560 ft² / acre)² / acre)

35. Aircraft

35.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar
Regulatory Area(s): San Antonio, TX

- Activity Title: Starting in 2028, add T-7As and increase TGOs by 2276

- Activity Description:

Starting in 2028, add T-7As and increase TGOs by 2276

- Activity Start Date

Start Month: 1
Start Year: 2028

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.461473
SO _x	0.311799
NO _x	5.701758
CO	0.951297
PM 10	0.030911

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.026757
Pb	0.000000
NH ₃	0.000000
CO _{2e}	955.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Pollutant	Emissions Per Year (TONs)
VOC	0.461473
SO _x	0.311799
NO _x	5.701758
CO	0.951297
PM 10	0.030911

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.026757
Pb	0.000000
NH ₃	0.000000
CO _{2e}	955.3

35.2 Aircraft & Engines

35.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

35.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

35.3 Flight Operations

35.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 4
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 2276
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.64
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.47
 Approach [Approach] (mins): 0.98
 Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

35.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

35.4 Auxiliary Power Unit (APU)

35.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

35.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

35.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF CONFORMITY ANALYSIS (ROCA)

1. General Information: The Air Force's Air Conformity Applicability Model (ACAM) was used to perform an analysis to assess the potential air quality impact/s associated with the action in accordance with the Air Force Manual 32-7002, Environmental Compliance and Pollution Prevention; the Environmental Impact Analysis Process (EIAP, 32 CFR 989); and the General Conformity Rule (GCR, 40 CFR 93 Subpart B). This report provides a summary of the ACAM analysis.

a. Action Location:

Base: RANDOLPH AFB
State: Texas
County(s): Bexar
Regulatory Area(s): San Antonio, TX

b. Action Title: Recapitalization of the T-38 Trainer At Randolph AFB - Alternative 2 (Bexar County and Guadalupe County ROIs)

c. Project Number/s (if applicable):

d. Projected Action Start Date: 1 / 2022

e. Action Description:

The proposed action encompasses the recapitalize of the T-38 flight-training program with newer and more capable T-7A aircraft at JBSA-Randolph and Lackland. In addition to the phased introduction of the T-7A aircraft, five military construction projects and 17 facilities sustainment, restoration, and modernization projects are proposed at JBSA-Randolph at JBSA-Lackland to provide modern facilities and infrastructure to support the T-7A aircraft's maintenance, training, and operational requirements. The number of personnel on JBSA-Randolph would increase due to the proposed aircraft recapitalization. No changes to airspace configurations (i.e., size, shape, or location) would be required to support the proposed operations of the T-7A aircraft; however, the T-7A aircraft may have more flight operations than occurs with the T 38C aircraft at both JBSA-Randolph and JBSA-Lackland. This Applicability Analysis present the worst-case of three aircraft operational intensities as the worst-case action alternatives for the Proposed Action.

A Conformity Evaluation is required for every proposed action that will occur within an area designated by the U.S. Environmental Protection Agency (EPA) as nonattainment or maintenance for any National Ambient Air Quality Standard (NAAQS). The proposed T-7A Recapitalization action will occur at both JBSA-Randolph AFB and JBSA-Lackland AFB which both fall entirely within Bexar County that has been designated by the U.S. Environmental Protection Agency (EPA) as a marginal nonattainment area for the 2015 Ozone NAAQS in 2018. Given this recent designation of Bexar County, the proposed action (as well as all proposed actions from federal agencies) are subject to the General Conformity Rule (GCR, 40 CFR 93 Subpart B). As a marginal nonattainment area for ozone, the GCR has established de minimis significance threshold values of less than 100 ton/yr (for any given year) for both nitrogen oxides (NOx) and volatile organic compounds (VOC).

f. Point of Contact:

Name: [REDACTED]
Title: NEPA Contract Support
Organization: [REDACTED]
Email:
Phone Number:

2. Analysis: Total combined direct and indirect emissions associated with the action were estimated through ACAM on a calendar-year basis for the "worst-case" and "steady state" (net gain/loss upon action fully implemented) emissions. General Conformity under the Clean Air Act, Section 1.76 has been evaluated for the action described above according to the requirements of 40 CFR 93, Subpart B.

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF CONFORMITY ANALYSIS (ROCA)

CO	35.486		
SO _x	2.465		
PM 10	-0.425		
PM 2.5	0.132		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	7838.3		

2026

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	29.151	100	No
NO _x	77.132	100	No
CO	53.972		
SO _x	3.903		
PM 10	-0.618		
PM 2.5	0.223		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	11713.6		

2027

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	43.744	100	No
NO _x	125.046	100	Yes
CO	39.983		
SO _x	6.004		
PM 10	-2.171		
PM 2.5	-0.492		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	17307.7		

2028

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	54.893	100	No
NO _x	165.497	100	Yes
CO	8.654		
SO _x	7.497		
PM 10	-3.997		
PM 2.5	-1.448		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	21176.3		

2029

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF CONFORMITY ANALYSIS (ROCA)

San Antonio, TX			
VOC	52.365	100	No
NO _x	169.625	100	Yes
CO	-38.904		
SO _x	7.271		
PM 10	-5.333		
PM 2.5	-2.384		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	20537.0		

2030

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	47.430	100	No
NO _x	171.047	100	Yes
CO	-104.782		
SO _x	6.761		
PM 10	-7.082		
PM 2.5	-3.646		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	19130.4		

2031

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	36.558	100	No
NO _x	167.961	100	Yes
CO	-225.684		
SO _x	5.521		
PM 10	-10.133		
PM 2.5	-5.857		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	15710.3		

2032

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	43.790	100	No
NO _x	180.448	100	Yes
CO	-188.983		
SO _x	6.427		
PM 10	-9.495		
PM 2.5	-5.286		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	18149.3		

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF CONFORMITY ANALYSIS (ROCA)

2033 - (Steady State)

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	43.790	100	No
NO _x	180.448	100	Yes
CO	-188.983		
SO _x	6.427		
PM 10	-9.495		
PM 2.5	-5.286		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	18149.3		

Some estimated emissions associated with this action are above the conformity threshold values established at 40 CFR 93.153 (b); Therefore, the requirements of the General Conformity Rule are applicable.

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1. General Information

- Action Location

Base: RANDOLPH AFB
State: Texas
County(s): Bexar
Regulatory Area(s): San Antonio, TX

- Action Title: Recapitalization of the T-38 Trainer At Randolph AFB - Alternative 2

- Project Number/s (if applicable):

- Projected Action Start Date: 1 / 2022

- Action Purpose and Need:

The T 38 Talon is a twin-engine, high-altitude, supersonic jet used by the USAF and other nations for pilot training. The aircraft originally was developed in the 1950s with production occurring between 1961 and 1972. The fleet has undergone periodic upgrades overtime. In 2001, the USAF upgraded several hundred T 38s with modern avionics and replaced propulsion components to provide increased performance and superior reliability.

The purpose of the Proposed Action is to allow the USAF T-7A to provide more efficient and effective pilot training to establish a T-7A pilot pipeline to allow for the transition to T-7A training throughout the entire USAF.

- Action Description:

The proposed action encompasses the recapitalize of the T-38 flight-training program with newer and more capable T-7A aircraft at JBSA-Randolph and Lackland. In addition to the phased introduction of the T-7A aircraft, five military construction projects and 17 facilities sustainment, restoration, and modernization projects are proposed at JBSA-Randolph at JBSA-Lackland to provide modern facilities and infrastructure to support the T-7A aircraft's maintenance, training, and operational requirements. The number of personnel on JBSA-Randolph would increase due to the proposed aircraft recapitalization. No changes to airspace configurations (i.e., size, shape, or location) would be required to support the proposed operations of the T-7A aircraft; however, the T-7A aircraft may have more flight operations than occurs with the T 38C aircraft at both JBSA-Randolph and JBSA-Lackland. This Applicability Analysis present the worst-case of three aircraft operational intensities as the worst-case action alternatives for the Proposed Action.

A Conformity Evaluation is required for every proposed action that will occur within an area designated by the U.S. Environmental Protection Agency (EPA) as nonattainment or maintenance for any National Ambient Air Quality Standard (NAAQS). The proposed T-7A Recapitalization action will occur at both JBSA-Randolph AFB and JBSA-Lackland AFB which both fall entirely within Bexar County that has been designated by the U.S. Environmental Protection Agency (EPA) as a marginal nonattainment area for the 2015 Ozone NAAQS in 2018. Given this recent designation of Bexar County, the proposed action (as well as all proposed actions from federal agencies) are subject to the General Conformity Rule (GCR, 40 CFR 93 Subpart B). As a marginal nonattainment area for ozone, the GCR has established de minimis significance threshold values of less than 100 ton/yr (for any given year) for both nitrogen oxides (NOx) and volatile organic compounds (VOC).

- Point of Contact

Name: [REDACTED]
Title: NEPA Contract Support
Organization: [REDACTED]
Email:
Phone Number:

- Activity List:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Activity Type		Activity Title
2.	Aircraft	T-7As and 759 LTOs
3.	Aircraft	T-7A Increase 1701 TGOs
4.	Aircraft	T-38 Removal 5 TGOs
5.	Aircraft	Add 10 T-7As and 1641LTOs
6.	Aircraft	Increase T-7A TGOs 3624
7.	Aircraft	Remove 11 T-38s and 2776 LTOs
8.	Aircraft	Remove 6,142 T-38 TGOs
9.	Aircraft	Add 8 new T-7As and 3261 LTOs
10.	Aircraft	Increase T-7A TGOs by 7353
11.	Aircraft	Remove 6 T-38s and reduce LTOs by 1534
12.	Aircraft	Decrease T-38 TGOs by 3394
13.	Aircraft	Add T-7As and increase LTOs by 3093
14.	Aircraft	Increase T-7A TGOs by 6947
15.	Aircraft	Remove T-38s and decrease LTOs by 3767
16.	Aircraft	Decrease T-38 TGOs by 8,328
17.	Aircraft	Add 19 new T-7As and increase LTOs by 5656
18.	Aircraft	Increase T-7A TGOs by 12595
19.	Aircraft	Remove 21 T-38s and decrease LTOs by 3,667
20.	Aircraft	Decrease T-38 TGOs by 8328
21.	Aircraft	Add T-7As and increase LTOs by 4941
22.	Aircraft	Increase T-7A TGOs by 10954
23.	Aircraft	Remove T-38s and decrease LTOs by 1445
24.	Aircraft	Decrease T-38 TGOs by 3193
25.	Aircraft	Add T-7As and increase LTOs by 581
26.	Aircraft	Increase T-7A TGOs by 1333
27.	Aircraft	Remove T-38s and decrease LTOs by 1715
28.	Aircraft	Decrease T-38 TGOs by 3792
29.	Aircraft	increase T-7 LTOs by 300
30.	Aircraft	Increase TGOs by 678
31.	Aircraft	Remove 14 T-38s and decrease LTOs by 2636
32.	Aircraft	2031 T-38 Removal 6076 TGOs
33.	Aircraft	decrease T-7A LTOs by 119
34.	Aircraft	decrease T-7A TGOs by 224
35.	Aircraft	Increase LTOs by 1428
36.	Aircraft	Increase T-7A TGOs by 3161
37.	Aircraft	2023 T-7A Increase Trim Test and Test Cell
38.	Aircraft	2024 T-7A Increase Trim Test and Engine Test Cell
39.	Aircraft	2025 T-38 Removal Trim Test and Test Cell
40.	Aircraft	2025 T-7A Increase Trim Test and Test Cell
41.	Aircraft	2026 T-38 Removal Trim Test and Test Cell
42.	Aircraft	2026 T-7A Increase Trim Test and Engine Test Cell
43.	Aircraft	2027 T-38 Removal Trim Test and Test Cell
44.	Aircraft	2027 T-7A Increase Trim Test and Test Cell
45.	Aircraft	2028 T-38 Removal Trim Test and Test Cell
46.	Aircraft	2028 T-7A Increase Trim Test and Test Cell
47.	Aircraft	2029 T-38 Removal Trim Test and Test Cell
48.	Aircraft	2030 T-38 Removal Trim Test and Test Cell
49.	Aircraft	2031 T-38 Removal Trim Test and Test Cell
50.	Personnel	2023 Increase 303 Personnel INDEFINITE
51.	Heating	2023 Heating for Buildings INDEFINITE
52.	Construction / Demolition	Construction and Demolition

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Emission factors and air emission estimating methods come from the United States Air Force's Air Emissions Guide for Air Force Stationary Sources, Air Emissions Guide for Air Force Mobile Sources, and Air Emissions Guide for Air Force Transitory Sources.

2. Aircraft

2.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: T-7As and 759 LTOs

- Activity Description:

Starting in 2023 add T-7As, and increase 759 LTOs

- Activity Start Date

Start Month: 1

Start Year: 2023

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	3.503273
SO _x	0.251578
NO _x	2.428146
CO	18.804690
PM 10	0.316361

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.283894
Pb	0.000000
NH ₃	0.000000
CO _{2e}	591.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	3.503273
SO _x	0.251578
NO _x	2.428146
CO	18.804690
PM 10	0.316361

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.283894
Pb	0.000000
NH ₃	0.000000
CO _{2e}	591.2

2.2 Aircraft & Engines

2.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

2.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

2.3 Flight Operations

2.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	8
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	759
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	9.74
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

2.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

2.4 Auxiliary Power Unit (APU)

2.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

2.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

2.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

3. Aircraft

3.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: T-7A Increase 1701 TGOs

- Activity Description:

Starting in 2023 add 8 new T-7As, and increase 1701 TGOs

- Activity Start Date

Start Month: 1

Start Year: 2023

- Activity End Date

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.342762
SO _x	0.184123
NO _x	3.967865
CO	0.483456
PM 10	0.023102

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.019997
Pb	0.000000
NH ₃	0.000000
CO _{2e}	556.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.342762
SO _x	0.184123
NO _x	3.967865
CO	0.483456
PM 10	0.023102

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.019997
Pb	0.000000
NH ₃	0.000000
CO _{2e}	556.5

3.2 Aircraft & Engines

3.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

3.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

3.3 Flight Operations

3.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 8
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1701
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

3.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

3.4 Auxiliary Power Unit (APU)

3.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

3.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

3.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

4. Aircraft

4.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

- Activity Title: T-38 Removal 5 TGOs

- Activity Description:

Starting in 2024, remove 5 T-38 TGOs

- Activity Start Date

Start Month: 1
 Start Year: 2024

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.000748
SO _x	-0.000244
NO _x	-0.000314
CO	-0.013707
PM 10	-0.000401

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.000162
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-0.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.000748
SO _x	-0.000244
NO _x	-0.000314
CO	-0.013707
PM 10	-0.000401

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.000162
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-0.7

4.2 Aircraft & Engines

4.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No
 - Original Aircraft Name:
 - Original Engine Name:

4.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

4.3 Flight Operations

4.3.1 Flight Operations Assumptions

- Flight Operations
 - Number of Aircraft: 91
 - Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 5
 - Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 - Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)
 - Taxi/Idle Out [Idle] (mins): 0
 - Takeoff [Military] (mins): 0.64
 - Takeoff [After Burn] (mins): 0
 - Climb Out [Intermediate] (mins): 0.47
 - Approach [Approach] (mins): 0.98
 - Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test
 - Idle (mins): 12
 - Approach (mins): 27
 - Intermediate (mins): 9
 - Military (mins): 9
 - AfterBurn (mins): 3

4.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year
 $AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

4.4 Auxiliary Power Unit (APU)

4.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

4.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

4.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

5. Aircraft

5.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Add 10 T-7As and 1641LTOs

- Activity Description:

Starting in 2024 add 10 new T-7As, and increase 1641 LTO

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Start Date

Start Month: 1
Start Year: 2024

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	7.574271
SO _x	0.543925
NO _x	5.249785
CO	40.656780
PM 10	0.683991

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.613794
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1278.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	7.574271
SO _x	0.543925
NO _x	5.249785
CO	40.656780
PM 10	0.683991

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.613794
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1278.2

5.2 Aircraft & Engines

5.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

5.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

5.3 Flight Operations

5.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 10
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1641

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	9.74
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

5.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

5.4 Auxiliary Power Unit (APU)

5.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

5.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

5.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

6. Aircraft

6.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs 3624

- Activity Description:

Starting in 2024 Increase T-7A TGOs 3624

- Activity Start Date

Start Month: 1

Start Year: 2024

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.734788
SO _x	0.496467
NO _x	9.078721
CO	1.514719
PM 10	0.049218

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.042604
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1521.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.734788
SO _x	0.496467
NO _x	9.078721
CO	1.514719
PM 10	0.049218

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.042604
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1521.0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

6.2 Aircraft & Engines

6.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

6.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

6.3 Flight Operations

6.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 7
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3624
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.64
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.47
Approach [Approach] (mins): 0.98
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

6.3.2 Flight Operations Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

6.4 Auxiliary Power Unit (APU)

6.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

6.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

6.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

7. Aircraft

7.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- **Activity Title:** Remove 11 T-38s and 2776 LTOs

- **Activity Description:**

Starting in 2025 remove T-38s and 2776 LTOs

- **Activity Start Date**

Start Month: 1

Start Year: 2025

- **Activity End Date**

Indefinite: Yes

End Month: N/A

End Year: N/A

- **Activity Emissions:**

Pollutant	Emissions Per Year (TONs)
VOC	-9.419282
SO _x	-0.807853
NO _x	-1.532868
CO	-100.821859
PM 10	-2.523479

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.028236
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2122.2

- **Activity Emissions [Flight Operations (includes Trim Test & APU) part]:**

Pollutant	Emissions Per Year (TONs)
VOC	-9.419282
SO _x	-0.807853
NO _x	-1.532868
CO	-100.821859
PM 10	-2.523479

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.028236
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2122.2

7.2 Aircraft & Engines

7.2.1 Aircraft & Engines Assumptions

- **Aircraft & Engine**

Aircraft Designation: T-38C

Engine Model: J85-GE-5R

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 2

- **Aircraft & Engine Surrogate**

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

7.2.2 Aircraft & Engines Emission Factor(s)

- **Aircraft & Engine Emissions Factors (lb/1000lb fuel)**

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234
------------	---------	------	------	------	-------	------	------	------

7.3 Flight Operations

7.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	11
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	2776
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	12.8
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

7.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

7.4 Auxiliary Power Unit (APU)

7.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

7.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

7.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs
- EF_{POL}: Emission Factor for Pollutant (lb/hr)
- 2000: Conversion Factor pounds to tons

8. Aircraft

8.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar
Regulatory Area(s): San Antonio, TX

- Activity Title: Remove 6,142 T-38 TGOs

- Activity Description:

Starting in 2025, remove 6142 -38 TGOs

- Activity Start Date

Start Month: 1
Start Year: 2025

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.918521
SO _x	-0.300318
NO _x	-0.385904
CO	-16.838007
PM 10	-0.492938

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.198506
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-907.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Pollutant	Emissions Per Year (TONs)
VOC	-0.918521
SO _x	-0.300318
NO _x	-0.385904
CO	-16.838007
PM 10	-0.492938

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.198506
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-907.7

8.2 Aircraft & Engines

8.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

8.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

8.3 Flight Operations

8.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 11
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 6142
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.64
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.47
 Approach [Approach] (mins): 0.98
 Taxi/Idle In [Idle] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

8.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

8.4 Auxiliary Power Unit (APU)

8.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

8.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

8.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

9. Aircraft

9.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Add 8 new T-7As and 3261 LTOs

- Activity Description:

Starting in 2025, add 8 new T-7As and 3261 LTOs

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	15.051613
SO _x	1.080889
NO _x	10.432389
CO	80.793272
PM 10	1.359229

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.219734
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2540.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	15.051613
SO _x	1.080889
NO _x	10.432389
CO	80.793272
PM 10	1.359229

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.219734
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2540.1

9.2 Aircraft & Engines

9.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Engine Name:

9.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

9.3 Flight Operations

9.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	8
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	3261
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	9.74
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

9.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

9.4 Auxiliary Power Unit (APU)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

9.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

9.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

9.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

10. Aircraft

10.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs by 7353

- Activity Description:

Starting in 2025, increase T-7A TGOs by 7353

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.490866
SO _x	1.007319
NO _x	18.420485
CO	3.073325
PM 10	0.099862

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.086442
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3086.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.490866
SO _x	1.007319
NO _x	18.420485
CO	3.073325
PM 10	0.099862

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.086442
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3086.2

10.2 Aircraft & Engines

10.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

10.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

10.3 Flight Operations

10.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 8
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 7353
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.64
 Takeoff [After Burn] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

10.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AE_{TCO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

10.4 Auxiliary Power Unit (APU)

10.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

10.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

10.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

LTO: Number of LTOs
 EFPOL: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

11. Aircraft

11.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove
- Activity Location
 - County: Bexar
 - Regulatory Area(s): San Antonio, TX
- Activity Title: Remove 6 T-38s and reduce LTOs by 1534
- Activity Description:
 - Starting in 2026, remove 6 T-38s and reduce LTOs by 1534
- Activity Start Date
 - Start Month: 1
 - Start Year: 2026
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-5.205036
SO _x	-0.446415
NO _x	-0.847053
CO	-55.713520
PM 10	-1.394458

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.120790
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1172.7

- Activity Emissions [Flight Operations (includes Trim Test & APU part)]:

Pollutant	Emissions Per Year (TONs)
VOC	-5.205036
SO _x	-0.446415
NO _x	-0.847053
CO	-55.713520
PM 10	-1.394458

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.120790
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1172.7

11.2 Aircraft & Engines

11.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-38C
 - Engine Model: J85-GE-5R
 - Primary Function: Trainer
 - Aircraft has After burn: Yes

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

11.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

11.3 Flight Operations

11.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 7
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1534
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 12.8
 Takeoff [Military] (mins): 0.41
 Takeoff [After Burn] (mins): 0.39
 Climb Out [Intermediate] (mins): 0.91
 Approach [Approach] (mins): 1.74
 Taxi/Idle In [Idle] (mins): 6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
 Approach (mins): 27
 Intermediate (mins): 9
 Military (mins): 9
 AfterBurn (mins): 3

11.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

11.4 Auxiliary Power Unit (APU)

11.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

11.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

11.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

12. Aircraft

12.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Decrease T-38 TGOs by 3394

- Activity Description:

Starting in 2026, decrease T-38 TGOs by 3394

- Activity Start Date

Start Month: 1

Start Year: 2026

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.507564
SO _x	-0.165952
NO _x	-0.213246
CO	-9.304493
PM 10	-0.272392

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.109692
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-501.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.507564
SO _x	-0.165952
NO _x	-0.213246
CO	-9.304493
PM 10	-0.272392

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.109692
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-501.6

12.2 Aircraft & Engines

12.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

12.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

12.3 Flight Operations

12.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3394
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.64
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.47
Approach [Approach] (mins): 0.98
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

12.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

12.4 Auxiliary Power Unit (APU)

12.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

12.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

12.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

13. Aircraft

13.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Add T-7As and increase LTOs by 3093

- Activity Description:

Starting in 2026, add T-7As and increase LTOs by 3093

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	14.276185
SO _x	1.025204
NO _x	9.894933
CO	76.630969
PM 10	1.289204

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.156896
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2409.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	14.276185
SO _x	1.025204
NO _x	9.894933
CO	76.630969
PM 10	1.289204

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.156896
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2409.2

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

13.2 Aircraft & Engines

13.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

13.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

13.3 Flight Operations

13.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3093
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 9.74
Takeoff [Military] (mins): 0.41
Takeoff [After Burn] (mins): 0.39
Climb Out [Intermediate] (mins): 0.91
Approach [Approach] (mins): 1.74
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

13.3.2 Flight Operations Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
 AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
 AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
 AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
 AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
 AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

13.4 Auxiliary Power Unit (APU)

13.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

13.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

13.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

14. Aircraft

14.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs by 6947

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Description:

Starting in 2026, increase T-7A TGOs by 6947

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.408547
SO _x	0.951699
NO _x	17.403388
CO	2.903630
PM 10	0.094348

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.081669
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2915.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.408547
SO _x	0.951699
NO _x	17.403388
CO	2.903630
PM 10	0.094348

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.081669
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2915.8

14.2 Aircraft & Engines

14.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

14.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

14.3 Flight Operations

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

14.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	6947
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

14.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

14.4 Auxiliary Power Unit (APU)

14.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

14.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

14.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

15. Aircraft

15.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Remove T-38s and decrease LTOs by 3767

- Activity Description:

Starting in 2027, remove T-38s and decrease LTOs by 3,767

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-12.781857
SO _x	-1.096248
NO _x	-2.080085
CO	-136.814100
PM 10	-3.424331

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.752292
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2879.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-12.781857

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.752292

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

SO _x	-1.096248
NO _x	-2.080085
CO	-136.814100
PM 10	-3.424331

Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2879.8

15.2 Aircraft & Engines

15.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

15.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

15.3 Flight Operations

15.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 16
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3767
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 12.8
 Takeoff [Military] (mins): 0.41
 Takeoff [After Burn] (mins): 0.39
 Climb Out [Intermediate] (mins): 0.91
 Approach [Approach] (mins): 1.74
 Taxi/Idle In [Idle] (mins): 6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

15.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

15.4 Auxiliary Power Unit (APU)

15.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

15.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

15.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

16. Aircraft

16.1 General Information & Timeline Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar
Regulatory Area(s): San Antonio, TX

- Activity Title: Decrease T-38 TGOs by 8,328

- Activity Description:

Starting in 2027, decrease T-38 TGOs by 8,328

- Activity Start Date

Start Month: 1
Start Year: 2027

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.245432
SO _x	-0.407204
NO _x	-0.523251
CO	-22.830824
PM 10	-0.668380

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.269156
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1230.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.245432
SO _x	-0.407204
NO _x	-0.523251
CO	-22.830824
PM 10	-0.668380

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.269156
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1230.7

16.2 Aircraft & Engines

16.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

16.2.2 Aircraft & Engines Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

16.3 Flight Operations

16.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	16
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	8328
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

16.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

16.4 Auxiliary Power Unit (APU)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

16.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

16.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

16.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

17. Aircraft

17.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Add 19 new T-7As and increase LTOs by 5656

- Activity Description:

Starting in 2027, add 19 new T-7As and increase LTOs by 5656

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
-----------	---------------------------

Pollutant	Emissions Per Year (TONs)
-----------	---------------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

VOC	26.106080
SO _x	1.874734
NO _x	18.094324
CO	140.130864
PM 10	2.357497

PM 2.5	2.115552
Pb	0.000000
NH ₃	0.000000
CO _{2e}	4405.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	26.106080
SO _x	1.874734
NO _x	18.094324
CO	140.130864
PM 10	2.357497

Pollutant	Emissions Per Year (TONs)
PM 2.5	2.115552
Pb	0.000000
NH ₃	0.000000
CO _{2e}	4405.6

17.2 Aircraft & Engines

17.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

17.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

17.3 Flight Operations

17.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 19
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 5656
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 9.74
 Takeoff [Military] (mins): 0.41
 Takeoff [After Burn] (mins): 0.39
 Climb Out [Intermediate] (mins): 0.91
 Approach [Approach] (mins): 1.74

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

17.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
 AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
 AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

17.4 Auxiliary Power Unit (APU)

17.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

17.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

17.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to tons

18. Aircraft

18.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs by 12595

- Activity Description:

Starting in 2027, increase T-7A TGOs by 12595

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	2.553713
SO _x	1.725442
NO _x	31.552565
CO	5.264318
PM 10	0.171055

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.148067
Pb	0.000000
NH ₃	0.000000
CO _{2e}	5286.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	2.553713
SO _x	1.725442
NO _x	31.552565
CO	5.264318
PM 10	0.171055

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.148067
Pb	0.000000
NH ₃	0.000000
CO _{2e}	5286.3

18.2 Aircraft & Engines

18.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

18.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

18.3 Flight Operations

18.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	19
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	12595
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

18.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

18.4 Auxiliary Power Unit (APU)

18.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

18.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

18.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

19. Aircraft

19.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Remove 21 T-38s and decrease LTOs by 3,667

- Activity Description:

Starting in 2028, remove 21 T-38s and decrease LTOs by 3,667

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-12.476477
SO _x	-1.070056
NO _x	-2.030388
CO	-133.545380
PM 10	-3.342518

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.686535
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2811.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-12.476477
SO _x	-1.070056
NO _x	-2.030388
CO	-133.545380
PM 10	-3.342518

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.686535
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2811.0

19.2 Aircraft & Engines

19.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

19.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

19.3 Flight Operations

19.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 21
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3677
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- **Default Settings Used:** No

- **Flight Operations TIMs (Time In Mode)**

Taxi/Idle Out [Idle] (mins):	12.8
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- **Trim Test**

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

19.3.2 Flight Operations Formula(s)

- **Aircraft Emissions per Mode for LTOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- **Aircraft Emissions for LTOs per Year**

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- **Aircraft Emissions per Mode for TGOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

19.4 Auxiliary Power Unit (APU)

19.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

19.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

19.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs
- EF_{POL}: Emission Factor for Pollutant (lb/hr)
- 2000: Conversion Factor pounds to tons

20. Aircraft

20.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar
Regulatory Area(s): San Antonio, TX

- Activity Title: Decrease T-38 TGOs by 8328

- Activity Description:

Starting in 2028, decrease T-38 TGOs by 8328

- Activity Start Date

Start Month: 1
Start Year: 2028

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.245432
SO _x	-0.407204
NO _x	-0.523251
CO	-22.830824
PM 10	-0.668380

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.269156
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1230.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.245432
SO _x	-0.407204
NO _x	-0.523251
CO	-22.830824
PM 10	-0.668380

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.269156
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1230.7

20.2 Aircraft & Engines

20.2.1 Aircraft & Engines Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

20.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

20.3 Flight Operations

20.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 16
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 8328
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.64
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.47
 Approach [Approach] (mins): 0.98
 Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
 Approach (mins): 27
 Intermediate (mins): 9
 Military (mins): 9
 AfterBurn (mins): 3

20.3.2 Flight Operations Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
 AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
 AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
 AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
 AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
 AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

20.4 Auxiliary Power Unit (APU)

20.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

20.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

20.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

21. Aircraft

21.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

- Activity Title: Add T-7As and increase LTOs by 4941

- Activity Description:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Starting in 2028, add T-7As and increase LTOs by 4941

- Activity Start Date

Start Month: 1
Start Year: 2028

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	22.799718
SO _x	1.495687
NO _x	14.954618
CO	121.755442
PM 10	2.059475

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.848115
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3391.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	22.799718
SO _x	1.495687
NO _x	14.954618
CO	121.755442
PM 10	2.059475

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.848115
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3391.3

21.2 Aircraft & Engines

21.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

21.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

21.3 Flight Operations

21.3.1 Flight Operations Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations

Number of Aircraft:	14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	4941
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	9.74
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

21.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

21.4 Auxiliary Power Unit (APU)

21.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

21.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

21.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

22. Aircraft

22.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs by 10954

- Activity Description:

Starting in 2028, increase T-7A TGOs by 10954

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	2.220991
SO _x	1.500635
NO _x	27.441588
CO	4.578431
PM 10	0.148768

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.128775
Pb	0.000000
NH ₃	0.000000
CO _{2e}	4597.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	2.220991
SO _x	1.500635
NO _x	27.441588
CO	4.578431

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.128775
Pb	0.000000
NH ₃	0.000000
CO _{2e}	4597.6

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

PM 10	0.148768
-------	----------

--	--

22.2 Aircraft & Engines

22.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

22.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

22.3 Flight Operations

22.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 10954
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.64
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.47
Approach [Approach] (mins): 0.98
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

22.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

22.4 Auxiliary Power Unit (APU)

22.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

22.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

22.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

23. Aircraft

23.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- **Activity Title:** Remove T-38s and decrease LTOs by 1445

- **Activity Description:**

Starting in 2029 T-38s and decrease LTOs by 1445

- **Activity Start Date**

Start Month: 1

Start Year: 2029

- **Activity End Date**

Indefinite: Yes

End Month: N/A

End Year: N/A

- **Activity Emissions:**

Pollutant	Emissions Per Year (TONs)
VOC	-4.903048
SO _x	-0.420514
NO _x	-0.797909
CO	-52.481119
PM 10	-1.313554

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.055764
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1104.7

- **Activity Emissions [Flight Operations (includes Trim Test & APU) part]:**

Pollutant	Emissions Per Year (TONs)
VOC	-4.903048
SO _x	-0.420514
NO _x	-0.797909
CO	-52.481119
PM 10	-1.313554

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.055764
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1104.7

23.2 Aircraft & Engines

23.2.1 Aircraft & Engines Assumptions

- **Aircraft & Engine**

Aircraft Designation: T-38C

Engine Model: J85-GE-5R

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 2

- **Aircraft & Engine Surrogate**

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

23.2.2 Aircraft & Engines Emission Factor(s)

- **Aircraft & Engine Emissions Factors (lb/1000lb fuel)**

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

23.3 Flight Operations

23.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	3
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	1445
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	12.8
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

23.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

23.4 Auxiliary Power Unit (APU)

23.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

23.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

23.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

24. Aircraft

24.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Decrease T-38 TGOs by 3193

- Activity Description:

Starting in 2029, decrease T-38 TGOs by 3193

- Activity Start Date

Start Month: 1

Start Year: 2029

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.477505
SO _x	-0.156124
NO _x	-0.200617
CO	-8.753461
PM 10	-0.256261

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.103196
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-471.9

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.477505
SO _x	-0.156124
NO _x	-0.200617
CO	-8.753461
PM 10	-0.256261

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.103196
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-471.9

24.2 Aircraft & Engines

24.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

24.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

24.3 Flight Operations

24.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 7
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3193
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.64
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.47
 Approach [Approach] (mins): 0.98
 Taxi/Idle In [Idle] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

24.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

24.4 Auxiliary Power Unit (APU)

24.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

24.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

24.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

25. Aircraft

25.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location
 - County: Bexar
 - Regulatory Area(s): San Antonio, TX

- Activity Title: Add T-7As and increase LTOs by 581

- Activity Description:
 - Starting in 2029, add T-7As and increase LTOs by 581

- Activity Start Date
 - Start Month: 1
 - Start Year: 2029

- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	2.681689
SO _x	0.192578
NO _x	1.858699
CO	14.394631
PM 10	0.242169

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.217315
Pb	0.000000
NH ₃	0.000000
CO _{2e}	452.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	2.681689
SO _x	0.192578
NO _x	1.858699
CO	14.394631
PM 10	0.242169

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.217315
Pb	0.000000
NH ₃	0.000000
CO _{2e}	452.6

25.2 Aircraft & Engines

25.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-7A
 - Engine Model: F404-GE-102
 - Primary Function: Trainer
 - Aircraft has After burn: Yes
 - Number of Engines: 1

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Aircraft Name:

Original Engine Name:

25.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

25.3 Flight Operations

25.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	0
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	581
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	9.74
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

25.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

25.4 Auxiliary Power Unit (APU)

25.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

25.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

25.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

26. Aircraft

26.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs by 1333

- Activity Description:

Starting in 2029, increase T-7A TGOs by 1333

- Activity Start Date

Start Month: 1

Start Year: 2029

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.270274
SO _x	0.182613
NO _x	3.339386
CO	0.557153
PM 10	0.018104

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.015671
Pb	0.000000
NH ₃	0.000000
CO _{2e}	559.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.270274
SO _x	0.182613
NO _x	3.339386
CO	0.557153
PM 10	0.018104

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.015671
Pb	0.000000
NH ₃	0.000000
CO _{2e}	559.5

26.2 Aircraft & Engines

26.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

26.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

26.3 Flight Operations

26.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 0
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1333
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.64

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

26.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

26.4 Auxiliary Power Unit (APU)

26.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

26.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

26.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

27. Aircraft

27.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove
- Activity Location
 - County: Bexar
 - Regulatory Area(s): San Antonio, TX
- Activity Title: Remove T-38s and decrease LTOs by 1715
- Activity Description:
 - Starting in 2030, remove T-38s and decrease LTOs by 1715
- Activity Start Date
 - Start Month: 1
 - Start Year: 2030
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-5.819189
SO _x	-0.499088
NO _x	-0.946999
CO	-62.287279
PM 10	-1.558993

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.253035
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1311.1

- Activity Emissions [Flight Operations (includes Trim Test & APU part)]:

Pollutant	Emissions Per Year (TONs)
VOC	-5.819189
SO _x	-0.499088
NO _x	-0.946999
CO	-62.287279
PM 10	-1.558993

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.253035
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1311.1

27.2 Aircraft & Engines

27.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-38C
 - Engine Model: J85-GE-5R
 - Primary Function: Trainer

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No
 - Original Aircraft Name:
 - Original Engine Name:

27.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

27.3 Flight Operations

27.3.1 Flight Operations Assumptions

- Flight Operations
 - Number of Aircraft: 6
 - Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1715
 - Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 - Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)
 - Taxi/Idle Out [Idle] (mins): 12.8
 - Takeoff [Military] (mins): 0.41
 - Takeoff [After Burn] (mins): 0.39
 - Climb Out [Intermediate] (mins): 0.91
 - Approach [Approach] (mins): 1.74
 - Taxi/Idle In [Idle] (mins): 6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test
 - Idle (mins): 12
 - Approach (mins): 27
 - Intermediate (mins): 9
 - Military (mins): 9
 - AfterBurn (mins): 3

27.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year
 $AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

- AE_{TRIM}: Aircraft Emissions (TONs)
- AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
- AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
- AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
- AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
- AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

27.4 Auxiliary Power Unit (APU)

27.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

27.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

27.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs
- EF_{POL}: Emission Factor for Pollutant (lb/hr)
- 2000: Conversion Factor pounds to tons

28. Aircraft

28.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

- County: Bexar
- Regulatory Area(s): San Antonio, TX

- Activity Title: Decrease T-38 TGOs by 3792

- Activity Description:

Starting in 2030, decrease T-38 TGOs by 3,792

- Activity Start Date

Start Month: 1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Start Year: 2030

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.567084
SO _x	-0.185413
NO _x	-0.238253
CO	-10.395591
PM 10	-0.304334

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.122555
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-560.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.567084
SO _x	-0.185413
NO _x	-0.238253
CO	-10.395591
PM 10	-0.304334

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.122555
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-560.4

28.2 Aircraft & Engines

28.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

28.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

28.3 Flight Operations

28.3.1 Flight Operations Assumptions

- Flight Operations

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Aircraft:	6
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	3792
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- **Default Settings Used:** No

- **Flight Operations TIMs (Time In Mode)**

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- **Trim Test**

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

28.3.2 Flight Operations Formula(s)

- **Aircraft Emissions per Mode for LTOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- **Aircraft Emissions for LTOs per Year**

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- **Aircraft Emissions per Mode for TGOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TIM: Time in Mode (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

28.4 Auxiliary Power Unit (APU)

28.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

28.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

28.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

29. Aircraft

29.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: increase T-7 LTOs by 300

- Activity Description:

Stating in 2030, increase LTOs by 300

- Activity Start Date

Start Month: 1

Start Year: 2030

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.384693
SO _x	0.099438
NO _x	0.959741
CO	7.432684
PM 10	0.125044

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.112211
Pb	0.000000
NH ₃	0.000000
CO _{2e}	233.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.384693
SO _x	0.099438
NO _x	0.959741
CO	7.432684
PM 10	0.125044

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.112211
Pb	0.000000
NH ₃	0.000000
CO _{2e}	233.7

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

29.2 Aircraft & Engines

29.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

29.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

29.3 Flight Operations

29.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 0
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 300
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 9.74
Takeoff [Military] (mins): 0.41
Takeoff [After Burn] (mins): 0.39
Climb Out [Intermediate] (mins): 0.91
Approach [Approach] (mins): 1.74
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

29.3.2 Flight Operations Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

29.4 Auxiliary Power Unit (APU)

29.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

29.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

29.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

30. Aircraft

30.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- **Activity Title:** Increase TGOs by 678

- **Activity Description:**
Starting in 2030, increase TGOs by 678

- **Activity Start Date**

Start Month: 1
Start Year: 2030

- **Activity End Date**

Indefinite: Yes
End Month: N/A
End Year: N/A

- **Activity Emissions:**

Pollutant	Emissions Per Year (TONs)
VOC	0.137469
SO _x	0.092882
NO _x	1.698503
CO	0.283383
PM 10	0.009208

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.007971
Pb	0.000000
NH ₃	0.000000
CO _{2e}	284.6

- **Activity Emissions [Flight Operations (includes Trim Test & APU) part]:**

Pollutant	Emissions Per Year (TONs)
VOC	0.137469
SO _x	0.092882
NO _x	1.698503
CO	0.283383
PM 10	0.009208

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.007971
Pb	0.000000
NH ₃	0.000000
CO _{2e}	284.6

30.2 Aircraft & Engines

30.2.1 Aircraft & Engines Assumptions

- **Aircraft & Engine**

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- **Aircraft & Engine Surrogate**

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

30.2.2 Aircraft & Engines Emission Factor(s)

- **Aircraft & Engine Emissions Factors (lb/1000lb fuel)**

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

30.3 Flight Operations

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

30.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	2
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	678
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

30.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

30.4 Auxiliary Power Unit (APU)

30.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

30.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

30.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

31. Aircraft

31.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Remove 14 T-38s and decrease LTOs by 2636

- Activity Description:

Starting in 2031, remove 14 T-38s and decrease TOs by 2,636

- Activity Start Date

Start Month: 1

Start Year: 2031

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-8.944246
SO _x	-0.767111
NO _x	-1.455562
CO	-95.737183
PM 10	-2.396214

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.925947
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2015.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
-----------	---------------------------

Pollutant	Emissions Per Year (TONs)
-----------	---------------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

VOC	-8.944246
SO _x	-0.767111
NO _x	-1.455562
CO	-95.737183
PM 10	-2.396214

PM 2.5	-1.925947
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2015.2

31.2 Aircraft & Engines

31.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

31.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

31.3 Flight Operations

31.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 14
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 2636
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 12.8
 Takeoff [Military] (mins): 0.41
 Takeoff [After Burn] (mins): 0.39
 Climb Out [Intermediate] (mins): 0.91
 Approach [Approach] (mins): 1.74
 Taxi/Idle In [Idle] (mins): 6.4

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

31.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

31.4 Auxiliary Power Unit (APU)

31.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

31.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

31.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

32. Aircraft

32.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar
Regulatory Area(s): San Antonio, TX

- Activity Title: 2031 T-38 Removal 6076 TGOs

- Activity Description:

Starting in 2031, decrease T-38 TGOs by 5840

- Activity Start Date

Start Month: 1
Start Year: 2031

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.908651
SO _x	-0.297091
NO _x	-0.381757
CO	-16.657071
PM 10	-0.487641

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.196373
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-897.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.908651
SO _x	-0.297091
NO _x	-0.381757
CO	-16.657071
PM 10	-0.487641

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.196373
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-897.9

32.2 Aircraft & Engines

32.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Engine Name:

32.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

32.3 Flight Operations

32.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	11
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	6076
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

32.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

32.4 Auxiliary Power Unit (APU)

32.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

32.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

32.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

33. Aircraft

33.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: decrease T-7A LTOs by 119

- Activity Description:

Starting in 2031, decrease T-7A LTOs by 119

- Activity Start Date

Start Month: 1

Start Year: 2031

- Activity End Date

Indefinite: Yes

End Month: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.549262
SO _x	-0.039444
NO _x	-0.380697
CO	-2.948298
PM 10	-0.049601

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.044510
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-92.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.549262
SO _x	-0.039444
NO _x	-0.380697
CO	-2.948298
PM 10	-0.049601

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.044510
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-92.7

33.2 Aircraft & Engines

33.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

33.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

33.3 Flight Operations

33.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 72
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 119
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 9.74

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

33.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

33.4 Auxiliary Power Unit (APU)

33.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

33.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

33.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

34. Aircraft

34.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

- Activity Title: decrease T-7A TGOs by 224

- Activity Description:

Starting in 2031, decrease T-7A TGOs by 258

- Activity Start Date

Start Month: 1
 Start Year: 2031

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.045417
SO _x	-0.030687
NO _x	-0.561157
CO	-0.093625
PM 10	-0.003042

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.002633
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-94.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.045417
SO _x	-0.030687
NO _x	-0.561157
CO	-0.093625
PM 10	-0.003042

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.002633
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-94.0

34.2 Aircraft & Engines

34.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

34.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

34.3 Flight Operations

34.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	72
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	224
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

34.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

34.4 Auxiliary Power Unit (APU)

34.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

34.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

34.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

35. Aircraft

35.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase LTOs by 1428

- Activity Description:

increase LTOs by 1428

- Activity Start Date

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Start Month: 1
Start Year: 2032

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	6.591139
SO _x	0.473324
NO _x	4.568369
CO	35.379575
PM 10	0.595210

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.534124
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1112.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	6.591139
SO _x	0.473324
NO _x	4.568369
CO	35.379575
PM 10	0.595210

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.534124
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1112.3

35.2 Aircraft & Engines

35.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

35.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

35.3 Flight Operations

35.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 5
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1428
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual Trim Test(s) per Aircraft:

0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	9.74
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

35.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

35.4 Auxiliary Power Unit (APU)

35.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

35.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

35.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

36. Aircraft

36.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs by 3161

- Activity Description:

Starting in 2032, increase T-7A TGOs by 3161

- Activity Start Date

Start Month: 1

Start Year: 2032

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.640912
SO _x	0.433039
NO _x	7.918830
CO	1.321200
PM 10	0.042930

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.037161
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1326.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.640912
SO _x	0.433039
NO _x	7.918830
CO	1.321200
PM 10	0.042930

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.037161
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1326.7

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

36.2 Aircraft & Engines

36.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

36.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

36.3 Flight Operations

36.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 5
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3161
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.64
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.47
Approach [Approach] (mins): 0.98
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

36.3.2 Flight Operations Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

36.4 Auxiliary Power Unit (APU)

36.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

36.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

36.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

37. Aircraft

37.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

- Activity Title: 2023 T-7A Increase Trim Test and Test Cell

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Description:

- Activity Start Date

Start Month: 1
Start Year: 2023

- Activity End Date

Indefinite: No
End Month: 12
End Year: 2023

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.084558
SO _x	0.027537
NO _x	0.469887
CO	1.450657
PM 10	0.032987

Pollutant	Total Emissions (TONs)
PM 2.5	0.029582
Pb	0.000000
NH ₃	0.000000
CO _{2e}	83.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	0.046147
SO _x	0.015141
NO _x	0.251550
CO	0.731888
PM 10	0.016822

Pollutant	Total Emissions (TONs)
PM 2.5	0.015074
Pb	0.000000
NH ₃	0.000000
CO _{2e}	45.8

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	0.038410
SO _x	0.012396
NO _x	0.218337
CO	0.718770
PM 10	0.016165

Pollutant	Total Emissions (TONs)
PM 2.5	0.014509
Pb	0.000000
NH ₃	0.000000
CO _{2e}	37.5

37.2 Aircraft & Engines

37.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

37.2.2 Aircraft & Engines Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

37.3 Flight Operations

37.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	8
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	0
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	1

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	6.8
Takeoff [Military] (mins):	0.25
Takeoff [After Burn] (mins):	0.25
Climb Out [Intermediate] (mins):	1.4
Approach [Approach] (mins):	4
Taxi/Idle In [Idle] (mins):	4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

37.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)
AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

37.4 Auxiliary Power Unit (APU)

37.4.1 Auxiliary Power Unit (APU) Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

37.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

37.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

37.5 Aircraft Engine Test Cell

37.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 8

- Default Settings Used: No

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine):	1
Idle Duration (mins):	0
Approach Duration (mins):	12
Intermediate Duration (mins):	0
Military Duration (mins):	8
After Burner Duration (mins):	2

37.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

37.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

EF: Emission Factor (lb/1000lb fuel)
 NE: Total Number of Engines (For All Aircraft)
 ARU: Annual Run-ups (Per Aircraft Engine)
 2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

TestCell: Aircraft Engine Test Cell Emissions (TONs)
 TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)
 TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)
 TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)
 TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)
 TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

38. Aircraft

38.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

- Activity Title: 2024 T-7A Increase Trim Test and Engine Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1
 Start Year: 2024

- Activity End Date

Indefinite: No
 End Month: 12
 End Year: 2024

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.190255
SO _x	0.061958
NO _x	1.057247
CO	3.263979
PM 10	0.074222

Pollutant	Total Emissions (TONs)
PM 2.5	0.066560
Pb	0.000000
NH ₃	0.000000
CO _{2e}	187.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	0.103831
SO _x	0.034068
NO _x	0.565988

Pollutant	Total Emissions (TONs)
PM 2.5	0.033916
Pb	0.000000
NH ₃	0.000000

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

CO	1.646748
PM 10	0.037849

CO _{2e}	103.0

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	0.086424
SO _x	0.027890
NO _x	0.491259
CO	1.617231
PM 10	0.036372

Pollutant	Total Emissions (TONs)
PM 2.5	0.032645
Pb	0.000000
NH ₃	0.000000
CO _{2e}	84.3

38.2 Aircraft & Engines

38.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

38.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

38.3 Flight Operations

38.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 18
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 1

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 6.8
 Takeoff [Military] (mins): 0.25
 Takeoff [After Burn] (mins): 0.25
 Climb Out [Intermediate] (mins): 1.4
 Approach [Approach] (mins): 4
 Taxi/Idle In [Idle] (mins): 4.4

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

38.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

38.4 Auxiliary Power Unit (APU)

38.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

38.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

38.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

38.5 Aircraft Engine Test Cell

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

38.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 18

- Default Settings Used: No

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 1
Idle Duration (mins): 0
Approach Duration (mins): 12
Intermediate Duration (mins): 0
Military Duration (mins): 8
After Burner Duration (mins): 2

38.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

38.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$\text{TestCellPS}_{\text{POL}} = (\text{TD} / 60) * (\text{FC} / 1000) * \text{EF} * \text{NE} * \text{ARU} / 2000$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

39. Aircraft

39.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Regulatory Area(s): San Antonio, TX

- Activity Title: 2025 T-38 Removal Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1
Start Year: 2025

- Activity End Date

Indefinite: No
End Month: 12
End Year: 2025

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	-0.250354
SO _x	-0.060969
NO _x	-0.178052
CO	-3.170952
PM 10	-0.067114

Pollutant	Total Emissions (TONs)
PM 2.5	-0.025080
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-184.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	-0.109701
SO _x	-0.028464
NO _x	-0.081041
CO	-1.447601
PM 10	-0.030287

Pollutant	Total Emissions (TONs)
PM 2.5	-0.010342
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-86.0

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	-0.140653
SO _x	-0.032505
NO _x	-0.097011
CO	-1.723351
PM 10	-0.036827

Pollutant	Total Emissions (TONs)
PM 2.5	-0.014738
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-98.2

39.2 Aircraft & Engines

39.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

39.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

39.3 Flight Operations

39.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	12
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	0
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	3

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	12.8
Takeoff [Military] (mins):	0.2
Takeoff [After Burn] (mins):	0.2
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	3.8
Taxi/Idle In [Idle] (mins):	6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

39.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

39.4 Auxiliary Power Unit (APU)

39.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

39.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

39.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

39.5 Aircraft Engine Test Cell

39.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 28

- Default Settings Used: Yes

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine):	3 (default)
Idle Duration (mins):	0 (default)
Approach Duration (mins):	12 (default)
Intermediate Duration (mins):	0 (default)
Military Duration (mins):	8 (default)
After Burner Duration (mins):	2 (default)

39.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

39.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

TestCell = TestCellPS_{IDLE} + TestCellPS_{APPROACH} + TestCellPS_{INTERMEDIATE} + TestCellPS_{MILITARY} + TestCellPS_{AFTERBURN}

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

40. Aircraft

40.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2025 T-7A Increase Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: No

End Month: 12

End Year: 2025

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.190255
SO _x	0.061958
NO _x	1.057247
CO	3.263979
PM 10	0.074222

Pollutant	Total Emissions (TONs)
PM 2.5	0.066560
Pb	0.000000
NH ₃	0.000000
CO _{2e}	187.3

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	0.103831
SO _x	0.034068
NO _x	0.565988
CO	1.646748
PM 10	0.037849

Pollutant	Total Emissions (TONs)
PM 2.5	0.033916
Pb	0.000000
NH ₃	0.000000
CO _{2e}	103.0

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	0.086424
SO _x	0.027890
NO _x	0.491259
CO	1.617231
PM 10	0.036372

Pollutant	Total Emissions (TONs)
PM 2.5	0.032645
Pb	0.000000
NH ₃	0.000000
CO _{2e}	84.3

40.2 Aircraft & Engines

40.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

40.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

40.3 Flight Operations

40.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 18
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 1

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 6.8
 Takeoff [Military] (mins): 0.25

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Takeoff [After Burn] (mins):	0.25
Climb Out [Intermediate] (mins):	1.4
Approach [Approach] (mins):	4
Taxi/Idle In [Idle] (mins):	4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

40.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

40.4 Auxiliary Power Unit (APU)

40.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

40.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

40.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

OH: Operation Hours for Each LTO (hour)
LTO: Number of LTOs
EF_{POL}: Emission Factor for Pollutant (lb/hr)
2000: Conversion Factor pounds to tons

40.5 Aircraft Engine Test Cell

40.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 18

- **Default Settings Used:** No

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine):	1
Idle Duration (mins):	0
Approach Duration (mins):	12
Intermediate Duration (mins):	0
Military Duration (mins):	8
After Burner Duration (mins):	2

40.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

40.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$TestCell = TestCellPS_{IDLE} + TestCellPS_{APPROACH} + TestCellPS_{INTERMEDIATE} + TestCellPS_{MILITARY} + TestCellPS_{AFTERBURN}$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

41. Aircraft

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

41.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove
- Activity Location
 - County: Bexar
 - Regulatory Area(s): San Antonio, TX
- Activity Title: 2026 T-38 Removal Trim Test and Test Cell
- Activity Description:
- Activity Start Date
 - Start Month: 1
 - Start Year: 2026
- Activity End Date
 - Indefinite: No
 - End Month: 12
 - End Year: 2026

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	-0.254971
SO _x	-0.063592
NO _x	-0.183926
CO	-3.279270
PM 10	-0.069105

Pollutant	Total Emissions (TONs)
PM 2.5	-0.024988
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-192.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	-0.164552
SO _x	-0.042696
NO _x	-0.121561
CO	-2.171401
PM 10	-0.045430

Pollutant	Total Emissions (TONs)
PM 2.5	-0.015513
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-129.0

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	-0.090420
SO _x	-0.020896
NO _x	-0.062364
CO	-1.107869
PM 10	-0.023675

Pollutant	Total Emissions (TONs)
PM 2.5	-0.009474
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-63.2

41.2 Aircraft & Engines

41.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-38C
 - Engine Model: J85-GE-5R

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No
 - Original Aircraft Name:
 - Original Engine Name:

41.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

41.3 Flight Operations

41.3.1 Flight Operations Assumptions

- Flight Operations
 - Number of Aircraft: 18
 - Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 - Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 - Number of Annual Trim Test(s) per Aircraft: 3

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)
 - Taxi/Idle Out [Idle] (mins): 12.8
 - Takeoff [Military] (mins): 0.2
 - Takeoff [After Burn] (mins): 0.2
 - Climb Out [Intermediate] (mins): 0.9
 - Approach [Approach] (mins): 3.8
 - Taxi/Idle In [Idle] (mins): 6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test
 - Idle (mins): 0
 - Approach (mins): 4.97
 - Intermediate (mins): 10.45
 - Military (mins): 6.14
 - AfterBurn (mins): 2.04

41.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year
 $AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

41.4 Auxiliary Power Unit (APU)

41.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

41.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

41.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

41.5 Aircraft Engine Test Cell

41.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 18

- Default Settings Used: Yes

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 3 (default)

Idle Duration (mins): 0 (default)

Approach Duration (mins): 12 (default)

Intermediate Duration (mins): 0 (default)

Military Duration (mins): 8 (default)

After Burner Duration (mins): 2 (default)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

41.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

41.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$\text{TestCellPS}_{\text{POL}} = (\text{TD} / 60) * (\text{FC} / 1000) * \text{EF} * \text{NE} * \text{ARU} / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

42. Aircraft

42.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2026 T-7A Increase Trim Test and Engine Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: No

End Month: 12

End Year: 2026

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.426622
SO _x	0.138892
NO _x	2.372578
CO	7.341493
PM 10	0.166876

Pollutant	Total Emissions (TONs)
PM 2.5	0.149655
Pb	0.000000
NH ₃	0.000000
CO _{2e}	419.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	0.224967
SO _x	0.073814
NO _x	1.226308
CO	3.567953
PM 10	0.082007

Pollutant	Total Emissions (TONs)
PM 2.5	0.073484
Pb	0.000000
NH ₃	0.000000
CO _{2e}	223.1

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	0.201655
SO _x	0.065078
NO _x	1.146270
CO	3.773540
PM 10	0.084869

Pollutant	Total Emissions (TONs)
PM 2.5	0.076171
Pb	0.000000
NH ₃	0.000000
CO _{2e}	196.7

42.2 Aircraft & Engines

42.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

42.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

42.3 Flight Operations

42.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 39
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 1

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	6.8
Takeoff [Military] (mins):	0.25
Takeoff [After Burn] (mins):	0.25
Climb Out [Intermediate] (mins):	1.4
Approach [Approach] (mins):	4
Taxi/Idle In [Idle] (mins):	4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

42.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

42.4 Auxiliary Power Unit (APU)

42.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

42.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

42.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$\text{APU}_{\text{POL}} = \text{APU} * \text{OH} * \text{LTO} * \text{EF}_{\text{POL}} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

42.5 Aircraft Engine Test Cell

42.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 42

- Default Settings Used: Yes

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine):	1 (default)
Idle Duration (mins):	0 (default)
Approach Duration (mins):	12 (default)
Intermediate Duration (mins):	0 (default)
Military Duration (mins):	8 (default)
After Burner Duration (mins):	2 (default)

42.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

42.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$\text{TestCellPS}_{\text{POL}} = (\text{TD} / 60) * (\text{FC} / 1000) * \text{EF} * \text{NE} * \text{ARU} / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONS

- Aircraft Engine Test Cell Emissions per Year

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)
 TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)
 TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)
 TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

43. Aircraft

43.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location
 - County: Bexar
 - Regulatory Area(s): San Antonio, TX

- Activity Title: 2027 T-38 Removal Trim Test and Test Cell

- Activity Description:

- Activity Start Date
 - Start Month: 1
 - Start Year: 2027

- Activity End Date
 - Indefinite: No
 - End Month: 12
 - End Year: 2027

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	-0.481613
SO _x	-0.120119
NO _x	-0.347415
CO	-6.194176
PM 10	-0.130532

Pollutant	Total Emissions (TONs)
PM 2.5	-0.047199
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-363.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	-0.310820
SO _x	-0.080648
NO _x	-0.229616
CO	-4.101536
PM 10	-0.085813

Pollutant	Total Emissions (TONs)
PM 2.5	-0.029303
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-243.8

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	-0.170793
SO _x	-0.039470
NO _x	-0.117799
CO	-2.092641
PM 10	-0.044719

Pollutant	Total Emissions (TONs)
PM 2.5	-0.017896
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-119.3

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

43.2 Aircraft & Engines

43.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

43.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

43.3 Flight Operations

43.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 34
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 3

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 6.8
Takeoff [Military] (mins): 0.25
Takeoff [After Burn] (mins): 0.25
Climb Out [Intermediate] (mins): 1.4
Approach [Approach] (mins): 4
Taxi/Idle In [Idle] (mins): 4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 0
Approach (mins): 4.97
Intermediate (mins): 10.45
Military (mins): 6.14

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AfterBurn (mins): 2.04

43.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

43.4 Auxiliary Power Unit (APU)

43.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

43.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

43.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

43.5 Aircraft Engine Test Cell

43.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 34

- Default Settings Used: Yes

- Annual Run-ups / Test Durations

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Annual Run-ups (Per Aircraft Engine):	3 (default)
Idle Duration (mins):	0 (default)
Approach Duration (mins):	12 (default)
Intermediate Duration (mins):	0 (default)
Military Duration (mins):	8 (default)
After Burner Duration (mins):	2 (default)

43.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

43.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$\text{TestCellPS}_{\text{POL}} = (\text{TD} / 60) * (\text{FC} / 1000) * \text{EF} * \text{NE} * \text{ARU} / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

44. Aircraft

44.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2027 T-7A Increase Trim Test and Test Cell

- Activity Description:

- Activity Start Date

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Start Month: 1
Start Year: 2027

- Activity End Date

Indefinite: No
End Month: 12
End Year: 2027

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.613043
SO _x	0.199644
NO _x	3.406684
CO	10.517266
PM 10	0.239159

Pollutant	Total Emissions (TONs)
PM 2.5	0.214473
Pb	0.000000
NH ₃	0.000000
CO _{2e}	603.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	0.334567
SO _x	0.109775
NO _x	1.823740
CO	5.306186
PM 10	0.121959

Pollutant	Total Emissions (TONs)
PM 2.5	0.109284
Pb	0.000000
NH ₃	0.000000
CO _{2e}	331.8

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	0.278476
SO _x	0.089869
NO _x	1.582944
CO	5.211079
PM 10	0.117200

Pollutant	Total Emissions (TONs)
PM 2.5	0.105189
Pb	0.000000
NH ₃	0.000000
CO _{2e}	271.6

44.2 Aircraft & Engines

44.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

44.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

44.3 Flight Operations

44.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	58
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	0
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	1

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	6.8
Takeoff [Military] (mins):	0.25
Takeoff [After Burn] (mins):	0.25
Climb Out [Intermediate] (mins):	1.4
Approach [Approach] (mins):	4
Taxi/Idle In [Idle] (mins):	4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

44.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

44.4 Auxiliary Power Unit (APU)

44.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1	0.25	No	4501687C	Hamilton Sundstrand
---	------	----	----------	---------------------

44.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

44.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

44.5 Aircraft Engine Test Cell

44.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 58

- Default Settings Used: No

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine):	1
Idle Duration (mins):	0
Approach Duration (mins):	12
Intermediate Duration (mins):	0
Military Duration (mins):	8
After Burner Duration (mins):	2

44.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

44.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

45. Aircraft

45.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar; Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2028 T-38 Removal Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: No

End Month: 12

End Year: 2028

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	-0.779079
SO _x	-0.194309
NO _x	-0.561995
CO	-10.019991
PM 10	-0.211155

Pollutant	Total Emissions (TONs)
PM 2.5	-0.076351
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-587.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	-0.502797
SO _x	-0.130460
NO _x	-0.371437
CO	-6.634837
PM 10	-0.138815

Pollutant	Total Emissions (TONs)
PM 2.5	-0.047402
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-394.3

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	-0.276282
SO _x	-0.063849
NO _x	-0.190557
CO	-3.385154
PM 10	-0.072340

Pollutant	Total Emissions (TONs)
PM 2.5	-0.028950
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-193.0

45.2 Aircraft & Engines

45.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

45.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

45.3 Flight Operations

45.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 55
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 3

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 6.8
 Takeoff [Military] (mins): 0.25
 Takeoff [After Burn] (mins): 0.25
 Climb Out [Intermediate] (mins): 1.4
 Approach [Approach] (mins): 4
 Taxi/Idle In [Idle] (mins): 4.4

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

45.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

45.4 Auxiliary Power Unit (APU)

45.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

45.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

45.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

45.5 Aircraft Engine Test Cell

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

45.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 55

- Default Settings Used: Yes

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 3 (default)
Idle Duration (mins): 0 (default)
Approach Duration (mins): 12 (default)
Intermediate Duration (mins): 0 (default)
Military Duration (mins): 8 (default)
After Burner Duration (mins): 2 (default)

45.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

45.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$TestCell = TestCellPS_{IDLE} + TestCellPS_{APPROACH} + TestCellPS_{INTERMEDIATE} + TestCellPS_{MILITARY} + TestCellPS_{AFTERBURN}$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

46. Aircraft

46.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Regulatory Area(s): San Antonio, TX

- Activity Title: 2028 T-7A Increase Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.761018
SO _x	0.247833
NO _x	4.228987
CO	13.055916
PM 10	0.296887

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.266242
Pb	0.000000
NH ₃	0.000000
CO _{2e}	749.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.415324
SO _x	0.136272
NO _x	2.263953
CO	6.586990
PM 10	0.151397

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.135663
Pb	0.000000
NH ₃	0.000000
CO _{2e}	411.9

- Activity Emissions [Test Cell part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.345694
SO _x	0.111562
NO _x	1.965034
CO	6.468926
PM 10	0.145489

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.130579
Pb	0.000000
NH ₃	0.000000
CO _{2e}	337.2

46.2 Aircraft & Engines

46.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

46.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

46.3 Flight Operations

46.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	72
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	0
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	1

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	6.8
Takeoff [Military] (mins):	0.25
Takeoff [After Burn] (mins):	0.25
Climb Out [Intermediate] (mins):	1.4
Approach [Approach] (mins):	4
Taxi/Idle In [Idle] (mins):	4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

46.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AE_{LTO}: Aircraft Emissions (TONs)
AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)
AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

46.4 Auxiliary Power Unit (APU)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

46.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

46.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

46.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

46.5 Aircraft Engine Test Cell

46.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 72

- Default Settings Used: No

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine):	1
Idle Duration (mins):	0
Approach Duration (mins):	12
Intermediate Duration (mins):	0
Military Duration (mins):	8
After Burner Duration (mins):	2

46.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

46.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Total Number of Engines (For All Aircraft)
 ARU: Annual Run-ups (Per Aircraft Engine)
 2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

TestCell: Aircraft Engine Test Cell Emissions (TONs)
 TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)
 TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)
 TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)
 TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)
 TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

47. Aircraft

47.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove
- Activity Location
 - County: Bexar
 - Regulatory Area(s): San Antonio, TX
- Activity Title: 2029 T-38 Removal Trim Test and Test Cell
- Activity Description:
- Activity Start Date
 - Start Month: 1
 - Start Year: 2029
- Activity End Date
 - Indefinite: No
 - End Month: 12
 - End Year: 2029

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	-0.878235
SO _x	-0.219040
NO _x	-0.633521
CO	-11.295262
PM 10	-0.238029

Pollutant	Total Emissions (TONs)
PM 2.5	-0.086069
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-662.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Pollutant	Total Emissions (TONs)
VOC	-0.566789
SO _x	-0.147064
NO _x	-0.418711
CO	-7.479271
PM 10	-0.156482

Pollutant	Total Emissions (TONs)
PM 2.5	-0.053435
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-444.5

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	-0.311446
SO _x	-0.071976
NO _x	-0.214810
CO	-3.815992
PM 10	-0.081547

Pollutant	Total Emissions (TONs)
PM 2.5	-0.032634
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-217.5

47.2 Aircraft & Engines

47.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

47.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

47.3 Flight Operations

47.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 62
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 3

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Taxi/Idle Out [Idle] (mins):	12.8
Takeoff [Military] (mins):	0.2
Takeoff [After Burn] (mins):	0.2
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	3.8
Taxi/Idle In [Idle] (mins):	6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

47.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

47.4 Auxiliary Power Unit (APU)

47.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

47.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

47.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

OH: Operation Hours for Each LTO (hour)
LTO: Number of LTOs
EF_{POL}: Emission Factor for Pollutant (lb/hr)
2000: Conversion Factor pounds to tons

47.5 Aircraft Engine Test Cell

47.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 62

- **Default Settings Used:** Yes

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 3 (default)
Idle Duration (mins): 0 (default)
Approach Duration (mins): 12 (default)
Intermediate Duration (mins): 0 (default)
Military Duration (mins): 8 (default)
After Burner Duration (mins): 2 (default)

47.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

47.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$TestCell = TestCellPS_{IDLE} + TestCellPS_{APPROACH} + TestCellPS_{INTERMEDIATE} + TestCellPS_{MILITARY} + TestCellPS_{AFTERBURN}$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

48. Aircraft

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

48.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove
- Activity Location
 - County: Bexar
 - Regulatory Area(s): San Antonio, TX
- Activity Title: 2030 T-38 Removal Trim Test and Test Cell
- Activity Description:
- Activity Start Date
 - Start Month: 1
 - Start Year: 2030
- Activity End Date
 - Indefinite: No
 - End Month: 12
 - End Year: 2030

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	-0.949060
SO _x	-0.236704
NO _x	-0.684612
CO	-12.206171
PM 10	-0.257225

Pollutant	Total Emissions (TONs)
PM 2.5	-0.093010
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-715.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	-0.612498
SO _x	-0.158924
NO _x	-0.452478
CO	-8.082438
PM 10	-0.169102

Pollutant	Total Emissions (TONs)
PM 2.5	-0.057744
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-480.3

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	-0.336562
SO _x	-0.077780
NO _x	-0.232134
CO	-4.123733
PM 10	-0.088123

Pollutant	Total Emissions (TONs)
PM 2.5	-0.035266
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-235.1

48.2 Aircraft & Engines

48.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-38C
 - Engine Model: J85-GE-5R

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No
 - Original Aircraft Name:
 - Original Engine Name:

48.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

48.3 Flight Operations

48.3.1 Flight Operations Assumptions

- Flight Operations
 - Number of Aircraft: 67
 - Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 0
 - Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 - Number of Annual Trim Test(s) per Aircraft: 3

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)
 - Taxi/Idle Out [Idle] (mins): 12.8
 - Takeoff [Military] (mins): 0.2
 - Takeoff [After Burn] (mins): 0.2
 - Climb Out [Intermediate] (mins): 0.9
 - Approach [Approach] (mins): 3.8
 - Taxi/Idle In [Idle] (mins): 6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test
 - Idle (mins): 0
 - Approach (mins): 4.97
 - Intermediate (mins): 10.45
 - Military (mins): 6.14
 - AfterBurn (mins): 2.04

48.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year
 $AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

48.4 Auxiliary Power Unit (APU)

48.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

48.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

48.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

48.5 Aircraft Engine Test Cell

48.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 67

- Default Settings Used: Yes

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 3 (default)

Idle Duration (mins): 0 (default)

Approach Duration (mins): 12 (default)

Intermediate Duration (mins): 0 (default)

Military Duration (mins): 8 (default)

After Burner Duration (mins): 2 (default)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

48.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

48.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$\text{TestCellPS}_{\text{POL}} = (\text{TD} / 60) * (\text{FC} / 1000) * \text{EF} * \text{NE} * \text{ARU} / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$$\text{TestCell} = \text{TestCellPS}_{\text{IDLE}} + \text{TestCellPS}_{\text{APPROACH}} + \text{TestCellPS}_{\text{INTERMEDIATE}} + \text{TestCellPS}_{\text{MILITARY}} + \text{TestCellPS}_{\text{AFTERBURN}}$$

TestCell: Aircraft Engine Test Cell Emissions (TONs)

TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)

TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)

TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)

TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)

TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

49. Aircraft

49.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2031 T-38 Removal Trim Test and Test Cell

- Activity Description:

- Activity Start Date

Start Month: 1

Start Year: 2031

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.374012
SO _x	-0.342691
NO _x	-0.991155
CO	-17.671620
PM 10	-0.372400

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.134656
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1035.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.886751
SO _x	-0.230084
NO _x	-0.655081
CO	-11.701440
PM 10	-0.244819

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.083599
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-695.4

- Activity Emissions [Test Cell part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.487262
SO _x	-0.112607
NO _x	-0.336074
CO	-5.970180
PM 10	-0.127581

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.051057
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-340.3

49.2 Aircraft & Engines

49.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

49.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

49.3 Flight Operations

49.3.1 Flight Operations Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations

Number of Aircraft:	97
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	0
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	3

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	12.8
Takeoff [Military] (mins):	0.2
Takeoff [After Burn] (mins):	0.2
Climb Out [Intermediate] (mins):	0.9
Approach [Approach] (mins):	3.8
Taxi/Idle In [Idle] (mins):	6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

49.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

49.4 Auxiliary Power Unit (APU)

49.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

49.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

49.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

49.5 Aircraft Engine Test Cell

49.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 97

- Default Settings Used: Yes

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine): 3 (default)

Idle Duration (mins): 0 (default)

Approach Duration (mins): 12 (default)

Intermediate Duration (mins): 0 (default)

Military Duration (mins): 8 (default)

After Burner Duration (mins): 2 (default)

49.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

49.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs

- Aircraft Engine Test Cell Emissions per Year

$$TestCell = TestCellPS_{IDLE} + TestCellPS_{APPROACH} + TestCellPS_{INTERMEDIATE} + TestCellPS_{MILITARY} + TestCellPS_{AFTERBURN}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TestCell: Aircraft Engine Test Cell Emissions (TONs)
TestCellPS_{IDLE}: Aircraft Engine Test Cell Emissions for Idle Power Setting (TONs)
TestCellPS_{APPROACH}: Aircraft Engine Test Cell Emissions for Approach Power Setting (TONs)
TestCellPS_{INTERMEDIATE}: Aircraft Engine Test Cell Emissions for Intermediate Power Setting (TONs)
TestCellPS_{MILITARY}: Aircraft Engine Test Cell Emissions for Military Power Setting (TONs)
TestCellPS_{AFTERBURN}: Aircraft Engine Test Cell Emissions for After Burner Power Setting (TONs)

50. Personnel

50.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add
- Activity Location
 - County: Bexar
 - Regulatory Area(s): San Antonio, TX
- Activity Title: 2023 Increase 303 Personnel INDEFINITE
- Activity Description:
- Activity Start Date
 - Start Month: 1
 - Start Year: 2023
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A
- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.620085
SO _x	0.004562
NO _x	0.528932
CO	7.305354
PM 10	0.013181

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.011378
Pb	0.000000
NH ₃	0.041964
CO _{2e}	668.7

50.2 Personnel Assumptions

- Number of Personnel
 - Active Duty Personnel: 303
 - Civilian Personnel: 0
 - Support Contractor Personnel: 0
 - Air National Guard (ANG) Personnel: 0
 - Reserve Personnel: 0
- Default Settings Used: Yes
- Average Personnel Round Trip Commute (mile): 20 (default)
- Personnel Work Schedule

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Active Duty Personnel:	5 Days Per Week (default)
Civilian Personnel:	5 Days Per Week (default)
Support Contractor Personnel:	5 Days Per Week (default)
Air National Guard (ANG) Personnel:	4 Days Per Week (default)
Reserve Personnel:	4 Days Per Month (default)

50.3 Personnel On Road Vehicle Mixture

- On Road Vehicle Mixture (%)

	LDGV	LDGT	HdGV	LDDV	LDDT	HDDV	MC
POVs	37.55	60.32	0	0.03	0.2	0	1.9
GOVs	54.49	37.73	4.67	0	0	3.11	0

50.4 Personnel Emission Factor(s)

- On Road Vehicle Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
LDGV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859
LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HdGV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007
LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

50.5 Personnel Formula(s)

- Personnel Vehicle Miles Travel for Work Days per Year

$$VMT_P = NP * WD * AC$$

VMT_P: Personnel Vehicle Miles Travel (miles/year)

NP: Number of Personnel

WD: Work Days per Year

AC: Average Commute (miles)

- Total Vehicle Miles Travel per Year

$$VMT_{Total} = VMT_{AD} + VMT_C + VMT_{SC} + VMT_{ANG} + VMT_{AFRC}$$

VMT_{Total}: Total Vehicle Miles Travel (miles)

VMT_{AD}: Active Duty Personnel Vehicle Miles Travel (miles)

VMT_C: Civilian Personnel Vehicle Miles Travel (miles)

VMT_{SC}: Support Contractor Personnel Vehicle Miles Travel (miles)

VMT_{ANG}: Air National Guard Personnel Vehicle Miles Travel (miles)

VMT_{AFRC}: Reserve Personnel Vehicle Miles Travel (miles)

- Vehicle Emissions per Year

$$V_{POL} = (VMT_{Total} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{Total}: Total Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Personnel On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

5.5	0.6	100	84	7.6	7.6			120390
-----	-----	-----	----	-----	-----	--	--	--------

51.4 Heating Formula(s)

- Heating Fuel Consumption ft³ per Year

$$FC_{HER} = HA * EI / HV / 1000000$$

FC_{HER}: Fuel Consumption for Heat Energy Requirement Method

HA: Area of floorspace to be heated (ft²)

EI: Energy Intensity Requirement (MMBtu/ft²)

HV: Heat Value (MMBTU/ft³)

1000000: Conversion Factor

- Heating Emissions per Year

$$HE_{POL} = FC * EF_{POL} / 2000$$

HE_{POL}: Heating Emission Emissions (TONs)

FC: Fuel Consumption

EF_{POL}: Emission Factor for Pollutant

2000: Conversion Factor pounds to tons

52. Construction / Demolition

52.1 General Information & Timeline Assumptions

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Construction and Demolition

- Activity Description:

- Activity Start Date

Start Month: 1

Start Month: 2022

- Activity End Date

Indefinite: False

End Month: 12

End Month: 2022

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.526940
SO _x	0.005198
NO _x	2.123360
CO	2.303931
PM 10	3.635660

Pollutant	Total Emissions (TONs)
PM 2.5	0.094714
Pb	0.000000
NH ₃	0.001988
CO _{2e}	506.5

52.1 Site Grading Phase

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

52.1.1 Site Grading Phase Timeline Assumptions

- Phase Start Date

Start Month: 1
 Start Quarter: 1
 Start Year: 2022

- Phase Duration

Number of Month: 1
 Number of Days: 0

52.1.2 Site Grading Phase Assumptions

- General Site Grading Information

Area of Site to be Graded (ft²): 322910
 Amount of Material to be Hauled On-Site (yd³): 0
 Amount of Material to be Hauled Off-Site (yd³): 0

- Site Grading Default Settings

Default Settings Used: Yes
 Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Graders Composite	1	8
Other Construction Equipment Composite	1	8
Rubber Tired Dozers Composite	1	8
Tractors/Loaders/Backhoes Composite	2	7

- Vehicle Exhaust

Average Hauling Truck Capacity (yd³): 20 (default)
 Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

52.1.3 Site Grading Phase Emission Factor(s)

- Construction Exhaust Emission Factors (lb/hour) (default)

Graders Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0806	0.0014	0.4657	0.5731	0.0217	0.0217	0.0072	132.92
Other Construction Equipment Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0507	0.0012	0.2785	0.3488	0.0105	0.0105	0.0045	122.61

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Rubber Tired Dozers Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.1919	0.0024	1.3611	0.7352	0.0536	0.0536	0.0173	239.51
Tractors/Loaders/Backhoes Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0383	0.0007	0.2301	0.3598	0.0095	0.0095	0.0034	66.884

- Vehicle Exhaust & Worker Trips Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
LDGV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859
LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HdGV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007
LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

52.1.4 Site Grading Phase Formula(s)

- Fugitive Dust Emissions per Phase

$$PM10_{FD} = (20 * ACRE * WD) / 2000$$

PM10_{FD}: Fugitive Dust PM 10 Emissions (TONs)

20: Conversion Factor Acre Day to pounds (20 lb / 1 Acre Day)

ACRE: Total acres (acres)

WD: Number of Total Work Days (days)

2000: Conversion Factor pounds to tons

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * EF_{POL}) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)

NE: Number of Equipment

WD: Number of Total Work Days (days)

H: Hours Worked per Day (hours)

EF_{POL}: Emission Factor for Pollutant (lb/hour)

2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = (HA_{OnSite} + HA_{OffSite}) * (1 / HC) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

HA_{OnSite}: Amount of Material to be Hauled On-Site (yd³)

HA_{OffSite}: Amount of Material to be Hauled Off-Site (yd³)

HC: Average Hauling Truck Capacity (yd³)

(1 / HC): Conversion Factor cubic yards to trips (1 trip / HC yd³)

HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Vehicle Exhaust On Road Vehicle Mixture (%)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)

WD: Number of Total Work Days (days)

WT: Average Worker Round Trip Commute (mile)

1.25: Conversion Factor Number of Construction Equipment to Number of Works

NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)

VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL} : Emission Factor for Pollutant (grams/mile)

VM: Worker Trips On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

52.2 Trenching/Excavating Phase

52.2.1 Trenching / Excavating Phase Timeline Assumptions

- Phase Start Date

Start Month: 2

Start Quarter: 1

Start Year: 2022

- Phase Duration

Number of Month: 1

Number of Days: 0

52.2.2 Trenching / Excavating Phase Assumptions

- General Trenching/Excavating Information

Area of Site to be Trenched/Excavated (ft²): 33000

Amount of Material to be Hauled On-Site (yd³): 0

Amount of Material to be Hauled Off-Site (yd³): 0

- Trenching Default Settings

Default Settings Used: Yes

Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Excavators Composite	2	8
Other General Industrial Equipmen Composite	1	8
Tractors/Loaders/Backhoes Composite	1	8

- Vehicle Exhaust

Average Hauling Truck Capacity (yd³): 20 (default)

Average Hauling Truck Round Trip Commute (mile): 20 (default)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

52.2.3 Trenching / Excavating Phase Emission Factor(s)

- Construction Exhaust Emission Factors (lb/hour) (default)

Graders Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0806	0.0014	0.4657	0.5731	0.0217	0.0217	0.0072	132.92
Other Construction Equipment Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0507	0.0012	0.2785	0.3488	0.0105	0.0105	0.0045	122.61
Rubber Tired Dozers Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.1919	0.0024	1.3611	0.7352	0.0536	0.0536	0.0173	239.51
Tractors/Loaders/Backhoes Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0383	0.0007	0.2301	0.3598	0.0095	0.0095	0.0034	66.884

- Vehicle Exhaust & Worker Trips Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
LDGV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859
LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HDCV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007
LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

52.2.4 Trenching / Excavating Phase Formula(s)

- Fugitive Dust Emissions per Phase

$$PM10_{FD} = (20 * ACRE * WD) / 2000$$

PM10_{FD}: Fugitive Dust PM 10 Emissions (TONs)
 20: Conversion Factor Acre Day to pounds (20 lb / 1 Acre Day)
 ACRE: Total acres (acres)
 WD: Number of Total Work Days (days)
 2000: Conversion Factor pounds to tons

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * EF_{POL}) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)
 NE: Number of Equipment
 WD: Number of Total Work Days (days)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

H: Hours Worked per Day (hours)
EF_{POL}: Emission Factor for Pollutant (lb/hour)
2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = (HA_{OnSite} + HA_{OffSite}) * (1 / HC) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)
HA_{OnSite}: Amount of Material to be Hauled On-Site (yd³)
HA_{OffSite}: Amount of Material to be Hauled Off-Site (yd³)
HC: Average Hauling Truck Capacity (yd³)
(1 / HC): Conversion Factor cubic yards to trips (1 trip / HC yd³)
HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)
0.002205: Conversion Factor grams to pounds
EF_{POL}: Emission Factor for Pollutant (grams/mile)
VM: Vehicle Exhaust On Road Vehicle Mixture (%)
2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)
WD: Number of Total Work Days (days)
WT: Average Worker Round Trip Commute (mile)
1.25: Conversion Factor Number of Construction Equipment to Number of Works
NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)
VMT_{VE}: Worker Trips Vehicle Miles Travel (miles)
0.002205: Conversion Factor grams to pounds
EF_{POL}: Emission Factor for Pollutant (grams/mile)
VM: Worker Trips On Road Vehicle Mixture (%)
2000: Conversion Factor pounds to tons

52.3 Building Construction Phase

52.3.1 Building Construction Phase Timeline Assumptions

- Phase Start Date

Start Month: 3
Start Quarter: 1
Start Year: 2022

- Phase Duration

Number of Month: 10
Number of Days: 0

52.3.2 Building Construction Phase Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- General Building Construction Information

Building Category: Office or Industrial
Area of Building (ft²): 101000
Height of Building (ft): 12
Number of Units: N/A

- Building Construction Default Settings

Default Settings Used: Yes
Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Cranes Composite	1	6
Forklifts Composite	2	6
Generator Sets Composite	1	8
Tractors/Loaders/Backhoes Composite	1	8
Welders Composite	3	8

- Vehicle Exhaust

Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

- Vendor Trips

Average Vendor Round Trip Commute (mile): 40 (default)

- Vendor Trips Vehicle Mixture (%)

	LDGV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

52.3.3 Building Construction Phase Emission Factor(s)

- Construction Exhaust Emission Factors (lb/hour) (default)

Cranes Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0797	0.0013	0.5505	0.3821	0.0203	0.0203	0.0071	128.81
Forklifts Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0274	0.0006	0.1265	0.2146	0.0043	0.0043	0.0024	54.457
Generator Sets Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0340	0.0006	0.2783	0.2694	0.0116	0.0116	0.0030	61.069
Tractors/Loaders/Backhoes Composite								

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0383	0.0007	0.2301	0.3598	0.0095	0.0095	0.0034	66.884
Welders Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0260	0.0003	0.1557	0.1772	0.0077	0.0077	0.0023	25.661

- Vehicle Exhaust & Worker Trips Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
LDGV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859
LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HdGV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007
LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

52.3.4 Building Construction Phase Formula(s)

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * EF_{POL}) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)

NE: Number of Equipment

WD: Number of Total Work Days (days)

H: Hours Worked per Day (hours)

EF_{POL}: Emission Factor for Pollutant (lb/hour)

2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = BA * BH * (0.42 / 1000) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

BA: Area of Building (ft²)

BH: Height of Building (ft)

(0.42 / 1000): Conversion Factor ft³ to trips (0.42 trip / 1000 ft³)

HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Worker Trips On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)

WD: Number of Total Work Days (days)

WT: Average Worker Round Trip Commute (mile)

1.25: Conversion Factor Number of Construction Equipment to Number of Works

NE: Number of Construction Equipment

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{WT} : Worker Trips Vehicle Miles Travel (miles)
0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
VM: Worker Trips On Road Vehicle Mixture (%)
2000: Conversion Factor pounds to tons

- Vender Trips Emissions per Phase

$$VMT_{VT} = BA * BH * (0.38 / 1000) * HT$$

VMT_{VT} : Vender Trips Vehicle Miles Travel (miles)
BA: Area of Building (ft²)
BH: Height of Building (ft)
(0.38 / 1000): Conversion Factor ft³ to trips (0.38 trip / 1000 ft³)
HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL} : Vehicle Emissions (TONs)
 VMT_{VT} : Vender Trips Vehicle Miles Travel (miles)
0.002205: Conversion Factor grams to pounds
 EF_{POL} : Emission Factor for Pollutant (grams/mile)
VM: Worker Trips On Road Vehicle Mixture (%)
2000: Conversion Factor pounds to tons

52.4 Architectural Coatings Phase

52.4.1 Architectural Coatings Phase Timeline Assumptions

- Phase Start Date

Start Month: 12
Start Quarter: 1
Start Year: 2022

- Phase Duration

Number of Month: 1
Number of Days: 0

52.4.2 Architectural Coatings Phase Assumptions

- General Architectural Coatings Information

Building Category: Non-Residential
Total Square Footage (ft²): 15200
Number of Units: N/A

- Architectural Coatings Default Settings

Default Settings Used: Yes
Average Day(s) worked per week: 5 (default)

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

	LDGV	LDGT	HDGV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

52.4.3 Architectural Coatings Phase Emission Factor(s)

- Worker Trips Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
LDGV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859
LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HDGV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007
LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

52.4.4 Architectural Coatings Phase Formula(s)

- Worker Trips Emissions per Phase

$$VMT_{WT} = (1 * WT * PA) / 800$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)

1: Conversion Factor man days to trips (1 trip / 1 man * day)

WT: Average Worker Round Trip Commute (mile)

PA: Paint Area (ft²)

800: Conversion Factor square feet to man days (1 ft² / 1 man * day)

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Worker Trips On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

- Off-Gassing Emissions per Phase

$$VOC_{AC} = (AB * 2.0 * 0.0116) / 2000.0$$

VOC_{AC}: Architectural Coating VOC Emissions (TONs)

BA: Area of Building (ft²)

2.0: Conversion Factor total area to coated area (2.0 ft² coated area / total area)

0.0116: Emission Factor (lb/ft²)

2000: Conversion Factor pounds to tons

52.5 Paving Phase

52.5.1 Paving Phase Timeline Assumptions

- Phase Start Date

Start Month: 12

Start Quarter: 1

Start Year: 2022

- Phase Duration

Number of Month: 1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Days: 0

52.5.2 Paving Phase Assumptions

- General Paving Information

Paving Area (ft²): 244000

- Paving Default Settings

Default Settings Used: Yes
Average Day(s) worked per week: 5 (default)

- Construction Exhaust (default)

Equipment Name	Number Of Equipment	Hours Per Day
Pavers Composite	1	8
Paving Equipment Composite	2	6
Rollers Composite	2	6

- Vehicle Exhaust

Average Hauling Truck Round Trip Commute (mile): 20 (default)

- Vehicle Exhaust Vehicle Mixture (%)

	LDCV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	0	0	0	0	0	100.00	0

- Worker Trips

Average Worker Round Trip Commute (mile): 20 (default)

- Worker Trips Vehicle Mixture (%)

	LDCV	LDGT	HDCV	LDDV	LDDT	HDDV	MC
POVs	50.00	50.00	0	0	0	0	0

52.5.3 Paving Phase Emission Factor(s)

- Construction Exhaust Emission Factors (lb/hour) (default)

Graders Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0806	0.0014	0.4657	0.5731	0.0217	0.0217	0.0072	132.92
Other Construction Equipment Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0507	0.0012	0.2785	0.3488	0.0105	0.0105	0.0045	122.61
Rubber Tired Dozers Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.1919	0.0024	1.3611	0.7352	0.0536	0.0536	0.0173	239.51
Tractors/Loaders/Backhoes Composite								
	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CH ₄	CO _{2e}
Emission Factors	0.0383	0.0007	0.2301	0.3598	0.0095	0.0095	0.0034	66.884

- Vehicle Exhaust & Worker Trips Emission Factors (grams/mile)

	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	Pb	NH ₃	CO _{2e}
LDCV	000.265	000.002	000.200	003.208	000.006	000.005		000.023	00325.859
LDGT	000.340	000.003	000.357	004.561	000.008	000.007		000.024	00421.180
HDCV	000.737	000.005	000.984	015.455	000.018	000.016		000.045	00783.227
LDDV	000.095	000.003	000.134	002.768	000.004	000.004		000.008	00318.007

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

LDDT	000.236	000.004	000.383	004.740	000.007	000.006		000.008	00451.951
HDDV	000.440	000.013	004.473	001.638	000.165	000.152		000.028	01512.371
MC	002.730	000.003	000.697	012.599	000.026	000.023		000.054	00395.818

52.5.4 Paving Phase Formula(s)

- Construction Exhaust Emissions per Phase

$$CEE_{POL} = (NE * WD * H * EF_{POL}) / 2000$$

CEE_{POL}: Construction Exhaust Emissions (TONs)

NE: Number of Equipment

WD: Number of Total Work Days (days)

H: Hours Worked per Day (hours)

EF_{POL}: Emission Factor for Pollutant (lb/hour)

2000: Conversion Factor pounds to tons

- Vehicle Exhaust Emissions per Phase

$$VMT_{VE} = PA * 0.25 * (1 / 27) * (1 / HC) * HT$$

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

PA: Paving Area (ft²)

0.25: Thickness of Paving Area (ft)

(1 / 27): Conversion Factor cubic feet to cubic yards (1 yd³ / 27 ft³)

HC: Average Hauling Truck Capacity (yd³)

(1 / HC): Conversion Factor cubic yards to trips (1 trip / HC yd³)

HT: Average Hauling Truck Round Trip Commute (mile/trip)

$$V_{POL} = (VMT_{VE} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{VE}: Vehicle Exhaust Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Vehicle Exhaust On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

- Worker Trips Emissions per Phase

$$VMT_{WT} = WD * WT * 1.25 * NE$$

VMT_{WT}: Worker Trips Vehicle Miles Travel (miles)

WD: Number of Total Work Days (days)

WT: Average Worker Round Trip Commute (mile)

1.25: Conversion Factor Number of Construction Equipment to Number of Works

NE: Number of Construction Equipment

$$V_{POL} = (VMT_{WT} * 0.002205 * EF_{POL} * VM) / 2000$$

V_{POL}: Vehicle Emissions (TONs)

VMT_{VE}: Worker Trips Vehicle Miles Travel (miles)

0.002205: Conversion Factor grams to pounds

EF_{POL}: Emission Factor for Pollutant (grams/mile)

VM: Worker Trips On Road Vehicle Mixture (%)

2000: Conversion Factor pounds to tons

- Off-Gassing Emissions per Phase

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$\text{VOC}_p = (2.62 * \text{PA}) / 43560$$

VOC_p: Paving VOC Emissions (TONs)

2.62: Emission Factor (lb/acre)

PA: Paving Area (ft²)

43560: Conversion Factor square feet to acre (43560 ft² / acre) / acre)

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF CONFORMITY ANALYSIS (ROCA)

1. General Information: The Air Force's Air Conformity Applicability Model (ACAM) was used to perform an analysis to assess the potential air quality impact/s associated with the action in accordance with the Air Force Manual 32-7002, Environmental Compliance and Pollution Prevention; the Environmental Impact Analysis Process (EIAP, 32 CFR 989); and the General Conformity Rule (GCR, 40 CFR 93 Subpart B). This report provides a summary of the ACAM analysis.

a. Action Location:

Base: RANDOLPH AFB
State: Texas
County(s): Bexar
Regulatory Area(s): San Antonio, TX

b. Action Title: Recapitalization of the T-38 Trainer At Randolph AFB - Alternative 3 (Bexar County and Guadalupe County ROIs)

c. Project Number/s (if applicable):

d. Projected Action Start Date: 1 / 2022

e. Action Description:

The proposed action encompasses the recapitalize of the T-38 flight-training program with newer and more capable T-7A aircraft at JBSA-Randolph and Lackland. In addition to the phased introduction of the T-7A aircraft, five military construction projects and 17 facilities sustainment, restoration, and modernization projects are proposed at JBSA-Randolph at JBSA-Lackland to provide modern facilities and infrastructure to support the T-7A aircraft's maintenance, training, and operational requirements. The number of personnel on JBSA-Randolph would increase due to the proposed aircraft recapitalization. No changes to airspace configurations (i.e., size, shape, or location) would be required to support the proposed operations of the T-7A aircraft; however, the T-7A aircraft may have more flight operations than occurs with the T 38C aircraft at both JBSA-Randolph and JBSA-Lackland. This Applicability Analysis present the worst-case of three aircraft operational intensities as the worst-case action alternatives for the Proposed Action.

A Conformity Evaluation is required for every proposed action that will occur within an area designated by the U.S. Environmental Protection Agency (EPA) as nonattainment or maintenance for any National Ambient Air Quality Standard (NAAQS). The proposed T-7A Recapitalization action will occur at both JBSA-Randolph AFB and JBSA-Lackland AFB which both fall entirely within Bexar County that has been designated by the U.S. Environmental Protection Agency (EPA) as a marginal nonattainment area for the 2015 Ozone NAAQS in 2018. Given this recent designation of Bexar County, the proposed action (as well as all proposed actions from federal agencies) are subject to the General Conformity Rule (GCR, 40 CFR 93 Subpart B). As a marginal nonattainment area for ozone, the GCR has established de minimis significance threshold values of less than 100 ton/yr (for any given year) for both nitrogen oxides (NO_x) and volatile organic compounds (VOC).

f. Point of Contact:

Name: [REDACTED]
Title: NEPA Contract Support
Organization: [REDACTED]
Email:
Phone Number:

2. Analysis: Total combined direct and indirect emissions associated with the action were estimated through ACAM on a calendar-year basis for the "worst-case" and "steady state" (net gain/loss upon action fully implemented) emissions. General Conformity under the Clean Air Act, Section 1.76 has been evaluated for the action described above according to the requirements of 40 CFR 93, Subpart B.

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF CONFORMITY ANALYSIS (ROCA)

CO	50.754		
SO _x	2.824		
PM 10	-0.146		
PM 2.5	0.370		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	8821.0		

2026

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	33.011	100	No
NO _x	83.751	100	No
CO	73.426		
SO _x	4.384		
PM 10	-0.279		
PM 2.5	0.528		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	13004.4		

2027

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	50.110	100	No
NO _x	136.064	100	Yes
CO	72.354		
SO _x	6.802		
PM 10	-1.606		
PM 2.5	0.015		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	19455.4		

2028

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	63.491	100	No
NO _x	180.234	100	Yes
CO	52.870		
SO _x	8.572		
PM 10	-3.216		
PM 2.5	-0.760		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	24065.6		

2029

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF CONFORMITY ANALYSIS (ROCA)

San Antonio, TX			
VOC	61.213	100	No
NO _x	184.804	100	Yes
CO	6.574		
SO _x	8.377		
PM 10	-4.531		
PM 2.5	-1.676		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	23512.4		

2030

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	56.451	100	No
NO _x	186.486	100	Yes
CO	-58.412		
SO _x	7.887		
PM 10	-6.264		
PM 2.5	-2.924		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	22157.8		

2031

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	45.743	100	No
NO _x	183.388	100	Yes
CO	-176.695		
SO _x	6.692		
PM 10	-9.259		
PM 2.5	-5.118		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	18876.4		

2032

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	54.755	100	No
NO _x	197.792	100	Yes
CO	-122.025		
SO _x	7.964		
PM 10	-8.254		
PM 2.5	-4.384		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	22393.2		

AIR CONFORMITY APPLICABILITY MODEL REPORT RECORD OF CONFORMITY ANALYSIS (ROCA)

2033 - (Steady State)

Pollutant	Action Emissions (ton/yr)	GENERAL CONFORMITY	
		Threshold (ton/yr)	Exceedance (Yes or No)
San Antonio, TX			
VOC	54.755	100	No
NO _x	197.792	100	Yes
CO	-122.025		
SO _x	7.964		
PM 10	-8.254		
PM 2.5	-4.384		
Pb	0.000		
NH ₃	0.042		
CO _{2e}	22393.2		

Some estimated emissions associated with this action are above the conformity threshold values established at 40 CFR 93.153 (b); Therefore, the requirements of the General Conformity Rule are applicable.

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

1. General Information

- Action Location

Base: RANDOLPH AFB
State: Texas
County(s): Bexar
Regulatory Area(s): San Antonio, TX

- Action Title: Recapitalization of the T-38 Trainer At Randolph AFB - Alternative 3

- Project Number/s (if applicable):

- Projected Action Start Date: 1 / 2022

- Action Purpose and Need:

The T 38 Talon is a twin-engine, high-altitude, supersonic jet used by the USAF and other nations for pilot training. The aircraft originally was developed in the 1950s with production occurring between 1961 and 1972. The fleet has undergone periodic upgrades overtime. In 2001, the USAF upgraded several hundred T 38s with modern avionics and replaced propulsion components to provide increased performance and superior reliability.

The purpose of the Proposed Action is to allow the USAF T-7A to provide more efficient and effective pilot training to establish a T-7A pilot pipeline to allow for the transition to T-7A training throughout the entire USAF.

- Action Description:

The proposed action encompasses the recapitalize of the T-38 flight-training program with newer and more capable T-7A aircraft at JBSA-Randolph and Lackland. In addition to the phased introduction of the T-7A aircraft, five military construction projects and 17 facilities sustainment, restoration, and modernization projects are proposed at JBSA-Randolph at JBSA-Lackland to provide modern facilities and infrastructure to support the T-7A aircraft's maintenance, training, and operational requirements. The number of personnel on JBSA-Randolph would increase due to the proposed aircraft recapitalization. No changes to airspace configurations (i.e., size, shape, or location) would be required to support the proposed operations of the T-7A aircraft; however, the T-7A aircraft may have more flight operations than occurs with the T 38C aircraft at both JBSA-Randolph and JBSA-Lackland. This Applicability Analysis present the worst-case of three aircraft operational intensities as the worst-case action alternatives for the Proposed Action.

A Conformity Evaluation is required for every proposed action that will occur within an area designated by the U.S. Environmental Protection Agency (EPA) as nonattainment or maintenance for any National Ambient Air Quality Standard (NAAQS). The proposed T-7A Recapitalization action will occur at both JBSA-Randolph AFB and JBSA-Lackland AFB which both fall entirely within Bexar County that has been designated by the U.S. Environmental Protection Agency (EPA) as a marginal nonattainment area for the 2015 Ozone NAAQS in 2018. Given this recent designation of Bexar County, the proposed action (as well as all proposed actions from federal agencies) are subject to the General Conformity Rule (GCR, 40 CFR 93 Subpart B). As a marginal nonattainment area for ozone, the GCR has established de minimis significance threshold values of less than 100 ton/yr (for any given year) for both nitrogen oxides (NOx) and volatile organic compounds (VOC).

- Point of Contact

Name: [REDACTED]
Title: NEPA Contract Support
Organization: [REDACTED]
Email:
Phone Number:

- Activity List:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Activity Type		Activity Title
2.	Aircraft	T-7As and 759 LTOs
3.	Aircraft	T-7A Increase 1702 TGOs
4.	Aircraft	T-38 Removal 5 TGOs
5.	Aircraft	Add 10 T-7As and 1849 LTOs
6.	Aircraft	Increase T-7A TGOs
7.	Aircraft	Remove 11 T-38s and 2766 LTOs
8.	Aircraft	Remove 6142 T-38 TGOs
9.	Aircraft	Add 8 new T-7As and 3545 LTOs
10.	Aircraft	Increase T-7A TGOs by 7993
11.	Aircraft	Remove 6 T-38s and reduce LTOs by 1534
12.	Aircraft	Decrease T-38 TGOs by 3394
13.	Aircraft	Add T-7As and increase LTOs by 3361
14.	Aircraft	Increase T-7A TGOs by 7550
15.	Aircraft	Remove T-38s and decrease LTOs by 3767
16.	Aircraft	Decrease T-38 TGOs by 8,328
17.	Aircraft	Add 19 new T-7As and increase LTOs by 6148
18.	Aircraft	Increase T-7A TGOs by 13690
19.	Aircraft	Remove 21 T-38s and decrease LTOs by 3,667
20.	Aircraft	Decrease T-38 TGOs by 8093
21.	Aircraft	Add T-7As and increase LTOs by 5372
22.	Aircraft	Increase T-7A TGOs by 11908
23.	Aircraft	Remove T-38s and decrease LTOs by 1445
24.	Aircraft	Decrease T-38 TGOs by 3193
25.	Aircraft	Add T-7As and increase LTOs by 630
26.	Aircraft	Increase T-7A TGOs by 1447
27.	Aircraft	Remove T-38s and decrease LTOs by 1715
28.	Aircraft	Decrease T-38 TGOs by 3792
29.	Aircraft	Increase T-7 LTOs by 326
30.	Aircraft	Increase T-7 TGOs by 737
31.	Aircraft	Remove 14 T-38s and decrease LTOs by 2636
32.	Aircraft	2031 T-38 Removal 5840 TGOs
33.	Aircraft	decrease T-7A LTOs by 130
34.	Aircraft	decrease T-7A TGOs by 280
35.	Aircraft	Increase T-7 LTOs by 1553
36.	Aircraft	Increase T-7A TGOs by 3436
37.	Aircraft	2023 T-7A Increase Trim Test and Test Cell
38.	Aircraft	2024 T-7A Increase Trim Test and Engine Test Cell
39.	Aircraft	2025 T-38 Removal Trim Test and Test Cell
40.	Aircraft	2025 T-7A Increase Trim Test and Test Cell
41.	Aircraft	2026 T-38 Removal Trim Test and Test Cell
42.	Aircraft	2026 T-7A Increase Trim Test and Engine Test Cell
43.	Aircraft	2027 T-38 Removal Trim Test and Test Cell
44.	Aircraft	2027 T-7A Increase Trim Test and Test Cell
45.	Aircraft	2028 T-38 Removal Trim Test and Test Cell
46.	Aircraft	2028 T-7A Increase Trim Test and Test Cell
47.	Aircraft	2029 T-38 Removal Trim Test and Test Cell
48.	Aircraft	2030 T-38 Removal Trim Test and Test Cell
49.	Aircraft	2031 T-38 Removal Trim Test and Test Cell
50.	Personnel	2023 Increase 303 Personnel INDEFINITE
51.	Heating	2023 Heating for Buildings INDEFINITE
52.	Construction / Demolition	Construction and Demolition

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Emission factors and air emission estimating methods come from the United States Air Force's Air Emissions Guide for Air Force Stationary Sources, Air Emissions Guide for Air Force Mobile Sources, and Air Emissions Guide for Air Force Transitory Sources.

2. Aircraft

2.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: T-7As and 759 LTOs

- Activity Description:

Starting in 2023 add T-7As, and increase 759 LTOs

- Activity Start Date

Start Month: 1

Start Year: 2023

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	3.503273
SO _x	0.251578
NO _x	2.428146
CO	18.804690
PM 10	0.316361

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.283894
Pb	0.000000
NH ₃	0.000000
CO _{2e}	591.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	3.503273
SO _x	0.251578
NO _x	2.428146
CO	18.804690
PM 10	0.316361

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.283894
Pb	0.000000
NH ₃	0.000000
CO _{2e}	591.2

2.2 Aircraft & Engines

2.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

2.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

2.3 Flight Operations

2.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	8
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	759
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	9.74
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

2.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

2.4 Auxiliary Power Unit (APU)

2.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

2.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

2.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

3. Aircraft

3.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: T-7A Increase 1702 TGOs

- Activity Description:

Starting in 2023 add 8 new T-7As, and increase 1702 TGOs

- Activity Start Date

Start Month: 1

Start Year: 2023

- Activity End Date

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.342963
SO _x	0.184232
NO _x	3.970197
CO	0.483741
PM 10	0.023115

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.020009
Pb	0.000000
NH ₃	0.000000
CO _{2e}	556.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.342963
SO _x	0.184232
NO _x	3.970197
CO	0.483741
PM 10	0.023115

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.020009
Pb	0.000000
NH ₃	0.000000
CO _{2e}	556.8

3.2 Aircraft & Engines

3.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

3.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

3.3 Flight Operations

3.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 8
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1702
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

3.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

3.4 Auxiliary Power Unit (APU)

3.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

3.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

3.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

4. Aircraft

4.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

- Activity Title: T-38 Removal 5 TGOs

- Activity Description:

Starting in 2024, remove 5 T-38 TGOs

- Activity Start Date

Start Month: 1
 Start Year: 2024

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.000748
SO _x	-0.000244
NO _x	-0.000314
CO	-0.013707
PM 10	-0.000401

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.000162
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-0.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.000748
SO _x	-0.000244
NO _x	-0.000314
CO	-0.013707
PM 10	-0.000401

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.000162
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-0.7

4.2 Aircraft & Engines

4.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No
 - Original Aircraft Name:
 - Original Engine Name:

4.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

4.3 Flight Operations

4.3.1 Flight Operations Assumptions

- Flight Operations
 - Number of Aircraft: 91
 - Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 5
 - Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 - Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)
 - Taxi/Idle Out [Idle] (mins): 0
 - Takeoff [Military] (mins): 0.64
 - Takeoff [After Burn] (mins): 0
 - Climb Out [Intermediate] (mins): 0.47
 - Approach [Approach] (mins): 0.98
 - Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test
 - Idle (mins): 12
 - Approach (mins): 27
 - Intermediate (mins): 9
 - Military (mins): 9
 - AfterBurn (mins): 3

4.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year
 $AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

4.4 Auxiliary Power Unit (APU)

4.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

4.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

4.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

5. Aircraft

5.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Add 10 T-7As and 1849 LTOs

- Activity Description:

Starting in 2024 add 10 new T-7As, and increase 1849 LTO

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Start Date

Start Month: 1
Start Year: 2024

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	8.534325
SO _x	0.612868
NO _x	5.915206
CO	45.810107
PM 10	0.770688

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.691594
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1440.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	8.534325
SO _x	0.612868
NO _x	5.915206
CO	45.810107
PM 10	0.770688

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.691594
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1440.2

5.2 Aircraft & Engines

5.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

5.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

5.3 Flight Operations

5.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 10
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1849

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	9.74
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

5.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

5.4 Auxiliary Power Unit (APU)

5.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

5.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

5.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

6. Aircraft

6.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs

- Activity Description:

Starting in 2024 Increase T-7A TGOs 4086

- Activity Start Date

Start Month: 1

Start Year: 2024

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.828461
SO _x	0.559758
NO _x	10.236108
CO	1.707821
PM 10	0.055493

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.048035
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1715.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.828461
SO _x	0.559758
NO _x	10.236108
CO	1.707821
PM 10	0.055493

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.048035
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1715.0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

6.2 Aircraft & Engines

6.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

6.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

6.3 Flight Operations

6.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 10
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 4086
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.64
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.47
Approach [Approach] (mins): 0.98
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

6.3.2 Flight Operations Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

6.4 Auxiliary Power Unit (APU)

6.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

6.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

6.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

7. Aircraft

7.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Title: Remove 11 T-38s and 2766 LTOs

- Activity Description:

Starting in 2025 remove T-38s and 2766LTOs

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-9.385351
SO _x	-0.804943
NO _x	-1.527347
CO	-100.458667
PM 10	-2.514388

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.020929
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2114.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-9.385351
SO _x	-0.804943
NO _x	-1.527347
CO	-100.458667
PM 10	-2.514388

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.020929
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2114.5

7.2 Aircraft & Engines

7.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C

Engine Model: J85-GE-5R

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

7.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234
------------	---------	------	------	------	-------	------	------	------

7.3 Flight Operations

7.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	11
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	2766
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	12.8
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

7.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

7.4 Auxiliary Power Unit (APU)

7.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

7.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

7.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

8. Aircraft

8.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Remove 6142 T-38 TGOs

- Activity Description:

Starting in 2025, remove 6142 T-38 TGOs

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.918521
SO _x	-0.300318
NO _x	-0.385904
CO	-16.838007
PM 10	-0.492938

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.198506
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-907.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Pollutant	Emissions Per Year (TONs)
VOC	-0.918521
SO _x	-0.300318
NO _x	-0.385904
CO	-16.838007
PM 10	-0.492938

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.198506
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-907.7

8.2 Aircraft & Engines

8.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

8.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

8.3 Flight Operations

8.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 14
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 6142
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.64
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.47
 Approach [Approach] (mins): 0.98
 Taxi/Idle In [Idle] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

8.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

8.4 Auxiliary Power Unit (APU)

8.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

8.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

8.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

9. Aircraft

9.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Add 8 new T-7As and 3545 LTOs

- Activity Description:

Starting in 2025, add 8 new T-7As and 3545 LTOs

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	16.362456
SO _x	1.175023
NO _x	11.340944
CO	87.829546
PM 10	1.477604

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.325960
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2761.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	16.362456
SO _x	1.175023
NO _x	11.340944
CO	87.829546
PM 10	1.477604

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.325960
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2761.3

9.2 Aircraft & Engines

9.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Engine Name:

9.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

9.3 Flight Operations

9.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	7
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	3545
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	9.74
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

9.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

9.4 Auxiliary Power Unit (APU)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

9.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

9.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

9.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

10. Aircraft

10.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs by 7993

- Activity Description:

Starting in 2025, increase T-7A TGOs by 7993

- Activity Start Date

Start Month: 1

Start Year: 2025

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.620630
SO _x	1.094995
NO _x	20.023791
CO	3.340825
PM 10	0.108554

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.093966
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3354.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.620630
SO _x	1.094995
NO _x	20.023791
CO	3.340825
PM 10	0.108554

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.093966
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3354.8

10.2 Aircraft & Engines

10.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

10.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

10.3 Flight Operations

10.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 7
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 7993
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.64
 Takeoff [After Burn] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

10.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AE_{TCO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

10.4 Auxiliary Power Unit (APU)

10.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

10.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

10.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

LTO: Number of LTOs
 EFPOL: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

11. Aircraft

11.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove
- Activity Location
 - County: Bexar
 - Regulatory Area(s): San Antonio, TX
- Activity Title: Remove 6 T-38s and reduce LTOs by 1534
- Activity Description:
 - Starting in 2026, remove 6 T-38s and reduce LTOs by 1534
- Activity Start Date
 - Start Month: 1
 - Start Year: 2026
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-5.205036
SO _x	-0.446415
NO _x	-0.847053
CO	-55.713520
PM 10	-1.394458

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.120790
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1172.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-5.205036
SO _x	-0.446415
NO _x	-0.847053
CO	-55.713520
PM 10	-1.394458

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.120790
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1172.7

11.2 Aircraft & Engines

11.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-38C
 - Engine Model: J85-GE-5R
 - Primary Function: Trainer
 - Aircraft has After burn: Yes

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

11.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

11.3 Flight Operations

11.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 7
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1534
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 12.8
 Takeoff [Military] (mins): 0.41
 Takeoff [After Burn] (mins): 0.39
 Climb Out [Intermediate] (mins): 0.91
 Approach [Approach] (mins): 1.74
 Taxi/Idle In [Idle] (mins): 6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
 Approach (mins): 27
 Intermediate (mins): 9
 Military (mins): 9
 AfterBurn (mins): 3

11.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

11.4 Auxiliary Power Unit (APU)

11.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

11.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

11.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

12. Aircraft

12.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Decrease T-38 TGOs by 3394

- Activity Description:

Starting in 2026, decrease T-38 TGOs by 3394

- Activity Start Date

Start Month: 1

Start Year: 2026

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.507564
SO _x	-0.165952
NO _x	-0.213246
CO	-9.304493
PM 10	-0.272392

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.109692
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-501.6

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.507564
SO _x	-0.165952
NO _x	-0.213246
CO	-9.304493
PM 10	-0.272392

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.109692
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-501.6

12.2 Aircraft & Engines

12.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

12.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

12.3 Flight Operations

12.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3394
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.64
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.47
Approach [Approach] (mins): 0.98
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

12.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

12.4 Auxiliary Power Unit (APU)

12.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

12.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

12.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

13. Aircraft

13.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Add T-7As and increase LTOs by 3361

- Activity Description:

Starting in 2026, add T-7As and increase LTOs by 3361

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	15.513178
SO _x	1.114035
NO _x	10.752302
CO	83.270833
PM 10	1.400910

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.257137
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2618.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	15.513178
SO _x	1.114035
NO _x	10.752302
CO	83.270833
PM 10	1.400910

Pollutant	Emissions Per Year (TONs)
PM 2.5	1.257137
Pb	0.000000
NH ₃	0.000000
CO _{2e}	2618.0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

13.2 Aircraft & Engines

13.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

13.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

13.3 Flight Operations

13.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3361
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 9.74
Takeoff [Military] (mins): 0.41
Takeoff [After Burn] (mins): 0.39
Climb Out [Intermediate] (mins): 0.91
Approach [Approach] (mins): 1.74
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

13.3.2 Flight Operations Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

13.4 Auxiliary Power Unit (APU)

13.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

13.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

13.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

14. Aircraft

14.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs by 7550

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Description:

Starting in 2026, increase T-7A TGOs by 7550

- Activity Start Date

Start Month: 1

Start Year: 2026

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.530809
SO _x	1.034306
NO _x	18.914003
CO	3.155665
PM 10	0.102538

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.088758
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3168.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.530809
SO _x	1.034306
NO _x	18.914003
CO	3.155665
PM 10	0.102538

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.088758
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3168.9

14.2 Aircraft & Engines

14.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

14.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

14.3 Flight Operations

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

14.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	7550
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

14.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

14.4 Auxiliary Power Unit (APU)

14.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

14.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

14.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

15. Aircraft

15.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Remove T-38s and decrease LTOs by 3767

- Activity Description:

Starting in 2027, remove T-38s and decrease LTOs by 3,767

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-12.781857
SO _x	-1.096248
NO _x	-2.080085
CO	-136.814100
PM 10	-3.424331

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.752292
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2879.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-12.781857

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.752292

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

SO _x	-1.096248
NO _x	-2.080085
CO	-136.814100
PM 10	-3.424331

Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2879.8

15.2 Aircraft & Engines

15.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

15.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

15.3 Flight Operations

15.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 16
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3767
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 12.8
 Takeoff [Military] (mins): 0.41
 Takeoff [After Burn] (mins): 0.39
 Climb Out [Intermediate] (mins): 0.91
 Approach [Approach] (mins): 1.74
 Taxi/Idle In [Idle] (mins): 6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

15.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

15.4 Auxiliary Power Unit (APU)

15.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

15.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

15.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

16. Aircraft

16.1 General Information & Timeline Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar
Regulatory Area(s): San Antonio, TX

- Activity Title: Decrease T-38 TGOs by 8,328

- Activity Description:

Starting in 2027, decrease T-38 TGOs by 8,328

- Activity Start Date

Start Month: 1
Start Year: 2027

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.245432
SO _x	-0.407204
NO _x	-0.523251
CO	-22.830824
PM 10	-0.668380

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.269156
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1230.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.245432
SO _x	-0.407204
NO _x	-0.523251
CO	-22.830824
PM 10	-0.668380

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.269156
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1230.7

16.2 Aircraft & Engines

16.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

16.2.2 Aircraft & Engines Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

16.3 Flight Operations

16.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	16
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	8328
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

16.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

16.4 Auxiliary Power Unit (APU)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

16.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

16.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

16.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

17. Aircraft

17.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Add 19 new T-7As and increase LTOs by 6148

- Activity Description:

Starting in 2027, add 19 new T-7As and increase LTOs by 6148

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
-----------	---------------------------

Pollutant	Emissions Per Year (TONs)
-----------	---------------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

VOC	28.376976
SO _x	2.037812
NO _x	19.668300
CO	152.320465
PM 10	2.562569

PM 2.5	2.299578
Pb	0.000000
NH ₃	0.000000
CO _{2e}	4788.8

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	28.376976
SO _x	2.037812
NO _x	19.668300
CO	152.320465
PM 10	2.562569

Pollutant	Emissions Per Year (TONs)
PM 2.5	2.299578
Pb	0.000000
NH ₃	0.000000
CO _{2e}	4788.8

17.2 Aircraft & Engines

17.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

17.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

17.3 Flight Operations

17.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 19
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 6148
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 9.74
 Takeoff [Military] (mins): 0.41
 Takeoff [After Burn] (mins): 0.39
 Climb Out [Intermediate] (mins): 0.91
 Approach [Approach] (mins): 1.74

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

17.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
 AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
 AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

17.4 Auxiliary Power Unit (APU)

17.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

17.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

17.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to tons

18. Aircraft

18.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs by 13690

- Activity Description:

Starting in 2027, increase T-7A TGOs by 13690

- Activity Start Date

Start Month: 1

Start Year: 2027

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	2.775731
SO _x	1.875451
NO _x	34.295722
CO	5.721994
PM 10	0.185926

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.160940
Pb	0.000000
NH ₃	0.000000
CO _{2e}	5745.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	2.775731
SO _x	1.875451
NO _x	34.295722
CO	5.721994
PM 10	0.185926

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.160940
Pb	0.000000
NH ₃	0.000000
CO _{2e}	5745.9

18.2 Aircraft & Engines

18.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

18.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

18.3 Flight Operations

18.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	19
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	13690
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

18.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

18.4 Auxiliary Power Unit (APU)

18.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

18.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

18.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

19. Aircraft

19.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Remove 21 T-38s and decrease LTOs by 3,667

- Activity Description:

Starting in 2028, remove 21 T-38s and decrease LTOs by 3,667

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-12.476477
SO _x	-1.070056
NO _x	-2.030388
CO	-133.545380
PM 10	-3.342518

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.686535
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2811.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-12.476477
SO _x	-1.070056
NO _x	-2.030388
CO	-133.545380
PM 10	-3.342518

Pollutant	Emissions Per Year (TONs)
PM 2.5	-2.686535
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2811.0

19.2 Aircraft & Engines

19.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

19.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

19.3 Flight Operations

19.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 21
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3677
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	12.8
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

19.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

19.4 Auxiliary Power Unit (APU)

19.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

19.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

19.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

- APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
- APU: Number of Auxiliary Power Units
- OH: Operation Hours for Each LTO (hour)
- LTO: Number of LTOs
- EF_{POL}: Emission Factor for Pollutant (lb/hr)
- 2000: Conversion Factor pounds to tons

20. Aircraft

20.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar
Regulatory Area(s): San Antonio, TX

- Activity Title: Decrease T-38 TGOs by 8093

- Activity Description:

Starting in 2028, decrease T-38 TGOs by 8093

- Activity Start Date

Start Month: 1
Start Year: 2028

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-1.210288
SO _x	-0.395714
NO _x	-0.508486
CO	-22.186583
PM 10	-0.649520

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.261561
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1196.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-1.210288
SO _x	-0.395714
NO _x	-0.508486
CO	-22.186583
PM 10	-0.649520

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.261561
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1196.0

20.2 Aircraft & Engines

20.2.1 Aircraft & Engines Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

20.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

20.3 Flight Operations

20.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 21
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 8093
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.64
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.47
 Approach [Approach] (mins): 0.98
 Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
 Approach (mins): 27
 Intermediate (mins): 9
 Military (mins): 9
 AfterBurn (mins): 3

20.3.2 Flight Operations Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
 AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
 AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
 AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
 AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
 AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

20.4 Auxiliary Power Unit (APU)

20.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

20.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

20.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

21. Aircraft

21.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

- Activity Title: Add T-7As and increase LTOs by 5372

- Activity Description:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Starting in 2028, add T-7As and increase LTOs by 5372

- Activity Start Date

Start Month: 1
Start Year: 2028

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	24.788522
SO _x	1.626155
NO _x	16.259099
CO	132.376085
PM 10	2.239122

Pollutant	Emissions Per Year (TONs)
PM 2.5	2.009325
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3687.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	24.788522
SO _x	1.626155
NO _x	16.259099
CO	132.376085
PM 10	2.239122

Pollutant	Emissions Per Year (TONs)
PM 2.5	2.009325
Pb	0.000000
NH ₃	0.000000
CO _{2e}	3687.2

21.2 Aircraft & Engines

21.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

21.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

21.3 Flight Operations

21.3.1 Flight Operations Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations

Number of Aircraft:	14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	5372
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	9.74
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

21.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

21.4 Auxiliary Power Unit (APU)

21.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: No

- Auxiliary Power Unit (APU)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

21.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

21.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

22. Aircraft

22.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs by 11908

- Activity Description:

Starting in 2028, increase T-7A TGOs by 11908

- Activity Start Date

Start Month: 1

Start Year: 2028

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	2.414420
SO _x	1.631327
NO _x	29.831516
CO	4.977174
PM 10	0.161724

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.139991
Pb	0.000000
NH ₃	0.000000
CO _{2e}	4998.0

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	2.414420
SO _x	1.631327
NO _x	29.831516
CO	4.977174

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.139991
Pb	0.000000
NH ₃	0.000000
CO _{2e}	4998.0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

PM 10	0.161724
-------	----------

--	--

22.2 Aircraft & Engines

22.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

22.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

22.3 Flight Operations

22.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 14
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 11908
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.64
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.47
Approach [Approach] (mins): 0.98
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

22.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

22.4 Auxiliary Power Unit (APU)

22.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

22.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

22.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

23. Aircraft

23.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- **Activity Title:** Remove T-38s and decrease LTOs by 1445

- **Activity Description:**

Starting in 2029 T-38s and decrease LTOs by 1445

- **Activity Start Date**

Start Month: 1

Start Year: 2029

- **Activity End Date**

Indefinite: Yes

End Month: N/A

End Year: N/A

- **Activity Emissions:**

Pollutant	Emissions Per Year (TONs)
VOC	-4.903048
SO _x	-0.420514
NO _x	-0.797909
CO	-52.481119
PM 10	-1.313554

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.055764
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1104.7

- **Activity Emissions [Flight Operations (includes Trim Test & APU) part]:**

Pollutant	Emissions Per Year (TONs)
VOC	-4.903048
SO _x	-0.420514
NO _x	-0.797909
CO	-52.481119
PM 10	-1.313554

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.055764
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1104.7

23.2 Aircraft & Engines

23.2.1 Aircraft & Engines Assumptions

- **Aircraft & Engine**

Aircraft Designation: T-38C

Engine Model: J85-GE-5R

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 2

- **Aircraft & Engine Surrogate**

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

23.2.2 Aircraft & Engines Emission Factor(s)

- **Aircraft & Engine Emissions Factors (lb/1000lb fuel)**

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

23.3 Flight Operations

23.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	3
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	1445
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	12.8
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

23.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)
AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)
AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)
AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)
AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)
AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)
AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

23.4 Auxiliary Power Unit (APU)

23.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

23.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

23.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

24. Aircraft

24.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Decrease T-38 TGOs by 3193

- Activity Description:

Starting in 2029, decrease T-38 TGOs by 3193

- Activity Start Date

Start Month: 1

Start Year: 2029

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.477505
SO _x	-0.156124
NO _x	-0.200617
CO	-8.753461
PM 10	-0.256261

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.103196
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-471.9

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.477505
SO _x	-0.156124
NO _x	-0.200617
CO	-8.753461
PM 10	-0.256261

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.103196
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-471.9

24.2 Aircraft & Engines

24.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

24.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

24.3 Flight Operations

24.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 7
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3193
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.64
 Takeoff [After Burn] (mins): 0
 Climb Out [Intermediate] (mins): 0.47
 Approach [Approach] (mins): 0.98
 Taxi/Idle In [Idle] (mins): 0

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

24.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

24.4 Auxiliary Power Unit (APU)

24.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

24.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

24.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

25. Aircraft

25.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location
 - County: Bexar
 - Regulatory Area(s): San Antonio, TX

- Activity Title: Add T-7As and increase LTOs by 630

- Activity Description:
 - Starting in 2029, add T-7As and increase LTOs by 630

- Activity Start Date
 - Start Month: 1
 - Start Year: 2029

- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	2.907855
SO _x	0.208819
NO _x	2.015457
CO	15.608636
PM 10	0.262593

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.235643
Pb	0.000000
NH ₃	0.000000
CO _{2e}	490.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	2.907855
SO _x	0.208819
NO _x	2.015457
CO	15.608636
PM 10	0.262593

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.235643
Pb	0.000000
NH ₃	0.000000
CO _{2e}	490.7

25.2 Aircraft & Engines

25.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-7A
 - Engine Model: F404-GE-102
 - Primary Function: Trainer
 - Aircraft has After burn: Yes
 - Number of Engines: 1

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Original Aircraft Name:

Original Engine Name:

25.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

25.3 Flight Operations

25.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	0
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	630
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	9.74
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

25.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

25.4 Auxiliary Power Unit (APU)

25.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

25.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

25.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

26. Aircraft

26.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs by 1447

- Activity Description:

Starting in 2029, increase T-7A TGOs by 1447

- Activity Start Date

Start Month: 1

Start Year: 2029

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.293388
SO _x	0.198231
NO _x	3.624975
CO	0.604801
PM 10	0.019652

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.017011
Pb	0.000000
NH ₃	0.000000
CO _{2e}	607.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.293388
SO _x	0.198231
NO _x	3.624975
CO	0.604801
PM 10	0.019652

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.017011
Pb	0.000000
NH ₃	0.000000
CO _{2e}	607.3

26.2 Aircraft & Engines

26.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

26.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

26.3 Flight Operations

26.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 0
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1447
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
 Takeoff [Military] (mins): 0.64

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

26.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

26.4 Auxiliary Power Unit (APU)

26.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

26.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

26.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL}: Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

27. Aircraft

27.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove
- Activity Location
 - County: Bexar
 - Regulatory Area(s): San Antonio, TX
- Activity Title: Remove T-38s and decrease LTOs by 1715
- Activity Description:
 - Starting in 2030, remove T-38s and decrease LTOs by 1715
- Activity Start Date
 - Start Month: 1
 - Start Year: 2030
- Activity End Date
 - Indefinite: Yes
 - End Month: N/A
 - End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-5.819189
SO _x	-0.499088
NO _x	-0.946999
CO	-62.287279
PM 10	-1.558993

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.253035
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1311.1

- Activity Emissions [Flight Operations (includes Trim Test & APU part)]:

Pollutant	Emissions Per Year (TONs)
VOC	-5.819189
SO _x	-0.499088
NO _x	-0.946999
CO	-62.287279
PM 10	-1.558993

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.253035
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-1311.1

27.2 Aircraft & Engines

27.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine
 - Aircraft Designation: T-38C
 - Engine Model: J85-GE-5R
 - Primary Function: Trainer

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate
 - Is Aircraft & Engine a Surrogate? No
 - Original Aircraft Name:
 - Original Engine Name:

27.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

27.3 Flight Operations

27.3.1 Flight Operations Assumptions

- Flight Operations
 - Number of Aircraft: 6
 - Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1715
 - Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 - Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)
 - Taxi/Idle Out [Idle] (mins): 12.8
 - Takeoff [Military] (mins): 0.41
 - Takeoff [After Burn] (mins): 0.39
 - Climb Out [Intermediate] (mins): 0.91
 - Approach [Approach] (mins): 1.74
 - Taxi/Idle In [Idle] (mins): 6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test
 - Idle (mins): 12
 - Approach (mins): 27
 - Intermediate (mins): 9
 - Military (mins): 9
 - AfterBurn (mins): 3

27.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year
 $AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

27.4 Auxiliary Power Unit (APU)

27.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

27.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

27.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

28. Aircraft

28.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Decrease T-38 TGOs by 3792

- Activity Description:

Starting in 2030, decrease T-38 TGOs by 3,792

- Activity Start Date

Start Month: 1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Start Year: 2030

- Activity End Date

Indefinite: Yes
 End Month: N/A
 End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.567084
SO _x	-0.185413
NO _x	-0.238253
CO	-10.395591
PM 10	-0.304334

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.122555
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-560.4

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.567084
SO _x	-0.185413
NO _x	-0.238253
CO	-10.395591
PM 10	-0.304334

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.122555
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-560.4

28.2 Aircraft & Engines

28.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

28.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

28.3 Flight Operations

28.3.1 Flight Operations Assumptions

- Flight Operations

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Number of Aircraft:	6
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	3792
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- **Default Settings Used:** No

- **Flight Operations TIMs (Time In Mode)**

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- **Trim Test**

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

28.3.2 Flight Operations Formula(s)

- **Aircraft Emissions per Mode for LTOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- **Aircraft Emissions for LTOs per Year**

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- **Aircraft Emissions per Mode for TGOs per Year**

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TIM: Time in Mode (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 TGO: Number of Touch-and-Go Cycles (for all aircraft)
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
 TD: Test Duration (min)
 60: Conversion Factor minutes to hours
 FC: Fuel Flow Rate (lb/hr)
 1000: Conversion Factor pounds to 1000pounds
 EF: Emission Factor (lb/1000lb fuel)
 NE: Number of Engines
 NA: Number of Aircraft
 NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

28.4 Auxiliary Power Unit (APU)

28.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

28.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

28.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

29. Aircraft

29.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7 LTOs by 326

- Activity Description:

Stating in 2030, increase LTOs by 326

- Activity Start Date

Start Month: 1

Start Year: 2030

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	1.546241
SO _x	0.111039
NO _x	1.071711
CO	8.299830
PM 10	0.139633

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.125302
Pb	0.000000
NH ₃	0.000000
CO _{2e}	260.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	1.546241
SO _x	0.111039
NO _x	1.071711
CO	8.299830
PM 10	0.139633

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.125302
Pb	0.000000
NH ₃	0.000000
CO _{2e}	260.9

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

29.2 Aircraft & Engines

29.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

29.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

29.3 Flight Operations

29.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 72
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 335
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 9.74
Takeoff [Military] (mins): 0.41
Takeoff [After Burn] (mins): 0.39
Climb Out [Intermediate] (mins): 0.91
Approach [Approach] (mins): 1.74
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

29.3.2 Flight Operations Formula(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

NTT: Number of Trim Test
 2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)
 $AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)
 $AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)
 $AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)
 $AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)
 $AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

29.4 Auxiliary Power Unit (APU)

29.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

29.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

29.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)
 APU: Number of Auxiliary Power Units
 OH: Operation Hours for Each LTO (hour)
 LTO: Number of LTOs
 EF_{POL} : Emission Factor for Pollutant (lb/hr)
 2000: Conversion Factor pounds to tons

30. Aircraft

30.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar
 Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7 TGOs by 737

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Description:

Starting in 2030, increase TGOs by 737

- Activity Start Date

Start Month: 1

Start Year: 2030

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.149431
SO _x	0.100965
NO _x	1.846307
CO	0.308043
PM 10	0.010009

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.008664
Pb	0.000000
NH ₃	0.000000
CO _{2e}	309.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.149431
SO _x	0.100965
NO _x	1.846307
CO	0.308043
PM 10	0.010009

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.008664
Pb	0.000000
NH ₃	0.000000
CO _{2e}	309.3

30.2 Aircraft & Engines

30.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

30.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

30.3 Flight Operations

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

30.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	0
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	737
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

30.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

30.4 Auxiliary Power Unit (APU)

30.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

30.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

30.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

31. Aircraft

31.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Remove 14 T-38s and decrease LTOs by 2636

- Activity Description:

Starting in 2031, remove 14 T-38s and decrease TOs by 2,636

- Activity Start Date

Start Month: 1

Start Year: 2031

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-8.944246
SO _x	-0.767111
NO _x	-1.455562
CO	-95.737183
PM 10	-2.396214

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.925947
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2015.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-8.944246

Pollutant	Emissions Per Year (TONs)
PM 2.5	-1.925947

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

SO _x	-0.767111
NO _x	-1.455562
CO	-95.737183
PM 10	-2.396214

Pb	0.000000
NH ₃	0.000000
CO _{2e}	-2015.2

31.2 Aircraft & Engines

31.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
 Engine Model: J85-GE-5R
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

31.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

31.3 Flight Operations

31.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 14
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 2636
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 12.8
 Takeoff [Military] (mins): 0.41
 Takeoff [After Burn] (mins): 0.39
 Climb Out [Intermediate] (mins): 0.91
 Approach [Approach] (mins): 1.74
 Taxi/Idle In [Idle] (mins): 6.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

31.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

31.4 Auxiliary Power Unit (APU)

31.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

31.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

31.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

32. Aircraft

32.1 General Information & Timeline Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar
Regulatory Area(s): San Antonio, TX

- Activity Title: 2031 T-38 Removal 5840 TGOs

- Activity Description:

Starting in 2031, decrease T-38 TGOs by 6076

- Activity Start Date

Start Month: 1
Start Year: 2031

- Activity End Date

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.908651
SO _x	-0.297091
NO _x	-0.381757
CO	-16.657071
PM 10	-0.487641

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.196373
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-897.9

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.908651
SO _x	-0.297091
NO _x	-0.381757
CO	-16.657071
PM 10	-0.487641

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.196373
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-897.9

32.2 Aircraft & Engines

32.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-38C
Engine Model: J85-GE-5R
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 2

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

32.2.2 Aircraft & Engines Emission Factor(s)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
Idle	520.00	16.80	1.07	1.08	177.45	4.70	4.02	3234
Approach	854.00	7.84	1.07	0.84	106.29	2.80	1.85	3234
Intermediate	1030.00	2.78	1.07	0.70	65.07	1.79	0.69	3234
Military	2220.00	0.75	1.07	1.92	30.99	1.13	0.04	3234
After Burn	7695.00	6.97	1.07	6.23	53.43	0.25	0.09	3234

32.3 Flight Operations

32.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	11
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	6076
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

32.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

32.4 Auxiliary Power Unit (APU)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

32.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
----------------------------	------------------------------	----------------	-------------	--------------

32.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

32.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

33. Aircraft

33.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: decrease T-7A LTOs by 130

- Activity Description:

Starting in 2031, decrease T-7A LTOs by 130

- Activity Start Date

Start Month: 1

Start Year: 2031

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
-----------	---------------------------

Pollutant	Emissions Per Year (TONs)
-----------	---------------------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

VOC	-0.600034
SO _x	-0.043090
NO _x	-0.415888
CO	-3.220830
PM 10	-0.054186

PM 2.5	-0.048625
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-101.3

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.600034
SO _x	-0.043090
NO _x	-0.415888
CO	-3.220830
PM 10	-0.054186

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.048625
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-101.3

33.2 Aircraft & Engines

33.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
 Engine Model: F404-GE-102
 Primary Function: Trainer
 Aircraft has After burn: Yes
 Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
 Original Aircraft Name:
 Original Engine Name:

33.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

33.3 Flight Operations

33.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 72
 Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 130
 Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
 Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 9.74
 Takeoff [Military] (mins): 0.41
 Takeoff [After Burn] (mins): 0.39
 Climb Out [Intermediate] (mins): 0.91
 Approach [Approach] (mins): 1.74

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

33.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)
 AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)
 AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

33.4 Auxiliary Power Unit (APU)

33.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

33.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

33.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to tons

34. Aircraft

34.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Remove

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: decrease T-7A TGOs by 280

- Activity Description:

Starting in 2031, decrease T-7A TGOs by 280

- Activity Start Date

Start Month: 1

Start Year: 2031

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	-0.056772
SO _x	-0.038358
NO _x	-0.701446
CO	-0.117031
PM 10	-0.003803

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.003292
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-117.5

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	-0.056772
SO _x	-0.038358
NO _x	-0.701446
CO	-0.117031
PM 10	-0.003803

Pollutant	Emissions Per Year (TONs)
PM 2.5	-0.003292
Pb	0.000000
NH ₃	0.000000
CO _{2e}	-117.5

34.2 Aircraft & Engines

34.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A

Engine Model: F404-GE-102

Primary Function: Trainer

Aircraft has After burn: Yes

Number of Engines: 1

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No

Original Aircraft Name:

Original Engine Name:

34.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

34.3 Flight Operations

34.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	72
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	280
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	0
Takeoff [Military] (mins):	0.64
Takeoff [After Burn] (mins):	0
Climb Out [Intermediate] (mins):	0.47
Approach [Approach] (mins):	0.98
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

34.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

34.4 Auxiliary Power Unit (APU)

34.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

34.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

34.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

35. Aircraft

35.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7 LTOs by 1553

- Activity Description:

increase LTOs by 1553

- Activity Start Date

Start Month: 1

Start Year: 2032

- Activity End Date

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

Indefinite: Yes
End Month: N/A
End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	7.168094
SO _x	0.514756
NO _x	4.968261
CO	38.476526
PM 10	0.647311

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.580879
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1209.7

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	7.168094
SO _x	0.514756
NO _x	4.968261
CO	38.476526
PM 10	0.647311

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.580879
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1209.7

35.2 Aircraft & Engines

35.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

35.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

35.3 Flight Operations

35.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 5
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 1553
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	9.74
Takeoff [Military] (mins):	0.41
Takeoff [After Burn] (mins):	0.39
Climb Out [Intermediate] (mins):	0.91
Approach [Approach] (mins):	1.74
Taxi/Idle In [Idle] (mins):	0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	12
Approach (mins):	27
Intermediate (mins):	9
Military (mins):	9
AfterBurn (mins):	3

35.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO}: Aircraft Emissions (TONs)

AEM_{IDLE_IN}: Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT}: Aircraft Emissions for Idle-Out Mode (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

$AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

35.4 Auxiliary Power Unit (APU)

35.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

35.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

35.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

36. Aircraft

36.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: Increase T-7A TGOs by 3436

- Activity Description:

Starting in 2032, increase T-7A TGOs by 3436

- Activity Start Date

Start Month: 1

Start Year: 2032

- Activity End Date

Indefinite: Yes

End Month: N/A

End Year: N/A

- Activity Emissions:

Pollutant	Emissions Per Year (TONs)
VOC	0.696670
SO _x	0.470712
NO _x	8.607750
CO	1.436141
PM 10	0.046665

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.040394
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1442.1

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Emissions Per Year (TONs)
VOC	0.696670
SO _x	0.470712
NO _x	8.607750
CO	1.436141
PM 10	0.046665

Pollutant	Emissions Per Year (TONs)
PM 2.5	0.040394
Pb	0.000000
NH ₃	0.000000
CO _{2e}	1442.1

36.2 Aircraft & Engines

36.2.1 Aircraft & Engines Assumptions

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

36.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

36.3 Flight Operations

36.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft: 5
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft: 3436
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft: 0
Number of Annual Trim Test(s) per Aircraft: 0

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins): 0
Takeoff [Military] (mins): 0.64
Takeoff [After Burn] (mins): 0
Climb Out [Intermediate] (mins): 0.47
Approach [Approach] (mins): 0.98
Taxi/Idle In [Idle] (mins): 0

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins): 12
Approach (mins): 27
Intermediate (mins): 9
Military (mins): 9
AfterBurn (mins): 3

36.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
LTO: Number of Landing and Take-off Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)
 AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)
 AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)
TIM: Time in Mode (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
TGO: Number of Touch-and-Go Cycles (for all aircraft)
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO} : Aircraft Emissions (TONs)
 $AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)
 $AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)
 $AEM_{TAKEOFF}$: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

$AEPS_{POL}$: Aircraft Emissions per Pollutant & Power Setting (TONs)
TD: Test Duration (min)
60: Conversion Factor minutes to hours
FC: Fuel Flow Rate (lb/hr)
1000: Conversion Factor pounds to 1000pounds
EF: Emission Factor (lb/1000lb fuel)
NE: Number of Engines
NA: Number of Aircraft
NTT: Number of Trim Test
2000: Conversion Factor pounds to TONS

- Aircraft Emissions for Trim per Year

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM} : Aircraft Emissions (TONs)

$AEPS_{IDLE}$: Aircraft Emissions for Idle Power Setting (TONs)

$AEPS_{APPROACH}$: Aircraft Emissions for Approach Power Setting (TONs)

$AEPS_{INTERMEDIATE}$: Aircraft Emissions for Intermediate Power Setting (TONs)

$AEPS_{MILITARY}$: Aircraft Emissions for Military Power Setting (TONs)

$AEPS_{AFTERBURN}$: Aircraft Emissions for After Burner Power Setting (TONs)

36.4 Auxiliary Power Unit (APU)

36.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU per Aircraft	Operation Hours for Each LTO	Exempt Source?	Designation	Manufacturer
1	0.25	No	4501687C	Hamilton Sundstrand

36.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
4501687C	211.0	0.010	0.230	1.380	1.070	-1.000	-1.000	740.4

36.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL} : Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL} : Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

37. Aircraft

37.1 General Information & Timeline Assumptions

- Add or Remove Activity from Baseline? Add

- Activity Location

County: Bexar

Regulatory Area(s): San Antonio, TX

- Activity Title: 2023 T-7A Increase Trim Test and Test Cell

- Activity Description:

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

- Activity Start Date

Start Month: 1
Start Year: 2023

- Activity End Date

Indefinite: No
End Month: 12
End Year: 2023

- Activity Emissions:

Pollutant	Total Emissions (TONs)
VOC	0.084558
SO _x	0.027537
NO _x	0.469887
CO	1.450657
PM 10	0.032987

Pollutant	Total Emissions (TONs)
PM 2.5	0.029582
Pb	0.000000
NH ₃	0.000000
CO _{2e}	83.2

- Activity Emissions [Flight Operations (includes Trim Test & APU) part]:

Pollutant	Total Emissions (TONs)
VOC	0.046147
SO _x	0.015141
NO _x	0.251550
CO	0.731888
PM 10	0.016822

Pollutant	Total Emissions (TONs)
PM 2.5	0.015074
Pb	0.000000
NH ₃	0.000000
CO _{2e}	45.8

- Activity Emissions [Test Cell part]:

Pollutant	Total Emissions (TONs)
VOC	0.038410
SO _x	0.012396
NO _x	0.218337
CO	0.718770
PM 10	0.016165

Pollutant	Total Emissions (TONs)
PM 2.5	0.014509
Pb	0.000000
NH ₃	0.000000
CO _{2e}	37.5

37.2 Aircraft & Engines

37.2.1 Aircraft & Engines Assumptions

- Aircraft & Engine

Aircraft Designation: T-7A
Engine Model: F404-GE-102
Primary Function: Trainer
Aircraft has After burn: Yes
Number of Engines: 1

- Aircraft & Engine Surrogate

Is Aircraft & Engine a Surrogate? No
Original Aircraft Name:
Original Engine Name:

37.2.2 Aircraft & Engines Emission Factor(s)

- Aircraft & Engine Emissions Factors (lb/1000lb fuel)

Proprietary Information. Contact Air Quality Subject Matter Expert for More Information regarding this engine's Emission Factors.

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

37.3 Flight Operations

37.3.1 Flight Operations Assumptions

- Flight Operations

Number of Aircraft:	8
Number of Annual LTOs (Landing and Take-off) cycles for all Aircraft:	0
Number of Annual TGOs (Touch-and-Go) cycles for all Aircraft:	0
Number of Annual Trim Test(s) per Aircraft:	1

- Default Settings Used: No

- Flight Operations TIMs (Time In Mode)

Taxi/Idle Out [Idle] (mins):	6.8
Takeoff [Military] (mins):	0.25
Takeoff [After Burn] (mins):	0.25
Climb Out [Intermediate] (mins):	1.4
Approach [Approach] (mins):	4
Taxi/Idle In [Idle] (mins):	4.4

Per the Air Emissions Guide for Air Force Mobile Sources, the defaults values for military aircraft equipped with after burner for takeoff is 50% military power and 50% afterburner. (Exception made for F-35 where KARNES 3.2 flight profile was used)

- Trim Test

Idle (mins):	0
Approach (mins):	4.97
Intermediate (mins):	10.45
Military (mins):	6.14
AfterBurn (mins):	2.04

37.3.2 Flight Operations Formula(s)

- Aircraft Emissions per Mode for LTOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * LTO / 2000$$

AEM_{POL} : Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

LTO: Number of Landing and Take-off Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for LTOs per Year

$$AE_{LTO} = AEM_{IDLE_IN} + AEM_{IDLE_OUT} + AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{LTO} : Aircraft Emissions (TONs)

AEM_{IDLE_IN} : Aircraft Emissions for Idle-In Mode (TONs)

AEM_{IDLE_OUT} : Aircraft Emissions for Idle-Out Mode (TONs)

$AEM_{APPROACH}$: Aircraft Emissions for Approach Mode (TONs)

$AEM_{CLIMBOUT}$: Aircraft Emissions for Climb-Out Mode (TONs)

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for TGOs per Year

$$AEM_{POL} = (TIM / 60) * (FC / 1000) * EF * NE * TGO / 2000$$

AEM_{POL}: Aircraft Emissions per Pollutant & Mode (TONs)

TIM: Time in Mode (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

TGO: Number of Touch-and-Go Cycles (for all aircraft)

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for TGOs per Year

$$AE_{TGO} = AEM_{APPROACH} + AEM_{CLIMBOUT} + AEM_{TAKEOFF}$$

AE_{TGO}: Aircraft Emissions (TONs)

AEM_{APPROACH}: Aircraft Emissions for Approach Mode (TONs)

AEM_{CLIMBOUT}: Aircraft Emissions for Climb-Out Mode (TONs)

AEM_{TAKEOFF}: Aircraft Emissions for Take-Off Mode (TONs)

- Aircraft Emissions per Mode for Trim per Year

$$AEPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * NA * NTT / 2000$$

AEPS_{POL}: Aircraft Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Number of Engines

NA: Number of Aircraft

NTT: Number of Trim Test

2000: Conversion Factor pounds to TONs

- Aircraft Emissions for Trim per Year

$$AE_{TRIM} = AEPS_{IDLE} + AEPS_{APPROACH} + AEPS_{INTERMEDIATE} + AEPS_{MILITARY} + AEPS_{AFTERBURN}$$

AE_{TRIM}: Aircraft Emissions (TONs)

AEPS_{IDLE}: Aircraft Emissions for Idle Power Setting (TONs)

AEPS_{APPROACH}: Aircraft Emissions for Approach Power Setting (TONs)

AEPS_{INTERMEDIATE}: Aircraft Emissions for Intermediate Power Setting (TONs)

AEPS_{MILITARY}: Aircraft Emissions for Military Power Setting (TONs)

AEPS_{AFTERBURN}: Aircraft Emissions for After Burner Power Setting (TONs)

37.4 Auxiliary Power Unit (APU)

37.4.1 Auxiliary Power Unit (APU) Assumptions

- Default Settings Used: Yes

- Auxiliary Power Unit (APU) (default)

Number of APU	Operation Hours	Exempt	Designation	Manufacturer
---------------	-----------------	--------	-------------	--------------

DETAIL AIR CONFORMITY APPLICABILITY MODEL REPORT

per Aircraft	for Each LTO	Source?	
--------------	--------------	---------	--

37.4.2 Auxiliary Power Unit (APU) Emission Factor(s)

- Auxiliary Power Unit (APU) Emission Factor (lb/hr)

Designation	Fuel Flow	VOC	SO _x	NO _x	CO	PM 10	PM 2.5	CO _{2e}
-------------	-----------	-----	-----------------	-----------------	----	-------	--------	------------------

37.4.3 Auxiliary Power Unit (APU) Formula(s)

- Auxiliary Power Unit (APU) Emissions per Year

$$APU_{POL} = APU * OH * LTO * EF_{POL} / 2000$$

APU_{POL}: Auxiliary Power Unit (APU) Emissions per Pollutant (TONs)

APU: Number of Auxiliary Power Units

OH: Operation Hours for Each LTO (hour)

LTO: Number of LTOs

EF_{POL}: Emission Factor for Pollutant (lb/hr)

2000: Conversion Factor pounds to tons

37.5 Aircraft Engine Test Cell

37.5.1 Aircraft Engine Test Cell Assumptions

- Engine Test Cell

Total Number of Aircraft Engines Tested Annually: 8

- Default Settings Used: No

- Annual Run-ups / Test Durations

Annual Run-ups (Per Aircraft Engine):	1
Idle Duration (mins):	0
Approach Duration (mins):	12
Intermediate Duration (mins):	0
Military Duration (mins):	8
After Burner Duration (mins):	2

37.5.2 Aircraft Engine Test Cell Emission Factor(s)

- See Aircraft & Engines Emission Factor(s)

37.5.3 Aircraft Engine Test Cell Formula(s)

- Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

$$TestCellPS_{POL} = (TD / 60) * (FC / 1000) * EF * NE * ARU / 2000$$

TestCellPS_{POL}: Aircraft Engine Test Cell Emissions per Pollutant & Power Setting (TONs)

TD: Test Duration (min)

60: Conversion Factor minutes to hours

FC: Fuel Flow Rate (lb/hr)

1000: Conversion Factor pounds to 1000pounds

EF: Emission Factor (lb/1000lb fuel)

NE: Total Number of Engines (For All Aircraft)

ARU: Annual Run-ups (Per Aircraft Engine)

2000: Conversion Factor pounds to TONs